



LARGE SYNOPTIC SURVEY TELESCOPE

Large Synoptic Survey Telescope (LSST)
Data Management

LSST Data Management Acceptance Test Specification

L.P. Guy, W.M. Wood-Vasey, E. Bellm, J.F. Bosch, J.L. Carlin,
G.P. Dubois-Felsmann, M.L. Graham, R. Gruendl, K.S. Krughoff,
K.-T. Lim, R.H. Lupton, C. Slater, G. Comoretto

LDM-639

Latest Revision: 2019-09-17

Draft Revision NOT YET Approved – This LSST document has been approved as a Content-Controlled Document by the LSST DM Change Control Board. If this document is changed or superseded, the new document will retain the Handle designation shown above. The control is on the most recent digital document with this Handle in the LSST digital archive and not printed versions. Additional information may be found in the corresponding DM RFC. – **Draft Revision NOT YET Approved**

Abstract

This document describes the detailed acceptance test specification for the LSST Data Management System.

Draft

Change Record

Version	Date	Description	Owner name
1.0	2019-02-07	Document first approved release. Approved on RFC-495.	L. Guy
2.0	2019-07-29	Add test cases for all Priority 1a requirements. Approved in RFC-622.	Document: J. Carlin; Approver: W. O'Mullane

Document curator: Leanne Guy

Document source location: <https://github.com/lsst/lsm-639> from Jira

Version from source repository: 549bad2

Contents

1	Introduction	1
1.1	Objectives	1
1.2	Scope	1
1.3	Applicable Documents	2
1.4	References	2
1.5	Acronyms	3
2	Approach	4
2.1	Features to be tested	4
2.2	Features not to be tested	5
2.3	Pass/fail criteria	5
2.4	Suspension criteria and resumption requirements	5
2.5	Naming convention	5
3	Test Cases Summary	6
4	Active Test Cases	13
4.1	LVV-T23 - Verify implementation of Storing Approximations of Per-pixel Meta-data	13
4.2	LVV-T24 - Verify implementation of Computing Derived Quantities	15
4.3	LVV-T25 - Verify implementation of Denormalizing Database Tables	17
4.4	LVV-T26 - Verify implementation of Maximum Likelihood Values and Covariances	18
4.5	LVV-T27 - Verify implementation of Data Availability	20
4.6	LVV-T28 - Verify implementation of Measurements in catalogs	21
4.7	LVV-T29 - Verify implementation of Raw Science Image Data Acquisition	24
4.8	LVV-T30 - Verify implementation of Wavefront Sensor Data Acquisition	25
4.9	LVV-T31 - Verify implementation of Crosstalk Corrected Science Image Data Acquisition	26
4.10	LVV-T32 - Verify implementation of Raw Image Assembly	27

4.11	LWV-T33 - Verify implementation of Raw Science Image Metadata	29
4.12	LWV-T34 - Verify implementation of Guider Calibration Data Acquisition	31
4.13	LWV-T35 - Verify implementation of Nightly Data Accessible Within 24 hrs . . .	32
4.14	LWV-T36 - Verify implementation of Difference Exposures	36
4.15	LWV-T37 - Verify implementation of Difference Exposure Attributes	39
4.16	LWV-T38 - Verify implementation of Processed Visit Images	41
4.17	LWV-T39 - Verify implementation of Generate Photometric Zeropoint for Visit Image	42
4.18	LWV-T40 - Verify implementation of Generate WCS for Visit Images	43
4.19	LWV-T41 - Verify implementation of Generate PSF for Visit Images	45
4.20	LWV-T42 - Verify implementation of Processed Visit Image Content	46
4.21	LWV-T43 - Verify implementation of Background Model Calculation	48
4.22	LWV-T44 - Verify implementation of Documenting Image Characterization . . .	50
4.23	LWV-T45 - Verify implementation of Prompt Processing Data Quality Report Def- inition	51
4.24	LWV-T46 - Verify implementation of Prompt Processing Performance Report Definition	52
4.25	LWV-T47 - Verify implementation of Prompt Processing Calibration Report Def- inition	54
4.26	LWV-T48 - Verify implementation of Exposure Catalog	55
4.27	LWV-T49 - Verify implementation of DIASource Catalog	56
4.28	LWV-T50 - Verify implementation of Faint DIASource Measurements	58
4.29	LWV-T51 - Verify implementation of DIAObject Catalog	61
4.30	LWV-T52 - Verify implementation of DIAObject Attributes	63
4.31	LWV-T53 - Verify implementation of SSObject Catalog	65
4.32	LWV-T54 - Verify implementation of Alert Content	67
4.33	LWV-T55 - Verify implementation of DIAForcedSource Catalog	71
4.34	LWV-T56 - Verify implementation of Characterizing Variability	73
4.35	LWV-T57 - Verify implementation of Calculating SSObject Parameters	75
4.36	LWV-T58 - Verify implementation of Matching DIASources to Objects	76

4.37	LWV-T59 - Verify implementation of Regenerating L1 Data Products During Data Release Processing	79
4.38	LWV-T60 - Verify implementation of Publishing predicted visit schedule	80
4.39	LWV-T61 - Verify implementation of Associate Sources to Objects	81
4.40	LWV-T62 - Verify implementation of Provide PSF for Coadded Images	82
4.41	LWV-T63 - Verify implementation of Produce Images for EPO	84
4.42	LWV-T64 - Verify implementation of Coadded Image Provenance	86
4.43	LWV-T65 - Verify implementation of Source Catalog	88
4.44	LWV-T66 - Verify implementation of Forced-Source Catalog	89
4.45	LWV-T67 - Verify implementation of Object Catalog	92
4.46	LWV-T68 - Verify implementation of Provide Photometric Redshifts of Galaxies	95
4.47	LWV-T69 - Verify implementation of Object Characterization	96
4.48	LWV-T71 - Verify implementation of Detecting extended low surface brightness objects	97
4.49	LWV-T72 - Verify implementation of Coadd Image Method Constraints	99
4.50	LWV-T73 - Verify implementation of Deep Detection Coadds	101
4.51	LWV-T74 - Verify implementation of Template Coadds	102
4.52	LWV-T75 - Verify implementation of Multi-band Coadds	104
4.53	LWV-T76 - Verify implementation of All-Sky Visualization of Data Releases	106
4.54	LWV-T77 - Verify implementation of Best Seeing Coadds	108
4.55	LWV-T78 - Verify implementation of Persisting Data Products	110
4.56	LWV-T79 - Verify implementation of PSF-Matched Coadds	111
4.57	LWV-T80 - Verify implementation of Detecting faint variable objects	112
4.58	LWV-T81 - Verify implementation of Targeted Coadds	115
4.59	LWV-T82 - Verify implementation of Tracking Characterization Changes Between Data Releases	117
4.60	LWV-T83 - Verify implementation of Bad Pixel Map	118
4.61	LWV-T84 - Verify implementation of Bias Residual Image	119
4.62	LWV-T85 - Verify implementation of Crosstalk Correction Matrix	122
4.63	LWV-T86 - Verify implementation of Illumination Correction Frame	123

4.64	LVV-T87 - Verify implementation of Monochromatic Flatfield Data Cube	124
4.65	LVV-T88 - Verify implementation of Calibration Data Products	125
4.66	LVV-T89 - Verify implementation of Calibration Image Provenance	127
4.67	LVV-T90 - Verify implementation of Dark Current Correction Frame	128
4.68	LVV-T91 - Verify implementation of Fringe Correction Frame	130
4.69	LVV-T92 - Verify implementation of Processing of Data From Special Programs	131
4.70	LVV-T93 - Verify implementation of Level 1 Processing of Special Programs Data	133
4.71	LVV-T94 - Verify implementation of Special Programs Database	134
4.72	LVV-T95 - Verify implementation of Constraints on Level 1 Special Program Products Generation	136
4.73	LVV-T96 - Verify implementation of Query Repeatability	137
4.74	LVV-T97 - Verify implementation of Uniqueness of IDs Across Data Releases .	139
4.75	LVV-T98 - Verify implementation of Selection of Datasets	140
4.76	LVV-T99 - Verify implementation of Processing of Datasets	142
4.77	LVV-T100 - Verify implementation of Transparent Data Access	143
4.78	LVV-T101 - Verify implementation of Transient Alert Distribution	144
4.79	LVV-T102 - Verify implementation of Solar System Objects Available Within Spec- ified Time	146
4.80	LVV-T103 - Verify implementation of Generate Data Quality Report Within Spec- ified Time	147
4.81	LVV-T104 - Verify implementation of Generate DMS Performance Report Within Specified Time	148
4.82	LVV-T105 - Verify implementation of Generate Calibration Report Within Spec- ified Time	149
4.83	LVV-T106 - Verify implementation of Calibration Images Available Within Spec- ified Time	150
4.84	LVV-T107 - Verify implementation of Level-1 Production Completeness	152
4.85	LVV-T108 - Verify implementation of Level 1 Source Association	153
4.86	LVV-T109 - Verify implementation of SSObject Precoversy	154
4.87	LVV-T110 - Verify implementation of DIASource Precoversy	155

4.88	LVV-T111 - Verify implementation of Use of External Orbit Catalogs	156
4.89	LVV-T112 - Verify implementation of Alert Filtering Service	157
4.90	LVV-T113 - Verify implementation of Performance Requirements for LSST Alert Filtering Service	158
4.91	LVV-T114 - Verify implementation of Pre-defined alert filters	160
4.92	LVV-T115 - Verify implementation of Calibration Production Processing	161
4.93	LVV-T116 - Verify implementation of Associating Objects across data releases	162
4.94	LVV-T117 - Verify implementation of DAC resource allocation for Level 3 pro- cessing	163
4.95	LVV-T118 - Verify implementation of Level 3 Data Product Self Consistency . .	165
4.96	LVV-T119 - Verify implementation of Provenance for Level 3 processing at DACs	166
4.97	LVV-T120 - Verify implementation of Software framework for Level 3 catalog processing	167
4.98	LVV-T121 - Verify implementation of Software framework for Level 3 image pro- cessing	168
4.99	LVV-T122 - Verify implementation of Level 3 Data Import	169
4.100	LVV-T123 - Verify implementation of Access Controls of Level 3 Data Products	171
4.101	LVV-T124 - Verify implementation of Software Architecture to Enable Commu- nity Re-Use	172
4.102	LVV-T125 - Verify implementation of Simulated Data	174
4.103	LVV-T126 - Verify implementation Image Differencing	175
4.104	LVV-T127 - Verify implementation of Provide Source Detection Software . . .	176
4.105	LVV-T128 - Verify implementation Provide Astrometric Model	177
4.106	LVV-T129 - Verify implementation of Provide Calibrated Photometry	178
4.107	LVV-T130 - Verify implementation of Enable a Range of Shape Measurement Approaches	180
4.108	LVV-T131 - Verify implementation of Provide User Interface Services	181
4.109	LVV-T132 - Verify implementation of Pre-cursor and Real Data	186
4.110	LVV-T133 - Verify implementation of Provide Beam Projector Coordinate Cal- culation Software	187

4.111	LVV-T134 - Verify implementation of Provide Image Access Services	189
4.112	LVV-T136 - Verify implementation of Data Product and Raw Data Access . . .	190
4.113	LVV-T137 - Verify implementation of Data Product Ingest	191
4.114	LVV-T138 - Verify implementation of Bulk Download Service	192
4.115	LVV-T140 - Verify implementation of Production Orchestration	194
4.116	LVV-T141 - Verify implementation of Production Monitoring	195
4.117	LVV-T142 - Verify implementation of Production Fault Tolerance	196
4.118	LVV-T144 - Verify implementation of Task Specification	197
4.119	LVV-T145 - Verify implementation of Task Configuration	198
4.120	LVV-T146 - Verify implementation of DMS Initialization Component	200
4.121	LVV-T147 - Verify implementation of Control of Level-1 Production	201
4.122	LVV-T148 - Verify implementation of Unique Processing Coverage	202
4.123	LVV-T149 - Verify implementation of Catalog Queries	203
4.124	LVV-T150 - Verify implementation of Maintain Archive Publicly Accessible . . .	204
4.125	LVV-T151 - Verify Implementation of Catalog Export Formats From the Note- book Aspect	205
4.126	LVV-T152 - Verify implementation of Keep Historical Alert Archive	208
4.127	LVV-T153 - Verify implementation of Provide Engineering and Facility Database Archive	209
4.128	LVV-T154 - Verify implementation of Raw Data Archiving Reliability	210
4.129	LVV-T155 - Verify implementation of Un-Archived Data Product Cache	211
4.130	LVV-T156 - Verify implementation of Regenerate Un-archived Data Products .	213
4.131	LVV-T157 - Verify implementation Level 1 Data Product Access	214
4.132	LVV-T158 - Verify implementation Level 1 and 2 Catalog Access	215
4.133	LVV-T159 - Verify implementation of Regenerating Data Products from Previous Data Releases	216
4.134	LVV-T160 - Verify implementation of Providing a Preccovery Service	217
4.135	LVV-T161 - Verify implementation of Logging of catalog queries	218
4.136	LVV-T162 - Verify implementation of Access to Previous Data Releases	219
4.137	LVV-T163 - Verify implementation of Data Access Services	221

4.138	LVV-T164 - Verify implementation of Operations Subsets	222
4.139	LVV-T165 - Verify implementation of Subsets Support	223
4.140	LVV-T166 - Verify implementation of Access Services Performance	224
4.141	LVV-T167 - Verify Capability to serve older Data Releases at Full Performance	225
4.142	LVV-T168 - Verify design of Data Access Services allows Evolution of the LSST Data Model	226
4.143	LVV-T169 - Verify implementation of Older Release Behavior	227
4.144	LVV-T170 - Verify implementation of Query Availability	228
4.145	LVV-T171 - Verify implementation of Pipeline Availability	229
4.146	LVV-T172 - Verify implementation of Optimization of Cost, Reliability and Avail- ability	230
4.147	LVV-T173 - Verify implementation of Pipeline Throughput	231
4.148	LVV-T174 - Verify implementation of Re-processing Capacity	232
4.149	LVV-T175 - Verify implementation of Temporary Storage for Communications Links	233
4.150	LVV-T176 - Verify implementation of Infrastructure Sizing for "catching up"	234
4.151	LVV-T177 - Verify implementation of Incorporate Fault-Tolerance	236
4.152	LVV-T178 - Verify implementation of Incorporate Autonomics	237
4.153	LVV-T179 - Verify implementation of Compute Platform Heterogeneity	238
4.154	LVV-T180 - Verify implementation of Data Management Unscheduled Down- time	239
4.155	LVV-T181 - Verify integration of Summit Facility Data Communications	240
4.156	LVV-T182 - Verify implementation of Prefer Computing and Storage Down	241
4.157	LVV-T183 - Verify implementation of DMS Communication with OCS	242
4.158	LVV-T185 - Verify implementation of Summit to Base Network Availability	243
4.159	LVV-T186 - Verify implementation of Summit to Base Network Reliability	244
4.160	LVV-T187 - Verify implementation of Summit to Base Network Secondary Link	245
4.161	LVV-T188 - Verify implementation of Summit to Base Network Ownership and Operation	246
4.162	LVV-T189 - Verify implementation of Base Facility Infrastructure	247

4.163	LVV-T190 - Verify implementation of Base Facility Co-Location with Existing Facility	248
4.164	LVV-T191 - Verify implementation of Commissioning Cluster	249
4.165	LVV-T192 - Verify implementation of Base Wireless LAN (WiFi)	250
4.166	LVV-T193 - Verify implementation of Base to Archive Network	251
4.167	LVV-T194 - Verify implementation of Base to Archive Network Availability	252
4.168	LVV-T195 - Verify implementation of Base to Archive Network Reliability	253
4.169	LVV-T196 - Verify implementation of Base to Archive Network Secondary Link	254
4.170	LVV-T197 - Verify implementation of Archive Center	255
4.171	LVV-T198 - Verify implementation of Archive Center Disaster Recovery	256
4.172	LVV-T199 - Verify implementation of Archive Center Co-Location with Existing Facility	257
4.173	LVV-T200 - Verify implementation of Archive to Data Access Center Network	258
4.174	LVV-T201 - Verify implementation of Archive to Data Access Center Network Availability	259
4.175	LVV-T202 - Verify implementation of Archive to Data Access Center Network Reliability	260
4.176	LVV-T203 - Verify implementation of Archive to Data Access Center Network Secondary Link	261
4.177	LVV-T204 - Verify implementation of Access to catalogs for external Level 3 processing	263
4.178	LVV-T205 - Verify implementation of Access to input catalogs for DAC-based Level 3 processing	264
4.179	LVV-T206 - Verify implementation of Federation with external catalogs	265
4.180	LVV-T207 - Verify implementation of Access to images for external Level 3 processing	266
4.181	LVV-T208 - Verify implementation of Access to input images for DAC-based Level 3 processing	267
4.182	LVV-T209 - Verify implementation of Data Access Centers	268

4.183	LVV-T210 - Verify implementation of Data Access Center Simultaneous Connections	269
4.184	LVV-T211 - Verify implementation of Data Access Center Geographical Distribution	270
4.185	LVV-T212 - Verify implementation of No Limit on Data Access Centers	271
4.186	LVV-T376 - Verify the Calculation of Ellipticity Correlations	272
4.187	LVV-T377 - Verify Calculation of Photometric Performance Metrics	273
4.188	LVV-T378 - Verify Calculation of Astrometric Performance Metrics	275
4.189	LVV-T385 - Verify implementation of minimum number of simultaneous retrievals of CCD-sized coadd cutouts	277
4.190	LVV-T1097 - Verify Summit to Base Network Implementation	279
4.191	LVV-T1168 - Test Summit - Base Network Integration	280
4.192	LVV-T1232 - Verify Implementation of Catalog Export Formats From the Portal Aspect	282
4.193	LVV-T1240 - Verify implementation of minimum astrometric standards per CCD	284
4.194	LVV-T1250 - Verify implementation of minimum number of simultaneous DM EFD query users	286
4.195	LVV-T1251 - Verify implementation of maximum time to retrieve DM EFD query results	287
4.196	LVV-T1252 - Verify number of simultaneous alert filter users	288
4.197	LVV-T1264 - Verify implementation of archiving camera test data	290
4.198	LVV-T1276 - Verify implementation of latency of reporting optical transients	291
4.199	LVV-T1277 - Verify processing of maximum number of calibration exposures	293
4.200	LVV-T1332 - Verify implementation of maximum time for retrieval of CCD-sized coadd cutouts	294
5	Reusable Test Cases	297
5.1	LVV-T12 - DRP-00-10: Data Release Includes Required Data Products	297
5.2	LVV-T18 - AG-00-05: Alert Generation Produces Required Data Products	297
5.3	LVV-T29 - Verify implementation of Raw Science Image Data Acquisition	298
5.4	LVV-T32 - Verify implementation of Raw Image Assembly	298



5.5	LVV-T1060 - Run Periodic Calibration Products Production Payload	298
5.6	LVV-T216 - Installation of the Alert Distribution payloads.	299
5.7	LVV-T217 - Full Stream Alert Distribution	299
5.8	LVV-T987 - Instantiate the Butler for reading data	300
5.9	LVV-T866 - Run Alert Production Payload	300
5.10	LVV-T1059 - Run Daily Calibration Products Update Payload	300
5.11	LVV-T21 - AG-00-20: Scientific Verification of DIASource Catalog	301
5.12	LVV-T22 - AG-00-25: Scientific Verification of DIAObject Catalog	301
5.13	LVV-T53 - Verify implementation of SSOBJect Catalog	302
5.14	LVV-T16 - DRP-00-35: Scientific Verification of Coadd Images	302
5.15	LVV-T1064 - Run Data Release Production Payload	303
5.16	LVV-T35 - Verify implementation of Nightly Data Accessible Within 24 hrs . . .	303
5.17	LVV-T140 - Verify implementation of Production Orchestration	304
5.18	LVV-T837 - Authenticate to Notebook Aspect	304
5.19	LVV-T838 - Access an empty notebook in the Notebook Aspect	305
5.20	LVV-T1207 - Execute a simple ADQL query using the TAP service in the notebook aspect	305
5.21	LVV-T1208 - Log out of the notebook aspect of the LSP	305
5.22	LVV-T849 - Authenticate to the portal aspect of the LSP	305
5.23	LVV-T850 - Log out of the portal aspect of the LSP	306
6 Deprecated Test Cases		307
A Traceability		308

LSST Data Management Acceptance Test Specification

1 Introduction

This document is intended to specify the acceptance test procedures for the LSST Data Management System. It is a work in progress; the current version provides Test Cases covering ~ 35% of the requirements. It does not yet provide full Test Plans for comprehensive testing nor identify the fraction of each requirement covered by the existing Test Cases.

This document will be updated as work continues on completing Test Cases, Test Plans, and requirements coverage.

1.1 Objectives

This document describes the test cases required to validate the Data Management System requirements described in the LSST DM Subsystem Requirements document LSE-61. It identifies test cases and procedures for the tests as well as the pass/fail criteria for each test.

A full description of the LSST Data Management System is provided in the Data Management System Design document, LDM-148 with the science requirements detailed in the LSST Science Requirements Document LPM-17.

1.2 Scope

This document provides the acceptance test plan for the whole Data Management System (DMS), as described by the Data Management System Requirements in LSE-61.

1.3 Applicable Documents

LPM-17	LSST Science Requirements Document
LDM-148	LSST Data Management System Design
LDM-294	LSST DM Organization & Management
LDM-503	LSST DM Test Plan
LSE-61	LSST DM Subsystem Requirements
LSE-163	LSST Data Products Definition Document
LDM-151	LSST DM Science Pipelines Design
LSE-180	Level 2 Photometric Calibration for the LSST Survey
LSE-30	LSST Observatory System Specifications

1.4 References

- [1] **[DMTR-82]**, Arcanjo, V., Astudillo, A., Bezerra, J., et al., 2018, *Network Bandwidth Tests between Chile and the United States*, DMTR-82, URL <https://ls.st/DMTR-82>
- [2] **[LSE-30]**, Claver, C.F., The LSST Systems Engineering Integrated Project Team, 2018, *Observatory System Specifications (OSS)*, LSE-30, URL <https://ls.st/LSE-30>
- [3] **[LSE-61]**, Dubois-Felsmann, G., Jenness, T., 2018, *LSST Data Management Subsystem Requirements*, LSE-61, URL <https://ls.st/LSE-61>
- [4] **[LDM-554]**, Dubois-Felsmann, G., Ciardi, D., Mueller, F., Economou, F., 2018, *Science Platform Requirements*, LDM-554, URL <https://ls.st/LDM-554>
- [5] **[LPM-17]**, Ivezić, Ž., The LSST Science Collaboration, 2018, *LSST Science Requirements Document*, LPM-17, URL <https://ls.st/LPM-17>
- [6] **[LSE-131]**, Jacoby, S., Emmons, B., Selvy, B., 2017, *Interface between Data Management and Education and Public Outreach*, LSE-131, URL <https://ls.st/LSE-131>
- [7] **[LSE-180]**, Jones, L., 2013, *Level 2 Photometric Calibration for the LSST Survey*, LSE-180, URL <https://ls.st/LSE-180>
- [8] **[LSE-163]**, Jurić, M., et al., 2017, *LSST Data Products Definition Document*, LSE-163, URL <https://ls.st/LSE-163>

- [9] **[LDM-148]**, Lim, K.T., Bosch, J., Dubois-Felsmann, G., et al., 2018, *Data Management System Design*, LDM-148, URL <https://ls.st/LDM-148>
- [10] **[LDM-294]**, O'Mullane, W., Swinbank, J., Jurić, M., DMLT, 2018, *Data Management Organization and Management*, LDM-294, URL <https://ls.st/LDM-294>
- [11] **[LDM-503]**, O'Mullane, W., Swinbank, J., Jurić, M., Economou, F., 2018, *Data Management Test Plan*, LDM-503, URL <https://ls.st/LDM-503>
- [12] **[LDM-151]**, Swinbank, J.D., et al., 2017, *Data Management Science Pipelines Design*, LDM-151, URL <https://ls.st/LDM-151>

1.5 Acronyms

Acronym	Description
AP	Alerts Production
C	Specific programming language (also called ANSI-C)
CPP	C++ Programming language
DAC	Data Access Center
DB	DataBase
DBB	Data BackBone
DM	Data Management
DMCCB	DM Change Control Board
DMS	Data Management Sub-system
DR	Data Release
DRP	Data Release Production
EFD	Engineering Facilities Database
IT	Integration Test
IVOA	International Virtual-Observatory Alliance
K	Kelvin; SI unit of temperature
LAN	Local Area Network
LDM	LSST Data Management (handle for controlled documents)
LPM	LSST Project Management (Document Handle)
LSE	LSST Systems Engineering (Document Handle)
LSP	LSST Science Platform
LSST	Large Synoptic Survey Telescope
M	Mega; SI units prefix for 1E6

MOPS	Moving Object Pipeline System
OCS	Observatory Control System
PDAC	Prototype Data Access Center
S	Strip (CCD chip along-scan coordinate identifier in focal plane)
SODA	SCOS ORATOS Distributed Access
SQL	Structured Query Language
STS	System Test Specification
W	Watt; SI unit of power
p	pico; SI units prefix for 1E-12

2 Approach

This document describes the acceptance tests for the integrated Data Management System, with a focus on whether the data products and functionality provided satisfy the requirements described in LSE-61.

The requirements from LSE-61 are extracted into the Jira "LSST Verification and Validation" Project, managed through the Jira Test Management Plugin system. Each LSE-61 requirement leads to a "LSST Verification and Validation" (LVV) Element. Each LVV Element comprises one or more more Test Cases. Each Test Case describes a Test Script to be executed, the coverage, pre-conditions, configuration, test results, and other details as specified by LDM-503. Test Scripts may have common set up and analysis steps. The Jira system allows for these steps to be shared by other Test Scripts. This improves clarity and consistency across all Test Cases.

In this document, each Test Case is listed here with the LVV Element it tests, a summary of the Test Items exercised by the Test Case, and the detailed steps to be executed by the Test Case. Shared steps between Test Scripts have been explicitly written out to appear fully in each Test Case.

2.1 Features to be tested

All top-level requirements for the LSST Data Management System described in LSE-61 are to be tested, including

- Data Products

- Alert, Calibration and Data Release Production
- LSST science pipeline software and middleware
- LSST facilities including the data archive, base, summit, and the communications between them to accept science and engineering data

2.2 Features not to be tested

This document does not describe facilities for periodically generating or collecting key performance metrics (KPMs), except insofar as those KPMs are incidentally measured as part of executing the documented test cases.

2.3 Pass/fail criteria

The results of all tests will be assessed using the criteria described in LDM-503 §4.

Note that when executing pipelines, tasks, or individual algorithms, any unexplained or unexpected errors or warnings appearing in the associated log or on screen output must be described in the documentation for the system under test. Any warning or error for which this is not the case must be filed as a software problem report and filed with the DMCCB.

2.4 Suspension criteria and resumption requirements

Refer to individual test cases where applicable.

2.5 Naming convention

LVV : Is the label for the “LSST Verification and Validation” project in Jira.

LVV-XXX : Are Verification Elements, where XXX is the Verification Element identifier. Each Verification Element has at least one Test Case.

LVV-TYYY : Are Test Cases. Each Test Case is associated with a Verification Element, where YYY is the Test Case identifier.

The Verification Elements are drawn from LSE-61 requirements which have names of the form DMS-REQ-ZZZZ.

3 Test Cases Summary

Test Id	Test Name
LVV-T23	Verify implementation of Storing Approximations of Per-pixel Metadata
LVV-T24	Verify implementation of Computing Derived Quantities
LVV-T25	Verify implementation of Denormalizing Database Tables
LVV-T26	Verify implementation of Maximum Likelihood Values and Covariances
LVV-T27	Verify implementation of Data Availability
LVV-T28	Verify implementation of Measurements in catalogs
LVV-T29	Verify implementation of Raw Science Image Data Acquisition
LVV-T30	Verify implementation of Wavefront Sensor Data Acquisition
LVV-T31	Verify implementation of Crosstalk Corrected Science Image Data Acquisition
LVV-T32	Verify implementation of Raw Image Assembly
LVV-T33	Verify implementation of Raw Science Image Metadata
LVV-T34	Verify implementation of Guider Calibration Data Acquisition
LVV-T35	Verify implementation of Nightly Data Accessible Within 24 hrs
LVV-T36	Verify implementation of Difference Exposures
LVV-T37	Verify implementation of Difference Exposure Attributes
LVV-T38	Verify implementation of Processed Visit Images
LVV-T39	Verify implementation of Generate Photometric Zeropoint for Visit Image
LVV-T40	Verify implementation of Generate WCS for Visit Images
LVV-T41	Verify implementation of Generate PSF for Visit Images
LVV-T42	Verify implementation of Processed Visit Image Content
LVV-T43	Verify implementation of Background Model Calculation
LVV-T44	Verify implementation of Documenting Image Characterization
LVV-T45	Verify implementation of Prompt Processing Data Quality Report Definition
LVV-T46	Verify implementation of Prompt Processing Performance Report Definition
LVV-T47	Verify implementation of Prompt Processing Calibration Report Definition
LVV-T48	Verify implementation of Exposure Catalog
LVV-T49	Verify implementation of DIASource Catalog
LVV-T50	Verify implementation of Faint DIASource Measurements

Test Id	Test Name
LVV-T51	Verify implementation of DIAObject Catalog
LVV-T52	Verify implementation of DIAObject Attributes
LVV-T53	Verify implementation of SSObject Catalog
LVV-T54	Verify implementation of Alert Content
LVV-T55	Verify implementation of DIAForcedSource Catalog
LVV-T56	Verify implementation of Characterizing Variability
LVV-T57	Verify implementation of Calculating SSObject Parameters
LVV-T58	Verify implementation of Matching DIASources to Objects
LVV-T59	Verify implementation of Regenerating L1 Data Products During Data Release Processing
LVV-T60	Verify implementation of Publishing predicted visit schedule
LVV-T61	Verify implementation of Associate Sources to Objects
LVV-T62	Verify implementation of Provide PSF for Coadded Images
LVV-T63	Verify implementation of Produce Images for EPO
LVV-T64	Verify implementation of Coadded Image Provenance
LVV-T65	Verify implementation of Source Catalog
LVV-T66	Verify implementation of Forced-Source Catalog
LVV-T67	Verify implementation of Object Catalog
LVV-T68	Verify implementation of Provide Photometric Redshifts of Galaxies
LVV-T69	Verify implementation of Object Characterization
LVV-T71	Verify implementation of Detecting extended low surface brightness objects
LVV-T72	Verify implementation of Coadd Image Method Constraints
LVV-T73	Verify implementation of Deep Detection Coadds
LVV-T74	Verify implementation of Template Coadds
LVV-T75	Verify implementation of Multi-band Coadds
LVV-T76	Verify implementation of All-Sky Visualization of Data Releases
LVV-T77	Verify implementation of Best Seeing Coadds
LVV-T78	Verify implementation of Persisting Data Products
LVV-T79	Verify implementation of PSF-Matched Coadds
LVV-T80	Verify implementation of Detecting faint variable objects
LVV-T81	Verify implementation of Targeted Coadds
LVV-T82	Verify implementation of Tracking Characterization Changes Between Data Releases

Test Id	Test Name
LVV-T83	Verify implementation of Bad Pixel Map
LVV-T84	Verify implementation of Bias Residual Image
LVV-T85	Verify implementation of Crosstalk Correction Matrix
LVV-T86	Verify implementation of Illumination Correction Frame
LVV-T87	Verify implementation of Monochromatic Flatfield Data Cube
LVV-T88	Verify implementation of Calibration Data Products
LVV-T89	Verify implementation of Calibration Image Provenance
LVV-T90	Verify implementation of Dark Current Correction Frame
LVV-T91	Verify implementation of Fringe Correction Frame
LVV-T92	Verify implementation of Processing of Data From Special Programs
LVV-T93	Verify implementation of Level 1 Processing of Special Programs Data
LVV-T94	Verify implementation of Special Programs Database
LVV-T95	Verify implementation of Constraints on Level 1 Special Program Products Generation
LVV-T96	Verify implementation of Query Repeatability
LVV-T97	Verify implementation of Uniqueness of IDs Across Data Releases
LVV-T98	Verify implementation of Selection of Datasets
LVV-T99	Verify implementation of Processing of Datasets
LVV-T100	Verify implementation of Transparent Data Access
LVV-T101	Verify implementation of Transient Alert Distribution
LVV-T102	Verify implementation of Solar System Objects Available Within Specified Time
LVV-T103	Verify implementation of Generate Data Quality Report Within Specified Time
LVV-T104	Verify implementation of Generate DMS Performance Report Within Specified Time
LVV-T105	Verify implementation of Generate Calibration Report Within Specified Time
LVV-T106	Verify implementation of Calibration Images Available Within Specified Time
LVV-T107	Verify implementation of Level-1 Production Completeness
LVV-T108	Verify implementation of Level 1 Source Association
LVV-T109	Verify implementation of SSObject Precoversy
LVV-T110	Verify implementation of DIASource Precoversy

Test Id	Test Name
LVV-T111	Verify implementation of Use of External Orbit Catalogs
LVV-T112	Verify implementation of Alert Filtering Service
LVV-T113	Verify implementation of Performance Requirements for LSST Alert Filtering Service
LVV-T114	Verify implementation of Pre-defined alert filters
LVV-T115	Verify implementation of Calibration Production Processing
LVV-T116	Verify implementation of Associating Objects across data releases
LVV-T117	Verify implementation of DAC resource allocation for Level 3 processing
LVV-T118	Verify implementation of Level 3 Data Product Self Consistency
LVV-T119	Verify implementation of Provenance for Level 3 processing at DACs
LVV-T120	Verify implementation of Software framework for Level 3 catalog processing
LVV-T121	Verify implementation of Software framework for Level 3 image processing
LVV-T122	Verify implementation of Level 3 Data Import
LVV-T123	Verify implementation of Access Controls of Level 3 Data Products
LVV-T124	Verify implementation of Software Architecture to Enable Community Re-Use
LVV-T125	Verify implementation of Simulated Data
LVV-T126	Verify implementation Image Differencing
LVV-T127	Verify implementation of Provide Source Detection Software
LVV-T128	Verify implementation Provide Astrometric Model
LVV-T129	Verify implementation of Provide Calibrated Photometry
LVV-T130	Verify implementation of Enable a Range of Shape Measurement Approaches
LVV-T131	Verify implementation of Provide User Interface Services
LVV-T132	Verify implementation of Pre-cursor and Real Data
LVV-T133	Verify implementation of Provide Beam Projector Coordinate Calculation Software
LVV-T134	Verify implementation of Provide Image Access Services
LVV-T136	Verify implementation of Data Product and Raw Data Access
LVV-T137	Verify implementation of Data Product Ingest
LVV-T138	Verify implementation of Bulk Download Service
LVV-T140	Verify implementation of Production Orchestration

Test Id	Test Name
LVV-T141	Verify implementation of Production Monitoring
LVV-T142	Verify implementation of Production Fault Tolerance
LVV-T144	Verify implementation of Task Specification
LVV-T145	Verify implementation of Task Configuration
LVV-T146	Verify implementation of DMS Initialization Component
LVV-T147	Verify implementation of Control of Level-1 Production
LVV-T148	Verify implementation of Unique Processing Coverage
LVV-T149	Verify implementation of Catalog Queries
LVV-T150	Verify implementation of Maintain Archive Publicly Accessible
LVV-T151	Verify Implementation of Catalog Export Formats From the Notebook Aspect
LVV-T152	Verify implementation of Keep Historical Alert Archive
LVV-T153	Verify implementation of Provide Engineering and Facility Database Archive
LVV-T154	Verify implementation of Raw Data Archiving Reliability
LVV-T155	Verify implementation of Un-Archived Data Product Cache
LVV-T156	Verify implementation of Regenerate Un-archived Data Products
LVV-T157	Verify implementation Level 1 Data Product Access
LVV-T158	Verify implementation Level 1 and 2 Catalog Access
LVV-T159	Verify implementation of Regenerating Data Products from Previous Data Releases
LVV-T160	Verify implementation of Providing a Precovery Service
LVV-T161	Verify implementation of Logging of catalog queries
LVV-T162	Verify implementation of Access to Previous Data Releases
LVV-T163	Verify implementation of Data Access Services
LVV-T164	Verify implementation of Operations Subsets
LVV-T165	Verify implementation of Subsets Support
LVV-T166	Verify implementation of Access Services Performance
LVV-T167	Verify Capability to serve older Data Releases at Full Performance
LVV-T168	Verify design of Data Access Services allows Evolution of the LSST Data Model
LVV-T169	Verify implementation of Older Release Behavior
LVV-T170	Verify implementation of Query Availability
LVV-T171	Verify implementation of Pipeline Availability

Test Id	Test Name
LVV-T172	Verify implementation of Optimization of Cost, Reliability and Availability
LVV-T173	Verify implementation of Pipeline Throughput
LVV-T174	Verify implementation of Re-processing Capacity
LVV-T175	Verify implementation of Temporary Storage for Communications Links
LVV-T176	Verify implementation of Infrastructure Sizing for “catching up”
LVV-T177	Verify implementation of Incorporate Fault-Tolerance
LVV-T178	Verify implementation of Incorporate Autonomics
LVV-T179	Verify implementation of Compute Platform Heterogeneity
LVV-T180	Verify implementation of Data Management Unscheduled Downtime
LVV-T181	Verify integration of Summit Facility Data Communications
LVV-T182	Verify implementation of Prefer Computing and Storage Down
LVV-T183	Verify implementation of DMS Communication with OCS
LVV-T185	Verify implementation of Summit to Base Network Availability
LVV-T186	Verify implementation of Summit to Base Network Reliability
LVV-T187	Verify implementation of Summit to Base Network Secondary Link
LVV-T188	Verify implementation of Summit to Base Network Ownership and Operation
LVV-T189	Verify implementation of Base Facility Infrastructure
LVV-T190	Verify implementation of Base Facility Co-Location with Existing Facility
LVV-T191	Verify implementation of Commissioning Cluster
LVV-T192	Verify implementation of Base Wireless LAN (WiFi)
LVV-T193	Verify implementation of Base to Archive Network
LVV-T194	Verify implementation of Base to Archive Network Availability
LVV-T195	Verify implementation of Base to Archive Network Reliability
LVV-T196	Verify implementation of Base to Archive Network Secondary Link
LVV-T197	Verify implementation of Archive Center
LVV-T198	Verify implementation of Archive Center Disaster Recovery
LVV-T199	Verify implementation of Archive Center Co-Location with Existing Facility
LVV-T200	Verify implementation of Archive to Data Access Center Network
LVV-T201	Verify implementation of Archive to Data Access Center Network Availability
LVV-T202	Verify implementation of Archive to Data Access Center Network Reliability

Test Id	Test Name
LVV-T203	Verify implementation of Archive to Data Access Center Network Secondary Link
LVV-T204	Verify implementation of Access to catalogs for external Level 3 processing
LVV-T205	Verify implementation of Access to input catalogs for DAC-based Level 3 processing
LVV-T206	Verify implementation of Federation with external catalogs
LVV-T207	Verify implementation of Access to images for external Level 3 processing
LVV-T208	Verify implementation of Access to input images for DAC-based Level 3 processing
LVV-T209	Verify implementation of Data Access Centers
LVV-T210	Verify implementation of Data Access Center Simultaneous Connections
LVV-T211	Verify implementation of Data Access Center Geographical Distribution
LVV-T212	Verify implementation of No Limit on Data Access Centers
LVV-T376	Verify the Calculation of Ellipticity Correlations
LVV-T377	Verify Calculation of Photometric Performance Metrics
LVV-T378	Verify Calculation of Astrometric Performance Metrics
LVV-T385	Verify implementation of minimum number of simultaneous retrievals of CCD-sized coadd cutouts
LVV-T1097	Verify Summit to Base Network Implementation
LVV-T1168	Test Summit - Base Network Integration
LVV-T1232	Verify Implementation of Catalog Export Formats From the Portal Aspect
LVV-T1240	Verify implementation of minimum astrometric standards per CCD
LVV-T1250	Verify implementation of minimum number of simultaneous DM EFD query users
LVV-T1251	Verify implementation of maximum time to retrieve DM EFD query results
LVV-T1252	Verify number of simultaneous alert filter users
LVV-T1264	Verify implementation of archiving camera test data
LVV-T1276	Verify implementation of latency of reporting optical transients
LVV-T1277	Verify processing of maximum number of calibration exposures
LVV-T1332	Verify implementation of maximum time for retrieval of CCD-sized coadd cutouts

4 Active Test Cases

This section documents all active test cases that have a status in the Jira/ATM system of Draft, Defined or Approved.

4.1 LVV-T23 - Verify implementation of Storing Approximations of Per-pixel Metadata

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Simon Krughoff

4.1.1 Verification Elements

- LVV-157 - DMS-REQ-0326-V-01: Storing Approximations of Per-pixel Metadata

4.1.2 Test Items

Test Items

Show that the compressed form depth and mask maps adequately represents the exact version of the same information.

4.1.3 Predecessors

4.1.4 Environment Needs

4.1.4.1 Software

4.1.4.2 Hardware

4.1.5 Input Specification

Test data: A data repository containing a full DRP data reduction of the HSC PDR dataset.

4.1.6 Output Specification

4.1.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T12	Description	The DM Stack shall be initialized using the loadLSST script (as described in DRP-00-00).
	Test Data	
	Expected	
	Result	
1-2 from LVV-T12	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected	
	Result	
1-3 from LVV-T12	Description	For each of the expected data products types (listed in Test Items section §4.3.2) and each of the expected units (PVLs, coadds, etc), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected	
	Result	
2	Description	Create the coadd pixel level depth map for the HSC PDR dataset from step 1.
	Test Data	No data.
	Expected	
	Result	
3	Description	Generate compressed representation of the pixel level depth map.
	Test Data	No data.
	Expected	
	Result	
4	Description	Create the coadd pixel level mask map for the HSC PDR dataset from step 1.
	Test Data	No data.
	Expected	
	Result	
5	Description	Generate compressed representation of the mask map.
	Test Data	No data.
	Expected	
	Result	

Step	Description, Input Data and Expected Result	
6	Description	Sample randomly from both the pixel level and compressed depth maps. Compare the distribution of depths sampled from the pixel level depth map to that sampled from the compressed representation.
	Test Data	No data.
	Expected Result	
7	Description	Divide the mask planes into two groups: INFO and BAD. BAD flags are any that would cause a particular pixel to be excluded from processing: e.g. EDGE, SAT, BAD. Sample masks from both the pixel level mask map and the compressed mask map. For each sample, compute $\text{sum}(\text{mask_pixel} \text{ xor } \text{mask_compressed})$. Produce the distribution of the number of bits that differ between the samples. Repeat for both the INFO flags and the BAD flags.
	Test Data	No data.
	Expected Result	

4.2 LVV-T24 - Verify implementation of Computing Derived Quantities

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Melissa Graham

4.2.1 Verification Elements

- LVV-162 - DMS-REQ-0331-V-01: Computing Derived Quantities

4.2.2 Test Items

To confirm that common derived quantities (apparent magnitude, FWHM in arcsec, ellipticity) are available to an end-user by, e.g., ensuring a color-color diagram is easy to construction, fitting functions to derived data, or generating other common scientific derivatives.

4.2.3 Predecessors

4.2.4 Environment Needs

4.2.4.1 Software

4.2.4.2 Hardware

4.2.5 Input Specification

Example data set (e.g., non-LSST or LSST commissioning) loaded into the Science Platform in a format consistent with the DPDD.

4.2.6 Output Specification

4.2.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T12	Description	The DM Stack shall be initialized using the loadLSST script (as described in DRP-00-00).
	Test Data	
	Expected	
	Result	
1-2 from LVV-T12	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected	
	Result	
1-3 from LVV-T12	Description	For each of the expected data products types (listed in Test Items section §4.3.2) and each of the expected units (PVI, coadds, etc), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected	
	Result	
2	Description	Load into DPDD+Science Platform
	Test Data	No data.
	Expected	
	Result	

Step	Description, Input Data and Expected Result	
3	Description	Constructing color-color diagram and fitting stellar locus in Science Platform.
	Test Data	No data.
	Expected Result	
4	Description	Invite three members of commissioning team to create color-color diagram from coadd catalogs based on merged coadd reference catalog.
	Test Data	No data.
	Expected Result	

4.3 LVV-T25 - Verify implementation of Denormalizing Database Tables

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.3.1 Verification Elements

- LVV-163 - DMS-REQ-0332-V-01: Denormalizing Database Tables

4.3.2 Test Items

Verify that commonly useful views of data are easy to obtain through the Science Platform.

4.3.3 Predecessors

4.3.4 Environment Needs

4.3.4.1 Software

4.3.4.2 Hardware

4.3.5 Input Specification

4.3.6 Output Specification

4.3.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Connect to the Science Platform's portal query interface.
	Test Data	No data.
	Expected Result	
2	Description	List the available views in the database.
	Test Data	No data.
	Expected Result	
3	Description	Take 20 sampled queries and determine which are easily done on views and which require complicated joins. Discuss the complicated ones and determine if any could be simplified by adding additional views.
	Test Data	No data.
	Expected Result	

4.4 LVV-T26 - Verify implementation of Maximum Likelihood Values and Covariances

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.4.1 Verification Elements

- LVV-164 - DMS-REQ-0333-V-01: Maximum Likelihood Values and Covariances

4.4.2 Test Items

- Check that all measurements in source and object schemas include columns containing uncertainties, including covariances between jointly-measured quantities.

- Check that all model-fit measurements in source and object schemas include columns that report goodness-of-fit.
- Check that most sources and objects with successful measurements report finite uncertainty values for those measurements.
- Check that most sources and objects with successful model-fit measurements report finite goodness-of-fit values.

4.4.3 Predecessors

4.4.4 Environment Needs

4.4.4.1 Software

4.4.4.2 Hardware

4.4.5 Input Specification

4.4.6 Output Specification

4.4.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T12	Description	The DM Stack shall be initialized using the loadLSST script (as described in DRP-00-00).
	Test Data	
	Expected	
	Result	
1-2 from LVV-T12	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected	
	Result	
1-3 from LVV-T12	Description	For each of the expected data products types (listed in Test Items section §4.3.2) and each of the expected units (PVLs, coadds, etc), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected	
	Result	

Step	Description, Input Data and Expected Result
2	Description
	Verify that maximum likelihood and covariant quantities are provided. Test and manually inspect that they are reasonable (finite, appropriately normed).
	Test Data
	No data.
	Expected Result

4.5 LVV-T27 - Verify implementation of Data Availability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Gregory Dubois-Felsmann

4.5.1 Verification Elements

- LVV-177 - DMS-REQ-0346-V-01: Data Availability

4.5.2 Test Items

Determine if all required categories of raw data (specifically enumerated: raw exposures, calibration frames, telemetry, configuration metadata) can be located through the Science Platform and are available for download. Verify through (1) administrative review; (2) checking with precursor data; (3) checking on early data feeds from the Summit such as from AuxTel and ComCam.

4.5.3 Predecessors

4.5.4 Environment Needs

4.5.4.1 Software

4.5.4.2 Hardware

4.5.5 Input Specification

4.5.6 Output Specification

4.5.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Invite two reviewers to review that plan that seems reasonable to expect the archiving and provision of raw data
	Test Data	No data.
	Expected Result	
2	Description	Pass a set of HSC data through (equal in size to the first public data release) the data backbone through ingest and provide interface
	Test Data	No data.
	Expected Result	
3	Description	Track the ingestion of AuxTel data during one month in 2018-2019 and verify delivery and test download.
	Test Data	No data.
	Expected Result	

4.6 LVV-T28 - Verify implementation of Measurements in catalogs

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.6.1 Verification Elements

- LVV-178 - DMS-REQ-0347-V-01: Measurements in catalogs

4.6.2 Test Items

Verify that source measurements in catalogs are in flux units.

4.6.3 Predecessors

4.6.4 Environment Needs

4.6.4.1 Software

4.6.4.2 Hardware

4.6.5 Input Specification

4.6.6 Output Specification

4.6.7 Test Procedure

Step	Description, Input Data and Expected Result
1-1 from LVV-T18	Description The DM Stack and Alert Processing packaged shall be initialized as described in LVT-T17 (AG-00-00).
	Test Data
	Expected
	Result
1-2 from LVV-T18	Description The alert generation processing will be executed using the verification cluster:
	<pre> "bash python ap_verify/bin/prepare_demo_slurm_files.py # At present we must run a single ccd+visit to handle ingestion before # parallel processing can begin ./ap_verify/bin/exec_demo_run_1ccd.sh 410915 25 ln -s ap_verify/bin/demo_run.sl ln -s ap_verify/bin/demo_cmds.conf sbatch demo_run.sl "</pre>
	and any errors or failures reported.
	Test Data
1-3 from LVV-T18	Expected
	Result
	Description A "Data Butler" will be initialized to access the repository.
	Test Data

Step	Description, Input Data and Expected Result	
	Expected Result	
1-4 from LVV-T18	Description	For each of the expected data products types (listed in §4.2.2) and each of the expected units (PVIs, catalogs, etc.), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected Result	
1-5 from LVV-T18	Description	DIAObjects are currently only stored in a database, without shims to the Butler, so the existence of the database table and its non-empty contents will be verified by directly accessing it using sqlite3 and executing appropriate SQL queries.
	Test Data	
	Expected Result	
2-1 from LVV-T12	Description	The DM Stack shall be initialized using the loadLSST script (as described in DRP-00-00).
	Test Data	
	Expected Result	
2-2 from LVV-T12	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected Result	
2-3 from LVV-T12	Description	For each of the expected data products types (listed in Test Items section §4.3.2) and each of the expected units (PVIs, coadds, etc), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected Result	
3	Description	Verify that each of the single-visit, coadd, and difference image catalogs from HSC reprocessing and HiTS reprocessing (which may be the first source of regular difference images) provide measurements in flux units.
	Test Data	No data.
	Expected Result	

4.7 LVV-T29 - Verify implementation of Raw Science Image Data Acquisition

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Kian-Tat Lim

4.7.1 Verification Elements

- LVV-8 - DMS-REQ-0018-V-01: Raw Science Image Data Acquisition

4.7.2 Test Items

Verify acquisition of raw data from L1 Test Stand DAQ while simulating all modes

4.7.3 Predecessors

4.7.4 Environment Needs

4.7.4.1 Software

4.7.4.2 Hardware

4.7.5 Input Specification

4.7.6 Output Specification

4.7.7 Test Procedure

Step	Description, Input Data and Expected Result		
1	Description	Ingest raw data from L1 Test Stand DAQ, simulating each observing mode	
	Test Data	No data.	
	Expected Result		
2	Description	Observe image and its metadata is present and queryable in the Data Backbone.	
	Test Data	No data.	

Step	Description, Input Data and Expected Result
Expected Result	Well-formed image data with appropriate associated metadata.

4.8 LVV-T30 - Verify implementation of Wavefront Sensor Data Acquisition

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Kian-Tat Lim

4.8.1 Verification Elements

- LVV-9 - DMS-REQ-0020-V-01: Wavefront Sensor Data Acquisition

4.8.2 Test Items

Verify successful ingestion of wavefront sensor data from L1 Test Stand DAQ while simulating all modes.

4.8.3 Predecessors

4.8.4 Environment Needs

4.8.4.1 Software

4.8.4.2 Hardware

4.8.5 Input Specification

4.8.6 Output Specification

4.8.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Ingest wavefront sensor data from L1 Test Stand DAQ while simulating all modes
	Test Data	No data.
	Expected Result	
2	Description	Observe wavefront sensor data and metadata archived in the Data Backbone.
	Test Data	No data.
	Expected Result	Well-formed wavefront sensor image data with appropriate associated metadata.

4.9 LVV-T31 - Verify implementation of Crosstalk Corrected Science Image Data Acquisition

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.9.1 Verification Elements

- LVV-10 - DMS-REQ-0022-V-01: Crosstalk Corrected Science Image Data Acquisition

4.9.2 Test Items

Verify successful ingestion of crosstalk corrected data from L1 Test Stand DAQ while simulating all modes.

4.9.3 Predecessors

4.9.4 Environment Needs

4.9.4.1 Software

4.9.4.2 Hardware

4.9.5 Input Specification

4.9.6 Output Specification

4.9.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Inject signals of different relative strength
	Test Data	No data.
	Expected Result	
2	Description	Apply Camera cross-talk correction
	Test Data	No data.
	Expected Result	
3	Description	Verify that DMS system can import the cross-talk corrected images
	Test Data	No data.
	Expected Result	
4	Description	Verify that images are corrected for crosstalk
	Test Data	No data.
	Expected Result	

4.10 LVV-T32 - Verify implementation of Raw Image Assembly

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Kian-Tat Lim

4.10.1 Verification Elements

- LVV-11 - DMS-REQ-0024-V-01: Raw Image Assembly

4.10.2 Test Items

Verify that the raw exposure data from all readout channels in a sensor can be assembled into a single image, and that all required/relevant metadata are associated with the image data.

4.10.3 Predecessors

4.10.4 Environment Needs

4.10.4.1 Software

4.10.4.2 Hardware

4.10.5 Input Specification

4.10.6 Output Specification

4.10.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Ingest data from the L1 Camera Test Stand DAQ.
	Test Data	No data.
	Expected Result	
2	Description	Simulate all different modes of data gathering.
	Test Data	No data.
	Expected Result	
3	Description	Verify that a raw image is constructed in correct format.
	Test Data	No data.
	Expected Result	A single raw image combining data from all readout channels for a given sensor.
4	Description	Verify that a raw image is constructed with correct metadata.
	Test Data	No data.

Step	Description, Input Data and Expected Result	
	Expected Result	Image header or ancillary table contains the required metadata about the observing context in which data were gathered.

4.11 LVV-T33 - Verify implementation of Raw Science Image Metadata

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Kian-Tat Lim

4.11.1 Verification Elements

- LVV-28 - DMS-REQ-0068-V-01: Raw Science Image Metadata
- LVV-1234 - OSS-REQ-0122-V-01: Provenance

4.11.2 Test Items

Verify successful ingestion of raw data from L1 Test Stand DAQ and that image metadata is present and queryable.

4.11.3 Predecessors

4.11.4 Environment Needs

4.11.4.1 Software

4.11.4.2 Hardware

4.11.5 Input Specification

4.11.6 Output Specification

4.11.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T29	Description	Ingest raw data from L1 Test Stand DAQ, simulating each observing mode
	Test Data	
	Expected	
	Result	
1-2 from LVV-T29	Description	Observe image and its metadata is present and queryable in the Data Backbone.
	Test Data	
	Expected	Well-formed image data with appropriate associated metadata.
	Result	
2-1 from LVV-T32	Description	Ingest data from the L1 Camera Test Stand DAQ.
	Test Data	
	Expected	
	Result	
2-2 from LVV-T32	Description	Simulate all different modes of data gathering.
	Test Data	
	Expected	
	Result	
2-3 from LVV-T32	Description	Verify that a raw image is constructed in correct format.
	Test Data	
	Expected	A single raw image combining data from all readout channels for a given sensor.
	Result	
2-4 from LVV-T32	Description	Verify that a raw image is constructed with correct metadata.
	Test Data	
	Expected	Image header or ancillary table contains the required metadata about the observing context in which data were gathered.
	Result	
3	Description	Verify that time of exposure start/end, site metadata, telescope metadata, and camera metadata are stored in DMS system.
	Test Data	No data.
	Expected	Raw image data contain the required metadata.
	Result	

4.12 LVV-T34 - Verify implementation of Guider Calibration Data Acquisition

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Kian-Tat Lim

4.12.1 Verification Elements

- LVV-96 - DMS-REQ-0265-V-01: Guider Calibration Data Acquisition

4.12.2 Test Items

Verify successful

1. Ingestion of calibration frames from L1 Test Stand DAQ
2. Execution of CPP payloads
3. Availability of observed guider calibration products

4.12.3 Predecessors

4.12.4 Environment Needs

4.12.4.1 Software

4.12.4.2 Hardware

4.12.5 Input Specification

4.12.6 Output Specification

4.12.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Ingest calibration frames for the guider sensors from L1 Test Stand DAQ
	Test Data	No data.
	Expected Result	

Step	Description, Input Data and Expected Result	
2-1 from LVV-T1060	Description	Execute the Calibration Products Production payload. The payload uses raw calibration images and information from the Transformed EFD to generate a subset of Master Calibration Images and Calibration Database entries in the Data Backbone.
	Test Data	
	Expected Result	
2-2 from LVV-T1060	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present and well-formed.
	Test Data	
	Expected Result	
3	Description	Observe that guider calibration products have been produced.
	Test Data	No data.
	Expected Result	Well-formed calibration frames for the guider sensors.

4.13 LVV-T35 - Verify implementation of Nightly Data Accessible Within 24 hrs

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.13.1 Verification Elements

- LVV-175 - DMS-REQ-0004-V-01: Time to L1 public release

4.13.2 Test Items

Test Items

Verify that

1. Alerts are available within OTT1
2. Level 1 Data Products are available within L1PublicT

3. Solar System Object orbits are available within L1PublicT of the updated calculations completion on the following night.

4.13.3 Predecessors

4.13.4 Environment Needs

4.13.4.1 Software

4.13.4.2 Hardware

4.13.5 Input Specification

4.13.6 Output Specification

4.13.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T18	Description	The DM Stack and Alert Processing packaged shall be initialized as described in LVT-T17 (AG-00-00).
	Test Data	
	Expected Result	
1-2 from LVV-T18	Description	The alert generation processing will be executed using the verification cluster:
	Test Data	<pre> """bash python ap_verify/bin/prepare_demo_slurm_files.py # At present we must run a single ccd+visit to handle ingestion before # parallel processing can begin ./ap_verify/bin/exec_demo_run_1ccd.sh 410915 25 ln -s ap_verify/bin/demo_run.sl ln -s ap_verify/bin/demo_cmds.conf sbatch demo_run.sl """ </pre>
	Expected Result	and any errors or failures reported.
	Test Data	
	Expected Result	
	Result	

Step	Description, Input Data and Expected Result	
1-3 from LVV-T18	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected	
	Result	
1-4 from LVV-T18	Description	For each of the expected data products types (listed in §4.2.2) and each of the expected units (PVIs, catalogs, etc.), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected	
	Result	
1-5 from LVV-T18	Description	DIAObjects are currently only stored in a database, without shims to the Butler, so the existence of the database table and its non-empty contents will be verified by directly accessing it using sqlite3 and executing appropriate SQL queries.
	Test Data	
	Expected	
	Result	
2-1 from LVV-T217	Description	
	Test Data	
	Expected	
	Result	
2-2 from LVV-T217	Description	Start a consumer that monitors the full stream and logs a deserialized version of every Nth packet:
	Test Data	
	Expected	Runs without error
	Result	
2-3 from LVV-T217	Description	Start a producer that reads alert packets from disk and loads them into the Kafka queue:
	Test Data	
	Expected	Runs without error
	Result	

Step	Description, Input Data and Expected Result	
2-4 from LVV-T217	Description	Determine the name of the alert sender pod with
		kubectl get pods
		Examine output log files.
		kubectl logs <pod name>
		Verify that alerts are being sent within 40 seconds by subtracting the timing measurements.
	Test Data	
	Expected Result	Similar to
		kubectl logs sender-7d6f98586f-nhwhj visit: 1570. time: 1530588618.0313473 visits finished: 1 time: 1530588653.5614944 visit: 1571. time: 1530588657.0087624 visits finished: 2 time: 1530588692.506188 visit: 1572. time: 1530588696.0051727 visits finished: 3 time: 1530588731.5900314
2-5 from LVV-T217	Description	Determine the name of the consumer pod with
		kubectl get pods
		Examine output log files.
		kubectl logs <pod name>
		The packet log should show deserialized alert packets with contents matching the input packets.
	Test Data	

Step	Description, Input Data and Expected Result	
	Expected Result	Similar to { 'alertId': 12132024420, 'idbld': 71776805594116, 'diaSource': { 'diaSourceId': 73499448928374785, 'ccdVisitId': 2020011570, 'diaObjectId': 71776805594116, 'ssObjectId': None, 'parentDiaSourceId': None, 'midPointTai': 59595.37041, 'filterName': 'y', 'ra': 172.24912810036074, 'decl': -80.64214929176521, 'ra_decl_Cov': { 'raSigma': 0.0003428002819418907, 'declSigma': 0.00027273103478364646, 'ra_decl_Cov': 0.000628734880592674}, 'x': 2979.08837890625, 'y': 3843.328857421875, 'x_y_Cov': { 'xSigma': 0.6135467886924744, 'ySigma': 0.77132648229599, 'x_y_Cov': 0.007463791407644749}, 'apFlux': None, 'apFluxErr': None, 'snr': 0.36651650071144104, 'psFlux': 7.698232025177276e-07, 'psRa': None, 'psDecl': None, 'ps_Cov': None, 'psLnL': None, 'psChi2': None, 'psNdata': None, 'trailFlux': None, 'trailRa': etc.
3	Description	Time processing of data starting from (pre-ingested) raw files until an alert is available for distribution; verify that this time is less than OTT1.
	Test Data	No data.
	Expected Result	
4	Description	Time processing of data starting from (pre-ingested) raw files until the required data products are available in the Science Platform. Verify that this time is less than L1PublicT.
	Test Data	No data.
	Expected Result	
5	Description	Run MOPS on 1 night equivalent of LSST observing worth of precursor data and verify that Solar System Object orbits can be updated within 24 hours.
	Test Data	No data.
	Expected Result	
6	Description	Record time between completion of MOPS processing and availability of the updated SSO object catalogue through the Science Platform; verify this time is less than L1PublicT.
	Test Data	No data.
	Expected Result	

4.14 LVV-T36 - Verify implementation of Difference Exposures

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.14.1 Verification Elements

- LVV-7 - DMS-REQ-0010-V-01: Difference Exposures

4.14.2 Test Items

Verify successful creation of a

1. PSF-matched template image for a given Processed Visit Image
2. Difference Exposure from each Processed Visit Image

4.14.3 Predecessors

4.14.4 Environment Needs

4.14.4.1 Software

4.14.4.2 Hardware

4.14.5 Input Specification

4.14.6 Output Specification

4.14.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T18	Description	The DM Stack and Alert Processing packaged shall be initialized as described in LVT-T17 (AG-00-00).
	Test Data	
	Expected	
	Result	

Step	Description, Input Data and Expected Result	
1-2 from LVV-T18	Description	The alert generation processing will be executed using the verification cluster:
		<pre> "bash python ap_verify/bin/prepare_demo_slurm_files.py # At present we must run a single ccd+visit to handle ingestion before # parallel processing can begin ./ap_verify/bin/exec_demo_run_1ccd.sh 410915 25 ln -s ap_verify/bin/demo_run.sl ln -s ap_verify/bin/demo_cmds.conf sbatch demo_run.sl " </pre>
	Test Data	and any errors or failures reported.
1-3 from LVV-T18	Expected Result	
	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
1-4 from LVV-T18	Expected Result	
	Description	For each of the expected data products types (listed in §4.2.2) and each of the expected units (PVI, catalogs, etc.), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
1-5 from LVV-T18	Expected Result	
	Description	DIAObjects are currently only stored in a database, without shims to the Butler, so the existence of the database table and its non-empty contents will be verified by directly accessing it using sqlite3 and executing appropriate SQL queries.
	Test Data	
2	Expected Result	
	Description	Demonstrate successful creation of a template image from HSC PDF and DECam HiTS data. Demonstrate successful creation of a Difference Exposure for at least 10 other images from survey, ideally at a range of airmass. In particular, HiTS has 2013A u-band data. While the Blanco 4-m does have an ADC, there are still some chromatic effects and we should demonstrate that we can successfully produce Difference Exposures and templates for different airmass bins.
	Test Data	No data.

Step	Description, Input Data and Expected Result
------	---

Expected Result

4.15 LVV-T37 - Verify implementation of Difference Exposure Attributes

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.15.1 Verification Elements

- LVV-32 - DMS-REQ-0074-V-01: Difference Exposure Attributes
- LVV-1234 - OSS-REQ-0122-V-01: Provenance

4.15.2 Test Items

Verify that for each Difference Exposure the DMS stores

1. The identify of the input exposures and related provenance information
2. Metadata attributes of the subtraction, including the PSF-matching kernel used.

4.15.3 Predecessors

4.15.4 Environment Needs

4.15.4.1 Software

4.15.4.2 Hardware

4.15.5 Input Specification

4.15.6 Output Specification

4.15.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T18	Description	The DM Stack and Alert Processing packaged shall be initialized as described in LVT-T17 (AG-00-00).
	Test Data	
	Expected	
	Result	
1-2 from LVV-T18	Description	The alert generation processing will be executed using the verification cluster:
	Test Data	
	Expected	<pre> "bash python ap_verify/bin/prepare_demo_slurm_files.py # At present we must run a single ccd+visit to handle ingestion before # parallel processing can begin ./ap_verify/bin/exec_demo_run_1ccd.sh 410915 25 ln -s ap_verify/bin/demo_run.sl ln -s ap_verify/bin/demo_cmds.conf sbatch demo_run.sl "</pre>
	Result	and any errors or failures reported.
1-3 from LVV-T18	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected	
	Result	
1-4 from LVV-T18	Description	For each of the expected data products types (listed in §4.2.2) and each of the expected units (PVI, catalogs, etc.), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected	
	Result	
1-5 from LVV-T18	Description	DIAObjects are currently only stored in a database, without shims to the Butler, so the existence of the database table and its non-empty contents will be verified by directly accessing it using sqlite3 and executing appropriate SQL queries.
	Test Data	
	Expected	
	Result	

Step	Description, Input Data and Expected Result	
2	Description	For each of HSC PDR and DECam HiTS data: set up three different templates and run subtractions on 10 different images from at least two different filters. Verify that we can recover the provenance information about which template was used for each subtraction, which input images were used for that template, and that we can successfully extract the PSF matching kernel.
	Test Data	No data.
	Expected Result	

4.16 LVV-T38 - Verify implementation of Processed Visit Images

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Eric Bellm

4.16.1 Verification Elements

- LVV-29 - DMS-REQ-0069-V-01: Processed Visit Images

4.16.2 Test Items

Verify that the DMS

1. Successfully produces Processed Visit Images, where the instrument signature has been removed.
2. Successfully combines images obtained during a standard visit.

4.16.3 Predecessors

4.16.4 Environment Needs

4.16.4.1 Software

4.16.4.2 Hardware

4.16.5 Input Specification

4.16.6 Output Specification

4.16.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Identify suitable precursor datasets containing unprocessed raw images.
	Test Data	No data.
	Expected Result	
2	Description	Run the Prompt Processing payload on these data. Verify that Processed Visit Images are generated at correct size and with significant instrumental artifacts removed.
	Test Data	No data.
	Expected Result	Raw precursor dataset images have been processed into Processed Visit Images, with instrumental artifacts corrected.
3	Description	Run camera test stand data through full acquisition+backbone+ISR.
	Test Data	No data.
	Expected Result	
4	Description	Run simulated LSST data with calibrations through prompt processing system and inspect Processed Visit images to verify that they have been cleaned of significant artifacts and are of the correct, shape, and described orientation.
	Test Data	No data.
	Expected Result	Raw images have been processed into Processed Visit Images, with instrumental artifacts corrected.

4.17 LVV-T39 - Verify implementation of Generate Photometric Zeropoint for Visit Image

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.17.1 Verification Elements

- LVV-12 - DMS-REQ-0029-V-01: Generate Photometric Zeropoint for Visit Image

4.17.2 Test Items

Verify that Processed Visit Image data products produced by the DRP and AP pipelines include the parameters of a model that relates the observed flux on the image to physical flux units.

4.17.3 Predecessors

4.17.4 Environment Needs

4.17.4.1 Software

4.17.4.2 Hardware

4.17.5 Input Specification

4.17.6 Output Specification

4.17.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to Alert Production
	Test Data	No data.
	Expected	
	Result	

4.18 LVV-T40 - Verify implementation of Generate WCS for Visit Images

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Jim Bosch

4.18.1 Verification Elements

- LVV-13 - DMS-REQ-0030-V-01: Absolute accuracy of WCS

4.18.2 Test Items

Verify that Processed Visit Images produced by the AP and DRP pipelines include FITS WCS accurate to specified **astrometricAccuracy** over the bounds of the image.

4.18.3 Predecessors

4.18.4 Environment Needs

4.18.4.1 Software

4.18.4.2 Hardware

4.18.5 Input Specification

4.18.6 Output Specification

4.18.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T987	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the following:
	Test Data	
	Expected Result	Butler repo available for reading.
2	Description	Ingest data from an appropriate processed dataset.
	Test Data	No data.
	Expected Result	
3	Description	Select a single visit from the dataset, and extract its WCS object and the source list.
	Test Data	No data.

Step	Description, Input Data and Expected Result	
	Expected Result	A table containing detected sources, and a WCS object associated with that catalog.
4	Description	Confirm that each CCD within the visit image contains at least astrometricMinStandards astrometric standards that were used in deriving the astrometric solution.
	Test Data	No data.
	Expected Result	At least astrometricMinStandards from each CCD were used in determining the WCS solution.
5	Description	Starting from the XY pixel coordinates of the sources, apply the WCS to obtain RA, Dec coordinates.
	Test Data	No data.
	Expected Result	A list of RA, Dec coordinates for all sources in the catalog.
6	Description	We will assume that Gaia provides a source of "truth." Match the source list to Gaia DR2, and calculate the positional offset between the test data and the Gaia catalog.
	Test Data	No data.
	Expected Result	A matched catalog of sources in common between the test source list and Gaia DR2.
7	Description	Apply appropriate cuts to extract the optimal dataset for comparison, then calculate statistics (median, 1-sigma range, etc.; also plot a histogram) of the offsets in milliarcseconds. Confirm that the offset is less than astrometricAccuracy .
	Test Data	No data.
	Expected Result	Histogram and relevant statistics needed to confirm that the WCS transformation is
8	Description	Repeat Step 5, but for subregions of the image, to confirm that the accuracy criterion is met at all positions.
	Test Data	No data.
	Expected Result	astrometricAccuracy requirement is met over the entire image.

4.19 LVV-T41 - Verify implementation of Generate PSF for Visit Images

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.19.1 Verification Elements

- LVV-30 - DMS-REQ-0070-V-01: Generate PSF for Visit Images

4.19.2 Test Items

Verify that Processed Visit Images produced by the DRP and AP pipelines are associated with a model from which one can obtain an image of the PSF given a point on the image.

4.19.3 Predecessors

4.19.4 Environment Needs

4.19.4.1 Software

4.19.4.2 Hardware

4.19.5 Input Specification

4.19.6 Output Specification

4.19.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to Alert Production
	Test Data	No data.
	Expected	
	Result	

4.20 LVV-T42 - Verify implementation of Processed Visit Image Content

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Jim Bosch

4.20.1 Verification Elements

- LVV-31 - DMS-REQ-0072-V-01: Processed Visit Image Content

4.20.2 Test Items

Verify that Processed Visit Images produced by the DRP and AP pipelines include the observed data, a mask array, a variance array, a PSF model, and a WCS model.

4.20.3 Predecessors

4.20.4 Environment Needs

4.20.4.1 Software

4.20.4.2 Hardware

4.20.5 Input Specification

4.20.6 Output Specification

4.20.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T987	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the following:
	Test Data	
	Expected Result	Butler repo available for reading.
2	Description	Ingest the data from an appropriate processed dataset.

Step	Description, Input Data and Expected Result	
	Test Data	No data.
	Expected Result	
3	Description	Select a single visit from the dataset, and extract its WCS object, calexp image, psf model, and source list.
	Test Data	No data.
	Expected Result	
4	Description	Inspect the calexp image to ensure that 1. A well-formed image is present, 2. The variance plane is present and well-behaved, 3. Mask planes are present and contain information about defects.
	Test Data	No data.
	Expected Result	An astronomical image with mask and variance planes. This can be readily visualized using Firefly, which displays mask planes by default.
5	Description	Plot images of the PSF model at various points, and verify that the PSF differs with position.
	Test Data	No data.
	Expected Result	A "star-like" image of the PSF evaluated at various positions. The PSF should vary slightly with position (this could be readily visualized by taking a difference of PSFs at two positions).
6	Description	Starting from the XY pixel coordinates of the sources, apply the WCS to obtain RA, Dec coordinates. Plot these positions and confirm that they match the expected values from the WCS object.
	Test Data	No data.
	Expected Result	RA, Dec coordinates that are returned should be near the central position of the visit coordinate as given in either the calexp metadata or the WCS.
7	Description	Repeat steps 2-6, but now with difference images created by the Alert Production pipeline (for example, in the 'ap_verify' test data processing).
	Test Data	No data.
	Expected Result	

4.21 LVV-T43 - Verify implementation of Background Model Calculation

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.21.1 Verification Elements

- LVV-158 - DMS-REQ-0327-V-01: Background Model Calculation

4.21.2 Test Items

Verify that Processed Visit Images produced by the DRP and AP pipelines have had a model of the background subtracted, and that this model is persisted in a way that permits the background subtracted from any CCD to be retrieved along with the image for that CCD.

4.21.3 Predecessors

LVV-T15

LVV-T19

4.21.4 Environment Needs

4.21.4.1 Software

4.21.4.2 Hardware

4.21.5 Input Specification

4.21.6 Output Specification

4.21.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to Alert Production
	Test Data	No data.
	Expected Result	

Step	Description, Input Data and Expected Result
------	---

4.22 LVV-T44 - Verify implementation of Documenting Image Characterization

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.22.1 Verification Elements

- LVV-159 - DMS-REQ-0328-V-01: Documenting Image Characterization

4.22.2 Test Items

Verify that the persisted format for Processed Visit Images and associated instrument-signature-removal data products is documented.

4.22.3 Predecessors

4.22.4 Environment Needs

4.22.4.1 Software

4.22.4.2 Hardware

4.22.5 Input Specification

4.22.6 Output Specification

4.22.7 Test Procedure

Step	Description, Input Data and Expected Result
------	---

1	Description	Delegate to Alert Production
	Test Data	No data.

Step	Description, Input Data and Expected Result
------	---

Expected Result

4.23 LVV-T45 - Verify implementation of Prompt Processing Data Quality Report Definition

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Eric Bellm

4.23.1 Verification Elements

- LVV-39 - DMS-REQ-0097-V-01: Level 1 Data Quality Report Definition

4.23.2 Test Items

Verify that the DMS produces a Prompt Processing Data Quality Report. Specifically check absolute value and temporal variation of

1. Photometric zeropoint
2. Sky brightness
3. Seeing
4. PSF
5. Detection efficiency

4.23.3 Predecessors

4.23.4 Environment Needs

4.23.4.1 Software

4.23.4.2 Hardware

4.23.5 Input Specification

4.23.6 Output Specification

4.23.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Ingest raw data from L1 Test Stand DAQ.
	Test Data	No data.
	Expected Result	
2-1 from LVV-T866	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame processing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is presumed that these are automated for a given dataset.
	Test Data	
	Expected Result	An output dataset including difference images and DIASource and DIAObject measurements.
2-2 from LVV-T866	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
	Test Data	
	Expected Result	
3	Description	Load the Prompt Processing QC reports, and observe that a dynamically updated Data Quality Report has become available at the relevant UI.
	Test Data	No data.
	Expected Result	A Prompt Processing QC report is available via a UI, and contains information about the photometric zeropoint, sky brightness, seeing, PSF, and detection efficiency, and possibly other relevant quantities.
4	Description	Check that a static report is created and archived in a readily-accessible location.
	Test Data	No data.
	Expected Result	Persistence of a static QC report in an accessible location, containing the same information as in the report from Step 3.

4.24 LVV-T46 - Verify implementation of Prompt Processing Performance Report Definition

Version	Status	Priority	Verification Type	Owner
---------	--------	----------	-------------------	-------

1	Draft	Normal	Test	Eric Bellm
---	-------	--------	------	------------

4.24.1 Verification Elements

- LVV-41 - DMS-REQ-0099-V-01: Level 1 Performance Report Definition

4.24.2 Test Items

Verify that the DMS produces a Prompt Processing Performance Report. Specifically check that the number of observations that describe each of the following:

1. Successfully processed, recoverable failures, unrecoverable failures.
2. Archived
3. Result in science.

This is testing more the processing rather than the observatory system.

4.24.3 Predecessors

4.24.4 Environment Needs

4.24.4.1 Software

4.24.4.2 Hardware

4.24.5 Input Specification

4.24.6 Output Specification

4.24.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute single-day operations rehearsal, observe report
	Test Data	No data.

Step	Description, Input Data and Expected Result
------	---

Expected Result

4.25 LVV-T47 - Verify implementation of Prompt Processing Calibration Report Definition

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Eric Bellm

4.25.1 Verification Elements

- LVV-43 - DMS-REQ-0101-V-01: Level 1 Calibration Report Definition

4.25.2 Test Items

Verify that the DMS produces a Prompt Processing Calibration Report. Specifically check that this report is capable of identifying when aspects of the telescope or camera are changing with time.

4.25.3 Predecessors

4.25.4 Environment Needs

4.25.4.1 Software

4.25.4.2 Hardware

4.25.5 Input Specification

4.25.6 Output Specification

4.25.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Identify precursor and simulated calibration datasets on which to run the L1 calibration pipeline.
	Test Data	No data.
	Expected Result	
2-1 from LVV-T1059	Description	Execute the Daily Calibration Products Update payload. The payload uses raw calibration images and information from the Transformed EFD to generate a subset of Master Calibration Images and Calibration Database entries in the Data_Backbone.
	Test Data	
	Expected Result	
2-2 from LVV-T1059	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present and well-formed.
	Test Data	
	Expected Result	
3	Description	Check that a dynamic report is created that triggers alerts if calibrations go out of range.
	Test Data	No data.
	Expected Result	A dynamic report is available via UI to users, and if any out-of-spec changes have occurred, alerts have been issued.
4	Description	Check that a static report is created and archived in a readily-accessible location.
	Test Data	No data.
	Expected Result	An archived version of the calibration report is available and will be retained in a static file format.

4.26 LVV-T48 - Verify implementation of Exposure Catalog

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Jim Bosch

4.26.1 Verification Elements

- LVV-97 - DMS-REQ-0266-V-01: Exposure Catalog

4.26.2 Test Items

Verify that the DMS creates an Exposure Catalog that includes

1. Observation datetime, exposure time
2. Filter
3. Dome, telescope orientation and status
4. Calibration status
5. Airmass and zenith
6. Environmental information
7. Per-sensor information

4.26.3 Predecessors

4.26.4 Environment Needs

4.26.4.1 Software

4.26.4.2 Hardware

4.26.5 Input Specification

4.26.6 Output Specification

4.26.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Verify that Exposure Catalogs contain the required elements. At present, the form of the exposure catalog is not defined. This information can be found for a given Butler repo from the metadata, but will ultimately be aggregated into a database/table summarizing available exposures.
	Test Data	No data.
	Expected Result	A list of the required metadata for a set of exposures is returned and both human- and machine-readable.

4.27 LVV-T49 - Verify implementation of DIASource Catalog

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.27.1 Verification Elements

- LVV-100 - DMS-REQ-0269-V-01: DIASource Catalog

4.27.2 Test Items

Verify that the DMS produces a Source catalog from Difference Exposures with the required attributes.

4.27.3 Predecessors

4.27.4 Environment Needs

4.27.4.1 Software

4.27.4.2 Hardware

4.27.5 Input Specification

4.27.6 Output Specification

4.27.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Verify that products are produced for DIASource catalog
	Test Data	No data.
	Expected Result	
2-1 from LVV-T18	Description	The DM Stack and Alert Processing packaged shall be initialized as described in LVT-T17 (AG-00-00).
	Test Data	

Step	Description, Input Data and Expected Result	
	Expected Result	
2-2 from LVV-T18	Description	The alert generation processing will be executed using the verification cluster: <pre> """bash python ap_verify/bin/prepare_demo_slurm_files.py # At present we must run a single ccd+visit to handle ingestion before # parallel processing can begin ./ap_verify/bin/exec_demo_run_1ccd.sh 410915 25 ln -s ap_verify/bin/demo_run.sl ln -s ap_verify/bin/demo_cmds.conf sbatch demo_run.sl """ </pre> and any errors or failures reported.
	Test Data	
	Expected Result	
2-3 from LVV-T18	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected Result	
2-4 from LVV-T18	Description	For each of the expected data products types (listed in §4.2.2) and each of the expected units (PVIs, catalogs, etc.), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected Result	
2-5 from LVV-T18	Description	DIAObjects are currently only stored in a database, without shims to the Butler, so the existence of the database table and its non-empty contents will be verified by directly accessing it using sqlite3 and executing appropriate SQL queries.
	Test Data	
	Expected Result	

4.28 LVV-T50 - Verify implementation of Faint DIASource Measurements

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.28.1 Verification Elements

- LVV-101 - DMS-REQ-0270-V-01: Faint DIASource Measurements

4.28.2 Test Items

Verify that the DMS can produces DIASources measurements for sources below the nominal S/N cutoff that satisfy additional criteria.

4.28.3 Predecessors

4.28.4 Environment Needs

4.28.4.1 Software

4.28.4.2 Hardware

4.28.5 Input Specification

Input Data
DECam HiTS data.

4.28.6 Output Specification

4.28.7 Test Procedure

Step	Description, Input Data and Expected Result
1-1 from LVV-T18	Description Test Data Expected Result The DM Stack and Alert Processing packaged shall be initialized as described in LVT-T17 (AG-00-00).

Step	Description, Input Data and Expected Result	
1-2 from LVV-T18	Description	The alert generation processing will be executed using the verification cluster:
		<pre> "bash python ap_verify/bin/prepare_demo_slurm_files.py # At present we must run a single ccd+visit to handle ingestion before # parallel processing can begin ./ap_verify/bin/exec_demo_run_1ccd.sh 410915 25 ln -s ap_verify/bin/demo_run.sl ln -s ap_verify/bin/demo_cmds.conf sbatch demo_run.sl "</pre>
	Test Data	and any errors or failures reported.
	Expected Result	
1-3 from LVV-T18	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected Result	
1-4 from LVV-T18	Description	For each of the expected data products types (listed in §4.2.2) and each of the expected units (PVIs, catalogs, etc.), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected Result	
1-5 from LVV-T18	Description	DIAObjects are currently only stored in a database, without shims to the Butler, so the existence of the database table and its non-empty contents will be verified by directly accessing it using sqlite3 and executing appropriate SQL queries.
	Test Data	
	Expected Result	
2	Description	As an example of selecting with constraints, Re-run source detection as an afterburner to select isolated sources (defined as more than 2 arcseconds away from any other objects in the single-image-depth catalog) that are fainter than the fiducial transSNR cut.
	Test Data	No data.
	Expected Result	
	Result	

4.29 LVV-T51 - Verify implementation of DIAObject Catalog

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.29.1 Verification Elements

- LVV-102 - DMS-REQ-0271-V-01: Max nearby galaxies associated with DIASource

4.29.2 Test Items

Verify that the DIAObject includes a unique ID, identifiers for nearest stars and nearest galaxies, and probability of matching to static Object.

4.29.3 Predecessors

4.29.4 Environment Needs

4.29.4.1 Software

4.29.4.2 Hardware

4.29.5 Input Specification

4.29.6 Output Specification

4.29.7 Test Procedure

Step	Description, Input Data and Expected Result
1-1 from LVV-T21	Description Test Data Expected Result The DM Stack shall be initialized using the loadLSST script (as described in LVV-T17 - AG-00-00).
1-2 from LVV-T21	Description Test Data A "Data Butler" will be initialized to access the repository.

Step	Description, Input Data and Expected Result	
	Expected Result	
1-3 from LVV-T21	Description	DIASource records will be accessed by querying the Butler, then examined interactively at a Python prompt.
	Test Data	
	Expected Result	
2-1 from LVV-T18	Description	The DM Stack and Alert Processing packaged shall be initialized as described in LVT-T17 (AG-00-00).
	Test Data	
	Expected Result	
2-2 from LVV-T18	Description	The alert generation processing will be executed using the verification cluster:
	Test Data	<pre> '''bash python ap_verify/bin/prepare_demo_slurm_files.py # At present we must run a single ccd+visit to handle ingestion before # parallel processing can begin ./ap_verify/bin/exec_demo_run_1ccd.sh 410915 25 ln -s ap_verify/bin/demo_run.sl ln -s ap_verify/bin/demo_cmds.conf sbatch demo_run.sl ''' </pre>
	Expected Result	and any errors or failures reported.
2-3 from LVV-T18	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected Result	
2-4 from LVV-T18	Description	For each of the expected data products types (listed in §4.2.2) and each of the expected units (PVIs, catalogs, etc.), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected Result	

Step	Description, Input Data and Expected Result	
2-5 from LVV-T18	Description	DIAObjects are currently only stored in a database, without shims to the Butler, so the existence of the database table and its non-empty contents will be verified by directly accessing it using sqlite3 and executing appropriate SQL queries.
	Test Data	
	Expected	
	Result	
3-1 from LVV-T22	Description	The DM Stack shall be initialized using the loadLSST script (as described in LVV-T17 - AG-00-00).
	Test Data	
	Expected	
	Result	
3-2 from LVV-T22	Description	sqlite3 or Python's sqlalchemy module will be used to access the Level 1 database.
	Test Data	
	Expected	
	Result	
4	Description	Verify that DIAObjects have diaNearbyObjMaxStar and diaNearbyObjMaxGalaxies that point to the Object catalog and are within dianNearbyObjRadius; the probability of association; and the required DIAObject properties.
	Test Data	No data.
	Expected	
	Result	

4.30 LVV-T52 - Verify implementation of DIAObject Attributes

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.30.1 Verification Elements

- LVV-103 - DMS-REQ-0272-V-01: DIAObject Attributes

4.30.2 Test Items

Verify that the DMS provides summary attributes for each DIAObject, including periodicity measures.

4.30.3 Predecessors

4.30.4 Environment Needs

4.30.4.1 Software

4.30.4.2 Hardware

4.30.5 Input Specification

4.30.6 Output Specification

4.30.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T18	Description	The DM Stack and Alert Processing packaged shall be initialized as described in LVT-T17 (AG-00-00).
	Test Data	
	Expected	
	Result	
1-2 from LVV-T18	Description	The alert generation processing will be executed using the verification cluster:
	Test Data	<pre> """bash python ap_verify/bin/prepare_demo_slurm_files.py # At present we must run a single ccd+visit to handle ingestion before # parallel processing can begin ./ap_verify/bin/exec_demo_run_1ccd.sh 410915 25 ln -s ap_verify/bin/demo_run.sl ln -s ap_verify/bin/demo_cmds.conf sbatch demo_run.sl """ </pre>
		and any errors or failures reported.
	Test Data	

Step	Description, Input Data and Expected Result	
	Expected Result	
1-3 from LVV-T18	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected Result	
1-4 from LVV-T18	Description	For each of the expected data products types (listed in §4.2.2) and each of the expected units (PVI, catalogs, etc.), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected Result	
1-5 from LVV-T18	Description	DIAObjects are currently only stored in a database, without shims to the Butler, so the existence of the database table and its non-empty contents will be verified by directly accessing it using sqlite3 and executing appropriate SQL queries.
	Test Data	
	Expected Result	

4.31 LVV-T53 - Verify implementation of SSOject Catalog

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.31.1 Verification Elements

- LVV-104 - DMS-REQ-0273-V-01: SSOject Catalog

4.31.2 Test Items

Verify that the DMS produces a catalog of Solar System Objects identify from Moving Object Processing.

Verify that the SSOject catalog includes orbital elements and additional related quantities.

4.31.3 Predecessors

4.31.4 Environment Needs

4.31.4.1 Software

4.31.4.2 Hardware

4.31.5 Input Specification

4.31.6 Output Specification

4.31.7 Test Procedure

Step	Description, Input Data and Expected Result
1-1 from LVV-T18	Description The DM Stack and Alert Processing packaged shall be initialized as described in LVT-T17 (AG-00-00).
	Test Data
	Expected
	Result
1-2 from LVV-T18	Description The alert generation processing will be executed using the verification cluster:
	<pre> "bash python ap_verify/bin/prepare_demo_slurm_files.py # At present we must run a single ccd+visit to handle ingestion before # parallel processing can begin ./ap_verify/bin/exec_demo_run_1ccd.sh 410915 25 ln -s ap_verify/bin/demo_run.sl ln -s ap_verify/bin/demo_cmds.conf sbatch demo_run.sl "</pre>
	and any errors or failures reported.
	Test Data
1-3 from LVV-T18	Expected
	Result
	Description A "Data Butler" will be initialized to access the repository.
	Test Data

Step	Description, Input Data and Expected Result	
	Expected Result	
1-4 from LVV-T18	Description	For each of the expected data products types (listed in §4.2.2) and each of the expected units (PVIs, catalogs, etc.), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected Result	
1-5 from LVV-T18	Description	DIAObjects are currently only stored in a database, without shims to the Butler, so the existence of the database table and its non-empty contents will be verified by directly accessing it using sqlite3 and executing appropriate SQL queries.
	Test Data	
	Expected Result	
2	Description	Run the MOPS pipeline on the Prompt Products database.
	Test Data	No data.
	Expected Result	
3	Description	Inspect SSOject catalog and verify the presence of the required elements (LVV-104).
	Test Data	No data.
	Expected Result	

4.32 LVV-T54 - Verify implementation of Alert Content

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.32.1 Verification Elements

- LVV-105 - DMS-REQ-0274-V-01: Alert Content

4.32.2 Test Items

Verify that the DMS creates an Alert for each detected DIASource

Verify that this Alert is broadcasted using community protocols

Verify that the context of the Alert packet match requirements.

4.32.3 Predecessors

4.32.4 Environment Needs

4.32.4.1 Software

4.32.4.2 Hardware

4.32.5 Input Specification

4.32.6 Output Specification

4.32.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T18	Description	The DM Stack and Alert Processing packaged shall be initialized as described in LVT-T17 (AG-00-00).
	Test Data	
	Expected Result	
1-2 from LVV-T18	Description	The alert generation processing will be executed using the verification cluster:
	Test Data	<pre> '''bash python ap_verify/bin/prepare_demo_slurm_files.py # At present we must run a single ccd+visit to handle ingestion before # parallel processing can begin ./ap_verify/bin/exec_demo_run_1ccd.sh 410915 25 ln -s ap_verify/bin/demo_run.sl ln -s ap_verify/bin/demo_cmds.conf sbatch demo_run.sl ''' </pre>
	Expected Result	and any errors or failures reported.

Step	Description, Input Data and Expected Result	
	Expected	
	Result	
1-3 from	Description	A "Data Butler" will be initialized to access the repository.
LVV-T18	Test Data	
	Expected	
	Result	
1-4 from	Description	For each of the expected data products types (listed in §4.2.2) and each of the expected units (PVI, catalogs, etc.), the data product will be retrieved from the Butler and verified to be non-empty.
LVV-T18	Test Data	
	Expected	
	Result	
1-5 from	Description	DIAObjects are currently only stored in a database, without shims to the Butler, so the existence of the database table and its non-empty contents will be verified by directly accessing it using sqlite3 and executing appropriate SQL queries.
LVV-T18	Test Data	
	Expected	
	Result	
2-1 from	Description	
LVV-T217	Test Data	
	Expected	
	Result	
2-2 from	Description	Start a consumer that monitors the full stream and logs a deserialized version of every Nth packet:
LVV-T217		<code>kubect1 create -f consumerall-deployment.yaml</code>
	Test Data	
	Expected	Runs without error
	Result	
2-3 from	Description	Start a producer that reads alert packets from disk and loads them into the Kafka queue:
LVV-T217		<code>kubect1 create -f sender-deployment.yaml</code>
	Test Data	
	Expected	Runs without error
	Result	

Step	Description, Input Data and Expected Result	
2-4 from LVV-T217	Description	Determine the name of the alert sender pod with
		kubectl get pods
		Examine output log files.
		kubectl logs <pod name>
		Verify that alerts are being sent within 40 seconds by subtracting the timing measurements.
	Test Data	
	Expected Result	Similar to
		kubectl logs sender-7d6f98586f-nhwhj visit: 1570. time: 1530588618.0313473 visits finished: 1 time: 1530588653.5614944 visit: 1571. time: 1530588657.0087624 visits finished: 2 time: 1530588692.506188 visit: 1572. time: 1530588696.0051727 visits finished: 3 time: 1530588731.5900314
2-5 from LVV-T217	Description	Determine the name of the consumer pod with
		kubectl get pods
		Examine output log files.
		kubectl logs <pod name>
		The packet log should show deserialized alert packets with contents matching the input packets.
	Test Data	

Step	Description, Input Data and Expected Result	
	Expected Result	Similar to {'alertId': 12132024420, 'l1dbId': 71776805594116, 'diaSource': {'diaSourceId': 73499448928374785, 'ccdVisitId': 2020011570, 'diaObjectId': 71776805594116, 'ssObjectId': None, 'parentDiaSourceId': None, 'midPointTai': 59595.37041, 'filterName': 'y', 'ra': 172.24912810036074, 'decl': -80.64214929176521, 'ra_decl_Cov': {'raSigma': 0.0003428002819418907, 'declSigma': 0.00027273103478364646, 'ra_decl_Cov': 0.000628734880592674}, 'x': 2979.08837890625, 'y': 3843.328857421875, 'x_y_Cov': {'xSigma': 0.6135467886924744, 'ySigma': 0.77132648229599, 'x_y_Cov': 0.007463791407644749}, 'apFlux': None, 'apFluxErr': None, 'snr': 0.36651650071144104, 'psFlux': 7.698232025177276e-07, 'psRa': None, 'psDecl': None, 'ps_Cov': None, 'psLnL': None, 'psChi2': None, 'psNdata': None, 'trailFlux': None, 'trailRa': etc.
3	Description	Examine the serialized alert packets to confirm the presence of the required elements (LVV-105).
	Test Data	No data.
	Expected Result	

4.33 LVV-T55 - Verify implementation of DIAForcedSource Catalog

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.33.1 Verification Elements

- LVV-148 - DMS-REQ-0317-V-01: DIAForcedSource Catalog

4.33.2 Test Items

Verify that the DMS produces a DIAForcedSource Catalog and that the catalog contains measured fluxes for DIAObjects.

4.33.3 Predecessors

4.33.4 Environment Needs

4.33.4.1 Software

4.33.4.2 Hardware

4.33.5 Input Specification

4.33.6 Output Specification

4.33.7 Test Procedure

Step	Description, Input Data and Expected Result
1-1 from LVV-T18	Description The DM Stack and Alert Processing packaged shall be initialized as described in LVT-T17 (AG-00-00).
	Test Data
	Expected
	Result
1-2 from LVV-T18	Description The alert generation processing will be executed using the verification cluster:
	<pre> "bash python ap_verify/bin/prepare_demo_slurm_files.py # At present we must run a single ccd+visit to handle ingestion before # parallel processing can begin ./ap_verify/bin/exec_demo_run_1ccd.sh 410915 25 ln -s ap_verify/bin/demo_run.sl ln -s ap_verify/bin/demo_cmds.conf sbatch demo_run.sl "</pre>
	and any errors or failures reported.
	Test Data
1-3 from LVV-T18	Description A "Data Butler" will be initialized to access the repository.
	Test Data
	Expected
	Result
1-4 from LVV-T18	Description For each of the expected data products types (listed in §4.2.2) and each of the expected units (PVIs, catalogs, etc.), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data
	Expected
	Result

Step	Description, Input Data and Expected Result	
1-5 from LVV-T18	Description	DIAObjects are currently only stored in a database, without shims to the Butler, so the existence of the database table and its non-empty contents will be verified by directly accessing it using sqlite3 and executing appropriate SQL queries.
	Test Data	
	Expected Result	

4.34 LVV-T56 - Verify implementation of Characterizing Variability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.34.1 Verification Elements

- LVV-150 - DMS-REQ-0319-V-01: Characterizing Variability

4.34.2 Test Items

Verify that the variability characterization in the DIAObject catalog includes data collected within previous “diaCharacterizationCutoff” period of time.

4.34.3 Predecessors

4.34.4 Environment Needs

4.34.4.1 Software

4.34.4.2 Hardware

4.34.5 Input Specification

4.34.6 Output Specification

4.34.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T18	Description	The DM Stack and Alert Processing packaged shall be initialized as described in LVT-T17 (AG-00-00).
	Test Data	
	Expected	
	Result	
1-2 from LVV-T18	Description	The alert generation processing will be executed using the verification cluster:
	Test Data	
	Expected	
	Result	<pre> """bash python ap_verify/bin/prepare_demo_slurm_files.py # At present we must run a single ccd+visit to handle ingestion before # parallel processing can begin ./ap_verify/bin/exec_demo_run_1ccd.sh 410915 25 ln -s ap_verify/bin/demo_run.sl ln -s ap_verify/bin/demo_cmds.conf sbatch demo_run.sl """ </pre> and any errors or failures reported.
1-3 from LVV-T18	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected	
	Result	
1-4 from LVV-T18	Description	For each of the expected data products types (listed in §4.2.2) and each of the expected units (PVIs, catalogs, etc.), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected	
	Result	
1-5 from LVV-T18	Description	DIAObjects are currently only stored in a database, without shims to the Butler, so the existence of the database table and its non-empty contents will be verified by directly accessing it using sqlite3 and executing appropriate SQL queries.
	Test Data	
	Expected	
	Result	
	Description	Verify that the issued alerts contain measurements during the diaCharacterizationCutoff.

Step	Description, Input Data and Expected Result	
	Test Data	No data.
	Expected Result	

4.35 LVV-T57 - Verify implementation of Calculating SSOBJECT Parameters

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.35.1 Verification Elements

- LVV-154 - DMS-REQ-0323-V-01: Calculating SSOBJECT Parameters

4.35.2 Test Items

Verify that the DMS database provides functions to compute phase angles and magnitudes in LSST bands for every SSOBJECT.

4.35.3 Predecessors

4.35.4 Environment Needs

4.35.4.1 Software

4.35.4.2 Hardware

4.35.5 Input Specification

4.35.6 Output Specification

4.35.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T53	Description	
	Test Data	
	Expected	
	Result	
1-2 from LVV-T53	Description	Run the MOPS pipeline on the Prompt Products database.
	Test Data	
	Expected	
	Result	
1-3 from LVV-T53	Description	Inspect SSOBJ catalog and verify the presence of the required elements (LVV-104).
	Test Data	
	Expected	
	Result	
2	Description	Computer the phase angle, reduced and absolute asteroid magnitudes for objects identified in SSOBJ Catalog
	Test Data	No data.
	Expected	
	Result	

4.36 LVV-T58 - Verify implementation of Matching DIASources to Objects

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.36.1 Verification Elements

- LVV-155 - DMS-REQ-0324-V-01: Matching DIASources to Objects

4.36.2 Test Items

Verify that a cross-match table is available between DIASources and Objects.

4.36.3 Predecessors

4.36.4 Environment Needs

4.36.4.1 Software

4.36.4.2 Hardware

4.36.5 Input Specification

4.36.6 Output Specification

4.36.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T12	Description	The DM Stack shall be initialized using the loadLSST script (as described in DRP-00-00).
	Test Data	
	Expected	
	Result	
1-2 from LVV-T12	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected	
	Result	
1-3 from LVV-T12	Description	For each of the expected data products types (listed in Test Items section §4.3.2) and each of the expected units (PVI, coadds, etc), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected	
	Result	
2-1 from LVV-T18	Description	The DM Stack and Alert Processing packaged shall be initialized as described in LVT-T17 (AG-00-00).
	Test Data	
	Expected	
	Result	

Step	Description, Input Data and Expected Result	
2-2 from LVV-T18	Description	The alert generation processing will be executed using the verification cluster:
	Test Data	<pre> "bash python ap_verify/bin/prepare_demo_slurm_files.py # At present we must run a single ccd+visit to handle ingestion before # parallel processing can begin ./ap_verify/bin/exec_demo_run_1ccd.sh 410915 25 ln -s ap_verify/bin/demo_run.sl ln -s ap_verify/bin/demo_cmds.conf sbatch demo_run.sl "</pre>
	Expected Result	and any errors or failures reported.
2-3 from LVV-T18	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected Result	
2-4 from LVV-T18	Description	For each of the expected data products types (listed in §4.2.2) and each of the expected units (PVIs, catalogs, etc.), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected Result	
2-5 from LVV-T18	Description	DIAObjects are currently only stored in a database, without shims to the Butler, so the existence of the database table and its non-empty contents will be verified by directly accessing it using sqlite3 and executing appropriate SQL queries.
	Test Data	
	Expected Result	
3	Description	Verify that a cross-match table between the Prompt DIASources and DRP Objects is available.
	Test Data	No data.
	Expected Result	

4.37 LVV-T59 - Verify implementation of Regenerating L1 Data Products During Data Release Processing

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.37.1 Verification Elements

- LVV-156 - DMS-REQ-0325-V-01: Regenerating L1 Data Products During Data Release Processing

4.37.2 Test Items

Verify that the Prompt Processing data products are regenerated during DRP.

4.37.3 Predecessors

4.37.4 Environment Needs

4.37.4.1 Software

4.37.4.2 Hardware

4.37.5 Input Specification

4.37.6 Output Specification

4.37.7 Test Procedure

Step	Description, Input Data and Expected Result
1	Description Execute DRP
	Test Data No data.
	Expected
	Result
2	Description Observe production of difference image data products

Step	Description, Input Data and Expected Result
Test Data	No data.
Expected Result	

4.38 LVV-T60 - Verify implementation of Publishing predicted visit schedule

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.38.1 Verification Elements

- LVV-184 - DMS-REQ-0353-V-01: Publishing predicted visit schedule

4.38.2 Test Items

Verify that a predict-visit schedule can be published by the OCS.

4.38.3 Predecessors

4.38.4 Environment Needs

4.38.4.1 Software

4.38.4.2 Hardware

4.38.5 Input Specification

4.38.6 Output Specification

4.38.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	
	Test Data	No data.
	Expected Result	

4.39 LVV-T61 - Verify implementation of Associate Sources to Objects

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Jim Bosch

4.39.1 Verification Elements

- LVV-16 - DMS-REQ-0034-V-01: Associate Sources to Objects

4.39.2 Test Items

Verify that each Source record contains an ID that associates it with a best guess at the Object it corresponds to.

4.39.3 Predecessors

4.39.4 Environment Needs

4.39.4.1 Software

4.39.4.2 Hardware

4.39.5 Input Specification

4.39.6 Output Specification

4.39.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T12	Description	The DM Stack shall be initialized using the loadLSST script (as described in DRP-00-00).
	Test Data	
	Expected	
	Result	
1-2 from LVV-T12	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected	
	Result	
1-3 from LVV-T12	Description	For each of the expected data products types (listed in Test Items section §4.3.2) and each of the expected units (PVI, coadds, etc), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected	
	Result	
2	Description	Verify that sources have objects
	Test Data	No data.
	Expected	
	Result	
3	Description	Verify that objects list sources that seem reasonably near them.
	Test Data	No data.
	Expected	
	Result	

4.40 LVV-T62 - Verify implementation of Provide PSF for Coadded Images

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.40.1 Verification Elements

- LVV-20 - DMS-REQ-0047-V-01: Provide PSF for Coadded Images

4.40.2 Test Items

Verify that all coadd images produced by the DRP pipelines include a model from which an image of the PSF at any point on the coadd can be obtained.

4.40.3 Predecessors

4.40.4 Environment Needs

4.40.4.1 Software

4.40.4.2 Hardware

4.40.5 Input Specification

Fully covered by preconditions for LVV-T16.

4.40.6 Output Specification

4.40.7 Test Procedure

Step	Description, Input Data and Expected Result
1-1 from LVV-T16	Description Test Data Expected Result The DM Stack shall be initialized using the loadLSST script (as described in LVV-T10 - DRP-00-00)
1-2 from LVV-T16	Description Test Data Expected Result A "Data Butler" will be initialized to access the repository.
1-3 from LVV-T16	Description Test Data Expected Result For each combination of tract/patch/filter, the PVI will be retrieved from the Butler, and the existence of all components described in Test items section §4.6.2 will be verified.
1-4 from LVV-T16	Description Test Data Expected Result Scripts from the pipe_analysis package will be run on every visit to check for the presence of data products and make plots

Step	Description, Input Data and Expected Result	
1-5 from LVV-T16	Test Data	
	Expected	
	Result	
	Description	Ten patches will be chosen at random and inspected by eye for unmasked artifacts.
	Test Data	
2	Expected	
	Result	
	Description	Select Objects classified as point sources on 10 different coadd images (including all bands). Evaluate the PSF model at the positions of these Objects, and verify that subtracting a scaled version of the PSF model from the coadd image yields residuals consistent with pure noise.
	Test Data	No data.
	Expected	
	Result	

4.41 LVV-T63 - Verify implementation of Produce Images for EPO

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Gregory Dubois-Felsmann

4.41.1 Verification Elements

- LVV-45 - DMS-REQ-0103-V-01: Produce Images for EPO

4.41.2 Test Items

This test will verify that the DRP pipelines produce the image data products called out in LSE-131. Currently this is limited to a color all-sky HiPS map. This will be verified (1) by inspection of pipeline configurations and (2) in operations rehearsals on precursor data. The production of a usable HiPS map will be verified by browsing it with community tools.

4.41.3 Predecessors

4.41.4 Environment Needs

4.41.4.1 Software

4.41.4.2 Hardware

4.41.5 Input Specification

In order for an operational test to be successful, as a precondition the inputs to that production must exist. For the only currently mandated image data production in LSE-131, a color all-sky HiPS map down to 1 arcsecond resolution, the prerequisite inputs to that are the single-filter coadds in the bands required by the yet-to-be-specified color prescription.

4.41.6 Output Specification

4.41.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T12	Description	The DM Stack shall be initialized using the loadLSST script (as described in DRP-00-00).
	Test Data	
	Expected	
	Result	
1-2 from LVV-T12	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected	
	Result	
1-3 from LVV-T12	Description	For each of the expected data products types (listed in Test Items section §4.3.2) and each of the expected units (PVLs, coadds, etc), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected	
	Result	
2	Description	Verify that a HiPS image map covering the LSST survey area, with a limiting depth yielding 1 arcsecond resolution, has been produced matching the color prescriptions provided by EPO (in updates to LSE-131 which are expected to be made "once ComCam data is available").

Step	Description, Input Data and Expected Result	
	Test Data	No data.
	Expected Result	
3	Description	Place the image map in a location accessible to a Firefly and an Aladin Lite client, ideally with the client running in the EPO data systems environment.
	Test Data	No data.
	Expected Result	
4	Description	Use Firefly to manually explore the image map at the largest scales to verify coverage of the entire sky. Sample in various locations to confirm the 1 arcsecond maximum depth. Confirm using Aladin Lite that the format of the image map is supported by this common community tool.
	Test Data	No data.
	Expected Result	
5	Description	Verify programmatically, perhaps both by sampling a variety of locations, and by counting the tiles created at the 1-arcsecond-resolution depth, that the map is complete and meets its specifications.
	Test Data	No data.
	Expected Result	
6	Description	Apply an IVOA-community HiPS service validation tool, if available, to the service location.
	Test Data	No data.
	Expected Result	
7	Description	Verify that the HiPS map created is in a location accessible to the EPO data systems.
	Test Data	No data.
	Expected Result	

4.42 LVV-T64 - Verify implementation of Coadded Image Provenance

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.42.1 Verification Elements

- LVV-46 - DMS-REQ-0106-V-01: Coadded Image Provenance
- LVV-1234 - OSS-REQ-0122-V-01: Provenance

4.42.2 Test Items

Verify that all coadd data products produced by the DRP pipelines are associated with provenance information that includes the set of input epochs contributing to that coadd as well as any additional information needed to exactly produce that coadd.

4.42.3 Predecessors

4.42.4 Environment Needs

4.42.4.1 Software

4.42.4.2 Hardware

4.42.5 Input Specification

4.42.6 Output Specification

4.42.7 Test Procedure

Step	Description, Input Data and Expected Result
1-1 from LVV-T12	Description The DM Stack shall be initialized using the loadLSST script (as described in DRP-00-00).
	Test Data
	Expected
	Result
1-2 from LVV-T12	Description A "Data Butler" will be initialized to access the repository.
	Test Data
	Expected
	Result

Step	Description, Input Data and Expected Result	
1-3 from LVV-T12	Description	For each of the expected data products types (listed in Test Items section §4.3.2) and each of the expected units (PVI, coadds, etc), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected Result	
2	Description	Query and verify provenance of input images, and software versions that went into producing stack.
	Test Data	No data.
	Expected Result	
3	Description	Test re-generating 10 different coadds tract+patches based on the provenance image given
	Test Data	No data.
	Expected Result	

4.43 LVV-T65 - Verify implementation of Source Catalog

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Jim Bosch

4.43.1 Verification Elements

- LVV-98 - DMS-REQ-0267-V-01: Source Catalog

4.43.2 Test Items

Verify that all Sources produced by the DRP pipelines contain the entries listed in DMS-REQ-0267.

4.43.3 Predecessors

4.43.4 Environment Needs

4.43.4.1 Software

4.43.4.2 Hardware

4.43.5 Input Specification

4.43.6 Output Specification

4.43.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Identify a suitable small dataset to process through the DRP.
	Test Data	No data.
	Expected Result	
2-1 from LVV-T1064	Description	Process data with the Data Release Production payload, starting from raw science images and generating science data products, placing them in the Data Backbone.
	Test Data	
	Expected Result	
3	Description	Confirm that source catalogs have been produced for single visits and coadds, and that it contains the required measurements.
	Test Data	No data.
	Expected Result	A source catalog containing the measured attributes (and associated errors), including location on the focal plane; a static point-source model fit to world coordinates and flux; a centroid and adaptive moments; and surface brightnesses through elliptical multiple apertures that are concentric, PSF-homogenized, and logarithmically spaced in intensity.

4.44 LVV-T66 - Verify implementation of Forced-Source Catalog

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.44.1 Verification Elements

- LVV-99 - DMS-REQ-0268-V-01: Forced-Source Catalog

4.44.2 Test Items

Verify that all ForcedSources produced by the DRP pipelines contain fluxes measured on difference and direct single-epoch images, associated uncertainties, an Object ID, and a Visit ID.

4.44.3 Predecessors

4.44.4 Environment Needs

4.44.4.1 Software

4.44.4.2 Hardware

4.44.5 Input Specification

4.44.6 Output Specification

4.44.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T18	Description	The DM Stack and Alert Processing packaged shall be initialized as described in LVT-T17 (AG-00-00).
	Test Data	
	Expected	
	Result	

Step	Description, Input Data and Expected Result	
1-2 from LVV-T18	Description	The alert generation processing will be executed using the verification cluster:
		<pre> "bash python ap_verify/bin/prepare_demo_slurm_files.py # At present we must run a single ccd+visit to handle ingestion before # parallel processing can begin ./ap_verify/bin/exec_demo_run_1ccd.sh 410915 25 ln -s ap_verify/bin/demo_run.sl ln -s ap_verify/bin/demo_cmds.conf sbatch demo_run.sl "</pre>
	Test Data	and any errors or failures reported.
	Expected Result	
1-3 from LVV-T18	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected Result	
1-4 from LVV-T18	Description	For each of the expected data products types (listed in §4.2.2) and each of the expected units (PVIs, catalogs, etc.), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected Result	
1-5 from LVV-T18	Description	DIAObjects are currently only stored in a database, without shims to the Butler, so the existence of the database table and its non-empty contents will be verified by directly accessing it using sqlite3 and executing appropriate SQL queries.
	Test Data	
	Expected Result	
2-1 from LVV-T12	Description	The DM Stack shall be initialized using the loadLSST script (as described in DRP-00-00).
	Test Data	
	Expected Result	
2-2 from LVV-T12	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	

Step	Description, Input Data and Expected Result	
	Expected Result	
2-3 from LVV-T12	Description	For each of the expected data products types (listed in Test Items section §4.3.2) and each of the expected units (PVI, coadds, etc), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected Result	
3	Description	Verify that there exist entries in the forced-photometry table for all coadd objects for the PVIs on which the object should appear.
	Test Data	No data.
	Expected Result	
4	Description	Verify that there exist entries in a forced-photometry table for each image for all DIAObjects.
	Test Data	No data.
	Expected Result	

4.45 LVV-T67 - Verify implementation of Object Catalog

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.45.1 Verification Elements

- LVV-106 - DMS-REQ-0275-V-01: Object Catalog

4.45.2 Test Items

Verify that the DRP pipelines produce an Object catalog derived from detections made on both coadded images and difference images and measurements performed on coadds and possibly overlapping single-epoch images.

4.45.3 Predecessors

4.45.4 Environment Needs

4.45.4.1 Software

4.45.4.2 Hardware

4.45.5 Input Specification

Input Data

DECam HiTS data (raw science images and master calibrations)

HSC "RC2" data (raw science images and master calibrations)

4.45.6 Output Specification

4.45.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	load LSST DM Stack
	Test Data	No data.
	Expected Result	
2	Description	Run the single-frame processing and self-calibration steps of the DRP pipeline.
	Test Data	No data.
	Expected Result	

Step	Description, Input Data and Expected Result	
3	Description	Insert simulated sources into all single-frame images, including:
		- static objects (e.g. galaxies), including some too faint to be detectable in single-epoch images; - objects with static positions that are sufficiently bright and variable that they should be detectable in single-epoch difference images; - transient objects that appear in only a few epochs; - stars with significant proper motions and parallaxes, some below the single-epoch detection limit - simulated solar system objects with orbits that can be constrained from just the epochs in the test dataset
	Test Data	No data.
4	Expected Result	
	Description	Run all remaining DRP pipeline steps.
	Test Data	No data.
5	Expected Result	
	Description	Load data into DRP database
	Test Data	No data.
6	Expected Result	
	Description	Verify that the injected simulated objects are recovered at a rate consistent with their S/N <i>when not blended with each other or real objects</i> , and that flags indicating how each Object was detected are consistent with their properties: - static objects should be detected in coadds only (not difference images) - static-position/variable-flux objects should be detected in coadds and possibly difference images - transient objects should be detected in difference images only - stars with significant proper motions may be detected in either coadds or difference images - solar system objects should be detected in difference images only.
	Test Data	No data.
	Expected Result	

4.46 LVV-T68 - Verify implementation of Provide Photometric Redshifts of Galaxies

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.46.1 Verification Elements

- LVV-19 - DMS-REQ-0046-V-01: Provide Photometric Redshifts of Galaxies

4.46.2 Test Items

Verify that Object catalogs produced by the DRP Pipeline include photometric redshift information.

4.46.3 Predecessors

4.46.4 Environment Needs

4.46.4.1 Software

4.46.4.2 Hardware

4.46.5 Input Specification

Input Data

HSC Public Data Release (raw science images, master calibrations)

Assorted public spectroscopic catalogs and high-accuracy photometric redshift catalogs in the HSC PDR footprint.

4.46.6 Output Specification

4.46.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Run DRP processing steps through (at least) final galaxy photometry measurements.
	Test Data	No data.
	Expected Result	
2	Description	Train photometric redshift algorithm(s) on spectroscopic and high-accuracy photometric redshift catalogs.
	Test Data	No data.
	Expected Result	
3	Description	Estimate photometric redshifts for all Objects generated by DRP processing.
	Test Data	No data.
	Expected Result	
4	Description	Load into DRP Database
	Test Data	No data.
	Expected Result	
5	Description	Inspect database to verify that photometric redshifts are present for all objects
	Test Data	No data.
	Expected Result	

4.47 LVV-T69 - Verify implementation of Object Characterization

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.47.1 Verification Elements

- LVV-107 - DMS-REQ-0276-V-01: Object Characterization

4.47.2 Test Items

Verify that Object catalogs produced by the DRP pipeline include all measurements listed in DMS-REQ-0276: a point-source model fit, a bulge-disk model fit, standard colors, a centroid, adaptive moments, Petrosian and Kron fluxes, surface brightness at multiple apertures, proper motion and parallax, and a variability characterization.

4.47.3 Predecessors

4.47.4 Environment Needs

4.47.4.1 Software

4.47.4.2 Hardware

4.47.5 Input Specification

4.47.6 Output Specification

4.47.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Precursor data, execute DRP, load results, observe catalog contents
	Test Data	No data.
	Expected Result	

4.48 LVV-T71 - Verify implementation of Detecting extended low surface brightness objects

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.48.1 Verification Elements

- LVV-180 - DMS-REQ-0349-V-01: Detecting extended low surface brightness objects

4.48.2 Test Items

Verify that low-surface brightness objects (including those whose PSF S/N is lower than the detection threshold) are detected in coadds.

4.48.3 Predecessors

4.48.4 Environment Needs

4.48.4.1 Software

4.48.4.2 Hardware

4.48.5 Input Specification

Input Data

HSC "RC2" data (raw science images and master calibrations)

4.48.6 Output Specification

4.48.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	load LSST DM Stack
	Test Data	No data.
	Expected Result	
2	Description	Run the single-frame processing and self-calibration steps of the DRP pipeline.
	Test Data	No data.
	Expected Result	

Step	Description, Input Data and Expected Result	
3	Description	Insert simulated low-surface-brightness galaxies (with exponential profiles) consistently into all calibrated single-epoch images.
	Test Data	No data.
	Expected Result	
4	Description	Run all remaining DRP pipeline steps.
	Test Data	No data.
	Expected Result	
5	Description	Load data into DRP database
	Test Data	No data.
	Expected Result	
6	Description	Verify that the injected simulated objects are recovered at a rate consistent with their S/N and true profile <i>when not blended with each other or real objects</i> .
	Test Data	No data.
	Expected Result	

4.49 LVV-T72 - Verify implementation of Coadd Image Method Constraints

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.49.1 Verification Elements

- LVV-109 - DMS-REQ-0278-V-01: Coadd Image Method Constraints

4.49.2 Test Items

Verify the implementation of how Coadd images are created.

4.49.3 Predecessors

4.49.4 Environment Needs

4.49.4.1 Software

4.49.4.2 Hardware

4.49.5 Input Specification

4.49.6 Output Specification

4.49.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T12	Description	The DM Stack shall be initialized using the loadLSST script (as described in DRP-00-00).
	Test Data	
	Expected	
	Result	
1-2 from LVV-T12	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected	
	Result	
1-3 from LVV-T12	Description	For each of the expected data products types (listed in Test Items section §4.3.2) and each of the expected units (PVI, coadds, etc), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected	
	Result	
2	Description	Verify that coadds were created following specification
	Test Data	No data.
	Expected	
	Result	

4.50 LVV-T73 - Verify implementation of Deep Detection Coadds

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.50.1 Verification Elements

- LVV-110 - DMS-REQ-0279-V-01: Deep Detection Coadds

4.50.2 Test Items

Verify that the DRP pipelines produce a suite of per-band coadded images that are optimized for depth.

4.50.3 Predecessors

4.50.4 Environment Needs

4.50.4.1 Software

4.50.4.2 Hardware

4.50.5 Input Specification

4.50.6 Output Specification

4.50.7 Test Procedure

Step	Description, Input Data and Expected Result
1-1 from LVV-T12	Description Test Data Expected Result The DM Stack shall be initialized using the loadLSST script (as described in DRP-00-00).
1-2 from LVV-T12	Description Test Data A "Data Butler" will be initialized to access the repository.

Step	Description, Input Data and Expected Result	
	Expected Result	
1-3 from LVV-T12	Description	For each of the expected data products types (listed in Test Items section §4.3.2) and each of the expected units (PVIs, coadds, etc), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected Result	
2	Description	Verify through inspection that per-filter coadds exist for each tract+patch possible
	Test Data	No data.
	Expected Result	
3	Description	Verify through inspection that the images used to generate those coadds met specified conditions
	Test Data	No data.
	Expected Result	
4	Description	Visually inspect a subset of the coadds to verify that they visually appear reasonable and to be from good quality data.
	Test Data	No data.
	Expected Result	

4.51 LVV-T74 - Verify implementation of Template Coadds

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.51.1 Verification Elements

- LVV-111 - DMS-REQ-0280-V-01: Template Coadds

4.51.2 Test Items

Verify that the DMS can produce Template Coadds for DIA processing.

4.51.3 Predecessors

4.51.4 Environment Needs

4.51.4.1 Software

4.51.4.2 Hardware

4.51.5 Input Specification

4.51.6 Output Specification

4.51.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T18	Description	The DM Stack and Alert Processing packaged shall be initialized as described in LVT-T17 (AG-00-00).
	Test Data	
	Expected Result	
1-2 from LVV-T18	Description	The alert generation processing will be executed using the verification cluster:
	Test Data	<pre> '''bash python ap_verify/bin/prepare_demo_slurm_files.py # At present we must run a single ccd+visit to handle ingestion before # parallel processing can begin ./ap_verify/bin/exec_demo_run_1ccd.sh 410915 25 ln -s ap_verify/bin/demo_run.sl ln -s ap_verify/bin/demo_cmds.conf sbatch demo_run.sl ''' </pre>
	Expected Result	and any errors or failures reported.
	Test Data	
	Expected Result	
	Result	

Step	Description, Input Data and Expected Result	
1-3 from LVV-T18	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected	
	Result	
1-4 from LVV-T18	Description	For each of the expected data products types (listed in §4.2.2) and each of the expected units (PVI, catalogs, etc.), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected	
	Result	
1-5 from LVV-T18	Description	DIAObjects are currently only stored in a database, without shims to the Butler, so the existence of the database table and its non-empty contents will be verified by directly accessing it using sqlite3 and executing appropriate SQL queries.
	Test Data	
	Expected	
	Result	

4.52 LVV-T75 - Verify implementation of Multi-band Coadds

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.52.1 Verification Elements

- LVV-112 - DMS-REQ-0281-V-01: Multi-band Coadds

4.52.2 Test Items

Verify that the DRP pipelines produce multi-band coadds for detection purposes.

4.52.3 Predecessors

4.52.4 Environment Needs

4.52.4.1 Software

4.52.4.2 Hardware

4.52.5 Input Specification

4.52.6 Output Specification

4.52.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T12	Description	The DM Stack shall be initialized using the loadLSST script (as described in DRP-00-00).
	Test Data	
	Expected	
	Result	
1-2 from LVV-T12	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected	
	Result	
1-3 from LVV-T12	Description	For each of the expected data products types (listed in Test Items section §4.3.2) and each of the expected units (PVI, coadds, etc), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected	
	Result	
2-1 from LVV-T16	Description	The DM Stack shall be initialized using the loadLSST script (as described in LVV-T10 - DRP-00-00)
	Test Data	
	Expected	
	Result	
2-2 from LVV-T16	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected	
	Result	
2-3 from LVV-T16	Description	For each combination of tract/patch/filter, the PVI will be retrieved from the Butler, and the existence of all components described in Test items section §4.6.2 will be verified.
	Test Data	
	Expected	
	Result	

Step	Description, Input Data and Expected Result	
2-4 from LVV-T16	Description	Scripts from the pipe_analysis package will be run on every visit to check for the presence of data products and make plots
	Test Data	
	Expected Result	
2-5 from LVV-T16	Description	Ten patches will be chosen at random and inspected by eye for unmasked artifacts.
	Test Data	
	Expected Result	
3	Description	Verify that deep detection coadds exist based on all filters.
	Test Data	No data.
	Expected Result	

4.53 LVV-T76 - Verify implementation of All-Sky Visualization of Data Releases

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Simon Krughoff

4.53.1 Verification Elements

- LVV-160 - DMS-REQ-0329-V-01: All-Sky Visualization of Data Releases

4.53.2 Test Items

Show that it's possible to produce large area visualizations from Data Release data products.

4.53.3 Predecessors

4.53.4 Environment Needs

4.53.4.1 Software

4.53.4.2 Hardware

4.53.5 Input Specification

Input Data

Dataset of perhaps ~100 square degrees. The first HSC Public Data Release will be used for this test. Larger (in sky area) datasets should be identified for further testing.

4.53.6 Output Specification

4.53.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T12	Description	The DM Stack shall be initialized using the loadLSST script (as described in DRP-00-00).
	Test Data	
	Expected	
	Result	
1-2 from LVV-T12	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected	
	Result	
1-3 from LVV-T12	Description	For each of the expected data products types (listed in Test Items section §4.3.2) and each of the expected units (PVI, coadds, etc), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected	
	Result	
2	Description	Run all sky tile generation task to produce the data products necessary for serving the all sky visualization.
	Test Data	No data.
	Expected	
	Result	

Step	Description, Input Data and Expected Result	
3	Description	Manually perform, and log (including timing where applicable), the following steps against that all sky visualization application. At all steps take special care to note any missing or un-rendered image tiles:
		1. Navigate to the all sky viewer and log the URL, browser and version. 2. Zoom to native pixel display (1 image pixel per display pixel) 3. Zoom to fit the full PDR footprint 4. Zoom to 1/4x native resolution 5. Pan to eastern edge of the footprint. 6. Pan to western edge of the footprint. 7. Navigate to the middle of the footprint. 8. Zoom to max magnification
	Test Data	No data.
	Expected Result	

4.54 LVV-T77 - Verify implementation of Best Seeing Coadds

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.54.1 Verification Elements

- LVV-161 - DMS-REQ-0330-V-01: Best Seeing Coadds

4.54.2 Test Items

Verify that the DRP pipelines produce a suite of per-band coadds with input images filtered to optimize the size of the effective PSF on the coadd.

4.54.3 Predecessors

4.54.4 Environment Needs

4.54.4.1 Software

4.54.4.2 Hardware

4.54.5 Input Specification

4.54.6 Output Specification

4.54.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T12	Description	The DM Stack shall be initialized using the loadLSST script (as described in DRP-00-00).
	Test Data	
	Expected	
	Result	
1-2 from LVV-T12	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected	
	Result	
1-3 from LVV-T12	Description	For each of the expected data products types (listed in Test Items section §4.3.2) and each of the expected units (PVI, coadds, etc), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected	
	Result	
2	Description	Explicitly create a coadd for a specified seeing range in each filter.
	Test Data	No data.
	Expected	
	Result	
3	Description	Verify that these coadds exist.
	Test Data	No data.
	Expected	
	Result	

4.55 LVV-T78 - Verify implementation of Persisting Data Products

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.55.1 Verification Elements

- LVV-165 - DMS-REQ-0334-V-01: Persisting Data Products

4.55.2 Test Items

Verify that per-band deep coadds and best-seeing coadds are present, kept, and available.

4.55.3 Predecessors

4.55.4 Environment Needs

4.55.4.1 Software

4.55.4.2 Hardware

4.55.5 Input Specification

Precursor data from HSC PDR.

4.55.6 Output Specification

4.55.7 Test Procedure

Step	Description, Input Data and Expected Result
1	Description
	Produce some relevant coadds and store them in the Archive
	Test Data
	No data.
	Expected
	Result
2	Description
	Examine the data retention policies for those products

Step	Description, Input Data and Expected Result
Test Data	No data.
Expected Result	

4.56 LVV-T79 - Verify implementation of PSF-Matched Coadds

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.56.1 Verification Elements

- LVV-166 - DMS-REQ-0335-V-01: PSF-Matched Coadds

4.56.2 Test Items

Verify that the DRP pipelines produce PSF matched coadds.

4.56.3 Predecessors

4.56.4 Environment Needs

4.56.4.1 Software

4.56.4.2 Hardware

4.56.5 Input Specification

4.56.6 Output Specification

4.56.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T12	Description	The DM Stack shall be initialized using the loadLSST script (as described in DRP-00-00).
	Test Data	
	Expected	
	Result	
1-2 from LVV-T12	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected	
	Result	
1-3 from LVV-T12	Description	For each of the expected data products types (listed in Test Items section §4.3.2) and each of the expected units (PVI, coadds, etc), the data product will be retrieved from the Butler and verified to be <u>non-empty</u> .
	Test Data	
	Expected	
	Result	
2	Description	Verify that PSF-matched coadds were created.
	Test Data	No data.
	Expected	
	Result	

4.57 LVV-T80 - Verify implementation of Detecting faint variable objects

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Melissa Graham

4.57.1 Verification Elements

- LVV-168 - DMS-REQ-0337-V-01: Detecting faint variable objects

4.57.2 Test Items

To verify that the Data Release Production pipeline will be able to detect faint sources with long-term variability (e.g., quasars, proper motion stars) via, e.g., shorter timescale coadds

(month to a few months).

4.57.3 Predecessors

4.57.4 Environment Needs

4.57.4.1 Software

4.57.4.2 Hardware

4.57.5 Input Specification

Input Data such as:

DECam HiTS data.

Gaia catalog of faint moving objects.

Catalog of spectroscopically confirmed quasars.

(Alternative: input data injected with faint variable sources).

4.57.6 Output Specification

4.57.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T18	Description	The DM Stack and Alert Processing packaged shall be initialized as described in LVT-T17 (AG-00-00).
	Test Data	
	Expected	
	Result	

Step	Description, Input Data and Expected Result	
1-2 from LVV-T18	Description	The alert generation processing will be executed using the verification cluster:
		<pre> "bash python ap_verify/bin/prepare_demo_slurm_files.py # At present we must run a single ccd+visit to handle ingestion before # parallel processing can begin ./ap_verify/bin/exec_demo_run_1ccd.sh 410915 25 ln -s ap_verify/bin/demo_run.sl ln -s ap_verify/bin/demo_cmds.conf sbatch demo_run.sl "</pre>
	Test Data	and any errors or failures reported.
	Expected Result	
1-3 from LVV-T18	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected Result	
1-4 from LVV-T18	Description	For each of the expected data products types (listed in §4.2.2) and each of the expected units (PVIs, catalogs, etc.), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected Result	
1-5 from LVV-T18	Description	DIAObjects are currently only stored in a database, without shims to the Butler, so the existence of the database table and its non-empty contents will be verified by directly accessing it using sqlite3 and executing appropriate SQL queries.
	Test Data	
	Expected Result	
2	Description	Identify 100 objects from Gaia with proper motions high enough to have detectably moved during HSC observations.
	Test Data	No data.
	Expected Result	
	Expected Result	

Step	Description, Input Data and Expected Result	
3	Description	Measure reported proper motion of these objects in DM Stack processing. Verify that it is consistent with Gaia objects.
	Test Data	No data.
	Expected Result	
4	Description	Identify 100 quasars from color-space or existing extragalactic spectroscopic catalog.
	Test Data	No data.
	Expected Result	
5	Description	Measure lightcurves of these quasars. Determine if structure function is reasonable (may require at least a year to determine if the structure function of 100 quasars is "reasonable").
	Test Data	No data.
	Expected Result	
6	Description	(Alternative: if faint variable source can be injected into the input data, test to see if they are recovered).
	Test Data	No data.
	Expected Result	(This Alternative would enable us not only to tell if faint variable objects are detected, but exactly which kinds, how faint, and with what efficiency.)

4.58 LVV-T81 - Verify implementation of Targeted Coadds

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

4.58.1 Verification Elements

- LVV-169 - DMS-REQ-0338-V-01: Targeted Coadds

4.58.2 Test Items

Verify that small sections of any coadd produced by the DRP pipelines can be retained, even if the full coadd is not.

4.58.3 Predecessors

4.58.4 Environment Needs

4.58.4.1 Software

4.58.4.2 Hardware

4.58.5 Input Specification

4.58.6 Output Specification

4.58.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Remove DR from disk
	Test Data	No data.
	Expected Result	
2	Description	Observe retention of designated coadd sections
	Test Data	No data.
	Expected Result	
3	Description	Observe accessibility of designated coadd sections via simulated DAC LSP instance
	Test Data	No data.
	Expected Result	

4.59 LVV-T82 - Verify implementation of Tracking Characterization Changes Between Data Releases

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Jim Bosch

4.59.1 Verification Elements

- LVV-170 - DMS-REQ-0339-V-01: Tracking Characterization Changes Between Data Releases

4.59.2 Test Items

Verify that small-area subsets of a DR can be retained when most of that DR is retired, for comparison with future DRs.

4.59.3 Predecessors

4.59.4 Environment Needs

4.59.4.1 Software

4.59.4.2 Hardware

4.59.5 Input Specification

4.59.6 Output Specification

4.59.7 Test Procedure

Step	Description, Input Data and Expected Result
1	Description Prepare a second DRP run -> DPDD with different configuration parameters for this second test Data Release.
	Test Data No data.
	Expected Result

Step	Description, Input Data and Expected Result	
2-1 from LVV-T1064	Description	Process data with the Data Release Production payload, starting from raw science images and generating science data products, placing them in the Data Backbone.
	Test Data	
	Expected	
	Result	
3	Description	Stage subset of products from first test Data Release to separate storage.
	Test Data	No data.
	Expected	
	Result	
4	Description	Scientifically compare the results of the subset of that region of sky to those in the second test Data Release comparing the results of the DRP Scientific Verification tests.
	Test Data	No data.
	Expected	Diagnostic plots quantifying the differences between scientific outputs between the first and second test datasets.
	Result	

4.60 LVV-T83 - Verify implementation of Bad Pixel Map

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton

4.60.1 Verification Elements

- LVV-22 - DMS-REQ-0059-V-01: Bad Pixel Map

4.60.2 Test Items

Verify that the DMS can produce a map of detector pixels that suffer from pathologies, and that these pathologies are encoded in at least 32-bit values.

4.60.3 Predecessors

4.60.4 Environment Needs

4.60.4.1 Software

4.60.4.2 Hardware

4.60.5 Input Specification

4.60.6 Output Specification

4.60.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Interrogate the calibRegistry for the metadata associated with a bad pixel map, where the validity range contains the date of interest.
	Test Data	No data.
	Expected Result	A bad pixel map for the requested date has been returned.
2	Description	Check that the bad pixel pathologies are encoded as at least 32-bit values, and that the various pathologies are represented by different encoding.
	Test Data	No data.
	Expected Result	Bad pixel values can be decoded to determine their pathologies using their 32-bit values.

4.61 LVV-T84 - Verify implementation of Bias Residual Image

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton

4.61.1 Verification Elements

- LVV-23 - DMS-REQ-0060-V-01: Bias Residual Image

4.61.2 Test Items

Verify that DMS can construct a bias residual image that corrects for temporally-stable bias structures.

Verify that DMS can do this on demand.

4.61.3 Predecessors

4.61.4 Environment Needs

4.61.4.1 Software

4.61.4.2 Hardware

4.61.5 Input Specification

4.61.6 Output Specification

4.61.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Identify the location of an appropriate precursor dataset.
	Test Data	No data.
	Expected Result	
2-1 from LVV-T987	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the following:
	Test Data	
	Expected Result	Butler repo available for reading.
3	Description	Import the standard libraries required for the rest of this test:
	Test Data	No data.

Step	Description, Input Data and Expected Result	
	Example Code	<pre>import os import lsst.afw.display as afwDisplay from lsst.daf.persistence import Butler from lsst.ip.isr import IsrTask from firefly_client import FireflyClient from IPython.display import IFrame</pre>
	Expected Result	
4	Description	Ingest the dataset from step 1 using the Butler (e.g., following example code below).
	Test Data	No data.
	Example Code	<pre>butler = Butler(\$REPOSITORY_PATH) raw = butler.get(`raw`, visit=\$VISIT_ID, detector=2) bias = butler.get(`bias`, visit=\$VISIT_ID, detector=2)</pre>
	Expected Result	
5	Description	Display the bias image and inspect that its pixels contain unique values.
	Test Data	No data.
	Expected Result	A relatively flat image showing the bias level with roughly Poisson noise.
6	Description	Configure and run an Instrument Signature Removal (ISR) task on the raw data. Most corrections are disabled for simplicity, but the bias frame is applied.
	Test Data	No data.
	Example Code	<pre>isr_config = IsrTask.ConfigClass() isr_config.doDark=False isr_config.doFlat=False isr_config.doFringe=False isr_config.doDefect=False isr_config.doAddDistortionModel=False isr_config.doLinearize=False isr = IsrTask(config=isr_config) result = isr.run(raw, bias=bias)</pre>
	Expected Result	A trimmed, bias-corrected image in 'result'.

Step	Description, Input Data and Expected Result	
7	Description	Display the 'result' image and confirm that the bias correction has been performed.
	Test Data	No data.
	Expected Result	A displayed image with bias removed (i.e., typical background counts reduced relative to the raw frame).

4.62 LVV-T85 - Verify implementation of Crosstalk Correction Matrix

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton

4.62.1 Verification Elements

- LVV-24 - DMS-REQ-0061-V-01: Crosstalk Correction Matrix

4.62.2 Test Items

Verify that the DMS can generate a cross-talk correction matrix from appropriate calibration data.

Verify that the DMS can measure the effectiveness of the cross-talk correction matrix.

4.62.3 Predecessors

4.62.4 Environment Needs

4.62.4.1 Software

4.62.4.2 Hardware

4.62.5 Input Specification

4.62.6 Output Specification

4.62.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Identify an appropriate calibration dataset that can be used to derive the crosstalk correction matrix.
	Test Data	No data.
	Expected Result	
2-1 from LVV-T1060	Description	Execute the Calibration Products Production payload. The payload uses raw calibration images and information from the Transformed EFD to generate a subset of Master Calibration Images and Calibration Database entries in the Data Backbone.
	Test Data	
	Expected Result	
2-2 from LVV-T1060	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present and well-formed.
	Test Data	
	Expected Result	
3	Description	Confirm that the crosstalk correction matrix is produced and persisted.
	Test Data	No data.
	Expected Result	A correction matrix quantifying what fraction of the signal detected in any given amplifier on each sensor in the focal plane appears in any other amplifier.
4	Description	Apply the crosstalk correction to simulated images, and confirm that the correction is performing as expected.
	Test Data	No data.
	Expected Result	A noticeable difference between images before and after applying the correction.

4.63 LVV-T86 - Verify implementation of Illumination Correction Frame

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Lupton

4.63.1 Verification Elements

- LVV-25 - DMS-REQ-0062-V-01: Illumination Correction Frame

4.63.2 Test Items

Verify that the DMS can produce an illumination correction frame calibration product.
Verify that the DMS can determine the effectiveness of an illumination correction and determine how often it should be updated.

4.63.3 Predecessors

4.63.4 Environment Needs

4.63.4.1 Software

4.63.4.2 Hardware

4.63.5 Input Specification

4.63.6 Output Specification

4.63.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to CPP
	Test Data	No data.
	Expected	
	Result	

4.64 LVV-T87 - Verify implementation of Monochromatic Flatfield Data Cube

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Lupton

4.64.1 Verification Elements

- LVV-26 - DMS-REQ-0063-V-01: Monochromatic Flatfield Data Cube

4.64.2 Test Items

Verify that the DMS can generate a calibration image/cube that corrects for pixel-to-pixel wavelength-dependent detector response.

Verify that the DMS can measure the effectiveness of this monochromatic flatfield data cube.

4.64.3 Predecessors

4.64.4 Environment Needs

4.64.4.1 Software

4.64.4.2 Hardware

4.64.5 Input Specification

4.64.6 Output Specification

4.64.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to CPP
	Test Data	No data.
	Expected	
	Result	

4.65 LVV-T88 - Verify implementation of Calibration Data Products

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton

4.65.1 Verification Elements

- LVV-57 - DMS-REQ-0130-V-01: Calibration Data Products

4.65.2 Test Items

Verify that the DMS can produce and archive the required Calibration Data Products: cross talk correction, bias, dark, monochromatic dome flats, broad-band flats, fringe correction, and illumination corrections.

4.65.3 Predecessors

4.65.4 Environment Needs

4.65.4.1 Software

4.65.4.2 Hardware

4.65.5 Input Specification

4.65.6 Output Specification

4.65.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Identify a suitable set of calibration frames, including biases, dark frames, and flat-field frames.
	Test Data	No data.
	Expected Result	
2-1 from LVV-T1060	Description	Execute the Calibration Products Production payload. The payload uses raw calibration images and information from the Transformed EFD to generate a subset of Master Calibration Images and Calibration Database entries in the Data Backbone.
	Test Data	
	Expected Result	
2-2 from LVV-T1060	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present and well-formed.
	Test Data	

Step	Description, Input Data and Expected Result	
	Test Data	
	Expected	
	Result	
3	Description	Confirm that the expected data products are created, and that they have the expected properties.
	Test Data	No data.
	Expected Result	A full set of calibration data products has been created, and they are well-formed.
4	Description	Test that the calibration products are archived, and can readily be applied to science data to produce the desired corrections.
	Test Data	No data.
	Expected Result	Confirmation that application of the calibration products to processed data has the desired effects.

4.66 LVV-T89 - Verify implementation of Calibration Image Provenance

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton

4.66.1 Verification Elements

- LVV-59 - DMS-REQ-0132-V-01: Calibration Image Provenance
- LVV-1234 - OSS-REQ-0122-V-01: Provenance

4.66.2 Test Items

Verify that the DMS records the required provenance information for the Calibration Data Products.

4.66.3 Predecessors

4.66.4 Environment Needs

4.66.4.1 Software

4.66.4.2 Hardware

4.66.5 Input Specification

4.66.6 Output Specification

4.66.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Ingest an appropriate precursor calibration dataset into a Butler repo.
	Test Data	No data.
	Expected Result	
2-1 from LVV-T1060	Description	Execute the Calibration Products Production payload. The payload uses raw calibration images and information from the Transformed EFD to generate a subset of Master Calibration Images and Calibration Database entries in the Data Backbone.
	Test Data	
	Expected Result	
2-2 from LVV-T1060	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present and well-formed.
	Test Data	
	Expected Result	
3	Description	Load the relevant database/Butler data product, and observe that all provenance information has been retained.
	Test Data	No data.
	Expected Result	A dataset consisting of calibration images, with provenance information recorded and properly associated with the calibration images.

4.67 LVV-T90 - Verify implementation of Dark Current Correction Frame

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton

4.67.1 Verification Elements

- LVV-113 - DMS-REQ-0282-V-01: Dark Current Correction Frame

4.67.2 Test Items

Verify that the DMS can produce a dark correction frame calibration product.

Verify that the DMS can determine the effectiveness of a dark correction and determine how often it should be updated.

4.67.3 Predecessors

4.67.4 Environment Needs

4.67.4.1 Software

4.67.4.2 Hardware

4.67.5 Input Specification

4.67.6 Output Specification

4.67.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Identify the path to a dataset containing dark frames (i.e., exposures taken with the shutter closed).
	Test Data	No data.
	Expected Result	
2	Description	Execute the relevant steps from 'cp_pipe' (the calibration pipeline) to produce dark correction frames.

Step	Description, Input Data and Expected Result	
	Test Data	No data.
	Expected Result	
	Description	Inspect the resulting dark correction frame to confirm that it appears as expected.
3	Test Data	No data.
	Expected Result	A well-formed dark correction frame is present and accessible via the Data Butler.
	Description	Determining whether the dark correction is being done properly will require on-sky science data. The dark correction can be applied to these frames and the results inspected to ensure that the correction was correctly measured and applied.
4	Test Data	No data.
	Expected Result	Applying the dark correction to a dataset produces noticeable differences between the original frame(s) and the corrected outputs.
	Description	

4.68 LVV-T91 - Verify implementation of Fringe Correction Frame

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Lupton

4.68.1 Verification Elements

- LVV-114 - DMS-REQ-0283-V-01: Fringe Correction Frame

4.68.2 Test Items

Verify that the DMS can produce an fringe-correction frame calibration product.

Verify that the DMS can determine the effectiveness of the fringe-correction frame and determine how often it should be updated.

4.68.3 Predecessors

4.68.4 Environment Needs

4.68.4.1 Software

4.68.4.2 Hardware

4.68.5 Input Specification

4.68.6 Output Specification

4.68.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to CPP
	Test Data	No data.
	Expected Result	

4.69 LVV-T92 - Verify implementation of Processing of Data From Special Programs

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Melissa Graham

4.69.1 Verification Elements

- LVV-151 - DMS-REQ-0320-V-01: Processing of Data From Special Programs

4.69.2 Test Items

For a simulated night of observing that includes some special program observations, show that the SP observations are reduced using their designated reconfigured pipelines (i.e., that the image metadata is sufficient to trigger the processing and include all other relevant images in the processing).

4.69.3 Predecessors

4.69.4 Environment Needs

4.69.4.1 Software

4.69.4.2 Hardware

4.69.5 Input Specification

A variety of imaging data from Special Programs, including these scenarios:

- (1) Special Programs data that can be processed by the Prompt pipeline (i.e., standard visits)
- (2) Special Programs data that requires 'real-time' (~24) processing with a reconfigured pipeline (e.g., DDF imaging sequence)
- (3) Special Programs data that can (should) be processed by the Data Release pipeline (e.g., North Ecliptic Spur standard visits)

4.69.6 Output Specification

4.69.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	(1) Special Programs data that can be processed by the Prompt pipeline (i.e., standard visits). Check that all images with the header keyword for SP were processed by the Prompt pipeline. Check that the Prompt pipeline's data products – DIASource, DIAObject catalogs and the Alerts – contain items flagged with their origin as that SP.
	Test Data	No data.
	Expected Result	
2	Description	(2) Special Programs data that requires 'real-time' (~24) processing with a reconfigured pipeline (e.g., DDF imaging sequence) Check that all images with the header keywords for a given SP were processed by their reconfigured pipeline. Check that the pipeline's data products have been updated, and passed their QA.
	Test Data	No data.
	Expected Result	

Step	Description, Input Data and Expected Result
3	Description (3) Special Programs data that can (should) be processed by the Data Release pipeline (e.g., North Ecliptic Spur standard visits). SP data would be added manually to the DRP processing. Check that the DRP's data products – Source, Object, CoAdds – contain items flagged as originating in that SP.
	Test Data No data.
	Expected Result

4.70 LVV-T93 - Verify implementation of Level 1 Processing of Special Programs Data

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Melissa Graham

4.70.1 Verification Elements

- LVV-152 - DMS-REQ-0321-V-01: Level 1 Processing of Special Programs Data

4.70.2 Test Items

Execute multi-day operations rehearsal. Observe whether Prompt Processing data products generated in time and confirm whether processing has completed before the start of the next simulated night.

4.70.3 Predecessors

4.70.4 Environment Needs

4.70.4.1 Software

4.70.4.2 Hardware

4.70.5 Input Specification

Imaging data obtained under a Special Program: for example, a sequence of consecutive images of a deep drilling field.

4.70.6 Output Specification

4.70.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	If imaging data for a Special Program that requires processing with the Prompt pipeline was obtained the previous night, check that there exist DIASources/Objects/Alerts with flags that they originated from the Special Program.
	Test Data	No data.
	Expected Result	
2	Description	If imaging data for a Special Program that requires prompt processing with a reconfigured pipeline was obtained the previous night, check that the relevant data products have been updated.
	Test Data	No data.
	Expected Result	

4.71 LVV-T94 - Verify implementation of Special Programs Database

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Melissa Graham

4.71.1 Verification Elements

- LVV-153 - DMS-REQ-0322-V-01: Special Programs Database

4.71.2 Test Items

To confirm that data products from Special Programs are based solely on images obtained as part of SP via, e.g., metadata queries. To confirm that the SP data products can be joined

to Prompt and DRP products by attempting to do so via, e.g., coordinate table joins, and attempting to e.g., find the faint counterparts in a Deep Drilling stack to variables with no Object detections in the DRP coadds.

4.71.3 Predecessors

4.71.4 Environment Needs

4.71.4.1 Software

4.71.4.2 Hardware

4.71.5 Input Specification

Databases created by reconfigured pipelines for processing Special Programs data (e.g., DIAObject/DIASource catalogs for a Deep Drilling Field).

4.71.6 Output Specification

4.71.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	SP data product: DDF DIAObjects catalog Non-SP data product: WFD DIAObjects catalog Test: join the two catalogs by coordinate (e.g., to get a longer time baseline for variable stars in the DDF)
	Test Data	No data.
	Expected Result	
2	Description	SP data product: DDF Objects catalog Non-SP data product: WFD DIAObjects catalog Test: join the two catalogs by coordinate to identify faint host galaxies of transients found in WFD
	Test Data	No data.
	Expected Result	

4.72 LVV-T95 - Verify implementation of Constraints on Level 1 Special Program Products Generation

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Melissa Graham

4.72.1 Verification Elements

- LVV-175 - DMS-REQ-0004-V-01: Time to L1 public release
- LVV-1276 - OSS-REQ-0127-V-01: Level 1 Data Product Availability

4.72.2 Test Items

Execute single-day operations rehearsal. Observe Prompt Processing data products generated in time. Confirm that data from Special Programs is processed with the same latency as required for main survey data: release of public data within L1publicT and Alerts within OTT1.

4.72.3 Predecessors

4.72.4 Environment Needs

4.72.4.1 Software

4.72.4.2 Hardware

4.72.5 Input Specification

Data from a Special Program that is appropriate for the Prompt pipeline (i.e., a Deep Drilling type series of standard visits from a non-crowded field).

4.72.6 Output Specification

4.72.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T35	Description	
	Test Data	
	Expected	
	Result	
1-2 from LVV-T35	Description	
	Test Data	
	Expected	
	Result	
1-3 from LVV-T35	Description	Time processing of data starting from (pre-ingested) raw files until an alert is available for distribution; verify that this time is less than OTT1.
	Test Data	
	Expected	
	Result	
1-4 from LVV-T35	Description	Time processing of data starting from (pre-ingested) raw files until the required data products are available in the Science Platform. Verify that this time is less than L1PublicT.
	Test Data	
	Expected	
	Result	
1-5 from LVV-T35	Description	Run MOPS on 1 night equivalent of LSST observing worth of precursor data and verify that Solar System Object orbits can be updated within 24 hours.
	Test Data	
	Expected	
	Result	
1-6 from LVV-T35	Description	Record time between completion of MOPS processing and availability of the updated SSO object catalogue through the Science Platform; verify this time is less than L1PublicT.
	Test Data	
	Expected	
	Result	

4.73 LVV-T96 - Verify implementation of Query Repeatability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.73.1 Verification Elements

- LVV-122 - DMS-REQ-0291-V-01: Query Repeatability

4.73.2 Test Items

Verify that prior queries can be rerun with identical results, or with new additional data for live (Alert Production) databases.

4.73.3 Predecessors

4.73.4 Environment Needs

4.73.4.1 Software

4.73.4.2 Hardware

4.73.5 Input Specification

4.73.6 Output Specification

4.73.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Select and download (deterministic) random subsample of records from Data Release Object and Source tables.
	Test Data	No data.
	Expected Result	
2	Description	Select and download random subsample of PPDB DIAObject and DIASource tables.
	Test Data	No data.
	Expected Result	
3	Description	As appropriate, wait for some amount of non-trivial database usage to occur, such as Prompt Processing ingestion or ingestion of other DRP database tables.
	Test Data	No data.

Step	Description, Input Data and Expected Result	
	Expected Result	
4	Description	Re-run the queries in steps 1 and 2 and verify that the resulting data are identical.
	Test Data	No data.
	Expected Result	

4.74 LVV-T97 - Verify implementation of Uniqueness of IDs Across Data Releases

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Kian-Tat Lim

4.74.1 Verification Elements

- LVV-123 - DMS-REQ-0292-V-01: Uniqueness of IDs Across Data Releases

4.74.2 Test Items

Verify that the IDs of Objects, Sources, DIAObjects, and DIASources from different Data Releases are unique.

4.74.3 Predecessors

4.74.4 Environment Needs

4.74.4.1 Software

4.74.4.2 Hardware

4.74.5 Input Specification

4.74.6 Output Specification

4.74.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Identify an appropriate precursor dataset to be processed through Data Release Production.
	Test Data	No data.
	Expected Result	
2-1 from LVV-T1064	Description	Process data with the Data Release Production payload, starting from raw science images and generating science data products, placing them in the Data Backbone.
	Test Data	
	Expected Result	
3-1 from LVV-T987	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the following:
	Test Data	
	Expected Result	Butler repo available for reading.
4	Description	After running the DRP payload multiple times, load the resulting data products (both data release and prompt products) using the Butler.
	Test Data	No data.
	Expected Result	Multiple datasets resulting from processing of the same input data.
5	Description	Inspect the IDs in the multiple data products and confirm that all IDs are unique.
	Test Data	No data.
	Expected Result	No IDs are repeated between multiple processings of the identical input dataset.

4.75 LVV-T98 - Verify implementation of Selection of Datasets

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Kian-Tat Lim

4.75.1 Verification Elements

- LVV-124 - DMS-REQ-0293-V-01: Selection of Datasets

4.75.2 Test Items

Verify that the DMS can identify and retrieve datasets consisting of logical groupings of Exposures, metadata, provenance, etc., or other groupings that are processed or produced as a logical unit.

4.75.3 Predecessors

4.75.4 Environment Needs

4.75.4.1 Software

4.75.4.2 Hardware

4.75.5 Input Specification

4.75.6 Output Specification

4.75.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T987	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the following:
	Test Data	
	Expected Result	Butler repo available for reading.
2	Description	Ingest data from an appropriate processed dataset.
	Test Data	No data.

Step	Description, Input Data and Expected Result	
	Expected Result	
3	Description	Observe retrieval of single Processed Visit Image (PVI) with metadata.
	Test Data	No data.
	Expected Result	A PVI and its associated metadata.
4	Description	Observe retrieval of multiple PVIs with metadata.
	Test Data	No data.
	Expected Result	A set of PVIs and their associated metadata.
5	Description	Observe retrieval of coadd patch with metadata and provenance information.
	Test Data	No data.
	Expected Result	An image of coadded data in a patch, along with its metadata and information describing the provenance of the patch constituents.
6	Description	Observe retrieval of subset of rows in each of the above catalogs.
	Test Data	No data.
	Expected Result	

4.76 LVV-T99 - Verify implementation of Processing of Datasets

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.76.1 Verification Elements

- LVV-125 - DMS-REQ-0294-V-01: Processing of Datasets

4.76.2 Test Items

Execute AP and DRP, simulate failures, observe correct processing

4.76.3 Predecessors

4.76.4 Environment Needs

4.76.4.1 Software

4.76.4.2 Hardware

4.76.5 Input Specification

4.76.6 Output Specification

4.76.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute AP and DRP
	Test Data	No data.
	Expected Result	
2	Description	Simulate failures
	Test Data	No data.
	Expected Result	
3	Description	Observe correct processing
	Test Data	No data.
	Expected Result	

4.77 LVV-T100 - Verify implementation of Transparent Data Access

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.77.1 Verification Elements

- LVV-126 - DMS-REQ-0295-V-01: Transparent Data Access

4.77.2 Test Items

Test Items

Observe dataset retrieval from multiple LSP instances

4.77.3 Predecessors

4.77.4 Environment Needs

4.77.4.1 Software

4.77.4.2 Hardware

4.77.5 Input Specification

4.77.6 Output Specification

4.77.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Observe dataset retrieval from multiple LSP instances
	Test Data	No data.
	Expected	
	Result	

4.78 LVV-T101 - Verify implementation of Transient Alert Distribution

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.78.1 Verification Elements

- LVV-3 - DMS-REQ-0002-V-01: Transient Alert Distribution

4.78.2 Test Items

Precursor or simulated data, execute AP, observe distribution to simulated clients using standard protocols

4.78.3 Predecessors

4.78.4 Environment Needs

4.78.4.1 Software

4.78.4.2 Hardware

4.78.5 Input Specification

Obtain precursor or simulated data; duplicated by LVV-T217 – delete?

4.78.6 Output Specification

4.78.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute AP
	Test Data	No data.
	Expected Result	
2	Description	Observe distribution to simulated clients using standard protocols
	Test Data	No data.
	Expected Result	

4.79 LVV-T102 - Verify implementation of Solar System Objects Available Within Specified Time

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.79.1 Verification Elements

- LVV-36 - DMS-REQ-0089-V-01: Solar System Objects Available Within Specified Time
- LVV-1276 - OSS-REQ-0127-V-01: Level 1 Data Product Availability
- LVV-9803 - DMS-REQ-0004-V-03: Time to availability of Solar System Object orbits

4.79.2 Test Items

Execute single-day operations rehearsal, observe data products generated in time

4.79.3 Predecessors

4.79.4 Environment Needs

4.79.4.1 Software

4.79.4.2 Hardware

4.79.5 Input Specification

4.79.6 Output Specification

4.79.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute single-day operations rehearsal
	Test Data	No data.

Step	Description, Input Data and Expected Result	
	Expected Result	
2	Description	Observe data products generated in time
	Test Data	No data.
	Expected Result	

4.80 LVV-T103 - Verify implementation of Generate Data Quality Report Within Specified Time

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Kian-Tat Lim

4.80.1 Verification Elements

- LVV-38 - DMS-REQ-0096-V-01: Generate Data Quality Report Within Specified Time

4.80.2 Test Items

Verify that the DMS can generate a nightly L1 Data Quality Report within **dqReportComplTime = 4[hour]**, in both human- and machine-readable formats.

4.80.3 Predecessors

4.80.4 Environment Needs

4.80.4.1 Software

4.80.4.2 Hardware

4.80.5 Input Specification

4.80.6 Output Specification

4.80.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute single-day operations rehearsal
	Test Data	No data.
	Expected Result	
2	Description	After dqReportComplTime = 4[hour] has passed, confirm (via timestamps) that the data quality report has been generated within dqReportComplTime = 4[hour] , and that it contains the correct contents.
	Test Data	No data.
	Expected Result	Both human- and machine-readable versions of the L1 Data Quality Report are available with dqReportComplTime.

4.81 LVV-T104 - Verify implementation of Generate DMS Performance Report Within Specified Time

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.81.1 Verification Elements

- LVV-40 - DMS-REQ-0098-V-01: Generate DMS Performance Report Within Specified Time

4.81.2 Test Items

Verify that the DMS can generate a nightly Performance Report within perfReportComplTime

4.81.3 Predecessors

4.81.4 Environment Needs

4.81.4.1 Software

4.81.4.2 Hardware

4.81.5 Input Specification

4.81.6 Output Specification

4.81.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute single-day operations rehearsal
	Test Data	No data.
	Expected Result	
2	Description	Observe performance report is generated on time and with correct contents
	Test Data	No data.
	Expected Result	

4.82 LVV-T105 - Verify implementation of Generate Calibration Report Within Specified Time

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.82.1 Verification Elements

- LVV-42 - DMS-REQ-0100-V-01: Generate Calibration Report Within Specified Time

4.82.2 Test Items

Verify that the DMS can generate a night Calibration Report in both human-readable and machine-parseable forms.

4.82.3 Predecessors

4.82.4 Environment Needs

4.82.4.1 Software

4.82.4.2 Hardware

4.82.5 Input Specification

4.82.6 Output Specification

4.82.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute single-day operations rehearsal
	Test Data	No data.
	Expected Result	
2	Description	Observe calibration report is generated on time and with correct contents
	Test Data	No data.
	Expected Result	

4.83 LVV-T106 - Verify implementation of Calibration Images Available Within Specified Time

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.83.1 Verification Elements

- LVV-58 - DMS-REQ-0131-V-01: Time allowed to process calibs

4.83.2 Test Items

Execute single-day operations rehearsal, observe data products generated

4.83.3 Predecessors

4.83.4 Environment Needs

4.83.4.1 Software

4.83.4.2 Hardware

4.83.5 Input Specification

4.83.6 Output Specification

4.83.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Identify a dataset of raw calibration exposures containing at least nCalExpProc = 25 exposures. (If it contains more than 25 exposures, use only 25 for the test.)
	Test Data	No data.
	Expected Result	
2-1 from LVV-T1059	Description	Execute the Daily Calibration Products Update payload. The payload uses raw calibration images and information from the Transformed EFD to generate a subset of Master Calibration Images and Calibration Database entries in the Data Backbone.
	Test Data	
	Expected Result	
2-2 from LVV-T1059	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present and well-formed.
	Test Data	
	Expected Result	
3	Description	Confirm that the processing completed successfully within calProcTime = 1200 seconds .

Step	Description, Input Data and Expected Result	
	Test Data	No data.
	Expected Result	Calibration products resulting from processed raw calibration exposures are present within calProcTime, and are well-formed images.

4.84 LVV-T107 - Verify implementation of Level-1 Production Completeness

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.84.1 Verification Elements

- LVV-115 - DMS-REQ-0284-V-01: Level-1 Production Completeness

4.84.2 Test Items

Verify that the DMS successfully processes all images of sufficiently quality for processing are eventually processed even after connectivity failures.

4.84.3 Predecessors

LVV-T284

4.84.4 Environment Needs

4.84.4.1 Software

4.84.4.2 Hardware

4.84.5 Input Specification

4.84.6 Output Specification

4.84.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Ingest raw data while simulating failures and outages, observe eventual recovery
	Test Data	No data.
	Expected Result	

4.85 LVV-T108 - Verify implementation of Level 1 Source Association

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.85.1 Verification Elements

- LVV-116 - DMS-REQ-0285-V-01: Level 1 Source Association

4.85.2 Test Items

Verify that the DMS associates DIASources into a DIAObject or SSObject.

4.85.3 Predecessors

4.85.4 Environment Needs

4.85.4.1 Software

4.85.4.2 Hardware

4.85.5 Input Specification

4.85.6 Output Specification

4.85.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to AP
	Test Data	No data.
	Expected Result	

4.86 LVV-T109 - Verify implementation of SSObject Precovery

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.86.1 Verification Elements

- LVV-117 - DMS-REQ-0286-V-01: SSObject Precovery

4.86.2 Test Items

Verify that the DMS associates additional DIAObjects (both forward and back in time) with objects classified as SSObjects.

4.86.3 Predecessors

4.86.4 Environment Needs

4.86.4.1 Software

4.86.4.2 Hardware

4.86.5 Input Specification

4.86.6 Output Specification

4.86.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to AP
	Test Data	No data.
	Expected Result	

4.87 LVV-T110 - Verify implementation of DIASource Precovery

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.87.1 Verification Elements

- LVV-118 - DMS-REQ-0287-V-01: Max look-back time for precovery

4.87.2 Test Items

Verify that DMS performs forced photometry for new DIAObjects at all available images within the precoveryWindow.

4.87.3 Predecessors

4.87.4 Environment Needs

4.87.4.1 Software

4.87.4.2 Hardware

4.87.5 Input Specification

4.87.6 Output Specification

4.87.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute single-day operations rehearsal, observe data products generated in time
	Test Data	No data.
	Expected Result	

4.88 LVV-T111 - Verify implementation of Use of External Orbit Catalogs

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.88.1 Verification Elements

- LVV-119 - DMS-REQ-0288-V-01: Use of External Orbit Catalogs

4.88.2 Test Items

Verify that the DMS can make use of external catalogs to improve identification of SSObjects.

4.88.3 Predecessors

4.88.4 Environment Needs

4.88.4.1 Software

4.88.4.2 Hardware

4.88.5 Input Specification

4.88.6 Output Specification

4.88.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to AP
	Test Data	No data.
	Expected	
	Result	

4.89 LVV-T112 - Verify implementation of Alert Filtering Service

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Eric Bellm

4.89.1 Verification Elements

- LVV-173 - DMS-REQ-0342-V-01: Alert Filtering Service

4.89.2 Test Items

Verify that user-defined filters can be used to generate a basic alert filtering service.

4.89.3 Predecessors

4.89.4 Environment Needs

4.89.4.1 Software

4.89.4.2 Hardware

4.89.5 Input Specification

4.89.6 Output Specification

4.89.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Identify a suitable precursor dataset for processing through the Alert Production pipeline.
	Test Data	No data.
	Expected Result	
2-1 from LVV-T866	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame processing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is presumed that these are automated for a given dataset.
	Test Data	
	Expected Result	An output dataset including difference images and DIASource and DIAObject measurements.
2-2 from LVV-T866	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
	Test Data	
	Expected Result	
3	Description	Confirm that alerts are generated, and that an Alert Distribution service is making them available via a stream.
	Test Data	No data.
	Expected Result	Via either a UI or API, confirmation that a stream of alerts are available.
4	Description	Confirm that a UI (or API) exists that allows users to define simple filters. Define a filter, and observe both the full and the filtered alert streams to confirm that the filter has reduced the volume of alerts.
	Test Data	No data.
	Expected Result	The user-defined filter has reduced the number of alerts being received relative to the full stream.

4.90 LVV-T113 - Verify implementation of Performance Requirements for LSST Alert Filtering Service

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Eric Bellm

4.90.1 Verification Elements

- LVV-174 - DMS-REQ-0343-V-01: Number of full-size alerts

4.90.2 Test Items

Verify that the DMS alert filter service provides sufficient bandwidth for **numBrokerUsers = 100** simultaneously-operating brokers to receive up to **numBrokerAlerts = 20** alerts per visit.

4.90.3 Predecessors

4.90.4 Environment Needs

4.90.4.1 Software

4.90.4.2 Hardware

4.90.5 Input Specification

4.90.6 Output Specification

4.90.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Create a simulated alert stream.
	Test Data	No data.
	Expected Result	
2	Description	Simultaneously execute user-defined alert filters for at least numBrokerUsers = 100 users, and confirm that the system successfully filters the stream as requested. Confirm that the bandwidth requirement of numBrokerAlerts = 20 per user was met.
	Test Data	No data.
	Expected Result	All of the (simulated) users successfully receive their requested filtered alerts, with numBrokerAlerts = 20 per user.

4.91 LVV-T114 - Verify implementation of Pre-defined alert filters

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Eric Bellm

4.91.1 Verification Elements

- LVV-179 - DMS-REQ-0348-V-01: Pre-defined alert filters

4.91.2 Test Items

Verify that users of the Alert Filtering service can use a predefined set of filters.

4.91.3 Predecessors

4.91.4 Environment Needs

4.91.4.1 Software

4.91.4.2 Hardware

4.91.5 Input Specification

4.91.6 Output Specification

4.91.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Create a simulated alert stream. Confirm that alerts are generated, and that an Alert Distribution service is making them available.
	Test Data	No data.
	Expected Result	A stream of alerts that is confirmed to be generated and distributed.
2	Description	Confirm that a UI (or API) exists that presents users some pre-defined filters.
	Test Data	No data.

Step	Description, Input Data and Expected Result	
	Expected Result	The UI (or API) for accessing alert streams has some pre-defined filters available for users.
3	Description	Select one of the pre-defined filters, and confirm that the results have been properly filtered.
	Test Data	No data.
	Expected Result	After applying the pre-defined filter, the number of alerts has decreased relative to the raw stream.

4.92 LVV-T115 - Verify implementation of Calibration Production Processing

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Kian-Tat Lim

4.92.1 Verification Elements

- LVV-120 - DMS-REQ-0289-V-01: Calibration Production Processing

4.92.2 Test Items

Execute CPP on a variety of representative cadences, and verify that the calibration pipeline correctly produces necessary calibration products.

4.92.3 Predecessors

4.92.4 Environment Needs

4.92.4.1 Software

4.92.4.2 Hardware

4.92.5 Input Specification

4.92.6 Output Specification

4.92.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Identify a suitable set of calibration frames, including biases, dark frames, and flat-field frames.
	Test Data	No data.
	Expected Result	
2-1 from LVV-T1060	Description	Execute the Calibration Products Production payload. The payload uses raw calibration images and information from the Transformed EFD to generate a subset of Master Calibration Images and Calibration Database entries in the Data Backbone.
	Test Data	
	Expected Result	
2-2 from LVV-T1060	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present and well-formed.
	Test Data	
	Expected Result	
3	Description	Confirm that the expected data products are created, and that they have the expected properties.
	Test Data	No data.
	Expected Result	Repos containing valid calibration products that are well-formed and ready to be applied to processed datasets.

4.93 LVV-T116 - Verify implementation of Associating Objects across data releases

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.93.1 Verification Elements

- LVV-181 - DMS-REQ-0350-V-01: Associating Objects across data releases

4.93.2 Test Items

Load DR, observe queryable association

4.93.3 Predecessors

4.93.4 Environment Needs

4.93.4.1 Software

4.93.4.2 Hardware

4.93.5 Input Specification

4.93.6 Output Specification

4.93.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Load DR
	Test Data	No data.
	Expected Result	
2	Description	Observe queryable association
	Test Data	No data.
	Expected Result	

4.94 LVV-T117 - Verify implementation of DAC resource allocation for Level 3 processing

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.94.1 Verification Elements

- LVV-47 - DMS-REQ-0119-V-01: DAC resource allocation for Level 3 processing

4.94.2 Test Items

Verify that compute time and storage space allocations can be granted to science users.

4.94.3 Predecessors

4.94.4 Environment Needs

4.94.4.1 Software

4.94.4.2 Hardware

4.94.5 Input Specification

4.94.6 Output Specification

4.94.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Create a test user account for the Science Platform.
	Test Data	No data.
	Expected Result	
2	Description	Set the LSP resource allocations for the test user to very low values.
	Test Data	No data.
	Expected Result	
3	Description	Initiate example batch jobs and notebook sessions that will exceed the specified resource limits.
	Test Data	No data.
	Expected Result	Quota error.

Step	Description, Input Data and Expected Result	
4	Description	Transfer sufficient data volumes into the user workspace and MyDB tables that would exceed the resource quotas.
	Test Data	No data.
	Expected Result	Quota error.
5	Description	Reset the user resource quotas to normal values.
	Test Data	No data.
	Expected Result	
6	Description	Initiate the same example batch jobs and notebook sessions that previously caused an error.
	Test Data	No data.
	Expected Result	Successful notebook and batch job execution.
7	Description	Transfer the same data volumes into the user workspace and MyDB tables that previously caused an error.
	Test Data	No data.
	Expected Result	Successful data transfer.

4.95 LVV-T118 - Verify implementation of Level 3 Data Product Self Consistency

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.95.1 Verification Elements

- LVV-48 - DMS-REQ-0120-V-01: Level 3 Data Product Self Consistency

4.95.2 Test Items

Verify that user-driven Level 3 processing is conducted on consistent sets of input data.

4.95.3 Predecessors

4.95.4 Environment Needs

4.95.4.1 Software

4.95.4.2 Hardware

4.95.5 Input Specification

4.95.6 Output Specification

4.95.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute representative processing on DR in PDAC, observe consistency
	Test Data	No data.
	Expected Result	

4.96 LVV-T119 - Verify implementation of Provenance for Level 3 processing at DACs

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.96.1 Verification Elements

- LVV-49 - DMS-REQ-0121-V-01: Provenance for Level 3 processing at DACs
- LVV-1234 - OSS-REQ-0122-V-01: Provenance

4.96.2 Test Items

Verify that provenance information is recorded and accessible for user-generated Level 3 products.

4.96.3 Predecessors

4.96.4 Environment Needs

4.96.4.1 Software

4.96.4.2 Hardware

4.96.5 Input Specification

4.96.6 Output Specification

4.96.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute representative processing on DR in PDAC, observe provenance recording
	Test Data	No data.
	Expected Result	

4.97 LVV-T120 - Verify implementation of Software framework for Level 3 catalog processing

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.97.1 Verification Elements

- LVV-53 - DMS-REQ-0125-V-01: Software framework for Level 3 catalog processing

4.97.2 Test Items

Verify that user-driven Level 3 processing can be consistently applied to all records in a catalog.

4.97.3 Predecessors

4.97.4 Environment Needs

4.97.4.1 Software

4.97.4.2 Hardware

4.97.5 Input Specification

4.97.6 Output Specification

4.97.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute representative processing on DR in PDAC, observe recognition of and recovery from failures
	Test Data	No data.
	Expected Result	

4.98 LVV-T121 - Verify implementation of Software framework for Level 3 image processing

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.98.1 Verification Elements

- LVV-56 - DMS-REQ-0128-V-01: Software framework for Level 3 image processing

4.98.2 Test Items

Verify that user-specified Level 3 processing can be applied to the desired set of images.

4.98.3 Predecessors

4.98.4 Environment Needs

4.98.4.1 Software

4.98.4.2 Hardware

4.98.5 Input Specification

4.98.6 Output Specification

4.98.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute representative processing on DR in PDAC, observe recognition of and recovery from failures
	Test Data	No data.
	Expected Result	

4.99 LVV-T122 - Verify implementation of Level 3 Data Import

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.99.1 Verification Elements

- LVV-121 - DMS-REQ-0290-V-01: Level 3 Data Import

4.99.2 Test Items

Verify that the Science Platform can ingest data from community-standard file formats.

4.99.3 Predecessors

4.99.4 Environment Needs

4.99.4.1 Software

4.99.4.2 Hardware

4.99.5 Input Specification

4.99.6 Output Specification

4.99.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Use the Science Platform catalog upload tool to ingest a small example FITS table.
	Test Data	No data.
	Expected Result	
2	Description	Use the Science Platform catalog upload tool to ingest a small example CSV table.
	Test Data	No data.
	Expected Result	
3	Description	Use the Science Platform catalog upload tool to ingest a large FITS table that needs to be spatially-sharded in the database.
	Test Data	No data.
	Expected Result	
4	Description	Perform example queries on each of the three tables to verify that all data is present.
	Test Data	No data.
	Expected Result	Data returned in the queries is identical to the data uploaded.

Step	Description, Input Data and Expected Result
------	---

4.100 LVV-T123 - Verify implementation of Access Controls of Level 3 Data Products

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.100.1 Verification Elements

- LVV-171 - DMS-REQ-0340-V-01: Access Controls of Level 3 Data Products

4.100.2 Test Items

This test touches upon the interface between the following areas: IT Security, Identity Management, LSP Portal, and Parallel Distributed Database. The purpose is to show that access to user generated data products (previously Level 3) can have a variety of access restrictions varying from single-user, a list, a named group, or open access.

4.100.3 Predecessors

4.100.4 Environment Needs

4.100.4.1 Software

4.100.4.2 Hardware

4.100.5 Input Specification

4.100.6 Output Specification

4.100.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Configure representative access controls in PDAC, observe proper restrictions
	Test Data	No data.
	Expected Result	

4.101 LVV-T124 - Verify implementation of Software Architecture to Enable Community Re-Use

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Simon Krughoff

4.101.1 Verification Elements

- LVV-139 - DMS-REQ-0308-V-01: Software Architecture to Enable Community Re-Use

4.101.2 Test Items

Show that the LSST software is capable of being executed in multiple contexts: single user instance, batch processing, continuous integration.

Also show that the algorithms are can be reconfigured and, if desired, completely replaced at run time.

4.101.3 Predecessors

4.101.4 Environment Needs

4.101.4.1 Software

4.101.4.2 Hardware

4.101.5 Input Specification

4.101.6 Output Specification

4.101.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Using curated test datasets for multiple precursor instruments, verify and log that the prototype DRP pipelines execute successfully in three contexts: 1. The CI system 2. On a single user system: laptop, desktop, or notebook running in the Notebook aspect of the LSP. 3. Project workflow system.
	Test Data	No data.
	Expected Result	
2	Description	Using a template testing notebook in the Notebook aspect of the LSP, verify and log the following: 1. Individual pipeline steps (tasks) are importable and executable on their own. this is not comprehensive, but demonstrative. 2. Individual pipeline steps may be overridden by configuration. 3. Users can implement a custom pipeline step and insert i into the processing flow via configuration.
	Test Data	No data.
	Expected Result	
3-1 from LVV-T12	Description	The DM Stack shall be initialized using the loadLSST script (as described in DRP-00-00).
	Test Data	
	Expected Result	
3-2 from LVV-T12	Description	A "Data Butler" will be initialized to access the repository.
	Test Data	
	Expected Result	
3-3 from LVV-T12	Description	For each of the expected data products types (listed in Test Items section §4.3.2) and each of the expected units (PVIs, coadds, etc), the data product will be retrieved from the Butler and verified to be non-empty.
	Test Data	
	Expected Result	
4	Description	Run subset of full DRP from previous step on an individual node. Was this organizationally easy? Did the performance scale appropriately?

Step	Description, Input Data and Expected Result	
	Test Data	No data.
	Expected Result	
	Description	Re-run aperture correction on subset. Verify that same results as DRP run are achieved.
5	Test Data	No data.
	Expected Result	
	Description	Re-run photometric redshift estimation algorithm on subset coadd catalogs. Verify that same results are achieved as from full DRP.
6	Test Data	No data.
	Expected Result	
	Description	Re-run photometric redshift estimation algorithm on subset coadd catalogs. Verify that same results are achieved as from full DRP.

4.102 LVV-T125 - Verify implementation of Simulated Data

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Lupton

4.102.1 Verification Elements

- LVV-6 - DMS-REQ-0009-V-01: Simulated Data

4.102.2 Test Items

Verify that the DMS can inject simulated data into data products for testing.

4.102.3 Predecessors

4.102.4 Environment Needs

4.102.4.1 Software

4.102.4.2 Hardware

4.102.5 Input Specification

4.102.6 Output Specification

4.102.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to AP and DRP
	Test Data	No data.
	Expected Result	

4.103 LVV-T126 - Verify implementation Image Differencing

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.103.1 Verification Elements

- LVV-14 - DMS-REQ-0032-V-01: Image Differencing

4.103.2 Test Items

Verify that the DMS can performance image differencing from single exposures and coadds.

4.103.3 Predecessors

4.103.4 Environment Needs

4.103.4.1 Software

4.103.4.2 Hardware

4.103.5 Input Specification

4.103.6 Output Specification

4.103.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to AP and DRP
	Test Data	No data.
	Expected Result	

4.104 LVV-T127 - Verify implementation of Provide Source Detection Software

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton

4.104.1 Verification Elements

- LVV-15 - DMS-REQ-0033-V-01: Provide Source Detection Software

4.104.2 Test Items

Verify that the DMS provides source detection software that can be applied to calibrated images, including both difference images and coadds. This will be verified using simulated data, but could also be done by inserting artificial sources into existing datasets.

4.104.3 Predecessors

4.104.4 Environment Needs

4.104.4.1 Software

4.104.4.2 Hardware

4.104.5 Input Specification

4.104.6 Output Specification

4.104.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Run DRP and AP processing, including source detection and measurement algorithms, on a small portion of the data from a simulated dataset.
	Test Data	No data.
	Expected Result	Source catalogs containing measurements of all sources detected in the input images.
2	Description	Confirm that the output repos contain catalogs of source detections. Compare these output catalogs to the original simulated source catalogs, and confirm that a large fraction of the sources within a reasonable signal-to-noise range were recovered.
	Test Data	No data.
	Expected Result	Most sources above a reasonable S/N threshold were detected, and their measured fluxes are reasonably close to the simulated inputs.

4.105 LVV-T128 - Verify implementation Provide Astrometric Model

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.105.1 Verification Elements

- LVV-17 - DMS-REQ-0042-V-01: Provide Astrometric Model

4.105.2 Test Items

Verify that an astrometric model is available for Objects and DIAObjects.

4.105.3 Predecessors

4.105.4 Environment Needs

4.105.4.1 Software

4.105.4.2 Hardware

4.105.5 Input Specification

4.105.6 Output Specification

4.105.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to AP and DRP
	Test Data	No data.
	Expected Result	

4.106 LVV-T129 - Verify implementation of Provide Calibrated Photometry

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton

4.106.1 Verification Elements

- LVV-18 - DMS-REQ-0043-V-01: Provide Calibrated Photometry

4.106.2 Test Items

Verify that the DMS provides photometry calibrated in AB mags and fluxes (in nJy) for all measured objects and sources. Must be tested for both DRP and AP products.

4.106.3 Predecessors

4.106.4 Environment Needs

4.106.4.1 Software

4.106.4.2 Hardware

4.106.5 Input Specification

4.106.6 Output Specification

4.106.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T987	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the following:
	Test Data	
	Expected Result	Butler repo available for reading.
2	Description	Ingest the data products from an appropriate DRP-processed dataset.
	Test Data	No data.
	Expected Result	
3	Description	Confirm that AB-calibrated magnitudes and fluxes are available for all measured Sources and Objects. [An enhanced verification could include matching the sources to an external source catalog and comparing the magnitudes to show that they are well-calibrated.]
	Test Data	No data.
	Expected Result	Calibrated fluxes and magnitudes are available for all sources, as well as tools to convert measured fluxes to magnitudes (and vice-versa).
4	Description	Ingest the data products from an appropriate AP processing dataset.
	Test Data	No data.
	Expected Result	
5	Description	Confirm that AB-calibrated magnitudes and fluxes are available for all measured Sources, DIASources, and Objects. [An enhanced verification could include matching the sources to an external source catalog and comparing the magnitudes to show that they are well-calibrated.]

Step	Description, Input Data and Expected Result	
	Test Data	No data.
	Expected Result	Calibrated fluxes and magnitudes are available for all Sources, DIASources, and Objects, as well as tools to convert measured fluxes to magnitudes (and vice-versa).

4.107 LVV-T130 - Verify implementation of Enable a Range of Shape Measurement Approaches

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.107.1 Verification Elements

- LVV-21 - DMS-REQ-0052-V-01: Enable a Range of Shape Measurement Approaches

4.107.2 Test Items

Verify that multiple shape measurement algorithms can be used.

4.107.3 Predecessors

4.107.4 Environment Needs

4.107.4.1 Software

4.107.4.2 Hardware

4.107.5 Input Specification

4.107.6 Output Specification

4.107.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to AP and DRP
	Test Data	No data.
	Expected Result	

4.108 LVV-T131 - Verify implementation of Provide User Interface Services

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Gregory Dubois-Felsmann

4.108.1 Verification Elements

- LVV-63 - DMS-REQ-0160-V-01: Provide User Interface Services

4.108.2 Test Items

Verify the availability and functionality of the broad range of user interface services called for in the requirement, as applied to both Nightly and DRP data. This will primarily be done by verifications performed at the LSST Science Platform level, based on the requirements in LDM-554; however, a high-level set of tests corresponding to the DMS-REQ-0160 requirement are defined below.

4.108.3 Predecessors

4.108.4 Environment Needs

4.108.4.1 Software

4.108.4.2 Hardware As noted in Verification Configuration, the systems required to carry out the tests include both an “inside” test execution platform - the ability to execute test notebooks within the Science Platform Notebook Aspect - and an “outside” test execution platform with connectivity to the Science Platform instance under test that is comparable to that available to offsite science users.

4.108.5 Input Specification

1. Testing this requirement relies on a set of data products meeting the data model implied by the DPDD existing in a deployment of the Science Platform and its underlying database and file services.
 - (a) In particular, both image and catalog data products are required.
 - (b) From the specific language of the underlying requirement, it appears clear that coadded data products are required, but in practice single-epoch data products should be included in the test as well.
2. Depending on when this requirement is tested, the tests may involve either or both of precursor data and LSST commissioning data. The use of the latter is ultimately essential to ensure that the tests are performed with as LSST-like a dataset as possible.

4.108.6 Output Specification

4.108.7 Test Procedure

Step	Description, Input Data and Expected Result
1	Description Establishment of test coordinates:
	Establish sky positions and surrounding regions (e.g., cones or polygons), field sizes, filter bands, and temporal epochs for the tests that are consistent with the known content of the test dataset, whether precursor or LSST commissioning data.
	Establishing sky positions should include pre-determining the corresponding LSST “tract and patch” identifiers.
	If the plan to not keep all calibrated single-epoch images on disk is still in place at the time of the test, identify for use in the test both images that are, and are not, on disk.
	Establish target image boundaries, projections, and pixel scales to be used for resampling tests. Ensure that at least some of these test conditions include coadded image boundaries that cross tract and patch boundaries, and single-epoch image boundaries that cross focal plane raft boundaries.
	Test Data No data.
	Expected Result

Step	Description, Input Data and Expected Result	
2	Description	Butler image access: From within the Notebook Aspect, verify that coadded images for the identified regions of sky and filter bands are accessible via the Butler. Verify that the same images are available whether obtained by direct reference to the previous established tract/patch identifiers or by the use of LSST stack code for retrieving images based on sky coordinates. From within the Notebook Aspect, verify that single-epoch raw images for the selected locations and times are available. Verify that calibrated images (PVI) for the selected locations and times are available; depending on the details of the test dataset, verify that PVIs still on disk can be retrieved immediately. Verify that lists or tables of image metadata, not just individual images, can be retrieved. E.g., a list of all the single-epoch images covering a selected sky location.
	Test Data	No data.
	Expected Result	
3	Description	Programmatic PVI re-creation: From within the Notebook Aspect, verify that the recreation on demand of a PVI can be performed. Ideally, this should be done as follows: • Verify that recreation of a PVI that <i>is</i> still available works and that it reproduces the original PVI exactly (except for provenance metadata that must be different) or within the reasonable ability of processing systems to do so (e.g., taking into account that the original calibration and the recreation may have run on different CPU architectures). • The test conditions should ensure the verification that a recreation was actually performed, i.e., that the still-available PVI was not returned instead. • Note that it does not appear to be a requirement that <i>at Butler level</i> recreation on demand of PVIs is a completely transparent process. If this <i>is</i> decided to be a requirement, the test must also verify that it has been satisfied. If it is <i>not</i> a requirement, verify that adequate documentation on the PVI-recreation process (e.g., the SuperTasks and configuration to be used) is available.
	Test Data	No data.
	Expected Result	
4	Description	Butler catalog access: From within the Notebook Aspect, verify that all the catalog data products described in the DPDD can be retrieved for the coordinates selected above via the Butler. (This test should include access to SObject data, but the details of how such a test would depend on the coordinate selections require additional thought.)
	Test Data	No data.

Step	Description, Input Data and Expected Result	
	Expected Result	
5	Description LSST-stack-based resampling/reprojection: Verify the availability of software in the LSST stack, and associated documentation, that permits the resampling of LSST images to different pixel grids and projections. Exercise this capability for the test conditions selected in Step 1 above. Perform photometric and astrometric tests on the resulting resampled images to provide evidence that the transformations performed were correct to the accuracy supported by the data.	
	Test Data	No data.
	Expected Result	
6	Description Comment: The following API Aspect test steps should be carried out on the required “offsite-like” test platform, to ensure that their success does not reflect any privileged access given to processes inside the Data Access Center or other Science Platform instance. However, at least a small sampling of them should <i>also</i> be carried out <i>within</i> the Science Platform environment, i.e., in the Notebook Aspect, and the results compared.	
	Test Data	No data.
	Expected Result	
7	Description API Aspect image access: Using IVOA services such as the Registry and ObsTAP, from the “offsite-like” test platform, verify that the existence of the classes of image data products foreseen in the DPDD can be determined. Verify that ObsTAP and/or SIAv2 can be used to find the same images and lists of images for the established test coordinates that were retrieved via the Butler in Step 2 above. Verify that the selected images are retrievable from the Web services. Verify that the retrieved images are identical in their pixel content and metadata. The tests must include both coadded and single-epoch images.	
	Test Data	No data.
	Expected Result	
8	Description API Aspect image transformations: Verify that image cutouts and resamplings can be performed via the IVOA SODA service, and that the results are identical to those obtained for the same parameters from the LSST-stack-based tests in Step 5. (The requirements for supported reprojections, if any, in the SODA service have not been established at the time of writing.)	

Step	Description, Input Data and Expected Result	
	Test Data	No data.
	Expected Result	
9	Description API Aspect catalog data access: Verify that the IVOA Registry, RegTAP, TAP_SCHEMA, and other relevant mechanisms can be used to discover the existence of all the catalog data products foreseen in the DPDD. Using the IVOA TAP service, verify that all the catalog data products foreseen in the DPDD can be retrieved for the coordinates determined in Step 1. Verify that their scientific content is the same as when they are retrieved via the Butler.	
	Test Data	No data.
	Expected Result	
10	Description Comment: The Portal Aspect tests below should be carried out from a web browser on an “offsite-like” test platform, to ensure that no privileged access provided to intra-data-center clients is relied upon.	
	Test Data	No data.
	Expected Result	
11	Description Portal Aspect data browsing: Verify that the Portal Aspect can be used to discover the existence of all the data products foreseen in the DPDD. Verify that the UI permits locating the data for the coordinates selected in Step 1 by visual means, e.g., by zooming and panning in from an all-sky view. Verify that the UI permits locating the data by typing in coordinates as well.	
	Test Data	No data.
	Expected Result	
12	Description Portal Aspect image access: Verify that the Portal Aspect allows both the retrieval of “original” image data, i.e., in its native LSST pixel projection and with full metadata, as well as retrieval of on-demand UI cutouts of coadded image data for selected locations.	
	Test Data	No data.
	Expected Result	

Step	Description, Input Data and Expected Result	
13	Description	Portal Aspect catalog query and visualization: Verify that the Portal Aspect allows graphical querying of DPDD catalog data, both coadded and single-epoch, for selected regions of sky and/or with selected properties, and supports the visualization of the results (including histogramming, scatterplots, time series, table manipulations, and overplotting on image data). (Note that the Science Platform requirements, LDM-554, lay out a detailed set of requirements on the selection and visualization of catalog data.)
	Test Data	No data.
	Expected Result	
14	Description	Portal Aspect data download: Verify that data identified and/or visualized in the Portal Aspect can be downloaded to the remote system running the web browser in which the Portal is displayed, as well as to the User Workspace.
	Test Data	No data.
	Expected Result	

4.109 LVV-T132 - Verify implementation of Pre-cursor and Real Data

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Gruendl

4.109.1 Verification Elements

- LVV-127 - DMS-REQ-0296-V-01: Pre-cursor, and Real Data

4.109.2 Test Items

Demonstrate that pixel-oriented data from astronomical imaging cameras (precursor or otherwise) can be processed using LSST Science Algorithms and organized for access through the Data Butler Access Client.

4.109.3 Predecessors

4.109.4 Environment Needs

4.109.4.1 Software

4.109.4.2 Hardware

4.109.5 Input Specification

4.109.6 Output Specification

4.109.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Confirm that the CI jobs used to test DRP and AP processing successfully run. These jobs use precursor datasets from cameras other than LSST.
	Test Data	No data.
	Expected Result	
2	Description	For each of these two datasets, instantiate the Butler, ingest the data products, and confirm that they exist as expected.
	Test Data	No data.
	Expected Result	Processed images, catalogs, calibration information, and other related data products are present and accessible via the Butler.

4.110 LVV-T133 - Verify implementation of Provide Beam Projector Coordinate Calculation Software

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton

4.110.1 Verification Elements

- LVV-182 - DMS-REQ-0351-V-01: Provide Beam Projector Coordinate Calculation Software

4.110.2 Test Items

Verify that the DMS provides software to calculate coordinates relating the collimated beam projector position and telescope pupil position to the illumination position on the telescope optical elements and focal plane.

4.110.3 Predecessors

4.110.4 Environment Needs

4.110.4.1 Software

4.110.4.2 Hardware

4.110.5 Input Specification

4.110.6 Output Specification

4.110.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	On the LSST development cluster or notebook aspect, git clone the repo containing the CBP package: https://github.com/lsst/cbp
	Test Data	No data.
	Expected Result	
2	Description	Follow the steps in the package README to install the package.
	Test Data	No data.
	Expected Result	
3	Description	Confirm that the package can be loaded in python, and that some of the tests in the 'tests/' folder will execute.
	Test Data	No data.
	Expected Result	Successful execution of test scripts, which demonstrate the calculation of beam projector coordinates.

4.111 LVV-T134 - Verify implementation of Provide Image Access Services

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Inspection	Gregory Dubois-Felsmann

4.111.1 Verification Elements

- LVV-27 - DMS-REQ-0065-V-01: Provide Image Access Services

4.111.2 Test Items

Verify that images can be identified and that images and image cut-outs can be retrieved using the network interfaces - primarily IVOA standards-based - and Python APIs provided for image access by science users.

4.111.3 Predecessors

4.111.4 Environment Needs

4.111.4.1 Software

4.111.4.2 Hardware

4.111.5 Input Specification

Testing requires the establishment of running services such as SIAv2 and SODA to which the tests can be applied.

4.111.6 Output Specification

4.111.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Inspect that the following test cases have been executed and passed: LVV-T803, LVV-T810, LVV-T811, LVV-T812.
		The requirement is fully satisfied by lower-level LSP test cases.
	Test Data	No data.
	Expected Result	Test cases LVV-T803, LVV-T810, LVV-T811, LVV-T812 passed without blocking issues.

4.112 LVV-T136 - Verify implementation of Data Product and Raw Data Access

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Colin Slater

4.112.1 Verification Elements

- LVV-129 - DMS-REQ-0298-V-01: Data Product and Raw Data Access

4.112.2 Test Items

Verify that available image, file, and catalog data products, and their metadata and provenance information, can be listed and retrieved.

4.112.3 Predecessors

4.112.4 Environment Needs

4.112.4.1 Software

4.112.4.2 Hardware

4.112.5 Input Specification

4.112.6 Output Specification

4.112.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Details of the Gen3 Butler and ObsTAP tables are still being worked out. The general overview of this test will be to use some combination of the Gen3 Butler and TAP access to the ObsTAP tables to test that the required access is provided.
	Test Data	No data.
	Expected Result	Verification that the relevant data products and their related tables, metadata, and provenance information are available and readily accessible.

4.113 LVV-T137 - Verify implementation of Data Product Ingest

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Colin Slater

4.113.1 Verification Elements

- LVV-130 - DMS-REQ-0299-V-01: Data Product Ingest

4.113.2 Test Items

Verify that data products can be ingested.

4.113.3 Predecessors

4.113.4 Environment Needs

4.113.4.1 Software

4.113.4.2 Hardware

4.113.5 Input Specification

4.113.6 Output Specification

4.113.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Identify a suitable set of raw data to be run through “mini-DRP” processing.
	Test Data	No data.
	Expected Result	
2-1 from LVV-T1064	Description	Process data with the Data Release Production payload, starting from raw science images and generating science data products, placing them in the Data Backbone.
	Test Data	
	Expected Result	
3-1 from LVV-T987	Description	Identify the path to the data repository, which we will refer to as ‘DATA/path’, then execute the following:
	Test Data	
	Expected Result	Butler repo available for reading.
4	Description	Confirm that the data products from the DRP processing have been ingested into the Data Backbone.
	Test Data	No data.
	Expected Result	Processed images, catalogs, calibration information, and other related data products are present and accessible via the Butler.

4.114 LVV-T138 - Verify implementation of Bulk Download Service

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.114.1 Verification Elements

- LVV-131 - DMS-REQ-0300-V-01: Bulk Download Service

4.114.2 Test Items

Bulk Download

4.114.3 Predecessors

4.114.4 Environment Needs

4.114.4.1 Software

4.114.4.2 Hardware

4.114.5 Input Specification

A large dataset (at least a few TB) must be available.

Requires identity management to confirm bulk download use.

While this can be tested and shown to work using LSST DAC, Chilean DAC, and IN2P3 endpoints, this should also be tested to demonstrate expected throughput for outside users (e.g. FNAL, NERSC sites could be tested).

4.114.6 Output Specification

4.114.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Setup large transfer request and examine the data transfer rates achieved.
	Test Data	No data.
	Expected Result	
2	Description	Test should be repeated while observing in firehose mode (with LSSTCam) during science verification to ensure that bulk transfer does not compromise normal nightly operations.
	Test Data	No data.
	Expected Result	

4.115 LVV-T140 - Verify implementation of Production Orchestration

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Gruendl

4.115.1 Verification Elements

- LVV-133 - DMS-REQ-0302-V-01: Production Orchestration

4.115.2 Test Items

Demonstrate use to orchestration software to perform real-time and batch production on LSST compute platform(s).

4.115.3 Predecessors

4.115.4 Environment Needs

4.115.4.1 Software

4.115.4.2 Hardware

4.115.5 Input Specification

4.115.6 Output Specification

4.115.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Identify an appropriate precursor dataset.
	Test Data	No data.
	Expected Result	
2	Description	Execute a batch processing job using the orchestration system, and confirm (manually and/or via QA tools typically used for HSC reprocessing) that the pipeline executed and produced all expected products (or error logs in cases of failure).

Step	Description, Input Data and Expected Result	
	Test Data	No data.
	Expected Result	Calexp single-visit and coadd images, and associated catalogs, are present in a Butler repository. Logs of the processing are available to be inspected for identification of problems in the processing.

4.116 LVV-T141 - Verify implementation of Production Monitoring

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Gruendl

4.116.1 Verification Elements

- LVV-134 - DMS-REQ-0303-V-01: Production Monitoring

4.116.2 Test Items

Demonstrate monitoring capabilities that give real-time view of pipeline execution and production systems usage/load.

4.116.3 Predecessors

4.116.4 Environment Needs

4.116.4.1 Software

4.116.4.2 Hardware

4.116.5 Input Specification

Data set and mechanism for Production Orchestration as outlined in LVV-T140.

4.116.6 Output Specification

4.116.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T140	Description	Identify an appropriate precursor dataset.
	Test Data	
	Expected	
	Result	
1-2 from LVV-T140	Description	Execute a batch processing job using the orchestration system, and confirm (manually and/or via QA tools typically used for HSC reprocessing) that the pipeline executed and produced all expected products (or error logs in cases of failure).
	Test Data	
	Expected	Calexp single-visit and coadd images, and associated catalogs, are present in a Butler repository.
	Result	Logs of the processing are available to be inspected for identification of problems in the processing.
2	Description	While DRP processing in step 1 is executing, monitor the progress and resource usage of processing.
	Test Data	No data.
	Expected	Ability to monitor in real-time the orchestrated production processing, including resource usage.
	Result	

4.117 LVV-T142 - Verify implementation of Production Fault Tolerance

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.117.1 Verification Elements

- LVV-135 - DMS-REQ-0304-V-01: Production Fault Tolerance

4.117.2 Test Items

Demonstrate production systems report faults in pipeline executions and that system is able to recover. Where recovery can mean the ability to provide production artifacts for examination, return production elements ready for subsequent use, and/or reset and repeat production attempts.

4.117.3 Predecessors

4.117.4 Environment Needs

4.117.4.1 Software

4.117.4.2 Hardware

4.117.5 Input Specification

4.117.6 Output Specification

4.117.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute AP and DRP, simulate failures, observe correct processing
	Test Data	No data.
	Expected Result	

4.118 LVV-T144 - Verify implementation of Task Specification

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Kian-Tat Lim

4.118.1 Verification Elements

- LVV-136 - DMS-REQ-0305-V-01: Task Specification

4.118.2 Test Items

Verify that the DMS provides the ability to define a new or modified pipeline task without recompilation.

4.118.3 Predecessors

4.118.4 Environment Needs

4.118.4.1 Software

4.118.4.2 Hardware

4.118.5 Input Specification

4.118.6 Output Specification

4.118.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Inspect software architecture. Verify that there exist Tasks that can be run and configured without re-compilation.
	Test Data	No data.
	Expected Result	Confirmation that the software architecture has allowed for reconfiguring and running Tasks without recompilation.
2	Description	Verify that an example science algorithm can be run through one of these Tasks. Three examples from different areas: source measurement, image subtraction, and photometric-redshift estimation.
	Test Data	No data.
	Expected Result	Successful Task execution with different configurations, including confirmation that the outputs are different from tasks with altered configurations.

4.119 LVV-T145 - Verify implementation of Task Configuration

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton

4.119.1 Verification Elements

- LVV-137 - DMS-REQ-0306-V-01: Task Configuration

4.119.2 Test Items

Verify that the DMS software provides configuration control to define, override, and verify the configuration for a DMS Task.

4.119.3 Predecessors

4.119.4 Environment Needs

4.119.4.1 Software

4.119.4.2 Hardware

4.119.5 Input Specification

4.119.6 Output Specification

4.119.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Inspect software design to verify that one can define the configuration for a Task.
	Test Data	No data.
	Expected Result	
2	Description	Run a Task with a known invalid configuration. Verify that the error is caught before the science algorithm executes.
	Test Data	No data.
	Expected Result	
3	Description	Run a simple task with two different configurations that make a material difference for a Task. E.g., specify a different source detection threshold. Verify that the configuration is different between the two runs through difference in recorded provenance and in results.
	Test Data	No data.
	Expected Result	

4.120 LVV-T146 - Verify implementation of DMS Initialization Component

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Gruendl

4.120.1 Verification Elements

- LVV-128 - DMS-REQ-0297-V-01: DMS Initialization Component

4.120.2 Test Items

Demonstrate that the DMS can be initialized in a safe state that will not allow data corruption/loss.

4.120.3 Predecessors

4.120.4 Environment Needs

4.120.4.1 Software

4.120.4.2 Hardware

4.120.5 Input Specification

4.120.6 Output Specification

4.120.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Power-cycle all of the DM systems at each Facility.
	Test Data	No data.
	Expected Result	Restart of all DM systems.
2	Description	Observe each system and ensure that it has recovered in a properly initialized state.
	Test Data	No data.

Step	Description, Input Data and Expected Result	
	Expected Result	Systems are all active and initialized for their designated purpose.

4.121 LVV-T147 - Verify implementation of Control of Level-1 Production

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.121.1 Verification Elements

- LVV-132 - DMS-REQ-0301-V-01: Control of Level-1 Production

4.121.2 Test Items

Demonstrate that the DMS can control all Prompt Processing across DMS facilities.

4.121.3 Predecessors

4.121.4 Environment Needs

4.121.4.1 Software

4.121.4.2 Hardware

4.121.5 Input Specification

4.121.6 Output Specification

4.121.7 Test Procedure

Step	Description, Input Data and Expected Result	
	Description	Observe existence and capability of Prompt DMCS
1	Test Data	No data.

Step	Description, Input Data and Expected Result
	Expected Result

4.122 LVV-T148 - Verify implementation of Unique Processing Coverage

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.122.1 Verification Elements

- LVV-138 - DMS-REQ-0307-V-01: Unique Processing Coverage

4.122.2 Test Items

Verify that a user-specified criterion can be used to process each record in a table exactly once.

4.122.3 Predecessors

4.122.4 Environment Needs

4.122.4.1 Software

4.122.4.2 Hardware

4.122.5 Input Specification

4.122.6 Output Specification

4.122.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute representative processing, observe lack of duplicates or missing rows even in the presence of failures
	Test Data	No data.
	Expected Result	

4.123 LVV-T149 - Verify implementation of Catalog Queries

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Colin Slater

4.123.1 Verification Elements

- LVV-33 - DMS-REQ-0075-V-01: Catalog Queries

4.123.2 Test Items

Verify that SQL, or a similar structured language, can be used to query catalogs.

4.123.3 Predecessors

4.123.4 Environment Needs

4.123.4.1 Software

4.123.4.2 Hardware

4.123.5 Input Specification

An operational QSERV database that has been verified via LVV-T1085 and LVV-T1086.

4.123.6 Output Specification

4.123.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute a simple query (for example, the one below) and confirm that it returns the expected result.
	Test Data	No data.
	Example Code	SELECT * FROM Object WHERE qserv_areaspec_box(316.582327, -6.839078, 316.653938, -6.781822)
	Expected Result	A catalog of objects satisfying the specified constraints.
2	Description	Repeat the query from all available access routes (e.g., an external VO client, internal DM tools on the development cluster, the Science Platform query tool, and from within the Notebook Aspect), confirming in each case that the results are as expected.
	Test Data	No data.
	Expected Result	

4.124 LVV-T150 - Verify implementation of Maintain Archive Publicly Accessible

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Colin Slater

4.124.1 Verification Elements

- LVV-34 - DMS-REQ-0077-V-01: Maintain Archive Publicly Accessible

4.124.2 Test Items

Verify that prior data releases remain accessible.

4.124.3 Predecessors

4.124.4 Environment Needs

4.124.4.1 Software

4.124.4.2 Hardware

4.124.5 Input Specification

Availability of at least three (3) data releases, of which at least one of them must be archived outside the QSERV database. These can be precursor datasets, if needed.

4.124.6 Output Specification

4.124.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Confirm that at least two data releases (the most recent, and one previous) are accessible to users (and can be queried) from the standard channels.
	Test Data	No data.
	Expected Result	Simple queries return catalog data from the data releases that are available in QSERV.
2	Description	Confirm that previous data releases are accessible for bulk download (perhaps with significant latency) from tape or other bulk store, and that the downloaded tables contain the expected data products.
	Test Data	No data.
	Expected Result	A download of an entire previous data release from its bulk store.

4.125 LVV-T151 - Verify Implementation of Catalog Export Formats From the Notebook Aspect

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Colin Slater

4.125.1 Verification Elements

- LVV-35 - DMS-REQ-0078-V-01: Catalog Export Formats

4.125.2 Test Items

Verify that catalog data is exportable from the notebook aspect in a variety of community-standard formats.

4.125.3 Predecessors

4.125.4 Environment Needs

4.125.4.1 Software

4.125.4.2 Hardware

4.125.5 Input Specification

4.125.6 Output Specification

4.125.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T837	Description	Authenticate to the notebook aspect of the LSST Science Platform (NB-LSP). This is currently at https://lsst-lsp-stable.ncsa.illinois.edu/nb .
	Test Data	
	Expected Result	Redirection to the spawner page of the NB-LSP allowing selection of the containerized stack version and machine flavor.
1-2 from LVV-T837	Description	Spawn a container by: 1) choosing an appropriate stack version: e.g. the latest weekly. 2) choosing an appropriate machine flavor: e.g. medium 3) click "Spawn"
	Test Data	
	Expected Result	Redirection to the JupyterLab environment served from the chosen container containing the correct stack version.

Step	Description, Input Data and Expected Result	
2-1 from LVV-T838	Description	Open a new launcher by navigating in the top menu bar "File" -> "New Launcher"
	Test Data	
	Expected Result	A launcher window with several sections, potentially with several kernel versions for each.
2-2 from LVV-T838	Description	Select the option under "Notebook" labeled "LSST" by clicking on the icon.
	Test Data	
	Expected Result	An empty notebook with a single empty cell. The kernel show up as "LSST" in the top right of the notebook.
3-1 from LVV- T1207	Description	Execute a query in a notebook to select a small number of stars. In the example code below, we query the WISE catalog, then extract the results to an Astropy table.
	Test Data	
	Expected Result	
4	Description	Using the example code below, save the files to your storage space on the LSP Notebook Aspect.
		Confirm that non-empty output files appear on disk.
	Test Data	No data.
	Example Code	<pre>tab.write('test.csv', format='ascii.csv') tab.write('test.vot', format='votable') tab.write('test.fits', format='fits')</pre>
	Expected Result	For the example given here, there should be the following files with the file size as listed: • test.csv 5.7M • test.vot 16M • test.fits 4.5M
5	Description	Check that these files contain the same number of rows:
	Test Data	No data.

Step	Description, Input Data and Expected Result	
Example Code	<pre>from astropy.table import Table dat_csv = Table.read('test.csv', format='ascii.csv') dat_vot = Table.read('test.vot', format='votable') dat_fits = Table.read('test.fits', format='fits') import numpy as np print(np.size(dat_csv), np.size(dat_vot), np.size(dat_fits))</pre>	
Expected Result	Print statement produces output "97058 97058 97058".	
6-1 from LVV-T1208	Description	Under the 'File' menu at the top of your Jupyter notebook session, select one of the following: • Save All, Exit, and Log Out • Exit and Log Out Without Saving
	Test Data	
	Expected Result	You will be returned to the LSP landing page: https://lsst-lsp-stable.ncsa.illinois.edu/ It is now safe to close the browser window.

4.126 LVV-T152 - Verify implementation of Keep Historical Alert Archive

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.126.1 Verification Elements

- LVV-37 - DMS-REQ-0094-V-01: Keep Historical Alert Archive

4.126.2 Test Items

Verify that the DMS preserves and makes accessible an Alert Archive for reference and for false alert analyses

4.126.3 Predecessors

4.126.4 Environment Needs

4.126.4.1 Software

4.126.4.2 Hardware

4.126.5 Input Specification

4.126.6 Output Specification

4.126.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Simulated alert stream, load Alert DB, observe access to Alert DB
	Test Data	No data.
	Expected Result	

4.127 LVV-T153 - Verify implementation of Provide Engineering and Facility Database Archive

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Gruendl

4.127.1 Verification Elements

- LVV-44 - DMS-REQ-0102-V-01: Provide Engineering & Facility Database Archive

4.127.2 Test Items

Demonstrate Engineering and Facilities Data (images, associated metadata, and observatory environment and control data) are archived and available for public access within **L1PublicT**

(24 hours).

4.127.3 Predecessors

4.127.4 Environment Needs

4.127.4.1 Software

4.127.4.2 Hardware

4.127.5 Input Specification

4.127.6 Output Specification

4.127.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute a single-day operations rehearsal, ingesting (simulated) OCS commands into the EFD.
	Test Data	No data.
	Expected Result	
2	Description	Wait at least L1PublicT=24 hours, then access the archived EFD. Confirm that the data products are present in the archived EFD after L1PublicT=24 hours have elapsed.
	Test Data	No data.
	Expected Result	The EFD contains the simulated OCS commands, and they were ingested within L1PublicT=24 hours of the operations rehearsal.
3	Description	From the public access portal to the EFD, execute a query and demonstrate that the data are publicly available.
	Test Data	No data.
	Expected Result	A query at the public interface to the EFD successfully executes and returns EFD data.

4.128 LVV-T154 - Verify implementation of Raw Data Archiving Reliability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.128.1 Verification Elements

- LVV-140 - DMS-REQ-0309-V-01: Raw Data Archiving Reliability

4.128.2 Test Items

Verify that raw images are reliably archived.

4.128.3 Predecessors

4.128.4 Environment Needs

4.128.4.1 Software

4.128.4.2 Hardware

4.128.5 Input Specification

4.128.6 Output Specification

4.128.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze sources of loss or corruption after mitigation to compute estimated reliability
	Test Data	No data.
	Expected Result	

4.129 LVV-T155 - Verify implementation of Un-Archived Data Product Cache

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.129.1 Verification Elements

- LVV-141 - DMS-REQ-0310-V-01: Un-Archived Data Product Cache

4.129.2 Test Items

Demonstrate that the DMS provides low-latency storage for at least 11 CacheLifetime (30 days) to keep prompt processing pre-covery images on hand.

4.129.3 Predecessors

4.129.4 Environment Needs

4.129.4.1 Software

4.129.4.2 Hardware

4.129.5 Input Specification

4.129.6 Output Specification

4.129.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to DBB
	Test Data	No data.
	Expected	
	Result	

4.130 LVV-T156 - Verify implementation of Regenerate Un-archived Data Products

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Simon Krughoff

4.130.1 Verification Elements

- LVV-142 - DMS-REQ-0311-V-01: Regenerate Un-archived Data Products

4.130.2 Test Items

Not all of the ancillary data products produced by a data release will be archived permanently. These ancillary products have been promised as accessible to the community. Show that these products can be produced from an archived data release after the fact.

4.130.3 Predecessors

4.130.4 Environment Needs

4.130.4.1 Software

4.130.4.2 Hardware

4.130.5 Input Specification

4.130.6 Output Specification

4.130.7 Test Procedure

Step	Description, Input Data and Expected Result
1	Description Run a small DRP processing job and download unarchived data products.
	Test Data No data.
	Expected
	Result

Step	Description, Input Data and Expected Result	
2	Description	Wait for (or force) a processing stack change so that the subsequent re-processing will be forced to use an older software build.
	Test Data	No data.
	Expected Result	
3	Description	Using provenance information from the products in Step 1, request a re-processing and compare results with previously unarchived products.
	Test Data	No data.
	Expected Result	

4.131 LVV-T157 - Verify implementation Level 1 Data Product Access

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.131.1 Verification Elements

- LVV-143 - DMS-REQ-0312-V-01: Level 1 Data Product Access

4.131.2 Test Items

Verify that Level 1 Data Products are accessible by science users.

4.131.3 Predecessors

4.131.4 Environment Needs

4.131.4.1 Software

4.131.4.2 Hardware

4.131.5 Input Specification

4.131.6 Output Specification

4.131.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to LSP
	Test Data	No data.
	Expected Result	

4.132 LVV-T158 - Verify implementation Level 1 and 2 Catalog Access

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.132.1 Verification Elements

- LVV-144 - DMS-REQ-0313-V-01: Level 1 & 2 Catalog Access

4.132.2 Test Items

Verify that Data Release Products are accessible by science users.

4.132.3 Predecessors

4.132.4 Environment Needs

4.132.4.1 Software

4.132.4.2 Hardware

4.132.5 Input Specification

4.132.6 Output Specification

4.132.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to LSP
	Test Data	No data.
	Expected	
	Result	

4.133 LVV-T159 - Verify implementation of Regenerating Data Products from Previous Data Releases

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Simon Krughoff

4.133.1 Verification Elements

- LVV-167 - DMS-REQ-0336-V-01: Regenerating Data Products from Previous Data Releases

4.133.2 Test Items

Show that un-archived data products from previous data releases can be generated using through the LSST Science Platform.

4.133.3 Predecessors

4.133.4 Environment Needs

4.133.4.1 Software

4.133.4.2 Hardware

4.133.5 Input Specification

4.133.6 Output Specification

4.133.7 Test Procedure

Step	Description, Input Data and Expected Result
1	Description Delegate to LSP
	Test Data No data.
	Expected
	Result

4.134 LVV-T160 - Verify implementation of Providing a Preccovery Service

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Gregory Dubois-Felsmann

4.134.1 Verification Elements

- LVV-172 - DMS-REQ-0341-V-01: Max elapsed time for preccovery results

4.134.2 Test Items

Verify that a technical capability to perform user-directed preccovery analyses on difference images exists and that it is exposed through the LSST Science Platform. Verified by testing against precursor datasets.

(Involves: LSP Portal, MOPS and Forced Photometry)

4.134.3 Predecessors

4.134.4 Environment Needs

4.134.4.1 Software

4.134.4.2 Hardware

4.134.5 Input Specification

1. DECam HiTS data could be an appropriate set for this activity.

2. Precover pipelines for follow-on to alert processing must exist and be made available as a containerized version within the Science Platform.
3. Determine limitations over which general precovery is supported. I would suggest that precovery services be limited to current (or last two) DRP campaigns with the possible addition of including non-DRP products to encompass observations over the preceding year (does this then require means to re-generate PVLs from Alert Production in addition to DRP?)
4. Could re-use elements of LVV-T80 where quasars are used to test faint object detection.

4.134.6 Output Specification

4.134.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Run Precover within follow-on Alert Production (i.e. daily post-processing on 30 day store).
	Test Data	No data.
	Expected Result	
2	Description	Within Science Platform, initiate request to perform precovery for a list of sources over same period (and longer). Include among the sources for precovery quasars from LVV-T80.
	Test Data	No data.
	Expected Result	
3	Description	Examine the results. Compare the results for the period where there is overlap with precovery run... and quasar photometry with those from LVV-T80 to verify user service performs as production services.
	Test Data	No data.
	Expected Result	

4.135 LVV-T161 - Verify implementation of Logging of catalog queries

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.135.1 Verification Elements

- LVV-176 - DMS-REQ-0345-V-01: Logging of catalog queries

4.135.2 Test Items

Demonstrate logging of queries of LSST databases. Logged queries are globally available to DB administrators but otherwise private excepting the user that made the query.

4.135.3 Predecessors

4.135.4 Environment Needs

4.135.4.1 Software

4.135.4.2 Hardware

4.135.5 Input Specification

4.135.6 Output Specification

4.135.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to LSP
	Test Data	No data.
	Expected	
	Result	

4.136 LVV-T162 - Verify implementation of Access to Previous Data Releases

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Gregory Dubois-Felsmann

4.136.1 Verification Elements

- LVV-189 - DMS-REQ-0363-V-01: Access to Previous Data Releases

4.136.2 Test Items

Verify this high-level requirement, which states that the other data access requirements, for images and catalogs, all must be satisfied for multiple data releases. Verified by inspection, i.e., by determining that the data access system components, from middleware through APIs to user interfaces, are designed to support data from multiple releases, as well as by direct testing using a synthetic test environment containing multiple releases.

(Involves: Data Backbone, Managed Database, LSP Portal, LSP JupyterLab, LSP Web APIs, Parallel Distributed Database)

4.136.3 Predecessors

4.136.4 Environment Needs

4.136.4.1 Software

4.136.4.2 Hardware

4.136.5 Input Specification

Requires two or more (fake) releases within DAC (or PDAC) with common area/observations (preferably with some differing results but could use metadata identifying provenance).

4.136.6 Output Specification

4.136.7 Test Procedure

Step	Description, Input Data and Expected Result
1	Description From Science Platform initiate request for image and catalog products from one of the two release sets.

Step	Description, Input Data and Expected Result	
	Test Data	No data.
	Expected	
	Result	
2	Description	From Science Platform re-issue the same request but specifying the alternate/earlier release set.
	Test Data	No data.
	Expected	
3	Description	Compare results and identify differences that are germane to the relevant Data Release Sets are found.
	Test Data	No data.
	Expected	
	Result	

4.137 LVV-T163 - Verify implementation of Data Access Services

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.137.1 Verification Elements

- LVV-190 - DMS-REQ-0364-V-01: Total number of data releases

4.137.2 Test Items

Demonstrate that Data Access Services are capable of scaling to serve data from nDRTot (11) data releases over a surveyYears (10) year survey.

4.137.3 Predecessors

4.137.4 Environment Needs

4.137.4.1 Software

4.137.4.2 Hardware

4.137.5 Input Specification

4.137.6 Output Specification

4.137.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to LSP
	Test Data	No data.
	Expected	
	Result	

4.138 LVV-T164 - Verify implementation of Operations Subsets

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.138.1 Verification Elements

- LVV-191 - DMS-REQ-0365-V-01: Operations Subsets

4.138.2 Test Items

Demonstrate that Data Access Services are designed such that subsets of a Data Release may be retained and served (made available) after a Data Release has been superseded. (Data Backbone, Managed Database, LSP Portal, LSP JupyterLab, LSP Web APIs, Parallel Distributed Database)

4.138.3 Predecessors

4.138.4 Environment Needs

4.138.4.1 Software

4.138.4.2 Hardware

4.138.5 Input Specification

4.138.6 Output Specification

4.138.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to LSP
	Test Data	No data.
	Expected Result	

4.139 LVV-T165 - Verify implementation of Subsets Support

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Lupton

4.139.1 Verification Elements

- LVV-192 - DMS-REQ-0366-V-01: Subsets Support

4.139.2 Test Items

Verify that the DMS can provide designated subsets of previous Data Releases.

4.139.3 Predecessors

4.139.4 Environment Needs

4.139.4.1 Software

4.139.4.2 Hardware

4.139.5 Input Specification

4.139.6 Output Specification

4.139.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to LSP
	Test Data	No data.
	Expected Result	

4.140 LVV-T166 - Verify implementation of Access Services Performance

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.140.1 Verification Elements

- LVV-193 - DMS-REQ-0367-V-01: Access Services Performance

4.140.2 Test Items

Demonstrate monitoring of Data Access Services that give real and long-time views of system performance and usage.

4.140.3 Predecessors

4.140.4 Environment Needs

4.140.4.1 Software

4.140.4.2 Hardware

4.140.5 Input Specification

4.140.6 Output Specification

4.140.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to LSP
	Test Data	No data.
	Expected	
	Result	

4.141 LVV-T167 - Verify Capability to serve older Data Releases at Full Performance

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.141.1 Verification Elements

- LVV-194 - DMS-REQ-0368-V-01: Implementation Provisions

4.141.2 Test Items

Verify that implementation of the data access services do not preclude serving all older Data Releases with the same performance requirements as current Data Releases. Note that it is an operational consideration whether sufficient compute and storage resources would actually be provisioned to meet those requirements.

4.141.3 Predecessors

4.141.4 Environment Needs

4.141.4.1 Software

4.141.4.2 Hardware

4.141.5 Input Specification

4.141.6 Output Specification

4.141.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to LSP
	Test Data	No data.
	Expected Result	

4.142 LVV-T168 - Verify design of Data Access Services allows Evolution of the LSST Data Model

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.142.1 Verification Elements

- LVV-195 - DMS-REQ-0369-V-01: Evolution

4.142.2 Test Items

Verify that the design of the Data Access Services are able to accommodate changes/evolution of the LSST data model from one release to another.

4.142.3 Predecessors

4.142.4 Environment Needs

4.142.4.1 Software

4.142.4.2 Hardware

4.142.5 Input Specification

4.142.6 Output Specification

4.142.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to LSP
	Test Data	No data.
	Expected Result	

4.143 LVV-T169 - Verify implementation of Older Release Behavior

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Gregory Dubois-Felsmann

4.143.1 Verification Elements

- LVV-196 - DMS-REQ-0370-V-01: Older Release Behavior

4.143.2 Test Items

Verify that the components of the data access system are technically capable of handling data releases beyond the two for which full services are required. DMS-REQ-0364 requires that up to 11 be supported. Verified by inspection, i.e., by determination that the system design and implementation contain the necessary features to support this number of releases, and by direct test in a synthetic test environment with multiple releases.

(Involves: Data Backbone, Managed Database, LSP Portal, LSP JupyterLab, LSP Web APIs, Parallel Distributed Database)

4.143.3 Predecessors

4.143.4 Environment Needs

4.143.4.1 Software

4.143.4.2 Hardware

4.143.5 Input Specification

4.143.6 Output Specification

4.143.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to LSP
	Test Data	No data.
	Expected Result	

4.144 LVV-T170 - Verify implementation of Query Availability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.144.1 Verification Elements

- LVV-197 - DMS-REQ-0371-V-01: Query Availability

4.144.2 Test Items

Verify that queries continue to be successfully executable over time.

4.144.3 Predecessors

4.144.4 Environment Needs

4.144.4.1 Software

4.144.4.2 Hardware

4.144.5 Input Specification

4.144.6 Output Specification

4.144.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to LSP
	Test Data	No data.
	Expected Result	

4.145 LVV-T171 - Verify implementation of Pipeline Availability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.145.1 Verification Elements

- LVV-5 - DMS-REQ-0008-V-01: Pipeline Availability

4.145.2 Test Items

Demonstrate that Data Management System pipelines are available for use without disruptions of greater than productionMaxDowntime (24 hours). This requires a regimented change control process and testing infrastructure for all pipelines and their underlying software services, and regimented management and monitoring of compute and networking resources. The list of services covered by this test include: Image and EFD Archiving, Prompt

Processing, OCS Driven Batch, Telemetry Gateway, Alert Distribution, Alert Filtering, Batch Production, Data Backbone, Compute/Storage/LAN, Inter-Site Networks, and Service Management and Monitoring.

4.145.3 Predecessors

4.145.4 Environment Needs

4.145.4.1 Software

4.145.4.2 Hardware

4.145.5 Input Specification

4.145.6 Output Specification

4.145.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze sources of downtime after mitigation to compute estimated reliability; observe unscheduled downtime of developer, integration, and pre-production systems
	Test Data	No data.
	Expected Result	

4.146 LVV-T172 - Verify implementation of Optimization of Cost, Reliability and Availability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.146.1 Verification Elements

- LVV-64 - DMS-REQ-0161-V-01: Optimization of Cost, Reliability and Availability in Order

4.146.2 Test Items

In matters of cost, system reliability (functioning properly at a given time) has precedence over system availability (ability to use the system at a given time). The optimization may be outside the realm of direct testing as it is more of a system provisioning guideline but on its face it demands that the Data Management System include failure reporting, regimented change control, acceptance testing, maintenance and monitoring.

4.146.3 Predecessors

4.146.4 Environment Needs

4.146.4.1 Software

4.146.4.2 Hardware

4.146.5 Input Specification

4.146.6 Output Specification

4.146.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze resource management policy
	Test Data	No data.
	Expected	
	Result	

4.147 LVV-T173 - Verify implementation of Pipeline Throughput

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.147.1 Verification Elements

- LVV-65 - DMS-REQ-0162-V-01: Pipeline Throughput

4.147.2 Test Items

Demonstrate that the Alert Production Pipeline is capable of processing nRawExpNightMax (2800) science exposures within a (24-nightDurationMax) 12 hour period and issue alerts in offline batch mode.

4.147.3 Predecessors

4.147.4 Environment Needs

4.147.4.1 Software

4.147.4.2 Hardware

4.147.5 Input Specification

4.147.6 Output Specification

4.147.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute single-day operations rehearsal, observe data products generated in time
	Test Data	No data.
	Expected	
	Result	

4.148 LVV-T174 - Verify implementation of Re-processing Capacity

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.148.1 Verification Elements

- LVV-66 - DMS-REQ-0163-V-01: Re-processing Capacity

4.148.2 Test Items

Verify that the DMS has sufficient processing, storage, and network to reprocess all data within “drProcessingPeriod” (1 year) while maintaining full Prompt Processing capability.

4.148.3 Predecessors

4.148.4 Environment Needs

4.148.4.1 Software

4.148.4.2 Hardware

4.148.5 Input Specification

4.148.6 Output Specification

4.148.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze sizing model; execute DRP, observe scaling
	Test Data	No data.
	Expected	
	Result	

4.149 LVV-T175 - Verify implementation of Temporary Storage for Communications Links

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.149.1 Verification Elements

- LVV-67 - DMS-REQ-0164-V-01: Temporary Storage for Communications Links

4.149.2 Test Items

Demonstrate that storage capacity is present and usable to prevent data loss if networking is interrupted between summit and base, base and archive, or archive and DAC. The requirement is to have storage necessary to hold tempStorageReIMTTR (200%) of the expected raw data that would arrive during the Mean Time to Repair (summToBaseNetMTTR = 24 hours, baseToArchNetMTTR = 48 hours, archToDacNetMTTR = 48 hours). This scale is further set by $nCalibExpDay + nRawExpNightMax = 450 + 2800 = 3250$ exposures/day.

4.149.3 Predecessors

4.149.4 Environment Needs

4.149.4.1 Software

4.149.4.2 Hardware

4.149.5 Input Specification

4.149.6 Output Specification

4.149.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze sizing model and network/storage design
	Test Data	No data.
	Expected Result	

4.150 LVV-T176 - Verify implementation of Infrastructure Sizing for “catching up”

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.150.1 Verification Elements

- LVV-68 - DMS-REQ-0165-V-01: Infrastructure Sizing for “catching up”
- LVV-994 - OSS-REQ-0051-V-01: Summit-Base Connectivity Loss

4.150.2 Test Items

Demonstrate Data Management System has sufficient excess capacity (compute infrastructure) to process one night’s data (2800 exposures) within 24 hours while also maintaining nightly Alert Production (note this is very similar to LVV-T173).

4.150.3 Predecessors

4.150.4 Environment Needs

4.150.4.1 Software

4.150.4.2 Hardware

4.150.5 Input Specification

4.150.6 Output Specification

4.150.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute single-day operations rehearsal including catch-up after failure, observe data products generated in time
	Test Data	No data.
	Expected Result	

4.151 LVV-T177 - Verify implementation of Incorporate Fault-Tolerance

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.151.1 Verification Elements

- LVV-69 - DMS-REQ-0166-V-01: Incorporate Fault-Tolerance

4.151.2 Test Items

Demonstrate that Data Management Systems have features that prevent data loss. Includes: MD5SUM/checksum verification for data transfer; RAID to eliminate single-point disk failures; multi-site and tape for disaster recovery of raw data; multiple site (and tape?) for backup/recovery of Data Release products; DB transaction logging and backup to maintain DB integrity. (Note: storage to prevent loss in case of networking failures is covered in LVV-T175).

4.151.3 Predecessors

4.151.4 Environment Needs

4.151.4.1 Software

4.151.4.2 Hardware

4.151.5 Input Specification

4.151.6 Output Specification

4.151.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze design; execute single-day operations rehearsal including failures, observe recovery without loss of data
	Test Data	No data.

Step	Description, Input Data and Expected Result
------	---

Expected Result

4.152 LVV-T178 - Verify implementation of Incorporate Autonomics

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.152.1 Verification Elements

- LVV-70 - DMS-REQ-0167-V-01: Incorporate Autonomics

4.152.2 Test Items

Demonstrate that production systems monitor and report faults. Where possible fault mitigation can include re-start, re-submission, or return of partial products for triage.

4.152.3 Predecessors

4.152.4 Environment Needs

4.152.4.1 Software

4.152.4.2 Hardware

4.152.5 Input Specification

4.152.6 Output Specification

4.152.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze design; execute single-day operations rehearsal including failures, observe automated recovery and continuation of processing
	Test Data	No data.
	Expected Result	

4.153 LVV-T179 - Verify implementation of Compute Platform Heterogeneity

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.153.1 Verification Elements

- LVV-145 - DMS-REQ-0314-V-01: Compute Platform Heterogeneity

4.153.2 Test Items

Demonstrate that production results are the same (within machine accuracy) when production occurs on different platforms (OS, kernel, hardware provisioning).

4.153.3 Predecessors

4.153.4 Environment Needs

4.153.4.1 Software

4.153.4.2 Hardware

4.153.5 Input Specification

4.153.6 Output Specification

4.153.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Configure heterogeneous cluster, execute AP+DRP+LSP, observe correct functioning
	Test Data	No data.
	Expected Result	

4.154 LVV-T180 - Verify implementation of Data Management Unscheduled Downtime

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.154.1 Verification Elements

- LVV-149 - DMS-REQ-0318-V-01: Data Management Unscheduled Downtime

4.154.2 Test Items

This applies only to downtime that would prevent the collection of survey data. Verification means that analysis has occurred to identify likely hardware failures that would prevent survey operations and that mitigations that minimize the downtime to less than DM Downtime (1 day/year) are in place. Known systems that fall in this category include: Image and EFD Archiving, Observatory Operations Data, Telemetry Gateway, Data Backbone, Managed Database, Inter-Site Networks, and Service Management and Monitoring.

4.154.3 Predecessors

4.154.4 Environment Needs

4.154.4.1 Software

4.154.4.2 Hardware

4.154.5 Input Specification

4.154.6 Output Specification

4.154.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze likely hardware failures with mitigations to compute estimated unplanned down-time
	Test Data	No data.
	Expected Result	

4.155 LVV-T181 - Verify integration of Summit Facility Data Communications

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.155.1 Verification Elements

- LVV-71 - DMS-REQ-0168-V-01: Summit Facility Data Communications

4.155.2 Test Items

This verifies that the Summit Network is integrated properly with the Summit - Base Network. (The former is a TS deliverable, the latter a DM deliverable). Demonstrate data is transferred over the summit instrument data fibers, from the DAQ to the Summit - Base DWDM, along with monitoring network performance. This requirement does not include testing the DAQ buffering of the data, nor the transfer from summit to base which are covered elsewhere.

4.155.3 Predecessors

4.155.4 Environment Needs

4.155.4.1 Software

4.155.4.2 Hardware

4.155.5 Input Specification

4.155.6 Output Specification

4.155.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to Networks
	Test Data	No data.
	Expected Result	

4.156 LVV-T182 - Verify implementation of Prefer Computing and Storage Down

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.156.1 Verification Elements

- LVV-72 - DMS-REQ-0170-V-01: Prefer Computing and Storage Down

4.156.2 Test Items

Only build compute or storage facilities at the summit that are justified by operational need or to prevent loss of data during networking downtimes.

4.156.3 Predecessors

4.156.4 Environment Needs

4.156.4.1 Software

4.156.4.2 Hardware

4.156.5 Input Specification

4.156.6 Output Specification

4.156.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze design
	Test Data	No data.
	Expected	
	Result	

4.157 LVV-T183 - Verify implementation of DMS Communication with OCS

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Gregory Dubois-Felsmann

4.157.1 Verification Elements

- LVV-146 - DMS-REQ-0315-V-01: DMS Communication with OCS

4.157.2 Test Items

Verify that the DMS at the Base Facility can receive commands from the OCS and send command responses, events, and telemetry back. Verified by Early Integration activities and during AuxTel commissioning.

4.157.3 Predecessors

4.157.4 Environment Needs

4.157.4.1 Software

4.157.4.2 Hardware

4.157.5 Input Specification

4.157.6 Output Specification

4.157.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	From the Base Site, connect to the (simulated) OCS telemetry stream.
	Test Data	No data.
	Expected Result	
2	Description	Send a command to the OCS, and observe that the command has been executed.
	Test Data	No data.
	Expected Result	Confirmation that the OCS command successfully executed.
3	Description	Extract information from the telemetry being broadcast by the OCS, and ensure that these data are readable.
	Test Data	No data.
	Expected Result	A readable extract from the OCS telemetry stream.

4.158 LVV-T185 - Verify implementation of Summit to Base Network Availability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.158.1 Verification Elements

- LVV-74 - DMS-REQ-0172-V-01: Summit to Base Network Availability

4.158.2 Test Items

Monitor summit to base networking and verify that the mean time between failures is less than summToBaseNetMTBF (90 days) over 1 year.

4.158.3 Predecessors

4.158.4 Environment Needs

4.158.4.1 Software

4.158.4.2 Hardware

4.158.5 Input Specification

4.158.6 Output Specification

4.158.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to Networks
	Test Data	No data.
	Expected	
	Result	

4.159 LVV-T186 - Verify implementation of Summit to Base Network Reliability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.159.1 Verification Elements

- LVV-75 - DMS-REQ-0173-V-01: Summit to Base Network Reliability

4.159.2 Test Items

Monitor Summit to Base networking and verify that the mean time to repair is less than summ-ToBaseNetMTTR (24 hours) over a 1-year period.

4.159.3 Predecessors

4.159.4 Environment Needs

4.159.4.1 Software

4.159.4.2 Hardware

4.159.5 Input Specification

4.159.6 Output Specification

4.159.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to Networks
	Test Data	No data.
	Expected Result	

4.160 LVV-T187 - Verify implementation of Summit to Base Network Secondary Link

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.160.1 Verification Elements

- LVV-76 - DMS-REQ-0174-V-01: Summit to Base Network Secondary Link

4.160.2 Test Items

A secondary transfer method (redundant fiber network, microwave link, or transportable medium) between Summit and Base capable of transferring 1 night of raw data ($n\text{CalibExpDay} + n\text{RawExpNightMax} = 450 + 2800 = 3250$ exposures) within $\text{summToBaseNet2TransMax}$ (72 hours).

4.160.3 Predecessors

4.160.4 Environment Needs

4.160.4.1 Software

4.160.4.2 Hardware

4.160.5 Input Specification

4.160.6 Output Specification

4.160.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to Networks
	Test Data	No data.
	Expected	
	Result	

4.161 LVV-T188 - Verify implementation of Summit to Base Network Ownership and Operation

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.161.1 Verification Elements

- LVV-77 - DMS-REQ-0175-V-01: Summit to Base Network Ownership and Operation

4.161.2 Test Items

Verify that the Summit to Base communications link is owned and operated by LSST and/or the operations entity.

4.161.3 Predecessors

4.161.4 Environment Needs

4.161.4.1 Software

4.161.4.2 Hardware

4.161.5 Input Specification

4.161.6 Output Specification

4.161.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to Networks
	Test Data	No data.
	Expected	
	Result	

4.162 LVV-T189 - Verify implementation of Base Facility Infrastructure

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.162.1 Verification Elements

- LVV-78 - DMS-REQ-0176-V-01: Base Facility Infrastructure

4.162.2 Test Items

Verify that the (a) planned infrastructure and (b) as-built infrastructure for the Base Facility satisfies the needs for data transfer and buffering, a copy of the Archive Facility, and support for Commissioning.

4.162.3 Predecessors

4.162.4 Environment Needs

4.162.4.1 Software

4.162.4.2 Hardware

4.162.5 Input Specification

4.162.6 Output Specification

4.162.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze design and sizing model
	Test Data	No data.
	Expected	
	Result	

4.163 LVV-T190 - Verify implementation of Base Facility Co-Location with Existing Facility

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.163.1 Verification Elements

- LVV-80 - DMS-REQ-0178-V-01: Base Facility Co-Location with Existing Facility

4.163.2 Test Items

Verify that the Base Facility is located at an existing known supported facility.

4.163.3 Predecessors

4.163.4 Environment Needs

4.163.4.1 Software

4.163.4.2 Hardware

4.163.5 Input Specification

4.163.6 Output Specification

4.163.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze design
	Test Data	No data.
	Expected Result	

4.164 LVV-T191 - Verify implementation of Commissioning Cluster

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.164.1 Verification Elements

- LVV-147 - DMS-REQ-0316-V-01: Commissioning Cluster

4.164.2 Test Items

Verify that the Commissioning Cluster has sufficient Compute/Storage/LAN at the Base Facility to support Commissioning.

4.164.3 Predecessors

4.164.4 Environment Needs

4.164.4.1 Software

4.164.4.2 Hardware

4.164.5 Input Specification

4.164.6 Output Specification

4.164.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze design and budget
	Test Data	No data.
	Expected	
	Result	

4.165 LVV-T192 - Verify implementation of Base Wireless LAN (WiFi)

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.165.1 Verification Elements

- LVV-183 - DMS-REQ-0352-V-01: Base Wireless LAN (WiFi)

4.165.2 Test Items

Verify (a) planned and (b) as-built wireless network at the Base Facility supports minBaseWiFi bandwidth.

4.165.3 Predecessors

4.165.4 Environment Needs

4.165.4.1 Software

4.165.4.2 Hardware

4.165.5 Input Specification

4.165.6 Output Specification

4.165.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to Networks
	Test Data	No data.
	Expected	
	Result	

4.166 LVV-T193 - Verify implementation of Base to Archive Network

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.166.1 Verification Elements

- LVV-81 - DMS-REQ-0180-V-01: Base to Archive Network

4.166.2 Test Items

Verify that the Base Facility can transfer a full image+metadata to the Archive Center in base-ToArchiveMaxTransferTime.

4.166.3 Predecessors

4.166.4 Environment Needs

4.166.4.1 Software

4.166.4.2 Hardware

4.166.5 Input Specification

4.166.6 Output Specification

4.166.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to Networks
	Test Data	No data.
	Expected	
	Result	

4.167 LVV-T194 - Verify implementation of Base to Archive Network Availability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.167.1 Verification Elements

- LVV-82 - DMS-REQ-0181-V-01: Base to Archive Network Availability

4.167.2 Test Items

Verify Network uptime between Base Facility and Archive Facility.

4.167.3 Predecessors

4.167.4 Environment Needs

4.167.4.1 Software

4.167.4.2 Hardware

4.167.5 Input Specification

4.167.6 Output Specification

4.167.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to Networks
	Test Data	No data.
	Expected	
	Result	

4.168 LVV-T195 - Verify implementation of Base to Archive Network Reliability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.168.1 Verification Elements

- LVV-83 - DMS-REQ-0182-V-01: Base to Archive Network Reliability

4.168.2 Test Items

Verify uptime of the Base Facility to Archive Facility network.

4.168.3 Predecessors

4.168.4 Environment Needs

4.168.4.1 Software

4.168.4.2 Hardware

4.168.5 Input Specification

4.168.6 Output Specification

4.168.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to Networks
	Test Data	No data.
	Expected	
	Result	

4.169 LVV-T196 - Verify implementation of Base to Archive Network Secondary Link

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.169.1 Verification Elements

- LVV-84 - DMS-REQ-0183-V-01: Base to Archive Network Secondary Link

4.169.2 Test Items

Verify the performance of a secondary network link meets needs for operations support and catching up after outages.

4.169.3 Predecessors

4.169.4 Environment Needs

4.169.4.1 Software

4.169.4.2 Hardware

4.169.5 Input Specification

4.169.6 Output Specification

4.169.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to Networks
	Test Data	No data.
	Expected	
	Result	

4.170 LVV-T197 - Verify implementation of Archive Center

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.170.1 Verification Elements

- LVV-85 - DMS-REQ-0185-V-01: Archive Center

4.170.2 Test Items

Verify that the Archive Center is sufficiently provisioned to support prompt processing, DRP, and data access needs.

4.170.3 Predecessors

4.170.4 Environment Needs

4.170.4.1 Software

4.170.4.2 Hardware

4.170.5 Input Specification

4.170.6 Output Specification

4.170.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze design and sizing model
	Test Data	No data.
	Expected	
	Result	

4.171 LVV-T198 - Verify implementation of Archive Center Disaster Recovery

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.171.1 Verification Elements

- LVV-86 - DMS-REQ-0186-V-01: Archive Center Disaster Recovery

4.171.2 Test Items

Verify disaster recovery plan for Archive Center.

4.171.3 Predecessors

4.171.4 Environment Needs

4.171.4.1 Software

4.171.4.2 Hardware

4.171.5 Input Specification

4.171.6 Output Specification

4.171.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze design; simulate storage failure, observe restore from disaster recovery
	Test Data	No data.
	Expected	
	Result	

4.172 LVV-T199 - Verify implementation of Archive Center Co-Location with Existing Facility

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.172.1 Verification Elements

- LVV-87 - DMS-REQ-0187-V-01: Archive Center Co-Location with Existing Facility

4.172.2 Test Items

Verify the Archive Center is located at an existing supported facility.

4.172.3 Predecessors

4.172.4 Environment Needs

4.172.4.1 Software

4.172.4.2 Hardware

4.172.5 Input Specification

4.172.6 Output Specification

4.172.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze design
	Test Data	No data.
	Expected	
	Result	

4.173 LVV-T200 - Verify implementation of Archive to Data Access Center Network

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.173.1 Verification Elements

- LVV-88 - DMS-REQ-0188-V-01: Archive to Data Access Center Network

4.173.2 Test Items

Verify sufficient bandwidth between Archive Center and Data Access Centers of at least arch-ToDacBandwidth.

4.173.3 Predecessors

4.173.4 Environment Needs

4.173.4.1 Software

4.173.4.2 Hardware

4.173.5 Input Specification

4.173.6 Output Specification

4.173.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to Networks
	Test Data	No data.
	Expected	
	Result	

4.174 LVV-T201 - Verify implementation of Archive to Data Access Center Network Availability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.174.1 Verification Elements

- LVV-89 - DMS-REQ-0189-V-01: Archive to Data Access Center Network Availability

4.174.2 Test Items

4.174.3 Predecessors

4.174.4 Environment Needs

4.174.4.1 Software

4.174.4.2 Hardware

4.174.5 Input Specification

4.174.6 Output Specification

4.174.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to Networks
	Test Data	No data.
	Expected Result	

4.175 LVV-T202 - Verify implementation of Archive to Data Access Center Network Reliability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.175.1 Verification Elements

- LVV-90 - DMS-REQ-0190-V-01: Archive to Data Access Center Network Reliability

4.175.2 Test Items

Verify the reliability of the Archive to Data Access Center communications.

4.175.3 Predecessors

4.175.4 Environment Needs

4.175.4.1 Software

4.175.4.2 Hardware

4.175.5 Input Specification

4.175.6 Output Specification

4.175.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Delegate to Networks
	Test Data	No data.
	Expected	
	Result	

4.176 LVV-T203 - Verify implementation of Archive to Data Access Center Network Secondary Link

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.176.1 Verification Elements

- LVV-91 - DMS-REQ-0191-V-01: Archive to Data Access Center Network Secondary Link

4.176.2 Test Items

Inter-Site Networks

4.176.3 Predecessors

4.176.4 Environment Needs

4.176.4.1 Software

4.176.4.2 Hardware

4.176.5 Input Specification

4.176.6 Output Specification

4.176.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Take primary network link down
	Test Data	No data.
	Expected Result	
2	Description	Observe operations support over secondary link
	Test Data	No data.
	Expected Result	
3	Description	Bring primary network link back up
	Test Data	No data.
	Expected Result	

Step	Description, Input Data and Expected Result	
4	Description	Observe catch-up capability over secondary link
	Test Data	No data.
	Expected Result	

4.177 LVV-T204 - Verify implementation of Access to catalogs for external Level 3 processing

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.177.1 Verification Elements

- LVV-50 - DMS-REQ-0122-V-01: Access to catalogs for external Level 3 processing

4.177.2 Test Items

Verify that catalog export, and maintenance/validation tools for Level 3 products to outside of the Data Access Centers.

4.177.3 Predecessors

4.177.4 Environment Needs

4.177.4.1 Software

4.177.4.2 Hardware

4.177.5 Input Specification

4.177.6 Output Specification

4.177.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute bulk distribution of DRP catalogs
	Test Data	No data.
	Expected Result	
2	Description	Observe correct transfer and use of maintenance/validation tools
	Test Data	No data.
	Expected Result	

4.178 LVV-T205 - Verify implementation of Access to input catalogs for DAC-based Level 3 processing

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

4.178.1 Verification Elements

- LVV-51 - DMS-REQ-0123-V-01: Access to input catalogs for DAC-based Level 3 processing

4.178.2 Test Items

Verify that data products are available at the Data Access Centers for use in Level 3 processing.

4.178.3 Predecessors

4.178.4 Environment Needs

4.178.4.1 Software

4.178.4.2 Hardware

4.178.5 Input Specification

4.178.6 Output Specification

4.178.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Load Prompt and DR catalogs into PDAC, observe access via LSP
	Test Data	No data.
	Expected Result	

4.179 LVV-T206 - Verify implementation of Federation with external catalogs

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.179.1 Verification Elements

- LVV-52 - DMS-REQ-0124-V-01: Federation with external catalogs

4.179.2 Test Items

Verify that LSST-produced data can be combined with external datasets.

4.179.3 Predecessors

4.179.4 Environment Needs

4.179.4.1 Software

4.179.4.2 Hardware

4.179.5 Input Specification

4.179.6 Output Specification

4.179.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Load external catalog into PDAC (using VO if possible), observe federation with other catalogs via LSP
	Test Data	No data.
	Expected Result	

4.180 LVV-T207 - Verify implementation of Access to images for external Level 3 processing

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.180.1 Verification Elements

- LVV-54 - DMS-REQ-0126-V-01: Access to images for external Level 3 processing

4.180.2 Test Items

Verify that bulk distribution of images, and accompanying maintenance/validation tools for Level 3 image products to outside of the Data Access Centers.

4.180.3 Predecessors

4.180.4 Environment Needs

4.180.4.1 Software

4.180.4.2 Hardware

4.180.5 Input Specification

4.180.6 Output Specification

4.180.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Execute bulk distribution of DRP images
	Test Data	No data.
	Expected Result	
2	Description	Observe correct transfer and use of maintenance/validation tools
	Test Data	No data.
	Expected Result	

4.181 LVV-T208 - Verify implementation of Access to input images for DAC-based Level 3 processing

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.181.1 Verification Elements

- LVV-55 - DMS-REQ-0127-V-01: Access to input images for DAC-based Level 3 processing

4.181.2 Test Items

Verify that prompt processing and DRP products are available at the DACs for Level 3 processing at the DACs.

4.181.3 Predecessors

4.181.4 Environment Needs

4.181.4.1 Software

4.181.4.2 Hardware

4.181.5 Input Specification

4.181.6 Output Specification

4.181.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Load Prompt and DR images into PDAC
	Test Data	No data.
	Expected Result	
2	Description	Observe access via LSP
	Test Data	No data.
	Expected Result	

4.182 LVV-T209 - Verify implementation of Data Access Centers

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Analysis	Kian-Tat Lim

4.182.1 Verification Elements

- LVV-92 - DMS-REQ-0193-V-01: Data Access Centers

4.182.2 Test Items

Verify that the Data Access Centers are provisioned with computing resources necessary to support end-user access to LSST Data Products.

4.182.3 Predecessors

4.182.4 Environment Needs

4.182.4.1 Software

4.182.4.2 Hardware

4.182.5 Input Specification

4.182.6 Output Specification

4.182.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze design
	Test Data	No data.
	Expected Result	

4.183 LVV-T210 - Verify implementation of Data Access Center Simultaneous Connections

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.183.1 Verification Elements

- LVV-93 - DMS-REQ-0194-V-01: Data Access Center Simultaneous Connections

4.183.2 Test Items

Verify that the each DAC can support at least dacMinConnections simultaneously

4.183.3 Predecessors

4.183.4 Environment Needs

4.183.4.1 Software

4.183.4.2 Hardware

4.183.5 Input Specification

4.183.6 Output Specification

4.183.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Simulate data access to PDAC
	Test Data	No data.
	Expected Result	
2	Description	Observe scaling
	Test Data	No data.
	Expected Result	

4.184 LVV-T211 - Verify implementation of Data Access Center Geographical Distribution

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Analysis	Kian-Tat Lim

4.184.1 Verification Elements

- LVV-94 - DMS-REQ-0196-V-01: Data Access Center Geographical Distribution

4.184.2 Test Items

Verify that the DACs are geographically distributed to provide low-latency access to data-rights community.

4.184.3 Predecessors

4.184.4 Environment Needs

4.184.4.1 Software

4.184.4.2 Hardware

4.184.5 Input Specification

4.184.6 Output Specification

4.184.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze design
	Test Data	No data.
	Expected Result	

4.185 LVV-T212 - Verify implementation of No Limit on Data Access Centers

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

4.185.1 Verification Elements

- LVV-95 - DMS-REQ-0197-V-01: No Limit on Data Access Centers

4.185.2 Test Items

Verify that additional Data Access Centers can be set up.

4.185.3 Predecessors

4.185.4 Environment Needs

4.185.4.1 Software

4.185.4.2 Hardware

4.185.5 Input Specification

4.185.6 Output Specification

4.185.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Analyze design; instantiate and load simulated DAC, observe correct functioning
	Test Data	No data.
	Expected Result	

4.186 LVV-T376 - Verify the Calculation of Ellipticity Correlations

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Leanne Guy

4.186.1 Verification Elements

- LVV-3404 - DMS-REQ-0362-V-01: Median residual PSF ellipticity correlations on 5 arcmin scales

4.186.2 Test Items

4.186.3 Predecessors

4.186.4 Environment Needs

4.186.4.1 Software

4.186.4.2 Hardware

4.186.5 Input Specification

4.186.6 Output Specification

4.186.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	
	Test Data	No data.
	Expected Result	

4.187 LVV-T377 - Verify Calculation of Photometric Performance Metrics

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Leanne Guy

4.187.1 Verification Elements

- LVV-3401 - DMS-REQ-0359-V-01: RMS photometric repeatability in uzy
- LVV-9751 - DMS-REQ-0359-V-02: Max fraction of sensors with excess unusable pixels
- LVV-9757 - DMS-REQ-0359-V-08: Max cross-talk imperfections
- LVV-9755 - DMS-REQ-0359-V-06: Accuracy of photometric transformation

- LVV-9754 - DMS-REQ-0359-V-05: Repeatability outlier limit in gri
- LVV-9752 - DMS-REQ-0359-V-03: Max fraction of outliers among non-saturated sources
- LVV-9756 - DMS-REQ-0359-V-07: RMS width of zero point in u-band
- LVV-9753 - DMS-REQ-0359-V-04: Accuracy of zero point for colors with u-band
- LVV-9762 - DMS-REQ-0359-V-13: Max sky brightness error
- LVV-9760 - DMS-REQ-0359-V-11: Fraction of zero point outliers
- LVV-9759 - DMS-REQ-0359-V-10: RMS photometric repeatability in gri
- LVV-9758 - DMS-REQ-0359-V-09: Repeatability outlier limit in uzy
- LVV-9761 - DMS-REQ-0359-V-12: Max fraction of unusable pixels per sensor
- LVV-9764 - DMS-REQ-0359-V-15: Percentage of image area with ghosts
- LVV-9766 - DMS-REQ-0359-V-17: Max RMS of resolved/unresolved flux ratio
- LVV-9763 - DMS-REQ-0359-V-14: RMS width of zero point in all bands except u
- LVV-9765 - DMS-REQ-0359-V-16: Accuracy of zero point for colors without u-band

4.187.2 Test Items

Verify that the DMS system provides software to calculate photometric performance metrics, and that the algorithms are properly calculating the desired quantities. Note that because the DMS requirement is that the software shall be provided (and not on the actual measured values of the metrics), we verify all of the requirements via a single test case.

4.187.3 Predecessors

4.187.4 Environment Needs

4.187.4.1 Software

4.187.4.2 Hardware

4.187.5 Input Specification

4.187.6 Output Specification

4.187.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T987	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the following:
	Test Data	
	Expected Result	Butler repo available for reading.
2	Description	Point the butler to a simulated dataset containing data in all filters, that is sufficient for the purposes of measuring photometric performance metrics.
	Test Data	No data.
	Expected Result	
3	Description	Execute the LSST Stack package 'validate_drp' (or an alternate package that is relevant) on this dataset to perform the measurements of the metrics.
	Test Data	No data.
	Expected Result	Measurements of validation metrics and the presence of QA plots resulting from the validation pipeline.
4	Description	Compare measured photometry to known values from input simulated data, and confirm that the output values for all of the photometric performance metrics are as expected.
	Test Data	No data.
	Expected Result	Measured astrometry metrics that are within reasonable values given the (known) input dataset.

4.188 LVV-T378 - Verify Calculation of Astrometric Performance Metrics

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Leanne Guy

4.188.1 Verification Elements

- LVV-3402 - DMS-REQ-0360-V-01: Median astrometric error on 20 arcmin scales
- LVV-9778 - DMS-REQ-0360-V-12: RMS difference between r-band and other filter separation
- LVV-9777 - DMS-REQ-0360-V-11: Max fraction of r-band color difference outliers
- LVV-9779 - DMS-REQ-0360-V-13: Max fraction exceeding limit on 200 arcmin scales
- LVV-9773 - DMS-REQ-0360-V-07: Outlier limit on 5 arcmin scales
- LVV-9770 - DMS-REQ-0360-V-05: Outlier limit on 20 arcmin scales
- LVV-9775 - DMS-REQ-0360-V-09: Outlier limit on 200 arcmin scales
- LVV-9769 - DMS-REQ-0360-V-04: Median absolute error in RA, Dec
- LVV-9774 - DMS-REQ-0360-V-08: Median astrometric error on 200 arcmin scales
- LVV-9768 - DMS-REQ-0360-V-03: Median astrometric error on 5 arcmin scales
- LVV-9771 - DMS-REQ-0360-V-06: Color difference outlier limit relative to r-band
- LVV-9776 - DMS-REQ-0360-V-10: Max fraction exceeding limit on 20 arcmin scales
- LVV-9767 - DMS-REQ-0360-V-02: Max fraction exceeding limit on 5 arcmin scales

4.188.2 Test Items

Verify that the DMS system provides software to calculate astrometric performance metrics, and that the algorithms are properly calculating the desired quantities. Note that because the DMS requirement is that the software shall be provided (and not on the actual measured values of the metrics), we verify all of the requirements via a single test case.

4.188.3 Predecessors

4.188.4 Environment Needs

4.188.4.1 Software

4.188.4.2 Hardware

4.188.5 Input Specification

4.188.6 Output Specification

4.188.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T987	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the following:
	Test Data	
	Expected Result	Butler repo available for reading.
2	Description	Point the butler to a simulated dataset containing data in all filters, that is sufficient for the purposes of measuring astrometric performance metrics.
	Test Data	No data.
	Expected Result	
3	Description	Execute the LSST Stack package 'validate_drp' (or an alternate package that is relevant) on this dataset to perform the measurements of the metrics.
	Test Data	No data.
	Expected Result	Measurements of validation metrics and the presence of QA plots resulting from the validation pipeline.
4	Description	Compare measured astrometry to known values from input simulated data, and confirm that the output values for all of the astrometric performance metrics are as expected.
	Test Data	No data.
	Expected Result	Measured astrometry metrics that are within reasonable values given the (known) input dataset.

4.189 LVV-T385 - Verify implementation of minimum number of simultaneous retrievals of CCD-sized coadd cutouts

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Leanne Guy

4.189.1 Verification Elements

- LVV-3394 - DMS-REQ-0377-V-01: Min number of simultaneous single-CCD coadd cutout image users

4.189.2 Test Items

Verify that at least **ccdRetrievalUsers = 20** users can simultaneously retrieve a single CCD-sized coadd cutout using the IVOA SODA protocol.

4.189.3 Predecessors

4.189.4 Environment Needs

4.189.4.1 Software

4.189.4.2 Hardware

4.189.5 Input Specification

4.189.6 Output Specification

4.189.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Confirm that CCD-sized cutouts from coadds, also containing mask and variance planes, are available on the SODA server. If none are available, copy an image (or some images) to the server.
	Test Data	No data.
	Expected Result	At least one CCD-sized coadd cutout is available, and is a well-formed image.
2	Description	Simulate SODA queries by at least ccdRetrievalUsers = 20 users at the same time.
	Test Data	No data.
	Expected Result	
3	Description	Confirm that all simulated users retrieved the desired image(s), and that the returned images are well-formed, with (at least) image, mask, and variance planes.

Step	Description, Input Data and Expected Result	
	Test Data	No data.
	Expected Result	All of the simulated ccdRetrievalUsers = 20 users retrieved images within the specified time (see related Verification Element and Test Case).

4.190 LVV-T1097 - Verify Summit to Base Network Implementation

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeff Kantor

4.190.1 Verification Elements

- LVV-73 - DMS-REQ-0171-V-01: Summit to Base Network
- LVV-71 - DMS-REQ-0168-V-01: Summit Facility Data Communications

4.190.2 Test Items

Verify that:

- Summit - Base Network has been properly implemented in Summit and Base facilities
- Summit - Base Network is properly integrated with Summit Control Network and DAQ/-Camera Data Backbone

4.190.3 Predecessors

None.

4.190.4 Environment Needs

4.190.4.1 Software OCS/DMCS test harness

Simulated images and meta-data

EFD

DAQ client

Archiver/forwarder (Data Backbone)

4.190.4.2 Hardware DAQ

Base servers with archiver

4.190.5 Input Specification

1. Summit Control Network and Camera Data Backbone installed and operating properly.
2. Summit - Base Network installed and operating properly.
3. Simulated or real DAQ installed on summit and pre-loaded with image data.
4. EFD installed on summit and pre-loaded with image meta-data.
5. Archiver/forwarders installed in Base and operating properly.
6. OCS/DMCS test harness installed and pre-configured to trigger read-out and transfer.

4.190.6 Output Specification

Image and meta-data transferred to Base Archiver/Forwarders.

4.190.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Verify the available documentation in order to ensure that the Summit to Base Network has been set-up and is working.
	Test Data	No data.
	Expected Result	List of documents that demonstrate the network implementation

4.191 LVV-T1168 - Test Summit - Base Network Integration

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Inspection	Jeff Kantor

4.191.1 Verification Elements

- LVV-73 - DMS-REQ-0171-V-01: Summit to Base Network

4.191.2 Test Items

3 phases done (in collaboration with equipment/installation vendors):

1. Installation of fiber optic cables and Optical Time Domain Reflector (OTDR) fiber testing (completed 20170602 REUNA deliverable RD10)
2. Installation of AURA DWDM and Data Transfer Node (DTN) (completed 20171218 DMTR-82)
3. Installation of LSST DWDM and Bit Error Rate Tester (BERT) data (completed 20190505 collection-7743)

4.191.3 Predecessors

See pre-conditions by phase above.

4.191.4 Environment Needs

4.191.4.1 Software perfsonar on DTN.

4.191.4.2 Hardware OTDR, DTN.

4.191.5 Input Specification

By phase:

1. Posts from Cerro Pachon to AURA Gatehouse repaired/improved. Fiber installed on posts from Cerro Pachon to AURA Gatehouse. Fiber installed from AURA Gatehouse to AURA compound in La Serena. OTDR purchased.
2. AURA DWDM installed in caseta on Cerro Pachon and in existing computer room in La Serena. DTN installed in La Serena. DTN loaded with software and test data staged.
3. Base Data Center (BDC) ready for installation of LSST DWDM. Fiber connecting existing computer room to BDC. LSST DWDM equipment installed in Summit Computer Room and BDC.

4.191.6 Output Specification

Fiber tested to within acceptable Db. Bandwidth, latency within specifications.

4.191.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Test optical fiber with OTDR
	Test Data	OTDR generated optical data
	Expected Result	Fiber tested to within acceptable Db.
2	Description	Test AURA DWDM
	Test Data	DTN perfSonar generated data
	Expected Result	Summit - Base bandwidth and latency within specifications
3	Description	Test LSST DWDM
	Test Data	BERT generated data
	Expected Result	Summit - Base bandwidth, latency, bit error rate within specifications

4.192 LVV-T1232 - Verify Implementation of Catalog Export Formats From the Portal Aspect

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Colin Slater

4.192.1 Verification Elements

- LVV-35 - DMS-REQ-0078-V-01: Catalog Export Formats

4.192.2 Test Items

Verify that catalog data is exportable from the portal aspect in a variety of community-standard formats.

4.192.3 Predecessors

4.192.4 Environment Needs

4.192.4.1 Software

4.192.4.2 Hardware

4.192.5 Input Specification

4.192.6 Output Specification

4.192.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T849	Description	Navigate to the portal endpoint. The stable version should be used for this test and is currently located at: https://lsst-lsp-stable.ncsa.illinois.edu/portal/suit/ .
	Test Data	
	Expected Result	Currently this drops the user into an active portal environment.
1-2 from LVV-T849	Description	Though the current stable system does not authenticate currently, this step and the previous one should be updated as the system evolves.
	Test Data	
	Expected Result	No-op.
2	Description	Select query type "ADQL".
	Test Data	No data.
	Expected Result	
3	Description	Execute the example query given in the example code below by entering the text in the ADQL Query box, then clicking "Search" at the lower left corner of the page.
	Test Data	No data.
	Example Code	<pre>SELECT cntr, ra, decl, w1mpro_ep, w2mpro_ep, w3mpro_ep FROM wise_00.allwise_p3as_mep WHERE CONTAINS(POINT('ICRS', ra, decl), CIRCLE('ICRS', 192.85, 27.13, .2)) = 1</pre>

Step	Description, Input Data and Expected Result	
	Expected Result	A new page will load with the search results as a table, with some plots as well.
4	Description	Click the icon that looks like a floppy disk (it says "Save the content as an IPAC, CSV, or TSV table" when you mouse over it).
	Test Data	No data.
	Expected Result	
5	Description	• Select "CSV", then specify a destination to save the file on your local computer. • Select "VOTable", then specify a destination to save the file on your local computer. • Select "FITS", then specify a destination to save the file on your local computer.
	Test Data	No data.
	Expected Result	
6	Description	Open each of the files (either in TOPCAT, or using Astropy io tools). Confirm that the data tables are well-formed, and that each table contains the same columns and the same number of rows.
	Test Data	No data.
	Expected Result	
7-1 from LVV-T850	Description	Currently, there is no logout mechanism on the portal. This should be updated as the system matures.
	Test Data	Simply close the browser window.
	Expected Result	Closed browser window. When navigating to the portal endpoint, expect to execute the steps in LVV-T849.

4.193 LVV-T1240 - Verify implementation of minimum astrometric standards per CCD

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Jim Bosch

4.193.1 Verification Elements

- LVV-9741 - DMS-REQ-0030-V-02: Minimum astrometric standards per CCD

4.193.2 Test Items

Verify that each CCD in a processed dataset had its astrometric solution determined by at least **astrometricMinStandards = 5** astrometric standards.

4.193.3 Predecessors

4.193.4 Environment Needs

4.193.4.1 Software

4.193.4.2 Hardware

4.193.5 Input Specification

4.193.6 Output Specification

4.193.7 Test Procedure

Step	Description, Input Data and Expected Result	
1-1 from LVV-T987	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the following:
	Test Data	
	Expected Result	Butler repo available for reading.
2	Description	Ingest data from an appropriate processed dataset.
	Test Data	No data.
	Expected Result	
3	Description	Select a single visit from the dataset, and extract its calibration data. For a subset of CCDs, check how many astrometric standards contributed to the solution. Confirm that this number is at least astrometricMinStandards = 5 .

Step	Description, Input Data and Expected Result	
	Test Data	No data.
	Expected Result	At least astrometricMinStandards from each CCD were used in determining the WCS solution.

4.194 LVV-T1250 - Verify implementation of minimum number of simultaneous DM EFD query users

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin

4.194.1 Verification Elements

- LVV-3400 - DMS-REQ-0358-V-01: Min number of simultaneous DM EFD query users

4.194.2 Test Items

Verify that the DM EFD can support **dmEfdQueryUsers = 5** simultaneous queries. The additional requirement that each query must last no more than **dmEfdQueryTime = 10 seconds** will be verified separately in LVV-T1251, but these must be satisfied together.

4.194.3 Predecessors

4.194.4 Environment Needs

4.194.4.1 Software

4.194.4.2 Hardware

4.194.5 Input Specification

4.194.6 Output Specification

4.194.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Send multiple (at least 5) simultaneous queries to the DM EFD.
	Test Data	No data.
	Expected Result	
2	Description	Confirm that (a) the queries executed successfully, and that (b) they return reasonable results.
	Test Data	No data.
	Expected Result	
3	Description	Repeat the above steps for different queries, and different numbers of simultaneous queries, to confirm that the expected performance is met regardless of the query being executed.
	Test Data	No data.
	Expected Result	

4.195 LVV-T1251 - Verify implementation of maximum time to retrieve DM EFD query results

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin

4.195.1 Verification Elements

- LVV-9788 - DMS-REQ-0358-V-02: Max time to retrieve DM EFD query results

4.195.2 Test Items

Verify that the DM EFD can support **dmEfdQueryUsers = 5** simultaneous queries, with each query must executing in no more than **dmEfdQueryTime = 10 seconds**. The requirement on at least 5 simultaneous queries will be verified separately in LVV-T1250, but these must be satisfied together.

4.195.3 Predecessors

4.195.4 Environment Needs

4.195.4.1 Software

4.195.4.2 Hardware

4.195.5 Input Specification

4.195.6 Output Specification

4.195.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Send multiple (at least 5) simultaneous queries to the DM EFD.
	Test Data	No data.
	Expected Result	
2	Description	Confirm that (a) the queries executed successfully, and that (b) they return reasonable results. Check that the time of execution for all queries was less than 10 seconds.
	Test Data	No data.
	Expected Result	
3	Description	Repeat the above steps for different queries, and different numbers of simultaneous queries, to confirm that the expected performance is met regardless of the query being executed.
	Test Data	No data.
	Expected Result	

4.196 LVV-T1252 - Verify number of simultaneous alert filter users

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Eric Bellm

4.196.1 Verification Elements

- LVV-9748 - DMS-REQ-0343-V-02: Number of simultaneous users

4.196.2 Test Items

Verify that the DMS alert filter service supports **numBrokerUsers = 100** simultaneous brokers.

4.196.3 Predecessors

4.196.4 Environment Needs

4.196.4.1 Software

4.196.4.2 Hardware

4.196.5 Input Specification

4.196.6 Output Specification

4.196.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Create a simulated alert stream.
	Test Data	No data.
	Expected Result	
2	Description	Simultaneously execute user-defined alert filters for at least numBrokerUsers = 100 users, and confirm that the system successfully filters the stream as requested. Confirm that the bandwidth requirement of numBrokerAlerts = 20 per user was met. Simultaneously execute user-defined alert filters for at least 100 users, and confirm that the system successfully filters the stream as requested.
	Test Data	No data.
	Expected Result	All of the (simulated) numBrokerUsers = 100 users successfully receive their requested filtered alerts.

4.197 LVV-T1264 - Verify implementation of archiving camera test data

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Gruendl

4.197.1 Verification Elements

- LVV-9637 - DMS-REQ-0372-V-01: Archiving Camera Test Data

4.197.2 Test Items

Verify that a subset of camera test data has been ingested into Butler repos and is available through standard data access tools.

4.197.3 Predecessors

4.197.4 Environment Needs

4.197.4.1 Software

4.197.4.2 Hardware

4.197.5 Input Specification

4.197.6 Output Specification

4.197.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Obtain some data on a camera test stand.
	Test Data	No data.
	Expected Result	
2	Description	Wait a sufficient amount of time, then confirm that automatic transfer/ingest of the data has occurred, and a repo is available at NCSA.

Step	Description, Input Data and Expected Result	
	Test Data	No data.
	Expected Result	The data is present at NCSA in non-empty repos.
3	Description	Identify the relevant Butler repo of ingested camera test stand data.
	Test Data	No data.
	Expected Result	
4-1 from LVV-T987	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the following:
	Test Data	
	Expected Result	Butler repo available for reading.
5	Description	Read various repo data products with the Butler, and confirm that they contain the expected data.
	Test Data	No data.
	Expected Result	Camera test stand data that is well-formed.

4.198 LVV-T1276 - Verify implementation of latency of reporting optical transients

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

4.198.1 Verification Elements

- LVV-9740 - DMS-REQ-0004-V-02: Latency of reporting optical transients

4.198.2 Test Items

Verify that alerts are generated for optical transients within **OTT1 = 1 minute** of the completion of the readout of the last image.

4.198.3 Predecessors

4.198.4 Environment Needs

4.198.4.1 Software

4.198.4.2 Hardware

4.198.5 Input Specification

4.198.6 Output Specification

4.198.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Identify a precursor dataset containing raw images (and templates), that is suitable for testing the Alert Production.
	Test Data	No data.
	Expected Result	
2-1 from LVV-T866	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame processing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is presumed that these are automated for a given dataset.
	Test Data	
	Expected Result	An output dataset including difference images and DIASource and DIAObject measurements.
2-2 from LVV-T866	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
	Test Data	
	Expected Result	
3	Description	Time processing of data starting from (pre-ingested) raw files until an alert is available for distribution; verify that this time is less than OTT1.
	Test Data	No data.
	Expected Result	Alerts are received via the alert stream within OTT1=1 minute from the time the Alert Production payload was executed.

Step Description, Input Data and Expected Result

4.199 LVV-T1277 - Verify processing of maximum number of calibration exposures

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim

4.199.1 Verification Elements

- LVV-9745 - DMS-REQ-0131-V-02: Max number of calibs to be processed

4.199.2 Test Items

Verify that as many as **nCalExpProc = 25** calibration exposures can be processed together within time calProcTime.

4.199.3 Predecessors

4.199.4 Environment Needs

4.199.4.1 Software

4.199.4.2 Hardware

4.199.5 Input Specification

4.199.6 Output Specification

4.199.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Identify a dataset of raw calibration exposures containing at least nCalExpProc = 25 exposures. (If it contains more than 25 exposures, use only 25 for the test.)
	Test Data	No data.
	Expected Result	
2-1 from LVV-T1059	Description	Execute the Daily Calibration Products Update payload. The payload uses raw calibration images and information from the Transformed EFD to generate a subset of Master Calibration Images and Calibration Database entries in the Data_Backbone.
	Test Data	
	Expected Result	
2-2 from LVV-T1059	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present and well-formed.
	Test Data	
	Expected Result	
3	Description	Confirm that the processing completed successfully within calProcTime = 1200 seconds .
	Test Data	No data.
	Expected Result	Calibration products resulting from processed raw calibration exposures are present within calProcTime, and are well-formed images.
4	Description	Perform the test again with <i>more than</i> nCalExpProc = 25 images, and confirm that the processing completes within calProcTime = 1200 seconds .
	Test Data	No data.
	Expected Result	Calibration products resulting from processed raw calibration exposures are present within calProcTime, and are well-formed images. (To verify that the test with 25 images was not at the limits of what the software can handle – should be able to exceed that bare minimum.)

4.200 LVV-T1332 - Verify implementation of maximum time for retrieval of CCD-sized coadd cutouts

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Leanne Guy

4.200.1 Verification Elements

- LVV-9797 - DMS-REQ-0377-V-02: Max time to retrieve single-CCD coadd cutout image

4.200.2 Test Items

Verify that at least **ccdRetrievalUsers = 20** users can retrieve CCD-sized coadd cutouts using the IVOA SODA protocol within a maximum retrieval time of **ccdRetrievalTime = 15 seconds**.

4.200.3 Predecessors

4.200.4 Environment Needs

4.200.4.1 Software

4.200.4.2 Hardware

4.200.5 Input Specification

4.200.6 Output Specification

4.200.7 Test Procedure

Step	Description, Input Data and Expected Result	
1	Description	Confirm that CCD-sized cutouts from coadds, also containing mask and variance planes, are available on the SODA server. If none are available, copy an image (or some images) to the server.
	Test Data	No data.
	Expected Result	At least one CCD-sized coadd cutout is available, and is a well-formed image.
2	Description	Simulate SODA queries by at least ccdRetrievalUsers = 20 users at the same time.
	Test Data	No data.
	Expected Result	
3	Description	Monitor the time that each query takes to complete, and confirm that all simulated users retrieved the desired image(s) within ccdRetrievalTime = 15 seconds .
	Test Data	No data.

Step	Description, Input Data and Expected Result	
	Expected Result	All of the simulated ccdRetrievalUsers = 20 users retrieved images within ccdRetrieval-Time = 15 seconds .

Draft

5 Reusable Test Cases

Test cases in this section are made up of commonly encountered steps that have been factored out into modular, reusable scripts. These test cases are meant solely for the building of actual tests used for verification, to be inserted in test scripts via the “Call to Test” functionality in Jira/ATM. They streamline the process of writing test scripts by providing pre-designed steps, while also ensuring homogeneity throughout the test suite. These reusable modules are not themselves verifying requirements. Also, these test cases shall not call other reusable test cases in their script.

5.1 LVV-T12 - DRP-00-10: Data Release Includes Required Data Products

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jim Bosch

5.1.1 Test Items

This test will check that the basic data products which should be in an data release are generated by execution of the science payload.

These products will include:

- Source catalogs, derived from PVIs and coadded images (DMS-REQ-0267 & DMS-REQ-0277);
- Forced source catalogs (DMS-REQ-0268);
- Object catalogs (DMS-REQ-0275);
- Processed visit images (PVIs; DMS-REQ-0069);
- Coadded images (DMS-REQ-0279);

5.2 LVV-T18 - AG-00-05: Alert Generation Produces Required Data Products

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Eric Bellm

5.2.1 Test Items

This test will check that the basic data products produced by Alert Generation are generated by execution of the science payload.

These products will include:

- Processed visit images (PVIs; DMS-REQ-0069);
- Difference Exposures (DMS-REQ-0010);
- DIASource catalogs (DMS-REQ-0269);
- DIAObject catalogs (DMS-REQ-0271);

5.3 LVV-T29 - Verify implementation of Raw Science Image Data Acquisition

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Kian-Tat Lim

5.3.1 Test Items

Verify acquisition of raw data from L1 Test Stand DAQ while simulating all modes

5.4 LVV-T32 - Verify implementation of Raw Image Assembly

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Kian-Tat Lim

5.4.1 Test Items

Verify that the raw exposure data from all readout channels in a sensor can be assembled into a single image, and that all required/relevant metadata are associated with the image data.

5.5 LVV-T1060 - Run Periodic Calibration Products Production Payload

Version	Status	Priority	Verification Type	Owner

1 Draft Normal Test Jeffrey Carlin

5.5.1 Test Items

Execute the Calibration Products Production payload to create a subset of Master Calibration images and Calibration Database entries.

5.6 LVV-T216 - Installation of the Alert Distribution payloads.

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Eric Bellm

5.6.1 Test Items

This test will check:

- That the Alert Distribution payloads are available from documented channels.
- That the Alert Distribution payloads can be installed on LSST Data Facility-managed systems.
- That the Alert Distribution payloads can be executed by LSST Data Facility-managed systems.

5.7 LVV-T217 - Full Stream Alert Distribution

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Eric Bellm

5.7.1 Test Items

This test will check that the full stream of LSST alerts can be distributed to end users.

Specifically, this will demonstrate that:

- Serialized alert packets can be loaded into the alert distribution system at LSST-relevant scales (10,000 alerts every 39 seconds);
- Alert packets can be retrieved from the queue system at LSST-relevant scales.

5.8 LVV-T987 - Instantiate the Butler for reading data

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin

5.8.1 Test Items

Create a Butler client to read data from an input repository.

5.9 LVV-T866 - Run Alert Production Payload

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin

5.9.1 Test Items

Execute Alert Production payload on a dataset. Generate all (or a subset of) Prompt science data products including Alerts (with the exception of Solar System object orbits) and load them into the Data Backbone and Prompt Products Database.

5.10 LVV-T1059 - Run Daily Calibration Products Update Payload

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin

5.10.1 Test Items

Execute the Daily Calibration Products Update payload to create a subset of Master Calibration images and Calibration Database entries.

5.11 LVV-T21 - AG-00-20: Scientific Verification of DIASource Catalog

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Eric Bellm

5.11.1 Test Items

This test will check that the difference image source catalogs delivered by the Alert Generation science payload meet the requirements laid down by LSE-61.

- Specifically, this will demonstrate that:
- Measurements in the catalog are presented in flux units (DMS-REQ-0347);
- Each DIASource record contains an appropriate subset of the attributes required by DMS-REQ-0269. In particular, the LDM-503-3-era pipeline is expected to provide DIASource positions (sky and focal plane), fluxes, and flags indicative of issues encountered during processing.
- Faint DIASources satisfying additional criteria are stored (DMS-REQ-0270).
- Derived quantities are provided in pre-computed columns (DMS-REQ-0331);

This test does not include quantitative targets for the science quality criteria.

5.12 LVV-T22 - AG-00-25: Scientific Verification of DIAObject Catalog

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Eric Bellm

5.12.1 Test Items

This test will check that the DIAObject catalogs delivered by the Alert Generation science payload meet the requirements laid down by LSE-61.

Specifically, this will demonstrate that:

- DIAObjects are recorded with unique identifiers (DMS-REQ-0271);
- Measurements in the catalog are presented in flux units (DMS-REQ-0347);
- EachDIAObjectrecordcontainscontainsanappropriatesetofsummaryattributes(DMS- REQ- 0271 and DMS-REQ-0272). Note:
 - This test is executed independently of the Data Release Production system. Hence, DIAObjects are not associated to Objects, and the association metadata specified by DMS-REQ-0271 is not expected to be available.
 - TheLDM-503-3erapipelineisnotexpectedto calculateorpersistallattributesspec- ified by DMS-REQ-0272 requirement.
- Relevant derived quantities are provided in pre-computed columns (DMS-REQ-0331);

This test does not include quantitative targets for the science quality criteria.

5.13 LVV-T53 - Verify implementation of SObject Catalog

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

5.13.1 Test Items

Verify that the DMS produces a catalog of Solar System Objects identify from Moving Object Processing.

Verify that the SObject catalog includes orbital elements and additional related quantities.

5.14 LVV-T16 - DRP-00-35: Scientific Verification of Coadd Images

Version	Status	Priority	Verification Type	Owner
---------	--------	----------	-------------------	-------

1

Approved Normal Test

Jim Bosch

5.14.1 Test Items

This test will check that the coadded images delivered by the DRP science payload meet the requirements laid down by LSE-61.

Specifically, this will demonstrate that:

- Coadds have been generated and persisted during payload execution;
- Each coadd provides a spatially varying PSF model (DMS-REQ-0047).
- Saturated pixels are correctly masked.
- Pixels affected by satellite trails and ghosts are rejected from the coadd.
- The background is not oversubtracted around bright objects.

This test does not include quantitative targets for the science quality criteria; we instead require for each test that we be able to quickly construct a plot or display summary images that allow such a target can be visualized.

5.15 LVV-T1064 - Run Data Release Production Payload

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin

5.15.1 Test Items

Execute the Data Release Production payload, starting from raw images and producing science data products.

5.16 LVV-T35 - Verify implementation of Nightly Data Accessible Within 24 hrs

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

5.16.1 Test Items

Test Items

Verify that

1. Alerts are available within OTT1
2. Level 1 Data Products are available within L1PublicT
3. Solar System Object orbits are available within L1PublicT of the updated calculations completion on the following night.

5.17 LVV-T140 - Verify implementation of Production Orchestration

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Gruendl

5.17.1 Test Items

Demonstrate use to orchestration software to perform real-time and batch production on LSST compute platform(s).

5.18 LVV-T837 - Authenticate to Notebook Aspect

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin

5.18.1 Test Items

Not specifically a test – modular script to be used in multiple other Test Scripts.

5.19 LVV-T838 - Access an empty notebook in the Notebook Aspect

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Simon Krughoff

5.19.1 Test Items

The steps here cover just those necessary to gain access to an empty notebook after authentication is complete.

5.20 LVV-T1207 - Execute a simple ADQL query using the TAP service in the notebook aspect

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin

5.20.1 Test Items

Extract a small amount of data from a catalog via the LSST TAP service.

5.21 LVV-T1208 - Log out of the notebook aspect of the LSP

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Simon Krughoff

5.21.1 Test Items

Leave the notebook aspect of the LSST Science Platform in a clean state

5.22 LVV-T849 - Authenticate to the portal aspect of the LSP

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Simon Krughoff

5.22.1 Test Items

Obtain an authenticated session in the portal aspect of the LSST Science Platform

5.23 LVV-T850 - Log out of the portal aspect of the LSP

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Simon Krughoff

5.23.1 Test Items

Leave the portal aspect of the LSST Science Platform in a clean state

6 Deprecated Test Cases

This section includes all test cases that have been marked as deprecated. These test cases will never be executed again, but have been in the past. For this reason it is important to keep them in the baseline as a reference.

No deprecated test cases found.

Draft

A Traceability

Verification Elements	High Level Requirements	Test Cases
LVV-157 - DMS-REQ-0326-V-01: Storing Approximations of Per-pixel Metadata	OSS-REQ-0391	LVV-T23 LVV-T24
LVV-162 - DMS-REQ-0331-V-01: Computing Derived Quantities	OSS-REQ-0391	LVV-T21 LVV-T22
LVV-163 - DMS-REQ-0332-V-01: Denormalizing Database Tables	OSS-REQ-0133	LVV-T25
LVV-164 - DMS-REQ-0333-V-01: Maximum Likelihood Values and Covariances	OSS-REQ-0391	LVV-T26
LVV-177 - DMS-REQ-0346-V-01: Data Availability	OSS-REQ-0004 OSS-REQ-0167 OSS-REQ-0313	LVV-T27
LVV-178 - DMS-REQ-0347-V-01: Measurements in catalogs	OSS-REQ-0391	LVV-T28 LVV-T21 LVV-T22
LVV-8 - DMS-REQ-0018-V-01: Raw Science Image Data Acquisition	OSS-REQ-0114	LVV-T29 LVV-T29
LVV-9 - DMS-REQ-0020-V-01: Wavefront Sensor Data Acquisition	OSS-REQ-0316	LVV-T30
LVV-10 - DMS-REQ-0022-V-01: Crosstalk Corrected Science Image Data Acquisition	OSS-REQ-0114 OSS-REQ-0127	LVV-T31
LVV-11 - DMS-REQ-0024-V-01: Raw Image Assembly	OSS-REQ-0114 OSS-REQ-0129	LVV-T32 LVV-T32
LVV-28 - DMS-REQ-0068-V-01: Raw Science Image Metadata	OSS-REQ-0122 DMS-REQ-0320 DMS-REQ-0066 OSS-REQ-0171	LVV-T33
LVV-1234 - OSS-REQ-0122-V-01: Provenance	OSS-REQ-0123	LVV-T33 LVV-T37 LVV-T64 LVV-T89 LVV-T119
LVV-96 - DMS-REQ-0265-V-01: Guider Calibration Data Acquisition	OSS-REQ-0194	LVV-T34
LVV-175 - DMS-REQ-0004-V-01: Time to L1 public release	DMS-REQ-0003 OSS-REQ-0127	LVV-T35 LVV-T35 LVV-T95
LVV-7 - DMS-REQ-0010-V-01: Difference Exposures	DMS-REQ-0011 DMS-REQ-0033 OSS-REQ-0129	LVV-T18 LVV-T36
LVV-32 - DMS-REQ-0074-V-01: Difference Exposure Attributes	OSS-REQ-0122 DMS-REQ-0066	LVV-T37
LVV-29 - DMS-REQ-0069-V-01: Processed Visit Images	OSS-REQ-0129	LVV-T18 LVV-T38
LVV-12 - DMS-REQ-0029-V-01: Generate Photometric Zeropoint for Visit Image	DMS-REQ-0090 OSS-REQ-0056 OSS-REQ-0152	LVV-T39

Verification Elements	High Level Requirements	Test Cases
LVV-13 - DMS-REQ-0030-V-01: Absolute accuracy of WCS	DMS-REQ-0090 DMS-REQ-0104 OSS-REQ-0149 OSS-REQ-0162	LVW-T40
LVV-30 - DMS-REQ-0070-V-01: Generate PSF for Visit Images	OSS-REQ-0056 DMS-REQ-0116	LVW-T41
LVV-31 - DMS-REQ-0072-V-01: Processed Visit Image Content	OSS-REQ-0129 DMS-REQ-0066	LVW-T42
LVV-158 - DMS-REQ-0327-V-01: Background Model Calculation	OSS-REQ-0056	LVW-T43
LVV-159 - DMS-REQ-0328-V-01: Documenting Image Characterization	OSS-REQ-0391	LVW-T44
LVV-39 - DMS-REQ-0097-V-01: Level 1 Data Quality Report Definition	OSS-REQ-0131 DMS-REQ-0096	LVW-T45
LVV-41 - DMS-REQ-0099-V-01: Level 1 Performance Report Definition	DMS-REQ-0098 OSS-REQ-0131	LVW-T46
LVV-43 - DMS-REQ-0101-V-01: Level 1 Calibration Report Definition	OSS-REQ-0131 DMS-REQ-0100	LVW-T47
LVV-97 - DMS-REQ-0266-V-01: Exposure Catalog	OSS-REQ-0130	LVW-T48
LVV-100 - DMS-REQ-0269-V-01: DIASource Catalog	OSS-REQ-0130 DMS-REQ-0270	LVW-T18 LVW-T49 LVW-T21
LVV-101 - DMS-REQ-0270-V-01: Faint DIASource Measurements	OSS-REQ-0166	LVW-T50 LVW-T21 LVW-T18
LVV-102 - DMS-REQ-0271-V-01: Max nearby galaxies associated with DIASource	OSS-REQ-0130	LVW-T22 LVW-T51
LVV-103 - DMS-REQ-0272-V-01: DIAObject Attributes	OSS-REQ-0130	LVW-T22 LVW-T52
LVV-104 - DMS-REQ-0273-V-01: SSObject Catalog	OSS-REQ-0130	LVW-T53 LVW-T53
LVV-105 - DMS-REQ-0274-V-01: Alert Content	OSS-REQ-0128	LVW-T54
LVV-148 - DMS-REQ-0317-V-01: DIAForcedSource Catalog	OSS-REQ-0130	LVW-T55
LVV-150 - DMS-REQ-0319-V-01: Characterizing Variability	OSS-REQ-0126	LVW-T56
LVV-154 - DMS-REQ-0323-V-01: Calculating SSObject Parameters	OSS-REQ-0126	LVW-T57
LVV-155 - DMS-REQ-0324-V-01: Matching DIASources to Objects	OSS-REQ-0126	LVW-T58
LVV-156 - DMS-REQ-0325-V-01: Regenerating L1 Data Products During Data Release Processing	OSS-REQ-0135	LVW-T59
LVV-184 - DMS-REQ-0353-V-01: Publishing predicted visit schedule	OSS-REQ-0378	LVW-T60
LVV-16 - DMS-REQ-0034-V-01: Associate Sources to Objects	DMS-REQ-0081 OSS-REQ-0339 OSS-REQ-0153	LVW-T61
LVV-20 - DMS-REQ-0047-V-01: Provide PSF for Coadded Images	DMS-REQ-0041 OSS-REQ-0136 OSS-REQ-0316	LVW-T16 LVW-T62
LVV-45 - DMS-REQ-0103-V-01: Produce Images for EPO	OSS-REQ-0136	LVW-T63
LVV-46 - DMS-REQ-0106-V-01: Coadded Image Provenance	OSS-REQ-0122 DMS-REQ-0104	LVW-T64

Verification Elements	High Level Requirements	Test Cases
LVV-98 - DMS-REQ-0267-V-01: Source Catalog	OSS-REQ-0137	LVV-T12 LVV-T65
LVV-99 - DMS-REQ-0268-V-01: Forced-Source Catalog	OSS-REQ-0137	LVV-T12 LVV-T66
LVV-106 - DMS-REQ-0275-V-01: Object Catalog	OSS-REQ-0137	LVV-T12 LVV-T67
LVV-19 - DMS-REQ-0046-V-01: Provide Photometric Redshifts of Galaxies	OSS-REQ-0133 DMS-REQ-0040	LVV-T68
LVV-107 - DMS-REQ-0276-V-01: Object Characterization	OSS-REQ-0137	LVV-T69
LVV-180 - DMS-REQ-0349-V-01: Detecting extended low surface brightness objects	OSS-REQ-0133	LVV-T71
LVV-109 - DMS-REQ-0278-V-01: Coadd Image Method Constraints	OSS-REQ-0136	LVV-T16 LVV-T72
LVV-110 - DMS-REQ-0279-V-01: Deep Detection Coadds	OSS-REQ-0136	LVV-T12 LVV-T16 LVV-T73
LVV-111 - DMS-REQ-0280-V-01: Template Coadds	OSS-REQ-0136	LVV-T74
LVV-112 - DMS-REQ-0281-V-01: Multi-band Coadds	OSS-REQ-0136	LVV-T75
LVV-160 - DMS-REQ-0329-V-01: All-Sky Visualization of Data Releases	OSS-REQ-0136	LVV-T76
LVV-161 - DMS-REQ-0330-V-01: Best Seeing Coadds	OSS-REQ-0136	LVV-T77
LVV-165 - DMS-REQ-0334-V-01: Persisting Data Products	OSS-REQ-0136	LVV-T12 LVV-T16 LVV-T78
LVV-166 - DMS-REQ-0335-V-01: PSF-Matched Coadds	OSS-REQ-0133	LVV-T79
LVV-168 - DMS-REQ-0337-V-01: Detecting faint variable objects	OSS-REQ-0136	LVV-T80
LVV-169 - DMS-REQ-0338-V-01: Targeted Coadds	LSR-REQ-0040 OSS-REQ-0136	LVV-T81
LVV-170 - DMS-REQ-0339-V-01: Tracking Characterization Changes Between Data Releases	LSR-REQ-0040	LVV-T82
LVV-22 - DMS-REQ-0059-V-01: Bad Pixel Map	OSS-REQ-0271 DMS-REQ-0058 OSS-REQ-0129	LVV-T83
LVV-23 - DMS-REQ-0060-V-01: Bias Residual Image	DMS-REQ-0055 OSS-REQ-0271 OSS-REQ-0046	LVV-T84
LVV-24 - DMS-REQ-0061-V-01: Crosstalk Correction Matrix	DMS-REQ-0056 OSS-REQ-0349 OSS-REQ-0271	LVV-T85
LVV-25 - DMS-REQ-0062-V-01: Illumination Correction Frame	OSS-REQ-0046 DMS-REQ-0058 OSS-REQ-0271	LVV-T86
LVV-26 - DMS-REQ-0063-V-01: Monochromatic Flatfield Data Cube	OSS-REQ-0046 DMS-REQ-0058 DMS-REQ-0057 DMS-REQ-0076	LVV-T87
LVV-57 - DMS-REQ-0130-V-01: Calibration Data Products	OSS-REQ-0271 OSS-REQ-0194 OSS-REQ-0129	LVV-T88

Verification Elements	High Level Requirements	Test Cases
LVV-59 - DMS-REQ-0132-V-01: Calibration Image Provenance	OSS-REQ-0122 OSS-REQ-0123 DMS-REQ-0130	LVV-T89
LVV-113 - DMS-REQ-0282-V-01: Dark Current Correction Frame	OSS-REQ-0271 OSS-REQ-0046	LVV-T90
LVV-114 - DMS-REQ-0283-V-01: Fringe Correction Frame	OSS-REQ-0271 OSS-REQ-0046	LVV-T91
LVV-151 - DMS-REQ-0320-V-01: Processing of Data From Special Programs	LSR-REQ-0075 LSR-REQ-0121 LSR-REQ-0122 OSS-REQ-0392	LVV-T92
LVV-152 - DMS-REQ-0321-V-01: Level 1 Processing of Special Programs Data	OSS-REQ-0392	LVV-T93
LVV-153 - DMS-REQ-0322-V-01: Special Programs Database	OSS-REQ-0392	LVV-T94
LVV-1276 - OSS-REQ-0127-V-01: Level 1 Data Product Availability		LVV-T95
LVV-122 - DMS-REQ-0291-V-01: Query Repeatability	OSS-REQ-0181	LVV-T96
LVV-123 - DMS-REQ-0292-V-01: Uniqueness of IDs Across Data Releases	OSS-REQ-0130 OSS-REQ-0137	LVV-T97
LVV-124 - DMS-REQ-0293-V-01: Selection of Datasets	OSS-REQ-0176 OSS-REQ-0118	LVV-T98
LVV-125 - DMS-REQ-0294-V-01: Processing of Datasets	OSS-REQ-0120 OSS-REQ-0119 OSS-REQ-0118 OSS-REQ-0117	LVV-T12 LVV-T99
LVV-126 - DMS-REQ-0295-V-01: Transparent Data Access	OSS-REQ-0176	LVV-T100
LVV-3 - DMS-REQ-0002-V-01: Transient Alert Distribution	OSS-REQ-0184 OSS-REQ-0127	LVV-T217 LVV-T101
LVV-36 - DMS-REQ-0089-V-01: Solar System Objects Available Within Specified Time	DMS-REQ-0004 DMS-REQ-0086 OSS-REQ-0127	LVV-T102
LVV-9803 - DMS-REQ-0004-V-03: Time to availability of Solar System Object orbits	DMS-REQ-0003 OSS-REQ-0127	LVV-T102
LVV-38 - DMS-REQ-0096-V-01: Generate Data Quality Report Within Specified Time	OSS-REQ-0131	LVV-T103
LVV-40 - DMS-REQ-0098-V-01: Generate DMS Performance Report Within Specified Time	OSS-REQ-0131	LVV-T104
LVV-42 - DMS-REQ-0100-V-01: Generate Calibration Report Within Specified Time	OSS-REQ-0131 OSS-REQ-0046	LVV-T105
LVV-58 - DMS-REQ-0131-V-01: Time allowed to process calibs	OSS-REQ-0021 OSS-REQ-0194 DMS-REQ-0130	LVV-T106
LVV-115 - DMS-REQ-0284-V-01: Level-1 Production Completeness	OSS-REQ-0052 OSS-REQ-0130	LVV-T107
LVV-116 - DMS-REQ-0285-V-01: Level 1 Source Association	OSS-REQ-0160 OSS-REQ-0159	LVV-T22 LVV-T108
LVV-117 - DMS-REQ-0286-V-01: SSObject Preccovery	OSS-REQ-0159	LVV-T109
LVV-118 - DMS-REQ-0287-V-01: Max look-back time for preccovery	OSS-REQ-0130	LVV-T110
LVV-119 - DMS-REQ-0288-V-01: Use of External Orbit Catalogs	OSS-REQ-0159	LVV-T111

Verification Elements	High Level Requirements	Test Cases
LVV-173 - DMS-REQ-0342-V-01: Alert Filtering Service	LSR-REQ-0025	LVV-T112
LVV-174 - DMS-REQ-0343-V-01: Number of full-size alerts	OSS-REQ-0193	LVV-T113
LVV-179 - DMS-REQ-0348-V-01: Pre-defined alert filters	OSS-REQ-0184	LVV-T114
LVV-120 - DMS-REQ-0289-V-01: Calibration Production Processing	LSR-REQ-0026	LVV-T115
LVV-181 - DMS-REQ-0350-V-01: Associating Objects across data releases	OSS-REQ-0004	LVV-T116
LVV-47 - DMS-REQ-0119-V-01: DAC resource allocation for Level 3 processing	OSS-REQ-0170	LVV-T117
LVV-48 - DMS-REQ-0120-V-01: Level 3 Data Product Self Consistency	OSS-REQ-0143	LVV-T118
LVV-49 - DMS-REQ-0121-V-01: Provenance for Level 3 processing at DACs	OSS-REQ-0120	LVV-T119
LVV-53 - DMS-REQ-0125-V-01: Software framework for Level 3 catalog processing	OSS-REQ-0118	LVV-T120
LVV-56 - DMS-REQ-0128-V-01: Software framework for Level 3 image processing	OSS-REQ-0122	LVV-T121
LVV-121 - DMS-REQ-0290-V-01: Level 3 Data Import	DMS-REQ-0120	LVV-T122
LVV-171 - DMS-REQ-0340-V-01: Access Controls of Level 3 Data Products	OSS-REQ-0121	LVV-T123
LVV-139 - DMS-REQ-0308-V-01: Software Architecture to Enable Community Re-Use	OSS-REQ-0121	LVV-T124
LVV-6 - DMS-REQ-0009-V-01: Simulated Data	OSS-REQ-0122	LVV-T125
LVV-14 - DMS-REQ-0032-V-01: Image Differencing	DMS-REQ-0120	LVV-T126
LVV-15 - DMS-REQ-0033-V-01: Provide Source Detection Software	OSS-REQ-0121	LVV-T127
LVV-17 - DMS-REQ-0042-V-01: Provide Astrometric Model	OSS-REQ-0353	LVV-T128
LVV-18 - DMS-REQ-0043-V-01: Provide Calibrated Photometry	DMS-REQ-0007	LVV-T21
LVV-21 - DMS-REQ-0052-V-01: Enable a Range of Shape Measurement Approaches	OSS-REQ-0351	LVV-T22
LVV-63 - DMS-REQ-0160-V-01: Provide User Interface Services	OSS-REQ-0354	LVV-T129
LVV-127 - DMS-REQ-0296-V-01: Pre-cursor, and Real Data	OSS-REQ-0121	LVV-T130
LVV-182 - DMS-REQ-0351-V-01: Provide Beam Projector Coordinate Calculation Software	OSS-REQ-0129	LVV-T131
	OSS-REQ-0130	LVV-T132
	OSS-REQ-0137	LVV-T133
	OSS-REQ-0121	
	DMS-REQ-0080	
	OSS-REQ-0153	
	OSS-REQ-0149	
	OSS-REQ-0160	
	OSS-REQ-0162	
	OSS-REQ-0130	
	OSS-REQ-0275	
	OSS-REQ-0137	
	OSS-REQ-0137	
	OSS-REQ-0057	
	OSS-REQ-0383	

Verification Elements	High Level Requirements	Test Cases
LVV-27 - DMS-REQ-0065-V-01: Provide Image Access Services	OSS-REQ-0180 OSS-REQ-0176 OSS-REQ-0181 DMS-REQ-0066	LWV-T134
LVV-129 - DMS-REQ-0298-V-01: Data Product and Raw Data Access	OSS-REQ-0176	LWV-T136
LVV-130 - DMS-REQ-0299-V-01: Data Product Ingest	OSS-REQ-0141 OSS-REQ-0004	LWV-T137
LVV-131 - DMS-REQ-0300-V-01: Bulk Download Service	OSS-REQ-0178 OSS-REQ-0004	LWV-T138
LVV-133 - DMS-REQ-0302-V-01: Production Orchestration	OSS-REQ-0038 OSS-REQ-0117 OSS-REQ-0004	LWV-T140 LWV-T140
LVV-134 - DMS-REQ-0303-V-01: Production Monitoring	OSS-REQ-0038 OSS-REQ-0034	LWV-T141
LVV-135 - DMS-REQ-0304-V-01: Production Fault Tolerance	OSS-REQ-0117	LWV-T142
LVV-136 - DMS-REQ-0305-V-01: Task Specification	OSS-REQ-0122 OSS-REQ-0121	LWV-T144
LVV-137 - DMS-REQ-0306-V-01: Task Configuration	OSS-REQ-0122 OSS-REQ-0121 OSS-REQ-0041	LWV-T145
LVV-128 - DMS-REQ-0297-V-01: DMS Initialization Component	OSS-REQ-0122 OSS-REQ-0307 OSS-REQ-0121	LWV-T146
LVV-132 - DMS-REQ-0301-V-01: Control of Level-1 Production	OSS-REQ-0044	LWV-T147
LVV-138 - DMS-REQ-0307-V-01: Unique Processing Coverage	OSS-REQ-0120 OSS-REQ-0118	LWV-T148
LVV-33 - DMS-REQ-0075-V-01: Catalog Queries	DMS-REQ-0076 OSS-REQ-0176	LWV-T149
LVV-34 - DMS-REQ-0077-V-01: Maintain Archive Publicly Accessible	DMS-REQ-0076 OSS-REQ-0186	LWV-T150
LVV-35 - DMS-REQ-0078-V-01: Catalog Export Formats	DMS-REQ-0076 OSS-REQ-0176	LWV-T151 LWV-T1232
LVV-37 - DMS-REQ-0094-V-01: Keep Historical Alert Archive	DMS-REQ-0092 OSS-REQ-0128	LWV-T152
LVV-44 - DMS-REQ-0102-V-01: Provide Engineering & Facility Database Archive	OSS-REQ-0132	LWV-T153
LVV-140 - DMS-REQ-0309-V-01: Raw Data Archiving Reliability	OSS-REQ-0111	LWV-T154
LVV-141 - DMS-REQ-0310-V-01: Un-Archived Data Product Cache	OSS-REQ-0130	LWV-T155
LVV-142 - DMS-REQ-0311-V-01: Regenerate Un-archived Data Products	OSS-REQ-0129	LWV-T156
LVV-143 - DMS-REQ-0312-V-01: Level 1 Data Product Access	OSS-REQ-0185 OSS-REQ-0127	LWV-T157
LVV-144 - DMS-REQ-0313-V-01: Level 1 & 2 Catalog Access	OSS-REQ-0186	LWV-T158
LVV-167 - DMS-REQ-0336-V-01: Regenerating Data Products from Previous Data Releases	LSR-REQ-0049	LWV-T159
LVV-172 - DMS-REQ-0341-V-01: Max elapsed time for precovery results	OSS-REQ-0126	LWV-T160
LVV-176 - DMS-REQ-0345-V-01: Logging of catalog queries	OSS-REQ-0134	LWV-T161
LVV-189 - DMS-REQ-0363-V-01: Access to Previous Data Releases	OSS-REQ-0186	LWV-T162
LVV-190 - DMS-REQ-0364-V-01: Total number of data releases	OSS-REQ-0396	LWV-T163

Verification Elements	High Level Requirements	Test Cases
LVV-191 - DMS-REQ-0365-V-01: Operations Subsets	OSS-REQ-0398	LVV-T164
LVV-192 - DMS-REQ-0366-V-01: Subsets Support	OSS-REQ-0400	LVV-T165
LVV-193 - DMS-REQ-0367-V-01: Access Services Performance	OSS-REQ-0394	LVV-T166
LVV-194 - DMS-REQ-0368-V-01: Implementation Provisions	OSS-REQ-0399	LVV-T167
LVV-195 - DMS-REQ-0369-V-01: Evolution	OSS-REQ-0395	LVV-T168
LVV-196 - DMS-REQ-0370-V-01: Older Release Behavior	OSS-REQ-0397	LVV-T169
LVV-197 - DMS-REQ-0371-V-01: Query Availability	OSS-REQ-0401	LVV-T170
LVV-5 - DMS-REQ-0008-V-01: Pipeline Availability		LVV-T171
LVV-64 - DMS-REQ-0161-V-01: Optimization of Cost, Reliability and Availability in Order		LVV-T172
LVV-65 - DMS-REQ-0162-V-01: Pipeline Throughput	OSS-REQ-0020 OSS-REQ-0127	LVV-T173
LVV-66 - DMS-REQ-0163-V-01: Re-processing Capacity	OSS-REQ-0134	LVV-T174
LVV-67 - DMS-REQ-0164-V-01: Temporary Storage for Communications Links	DMS-REQ-0162 OSS-REQ-0052	LVV-T175
LVV-68 - DMS-REQ-0165-V-01: Infrastructure Sizing for "catching up"	OSS-REQ-0051 DMS-REQ-0162 OSS-REQ-0050	LVV-T176
LVV-994 - OSS-REQ-0051-V-01: Summit-Base Connectivity Loss		LVV-T176
LVV-69 - DMS-REQ-0166-V-01: Incorporate Fault-Tolerance	DMS-REQ-0161	LVV-T177
LVV-70 - DMS-REQ-0167-V-01: Incorporate Autonomics	DMS-REQ-0166	LVV-T178
LVV-145 - DMS-REQ-0314-V-01: Compute Platform Heterogeneity	OSS-REQ-0177 OSS-REQ-0124	LVV-T179
LVV-149 - DMS-REQ-0318-V-01: Data Management Unscheduled Downtime	OSS-REQ-0373	LVV-T180
LVV-71 - DMS-REQ-0168-V-01: Summit Facility Data Communications	OSS-REQ-0002	LVV-T181 LVV-T1097
LVV-72 - DMS-REQ-0170-V-01: Prefer Computing and Storage Down	DMS-REQ-0161	LVV-T182
LVV-146 - DMS-REQ-0315-V-01: DMS Communication with OCS	OSS-REQ-0003	LVV-T183
LVV-74 - DMS-REQ-0172-V-01: Summit to Base Network Availability	OSS-REQ-0373 DMS-REQ-0161	LVV-T185
LVV-75 - DMS-REQ-0173-V-01: Summit to Base Network Reliability	OSS-REQ-0373 DMS-REQ-0161	LVV-T186
LVV-76 - DMS-REQ-0174-V-01: Summit to Base Network Secondary Link	DMS-REQ-0173 OSS-REQ-0049 DMS-REQ-0172	LVV-T187
LVV-77 - DMS-REQ-0175-V-01: Summit to Base Network Ownership and Operation	DMS-REQ-0173 OSS-REQ-0036 DMS-REQ-0172	LVV-T188
LVV-78 - DMS-REQ-0176-V-01: Base Facility Infrastructure	OSS-REQ-0003	LVV-T189
LVV-80 - DMS-REQ-0178-V-01: Base Facility Co-Location with Existing Facility	DMS-REQ-0161 OSS-REQ-0006	LVV-T190
LVV-147 - DMS-REQ-0316-V-01: Commissioning Cluster		LVV-T191
LVV-183 - DMS-REQ-0352-V-01: Base Wireless LAN (WiFi)	OSS-REQ-0003 OSS-REQ-0053	LVV-T192
LVV-81 - DMS-REQ-0180-V-01: Base to Archive Network	OSS-REQ-0055 DMS-REQ-0162	LVV-T193

Verification Elements	High Level Requirements	Test Cases
LVV-82 - DMS-REQ-0181-V-01: Base to Archive Network Availability	OSS-REQ-0053 DMS-REQ-0162 DMS-REQ-0161	LVV-T194
LVV-83 - DMS-REQ-0182-V-01: Base to Archive Network Reliability	OSS-REQ-0053 DMS-REQ-0161 DMS-REQ-0181	LVV-T195
LVV-84 - DMS-REQ-0183-V-01: Base to Archive Network Secondary Link	DMS-REQ-0182 OSS-REQ-0049	LVV-T196
LVV-85 - DMS-REQ-0185-V-01: Archive Center	OSS-REQ-0004 DMS-REQ-0163	LVV-T197
LVV-86 - DMS-REQ-0186-V-01: Archive Center Disaster Recovery	OSS-REQ-0176 DMS-REQ-0161	LVV-T198
LVV-87 - DMS-REQ-0187-V-01: Archive Center Co-Location with Existing Facility	OSS-REQ-0022 DMS-REQ-0161	LVV-T199
LVV-88 - DMS-REQ-0188-V-01: Archive to Data Access Center Network	OSS-REQ-0004	LVV-T200
LVV-89 - DMS-REQ-0189-V-01: Archive to Data Access Center Network Availability	DMS-REQ-0161	LVV-T201
LVV-90 - DMS-REQ-0190-V-01: Archive to Data Access Center Network Reliability	DMS-REQ-0161	LVV-T202
LVV-91 - DMS-REQ-0191-V-01: Archive to Data Access Center Network Secondary Link	DMS-REQ-0189 DMS-REQ-0190	LVV-T203
LVV-50 - DMS-REQ-0122-V-01: Access to catalogs for external Level 3 processing	OSS-REQ-0180 OSS-REQ-0140	LVV-T204
LVV-51 - DMS-REQ-0123-V-01: Access to input catalogs for DAC-based Level 3 processing	OSS-REQ-0140	LVV-T205
LVV-52 - DMS-REQ-0124-V-01: Federation with external catalogs	OSS-REQ-0140 DMS-REQ-0125	LVV-T206
LVV-54 - DMS-REQ-0126-V-01: Access to images for external Level 3 processing	OSS-REQ-0180 OSS-REQ-0140	LVV-T207
LVV-55 - DMS-REQ-0127-V-01: Access to input images for DAC-based Level 3 processing	OSS-REQ-0140	LVV-T208
LVV-92 - DMS-REQ-0193-V-01: Data Access Centers	OSS-REQ-0004	LVV-T209
LVV-93 - DMS-REQ-0194-V-01: Data Access Center Simultaneous Connections		LVV-T210
LVV-94 - DMS-REQ-0196-V-01: Data Access Center Geographical Distribution	DMS-REQ-0193 OSS-REQ-0021 OSS-REQ-0022	LVV-T211
LVV-95 - DMS-REQ-0197-V-01: No Limit on Data Access Centers	DMS-REQ-0193 OSS-REQ-0021 OSS-REQ-0022	LVV-T212
LVV-3404 - DMS-REQ-0362-V-01: Median residual PSF ellipticity correlations on 5 arcmin scales	OSS-REQ-0390	LVV-T376
LVV-3401 - DMS-REQ-0359-V-01: RMS photometric repeatability in uzy	OSS-REQ-0387	LVV-T377
LVV-9751 - DMS-REQ-0359-V-02: Max fraction of sensors with excess unusable pixels	OSS-REQ-0387	LVV-T377
LVV-9757 - DMS-REQ-0359-V-08: Max cross-talk imperfections	OSS-REQ-0387	LVV-T377
LVV-9755 - DMS-REQ-0359-V-06: Accuracy of photometric transformation	OSS-REQ-0387	LVV-T377
LVV-9754 - DMS-REQ-0359-V-05: Repeatability outlier limit in gri	OSS-REQ-0387	LVV-T377
LVV-9752 - DMS-REQ-0359-V-03: Max fraction of outliers among non-saturated sources	OSS-REQ-0387	LVV-T377

Verification Elements	High Level Requirements	Test Cases
LVV-9756 - DMS-REQ-0359-V-07: RMS width of zero point in u-band	OSS-REQ-0387	LVV-T377
LVV-9753 - DMS-REQ-0359-V-04: Accuracy of zero point for colors with u-band	OSS-REQ-0387	LVV-T377
LVV-9762 - DMS-REQ-0359-V-13: Max sky brightness error	OSS-REQ-0387	LVV-T377
LVV-9760 - DMS-REQ-0359-V-11: Fraction of zero point outliers	OSS-REQ-0387	LVV-T377
LVV-9759 - DMS-REQ-0359-V-10: RMS photometric repeatability in gri	OSS-REQ-0387	LVV-T377
LVV-9758 - DMS-REQ-0359-V-09: Repeatability outlier limit in uzy	OSS-REQ-0387	LVV-T377
LVV-9761 - DMS-REQ-0359-V-12: Max fraction of unusable pixels per sensor	OSS-REQ-0387	LVV-T377
LVV-9764 - DMS-REQ-0359-V-15: Percentage of image area with ghosts	OSS-REQ-0387	LVV-T377
LVV-9766 - DMS-REQ-0359-V-17: Max RMS of resolved/unresolved flux ratio	OSS-REQ-0387	LVV-T377
LVV-9763 - DMS-REQ-0359-V-14: RMS width of zero point in all bands except u	OSS-REQ-0387	LVV-T377
LVV-9765 - DMS-REQ-0359-V-16: Accuracy of zero point for colors without u-band	OSS-REQ-0387	LVV-T377
LVV-3402 - DMS-REQ-0360-V-01: Median astrometric error on 20 arcmin scales	OSS-REQ-0388	LVV-T378
LVV-9778 - DMS-REQ-0360-V-12: RMS difference between r-band and other filter separation	OSS-REQ-0388	LVV-T378
LVV-9777 - DMS-REQ-0360-V-11: Max fraction of r-band color difference outliers	OSS-REQ-0388	LVV-T378
LVV-9779 - DMS-REQ-0360-V-13: Max fraction exceeding limit on 200 arcmin scales	OSS-REQ-0388	LVV-T378
LVV-9773 - DMS-REQ-0360-V-07: Outlier limit on 5 arcmin scales	OSS-REQ-0388	LVV-T378
LVV-9770 - DMS-REQ-0360-V-05: Outlier limit on 20 arcmin scales	OSS-REQ-0388	LVV-T378
LVV-9775 - DMS-REQ-0360-V-09: Outlier limit on 200 arcmin scales	OSS-REQ-0388	LVV-T378
LVV-9769 - DMS-REQ-0360-V-04: Median absolute error in RA, Dec	OSS-REQ-0388	LVV-T378
LVV-9774 - DMS-REQ-0360-V-08: Median astrometric error on 200 arcmin scales	OSS-REQ-0388	LVV-T378
LVV-9768 - DMS-REQ-0360-V-03: Median astrometric error on 5 arcmin scales	OSS-REQ-0388	LVV-T378
LVV-9771 - DMS-REQ-0360-V-06: Color difference outlier limit relative to r-band	OSS-REQ-0388	LVV-T378
LVV-9776 - DMS-REQ-0360-V-10: Max fraction exceeding limit on 20 arcmin scales	OSS-REQ-0388	LVV-T378
LVV-9767 - DMS-REQ-0360-V-02: Max fraction exceeding limit on 5 arcmin scales	OSS-REQ-0388	LVV-T378
LVV-3394 - DMS-REQ-0377-V-01: Min number of simultaneous single-CCD coadd cutout image users	OSS-REQ-0181	LVV-T385
LVV-73 - DMS-REQ-0171-V-01: Summit to Base Network	OSS-REQ-0003 OSS-REQ-0127 DMS-REQ-0090	LVV-T1097 LVV-T1168
LVV-9741 - DMS-REQ-0030-V-02: Minimum astrometric standards per CCD	DMS-REQ-0104 OSS-REQ-0149 OSS-REQ-0162	LVV-T1240
LVV-3400 - DMS-REQ-0358-V-01: Min number of simultaneous DM EFD query users	OSS-REQ-0181	LVV-T1250
LVV-9788 - DMS-REQ-0358-V-02: Max time to retrieve DM EFD query results	OSS-REQ-0181	LVV-T1251
LVV-9748 - DMS-REQ-0343-V-02: Number of simultaneous users	OSS-REQ-0193 OSS-REQ-0184	LVV-T1252
LVV-9637 - DMS-REQ-0372-V-01: Archiving Camera Test Data		LVV-T1264
LVV-9740 - DMS-REQ-0004-V-02: Latency of reporting optical transients	DMS-REQ-0003 OSS-REQ-0127 OSS-REQ-0046	LVV-T1276
LVV-9745 - DMS-REQ-0131-V-02: Max number of calibs to be processed	OSS-REQ-0021 OSS-REQ-0194 DMS-REQ-0130	LVV-T1277
LVV-9797 - DMS-REQ-0377-V-02: Max time to retrieve single-CCD coadd cutout image	OSS-REQ-0181	LVV-T1332



Verification Elements	High Level Require- ments	Test Cases
-----------------------	------------------------------	------------

Draft