

Large Synoptic Survey Telescope (LSST) Data Management

LSST Data Management Acceptance Test Specification

L.P. Guy, W.M. Wood-Vasey, E. Bellm, J.F. Bosch, J.L. Carlin, G.P. Dubois-Felsmann, M.L. Graham, R. Gruendl, K.S. Krughoff, K.-T. Lim, R.H. Lupton, C. Slater, G. Comoretto

LDM-639

Latest Revision: 2020-02-17

Draft Revision NOT YET Approved – This LSST document has been approved as a Content-Controlled Document by the LSST DM Change Control Board. If this document is changed or superseded, the new document will retain the Handle designation shown above. The control is on the most recent digital document with this Handle in the LSST digital archive and not printed versions. Additional information may be found in the corresponding DM RFC. – Draft Revision NOT YET Approved



LDM-639

Abstract

This document describes the detailed acceptance test specification for the LSST Data Management System.





Change Record

Version	Date	Description	Owner name
1.0	2019-02-07	Document first approved release. Approved	L. Guy
		on RFC-495.	
2.0	2019-07-29	Add test cases for all Priority 1a requirements.	Document: J. Carlin;
		Approved in RFC-622.	Approver:
			W. O'Mullane
2.1	2020-02-17	Consolidated test cases for DMTR-201 test ac-	J. Carlin
		tivity. Approved in RFC-669.	

Document curator: Leanne Guy Document source location: https://github.com/lsst/ldm-639 from Jira Version from source repository: cc5686b



Contents

1	Intro	duction	1
	1.1	Objectives	1
	1.2	Scope	1
	1.3	Applicable Documents	2
	1.4	References	2
	1.5	Acronyms	3
2	Appro	bach	4
	2.1	Features to be tested	4
	2.2	Features not to be tested	5
	2.3	Pass/fail criteria	5
	2.4	Suspension criteria and resumption requirements	5
	2.5	Naming convention	5
3	Test (Cases Summary	7
4	Activ	e Test Cases	15
4	Activ 4.1	e Test Cases LVV-T23 - Verify implementation of Storing Approximations of Per-pixel Metadata	15 15
4	Activ 4.1 4.2	e Test Cases LVV-T23 - Verify implementation of Storing Approximations of Per-pixel Metadata LVV-T24 - Verify implementation of Computing Derived Quantities	15 15 18
4	Active 4.1 4.2 4.3	e Test Cases LVV-T23 - Verify implementation of Storing Approximations of Per-pixel Metadata LVV-T24 - Verify implementation of Computing Derived Quantities LVV-T25 - Verify implementation of Denormalizing Database Tables	15 15 18 20
4	Active 4.1 4.2 4.3 4.4	e Test Cases LVV-T23 - Verify implementation of Storing Approximations of Per-pixel Metadata LVV-T24 - Verify implementation of Computing Derived Quantities LVV-T25 - Verify implementation of Denormalizing Database Tables LVV-T26 - Verify implementation of Maximum Likelihood Values and Covariances	15 15 18 20 21
4	Active 4.1 4.2 4.3 4.4 4.5	e Test Cases LVV-T23 - Verify implementation of Storing Approximations of Per-pixel Metadata LVV-T24 - Verify implementation of Computing Derived Quantities LVV-T25 - Verify implementation of Denormalizing Database Tables LVV-T26 - Verify implementation of Maximum Likelihood Values and Covariances LVV-T27 - Verify implementation of Data Availability	15 15 18 20 21 24
4	Active 4.1 4.2 4.3 4.4 4.5 4.6	e Test Cases LVV-T23 - Verify implementation of Storing Approximations of Per-pixel Metadata LVV-T24 - Verify implementation of Computing Derived Quantities LVV-T25 - Verify implementation of Denormalizing Database Tables LVV-T26 - Verify implementation of Maximum Likelihood Values and Covariances LVV-T27 - Verify implementation of Data Availability LVV-T28 - Verify implementation of Measurements in catalogs	15 15 20 21 24 25
4	Active 4.1 4.2 4.3 4.4 4.5 4.6 4.7	e Test Cases LVV-T23 - Verify implementation of Storing Approximations of Per-pixel Metadata LVV-T24 - Verify implementation of Computing Derived Quantities LVV-T25 - Verify implementation of Denormalizing Database Tables LVV-T26 - Verify implementation of Maximum Likelihood Values and Covariances LVV-T27 - Verify implementation of Data Availability LVV-T28 - Verify implementation of Measurements in catalogs LVV-T29 - Verify implementation of Raw Science Image Data Acquisition	 15 18 20 21 24 25 26
4	Active 4.1 4.2 4.3 4.4 4.5 4.6 4.7 4.8	e Test Cases LVV-T23 - Verify implementation of Storing Approximations of Per-pixel Metadata LVV-T24 - Verify implementation of Computing Derived Quantities LVV-T25 - Verify implementation of Denormalizing Database Tables LVV-T26 - Verify implementation of Maximum Likelihood Values and Covariances LVV-T27 - Verify implementation of Data Availability LVV-T28 - Verify implementation of Measurements in catalogs LVV-T29 - Verify implementation of Raw Science Image Data Acquisition	 15 18 20 21 24 25 26 28
4	Active 4.1 4.2 4.3 4.4 4.5 4.6 4.7 4.8 4.9	e Test Cases LVV-T23 - Verify implementation of Storing Approximations of Per-pixel Metadata LVV-T24 - Verify implementation of Computing Derived Quantities LVV-T25 - Verify implementation of Denormalizing Database Tables LVV-T26 - Verify implementation of Maximum Likelihood Values and Covariances LVV-T27 - Verify implementation of Data Availability LVV-T28 - Verify implementation of Measurements in catalogs LVV-T29 - Verify implementation of Raw Science Image Data Acquisition LVV-T30 - Verify implementation of Crosstalk Corrected Science Image Data Ac-	 15 18 20 21 24 25 26 28
4	Active 4.1 4.2 4.3 4.4 4.5 4.6 4.7 4.8 4.9	e Test CasesLVV-T23 - Verify implementation of Storing Approximations of Per-pixel MetadataLVV-T24 - Verify implementation of Computing Derived QuantitiesLVV-T25 - Verify implementation of Denormalizing Database TablesLVV-T26 - Verify implementation of Maximum Likelihood Values and CovariancesLVV-T27 - Verify implementation of Data AvailabilityLVV-T28 - Verify implementation of Measurements in catalogsLVV-T29 - Verify implementation of Raw Science Image Data AcquisitionLVV-T30 - Verify implementation of Crosstalk Corrected Science Image Data Acquisition	 15 18 20 21 24 25 26 28 29
4	Active 4.1 4.2 4.3 4.4 4.5 4.6 4.7 4.8 4.9 4.10	e Test CasesLVV-T23 - Verify implementation of Storing Approximations of Per-pixel MetadataLVV-T24 - Verify implementation of Computing Derived QuantitiesLVV-T25 - Verify implementation of Denormalizing Database TablesLVV-T26 - Verify implementation of Maximum Likelihood Values and CovariancesLVV-T27 - Verify implementation of Data AvailabilityLVV-T28 - Verify implementation of Measurements in catalogsLVV-T29 - Verify implementation of Raw Science Image Data AcquisitionLVV-T30 - Verify implementation of Crosstalk Corrected Science Image Data Ac-quisitionLVV-T32 - Verify implementation of Raw Image Assembly	 15 18 20 21 24 25 26 28 29 30
4	Active 4.1 4.2 4.3 4.4 4.5 4.6 4.7 4.8 4.9 4.10 4.11	e Test CasesLVV-T23 - Verify implementation of Storing Approximations of Per-pixel MetadataLVV-T24 - Verify implementation of Computing Derived QuantitiesLVV-T25 - Verify implementation of Denormalizing Database TablesLVV-T26 - Verify implementation of Maximum Likelihood Values and CovariancesLVV-T27 - Verify implementation of Data AvailabilityLVV-T28 - Verify implementation of Measurements in catalogsLVV-T29 - Verify implementation of Raw Science Image Data AcquisitionLVV-T30 - Verify implementation of Crosstalk Corrected Science Image Data Ac-quisitionLVV-T32 - Verify implementation of Raw Image AssemblyLVV-T33 - Verify implementation of Raw Science Image Metadata	 15 18 20 21 24 25 26 28 29 30 32



4.13	LVV-T35 - Verify implementation of Nightly Data Accessible Within 24 hrs \ldots	35
4.14	LVV-T36 - Verify implementation of Difference Exposures	38
4.15	LVV-T37 - Verify implementation of Difference Exposure Attributes	40
4.16	LVV-T38 - Verify implementation of Processed Visit Images	42
4.17	LVV-T39 - Verify implementation of Generate Photometric Zeropoint for Visit	
	Image	43
4.18	LVV-T40 - Verify implementation of Generate WCS for Visit Images	45
4.19	LVV-T41 - Verify implementation of Generate PSF for Visit Images	47
4.20	LVV-T42 - Verify implementation of Processed Visit Image Content	48
4.21	LVV-T43 - Verify implementation of Background Model Calculation	50
4.22	LVV-T44 - Verify implementation of Documenting Image Characterization	52
4.23	LVV-T45 - Verify implementation of Prompt Processing Data Quality Report Def-	
	inition	53
4.24	LVV-T46 - Verify implementation of Prompt Processing Performance Report	
	Definition	55
4.25	LVV-T47 - Verify implementation of Prompt Processing Calibration Report Def-	
	inition	56
4.26	LVV-T48 - Verify implementation of Exposure Catalog	58
4.27	LVV-T49 - Verify implementation of DIASource Catalog	59
4.28	LVV-T50 - Verify implementation of Faint DIASource Measurements	61
4.29	LVV-T51 - Verify implementation of DIAObject Catalog	64
4.30	LVV-T52 - Verify implementation of DIAObject Attributes	65
4.31	LVV-T53 - Verify implementation of SSObject Catalog	67
4.32	LVV-T54 - Verify implementation of Alert Content	69
4.33	LVV-T55 - Verify implementation of DIAForcedSource Catalog	70
4.34	LVV-T56 - Verify implementation of Characterizing Variability	72
4.35	LVV-T57 - Verify implementation of Calculating SSObject Parameters	73
4.36	LVV-T58 - Verify implementation of Matching DIASources to Objects	75
4.37	LVV-T59 - Verify implementation of Regenerating L1 Data Products During Data	
	Release Processing	77



4.38	LVV-T60 - Verify implementation of Publishing predicted visit schedule	78
4.39	LVV-T61 - Verify implementation of Associate Sources to Objects	79
4.40	LVV-T62 - Verify implementation of Provide PSF for Coadded Images	81
4.41	LVV-T63 - Verify implementation of Produce Images for EPO	82
4.42	LVV-T64 - Verify implementation of Coadded Image Provenance	85
4.43	LVV-T65 - Verify implementation of Source Catalog	87
4.44	LVV-T66 - Verify implementation of Forced-Source Catalog	88
4.45	LVV-T67 - Verify implementation of Object Catalog	90
4.46	LVV-T68 - Verify implementation of Provide Photometric Redshifts of Galaxies	93
4.47	LVV-T69 - Verify implementation of Object Characterization	94
4.48	LVV-T71 - Verify implementation of Detecting extended low surface brightness	
	objects	96
4.49	LVV-T72 - Verify implementation of Coadd Image Method Constraints	97
4.50	LVV-T73 - Verify implementation of Deep Detection Coadds	99
4.51	LVV-T74 - Verify implementation of Template Coadds	100
4.52	LVV-T75 - Verify implementation of Multi-band Coadds	102
4.53	LVV-T76 - Verify implementation of All-Sky Visualization of Data Releases	103
4.54	LVV-T77 - Verify implementation of Best Seeing Coadds	105
4.55	LVV-T78 - Verify implementation of Persisting Data Products	107
4.56	LVV-T79 - Verify implementation of PSF-Matched Coadds	108
4.57	LVV-T80 - Verify implementation of Detecting faint variable objects	109
4.58	LVV-T81 - Verify implementation of Targeted Coadds	112
4.59	LVV-T82 - Verify implementation of Tracking Characterization Changes Between	
	Data Releases	113
4.60	LVV-T83 - Verify implementation of Bad Pixel Map	115
4.61	LVV-T84 - Verify implementation of Bias Residual Image	116
4.62	LVV-T85 - Verify implementation of Crosstalk Correction Matrix	119
4.63	LVV-T86 - Verify implementation of Illumination Correction Frame	120
4.64	LVV-T87 - Verify implementation of Monochromatic Flatfield Data Cube \ldots	122
4.65	LVV-T88 - Verify implementation of Calibration Data Products	123



LVV-T89 - Verify implementation of Calibration Image Provenance	125
LVV-T90 - Verify implementation of Dark Current Correction Frame	126
LVV-T91 - Verify implementation of Fringe Correction Frame	128
LVV-T92 - Verify implementation of Processing of Data From Special Programs	129
LVV-T93 - Verify implementation of Level 1 Processing of Special Programs Data	a 131
LVV-T94 - Verify implementation of Special Programs Database	132
LVV-T95 - Verify implementation of Constraints on Level 1 Special Program	
Products Generation	134
LVV-T96 - Verify implementation of Query Repeatability	136
LVV-T97 - Verify implementation of Uniqueness of IDs Across Data Releases .	137
LVV-T98 - Verify implementation of Selection of Datasets	139
LVV-T99 - Verify implementation of Processing of Datasets	141
LVV-T100 - Verify implementation of Transparent Data Access	142
LVV-T101 - Verify implementation of Transient Alert Distribution	143
LVV-T102 - Verify implementation of Solar System Objects Available Within Spec-	
ified Time	145
LVV-T103 - Verify implementation of Generate Data Quality Report Within Spec-	
ified Time	146
LVV-T104 - Verify implementation of Generate DMS Performance Report Within	
Specified Time	147
LVV-T105 - Verify implementation of Generate Calibration Report Within Spec-	
ified Time	149
LVV-T106 - Verify implementation of Calibration Images Available Within Spec-	
ified Time	150
LVV-T107 - Verify implementation of Level-1 Production Completeness	151
LVV-T108 - Verify implementation of Level 1 Source Association	153
LVV-T109 - Verify implementation of SSObject Precovery	154
LVV-T110 - Verify implementation of DIASource Precovery	155
LVV-T111 - Verify implementation of Use of External Orbit Catalogs	156
LVV-T112 - Verify implementation of Alert Filtering Service	157
	LW-T89 - Verify implementation of Calibration Image Provenance LW-T90 - Verify implementation of Dark Current Correction Frame LW-T91 - Verify implementation of Fringe Correction Frame LW-T92 - Verify implementation of Processing of Data From Special Programs LW-T93 - Verify implementation of Level 1 Processing of Special Programs Data LW-T94 - Verify implementation of Special Programs Database LW-T95 - Verify implementation of Constraints on Level 1 Special Program Products Generation LW-T97 - Verify implementation of Query Repeatability LW-T98 - Verify implementation of Uniqueness of IDs Across Data Releases LW-T99 - Verify implementation of Processing of Datasets LW-T99 - Verify implementation of Transparent Data Access LVV-T100 - Verify implementation of Solar System Objects Available Within Spec- ified Time LW-T103 - Verify implementation of Generate Data Quality Report Within Spec- ified Time LW-T104 - Verify implementation of Generate Calibration Report Within Spec- ified Time LW-T105 - Verify implementation of Calibration Images Available Within Spec- ified Time LW-T104 - Verify implementation of Generate Calibration Report Within Spec- ified Time LW-T105 - Verify implementation of Level 1 Production Completeness



4.90	LVV-T113 - Verify implementation of Performance Requirements for LSST Alert	
	Filtering Service	159
4.91	LVV-T114 - Verify implementation of Pre-defined alert filters	160
4.92	LVV-T115 - Verify implementation of Calibration Production Processing	161
4.93	LVV-T116 - Verify implementation of Associating Objects across data releases	163
4.94	LVV-T117 - Verify implementation of DAC resource allocation for Level 3 pro-	
	cessing	164
4.95	LVV-T118 - Verify implementation of Level 3 Data Product Self Consistency	166
4.96	LVV-T119 - Verify implementation of Provenance for Level 3 processing at DACs	167
4.97	LVV-T120 - Verify implementation of Software framework for Level 3 catalog	
	processing	168
4.98	LVV-T121 - Verify implementation of Software framework for Level 3 image pro-	
	cessing	169
4.99	LVV-T122 - Verify implementation of Level 3 Data Import	171
4.100	LVV-T123 - Verify implementation of Access Controls of Level 3 Data Products	172
4.101	LVV-T124 - Verify implementation of Software Architecture to Enable Commu-	
	nity Re-Use	173
4.102	LVV-T125 - Verify implementation of Simulated Data	176
4.103	LVV-T126 - Verify implementation Image Differencing	177
4.104	LVV-T127 - Verify implementation of Provide Source Detection Software	179
4.105	LVV-T128 - Verify implementation Provide Astrometric Model	180
4.106	LVV-T129 - Verify implementation of Provide Calibrated Photometry \ldots .	181
4.107	LVV-T130 - Verify implementation of Enable a Range of Shape Measurement	
	Approaches	183
4.108	LVV-T131 - Verify implementation of Provide User Interface Services	184
4.109	LVV-T132 - Verify implementation of Pre-cursor and Real Data	190
4.110	LVV-T133 - Verify implementation of Provide Beam Projector Coordinate Cal-	
	culation Software	191
4.111	LVV-T134 - Verify implementation of Provide Image Access Services	192
4.112	LVV-T136 - Verify implementation of Data Product and Raw Data Access	194



4.113	LVV-T137 - Verify implementation of Data Product Ingest	195
4.114	LVV-T138 - Verify implementation of Bulk Download Service	196
4.115	LVV-T140 - Verify implementation of Production Orchestration	198
4.116	LVV-T141 - Verify implementation of Production Monitoring	199
4.117	LVV-T142 - Verify implementation of Production Fault Tolerance	201
4.118	LVV-T144 - Verify implementation of Task Specification	202
4.119	LVV-T145 - Verify implementation of Task Configuration	203
4.120	LVV-T146 - Verify implementation of DMS Initialization Component	205
4.121	LVV-T147 - Verify implementation of Control of Level-1 Production	206
4.122	LVV-T148 - Verify implementation of Unique Processing Coverage	207
4.123	LVV-T149 - Verify implementation of Catalog Queries	208
4.124	LVV-T150 - Verify implementation of Maintain Archive Publicly Accessible	209
4.125	LVV-T151 - Verify Implementation of Catalog Export Formats From the Note-	
	book Aspect	211
4.126	LVV-T152 - Verify implementation of Keep Historical Alert Archive	214
4.127	LVV-T153 - Verify implementation of Provide Engineering and Facility Database	
4.127	LVV-T153 - Verify implementation of Provide Engineering and Facility DatabaseArchive	215
4.127 4.128	LVV-T153 - Verify implementation of Provide Engineering and Facility DatabaseArchiveLVV-T154 - Verify implementation of Raw Data Archiving Reliability	215 216
4.127 4.128 4.129	LVV-T153 - Verify implementation of Provide Engineering and Facility DatabaseArchiveLVV-T154 - Verify implementation of Raw Data Archiving ReliabilityLVV-T155 - Verify implementation of Un-Archived Data Product Cache	215 216 217
4.127 4.128 4.129 4.130	LVV-T153 - Verify implementation of Provide Engineering and Facility DatabaseArchiveLVV-T154 - Verify implementation of Raw Data Archiving ReliabilityLVV-T155 - Verify implementation of Un-Archived Data Product CacheLVV-T156 - Verify implementation of Regenerate Un-archived Data Products	215 216 217 219
4.127 4.128 4.129 4.130 4.131	LVV-T153 - Verify implementation of Provide Engineering and Facility DatabaseArchiveLVV-T154 - Verify implementation of Raw Data Archiving ReliabilityLVV-T155 - Verify implementation of Un-Archived Data Product CacheLVV-T156 - Verify implementation of Regenerate Un-archived Data ProductsLVV-T157 - Verify implementation Level 1 Data Product Access	215 216 217 219 220
4.127 4.128 4.129 4.130 4.131 4.132	LVV-T153 - Verify implementation of Provide Engineering and Facility DatabaseArchiveLVV-T154 - Verify implementation of Raw Data Archiving ReliabilityLVV-T155 - Verify implementation of Un-Archived Data Product CacheLVV-T156 - Verify implementation of Regenerate Un-archived Data ProductsLVV-T157 - Verify implementation Level 1 Data Product AccessLVV-T158 - Verify implementation Level 1 and 2 Catalog Access	215 216 217 219 220 221
4.127 4.128 4.129 4.130 4.131 4.132 4.133	LVV-T153 - Verify implementation of Provide Engineering and Facility DatabaseArchiveLVV-T154 - Verify implementation of Raw Data Archiving ReliabilityLVV-T155 - Verify implementation of Un-Archived Data Product CacheLVV-T156 - Verify implementation of Regenerate Un-archived Data ProductsLVV-T157 - Verify implementation Level 1 Data Product AccessLVV-T158 - Verify implementation Level 1 and 2 Catalog AccessLVV-T159 - Verify implementation of Regenerating Data Products from Previous	215 216 217 219 220 221
4.127 4.128 4.129 4.130 4.131 4.132 4.133	LVV-T153 - Verify implementation of Provide Engineering and Facility DatabaseArchiveLVV-T154 - Verify implementation of Raw Data Archiving ReliabilityLVV-T155 - Verify implementation of Un-Archived Data Product CacheLVV-T156 - Verify implementation of Regenerate Un-archived Data ProductsLVV-T157 - Verify implementation Level 1 Data Product AccessLVV-T158 - Verify implementation of Regenerating Data Products from PreviousData Releases	215 216 217 219 220 221 222
 4.127 4.128 4.129 4.130 4.131 4.132 4.133 4.134 	LVV-T153 - Verify implementation of Provide Engineering and Facility DatabaseArchiveLVV-T154 - Verify implementation of Raw Data Archiving ReliabilityLVV-T155 - Verify implementation of Un-Archived Data Product CacheLVV-T156 - Verify implementation of Regenerate Un-archived Data ProductsLVV-T157 - Verify implementation Level 1 Data Product AccessLVV-T158 - Verify implementation of Regenerating Data Products from PreviousData ReleasesLVV-T160 - Verify implementation of Providing a Precovery Service	 215 216 217 219 220 221 222 223
 4.127 4.128 4.129 4.130 4.131 4.132 4.133 4.134 4.135 	LVV-T153 - Verify implementation of Provide Engineering and Facility DatabaseArchiveLVV-T154 - Verify implementation of Raw Data Archiving ReliabilityLVV-T155 - Verify implementation of Un-Archived Data Product CacheLVV-T156 - Verify implementation of Regenerate Un-archived Data ProductsLVV-T157 - Verify implementation Level 1 Data Product AccessLVV-T158 - Verify implementation Cevel 1 and 2 Catalog AccessLVV-T159 - Verify implementation of Regenerating Data Products from PreviousData ReleasesLVV-T160 - Verify implementation of Providing a Precovery ServiceLVV-T161 - Verify implementation of Logging of catalog queries	 215 216 217 219 220 221 222 223 225
4.127 4.128 4.129 4.130 4.131 4.132 4.133 4.134 4.135 4.136	LVV-T153 - Verify implementation of Provide Engineering and Facility DatabaseArchiveLVV-T154 - Verify implementation of Raw Data Archiving ReliabilityLVV-T155 - Verify implementation of Un-Archived Data Product CacheLVV-T156 - Verify implementation of Regenerate Un-archived Data ProductsLVV-T157 - Verify implementation Level 1 Data Product AccessLVV-T158 - Verify implementation Cevel 1 and 2 Catalog AccessLVV-T159 - Verify implementation of Regenerating Data Products from PreviousData ReleasesLVV-T160 - Verify implementation of Providing a Precovery ServiceLVV-T161 - Verify implementation of Logging of catalog queriesLVV-T162 - Verify implementation of Access to Previous Data Releases	 215 216 217 219 220 221 222 223 225 226
4.127 4.128 4.129 4.130 4.131 4.132 4.133 4.134 4.135 4.136 4.137	LVV-T153 - Verify implementation of Provide Engineering and Facility DatabaseArchiveLVV-T154 - Verify implementation of Raw Data Archiving ReliabilityLVV-T155 - Verify implementation of Un-Archived Data Product CacheLVV-T156 - Verify implementation of Regenerate Un-archived Data ProductsLVV-T157 - Verify implementation Level 1 Data Product AccessLVV-T158 - Verify implementation Level 1 and 2 Catalog AccessLVV-T159 - Verify implementation of Regenerating Data Products from PreviousData ReleasesLVV-T160 - Verify implementation of Providing a Precovery ServiceLVV-T161 - Verify implementation of Logging of catalog queriesLVV-T162 - Verify implementation of Access to Previous Data ReleasesLVV-T163 - Verify implementation of Data Access Services	 215 216 217 219 220 221 222 223 225 226 228
4.127 4.128 4.129 4.130 4.131 4.132 4.133 4.134 4.135 4.136 4.137 4.138	LVV-T153 - Verify implementation of Provide Engineering and Facility DatabaseArchiveLVV-T154 - Verify implementation of Raw Data Archiving ReliabilityLVV-T155 - Verify implementation of Un-Archived Data Product CacheLVV-T156 - Verify implementation of Regenerate Un-archived Data ProductsLVV-T157 - Verify implementation Level 1 Data Product AccessLVV-T158 - Verify implementation Level 1 and 2 Catalog AccessLVV-T159 - Verify implementation of Regenerating Data Products from PreviousData ReleasesLVV-T160 - Verify implementation of Providing a Precovery ServiceLVV-T161 - Verify implementation of Logging of catalog queriesLVV-T162 - Verify implementation of Data Access ServicesLVV-T163 - Verify implementation of Data Access Services	 215 216 217 219 220 221 222 223 225 226 228 229



LVV-T166 - Verify implementation of Access Services Performance	231
LVV-T167 - Verify Capability to serve older Data Releases at Full Performance .	233
LVV-T168 - Verify design of Data Access Services allows Evolution of the LSST	
Data Model	234
LVV-T169 - Verify implementation of Older Release Behavior	235
LVV-T170 - Verify implementation of Query Availability	236
LVV-T171 - Verify implementation of Pipeline Availability	237
LVV-T172 - Verify implementation of Optimization of Cost, Reliability and Avail-	
ability	239
LVV-T173 - Verify implementation of Pipeline Throughput	240
LVV-T174 - Verify implementation of Re-processing Capacity	241
LVV-T175 - Verify implementation of Temporary Storage for Communications	
Links	242
LVV-T176 - Verify implementation of Infrastructure Sizing for "catching up"	243
LVV-T177 - Verify implementation of Incorporate Fault-Tolerance	244
LVV-T178 - Verify implementation of Incorporate Autonomics	246
LVV-T179 - Verify implementation of Compute Platform Heterogeneity	247
LVV-T180 - Verify implementation of Data Management Unscheduled Downtime	e248
LVV-T182 - Verify implementation of Prefer Computing and Storage Down	249
LVV-T183 - Verify implementation of DMS Communication with OCS	250
LVV-T185 - Verify implementation of Summit to Base Network Availability \ldots	252
LVV-T186 - Verify implementation of Summit to Base Network Reliability	253
LVV-T187 - Verify implementation of Summit to Base Network Secondary Link	255
LVV-T188 - Verify implementation of Summit to Base Network Ownership and	
Operation	256
LVV-T189 - Verify implementation of Base Facility Infrastructure	257
LVV-T190 - Verify implementation of Base Facility Co-Location with Existing Facility	y259
LVV-T191 - Verify implementation of Commissioning Cluster	260
LVV-T192 - Verify implementation of Base Wireless LAN (WiFi)	261
LVV-T193 - Verify implementation of Base to Archive Network	262
	LWV-T166 - Verify implementation of Access Services Performance LVV-T167 - Verify Capability to serve older Data Releases at Full Performance . LVV-T168 - Verify design of Data Access Services allows Evolution of the LSST Data Model LVV-T169 - Verify implementation of Older Release Behavior . LVV-T170 - Verify implementation of Query Availability LVV-T171 - Verify implementation of Optimization of Cost, Reliability and Availability ability LVV-T173 - Verify implementation of Pipeline Throughput LVV-T173 - Verify implementation of Re-processing Capacity LVV-T175 - Verify implementation of Infrastructure Sizing for "catching up" LVV-T176 - Verify implementation of Incorporate Fault-Tolerance LVV-T177 - Verify implementation of Compute Platform Heterogeneity LVV-T178 - Verify implementation of Data Management Unscheduled Downtime LVV-T180 - Verify implementation of Summit to Base Network Availability LVV-T185 - Verify implementation of Summit to Base Network Availability LVV-T186 - Verify implementation of Summit to Base Network Neuralbility LVV-T188 - Verify implementation of Summit to Base Network Neuralbility LVV-T188 - Verify implementation of Summit to Base Network Neuralbility LVV-T189 - Verify implementation of Summit to Base Network Neuralbility LVV-T189 - Verify implementation of Summit to Base Network Neura



4.166	LVV-T194 - Verify implementation of Base to Archive Network Availability	264
4.167	LVV-T195 - Verify implementation of Base to Archive Network Reliability \ldots	265
4.168	LVV-T196 - Verify implementation of Base to Archive Network Secondary Link	267
4.169	LVV-T197 - Verify implementation of Archive Center	268
4.170	LVV-T198 - Verify implementation of Archive Center Disaster Recovery	269
4.171	LVV-T199 - Verify implementation of Archive Center Co-Location with Existing	
	Facility	270
4.172	LVV-T200 - Verify implementation of Archive to Data Access Center Network .	272
4.173	LVV-T201 - Verify implementation of Archive to Data Access Center Network	
	Availability	273
4.174	LVV-T202 - Verify implementation of Archive to Data Access Center Network	
	Reliability	274
4.175	LVV-T203 - Verify implementation of Archive to Data Access Center Network	
	Secondary Link	276
4.176	LVV-T204 - Verify implementation of Access to catalogs for external Level 3 pro-	
	cessing	277
4.177	LVV-T205 - Verify implementation of Access to input catalogs for DAC-based	
	Level 3 processing	279
4.178	LVV-T206 - Verify implementation of Federation with external catalogs	280
4.179	LVV-T207 - Verify implementation of Access to images for external Level 3 pro-	
	cessing	281
4.180	LVV-T208 - Verify implementation of Access to input images for DAC-based	
	Level 3 processing	282
4.181		
	LVV-T209 - Verify implementation of Data Access Centers	283
4.182	LVV-T209 - Verify implementation of Data Access Centers	283
4.182	LVV-T209 - Verify implementation of Data Access CentersLVV-T210 - Verify implementation of Data Access Center Simultaneous Connectionstions	283 284
4.182 4.183	LVV-T209 - Verify implementation of Data Access CentersLVV-T210 - Verify implementation of Data Access Center Simultaneous ConnectionsLVV-T211 - Verify implementation of Data Access Center Geographical Distri-	283 284
4.182 4.183	LVV-T209 - Verify implementation of Data Access CentersLVV-T210 - Verify implementation of Data Access Center Simultaneous ConnectionstionsLVV-T211 - Verify implementation of Data Access Center Geographical Distribution	283 284 286
4.1824.1834.184	LVV-T209 - Verify implementation of Data Access CentersLVV-T210 - Verify implementation of Data Access Center Simultaneous ConnectionstionsLVV-T211 - Verify implementation of Data Access Center Geographical DistributionLVV-T212 - Verify implementation of No Limit on Data Access Centers	283 284 286 287
4.1824.1834.1844.185	LVV-T209 - Verify implementation of Data Access CentersLVV-T210 - Verify implementation of Data Access Center Simultaneous ConnectionstionsLVV-T211 - Verify implementation of Data Access Center Geographical DistributionLVV-T212 - Verify implementation of No Limit on Data Access CentersLVV-T376 - Verify the Calculation of Ellipticity Residuals and Correlations	283 284 286 287 288



4.186	LVV-T377 - Verify Calculation of Photometric Performance Metrics	290
4.187	LVV-T378 - Verify Calculation of Astrometric Performance Metrics	292
4.188	LVV-T385 - Verify implementation of minimum number of simultaneous re-	
	trievals of CCD-sized coadd cutouts	294
4.189	LVV-T1097 - Verify Summit to Base Network Implementation	296
4.190	LVV-T1168 - Verify Summit - Base Network Integration	297
4.191	LVV-T1232 - Verify Implementation of Catalog Export Formats From the Portal	
	Aspect	299
4.192	LVV-T1240 - Verify implementation of minimum astrometric standards per CCD	302
4.193	LVV-T1250 - Verify implementation of minimum number of simultaneous DM	
	EFD query users	303
4.194	LVV-T1251 - Verify implementation of maximum time to retrieve DM EFD query	
	results	305
4.195	LVV-T1252 - Verify number of simultaneous alert filter users	306
4.196	LVV-T1264 - Verify implementation of archiving camera test data	308
4.197	LVV-T1276 - Verify implementation of latency of reporting optical transients .	309
4.198	LVV-T1277 - Verify processing of maximum number of calibration exposures .	311
4.199	LVV-T1332 - Verify implementation of maximum time for retrieval of CCD-sized	
	coadd cutouts	313
4.200	coadd cutouts	313 314
4.200 4.201	coadd cutouts	313 314
4.200 4.201	coadd cutouts	313 314 315
4.200 4.201 4.202	coadd cutouts	313314315316
4.2004.2014.2024.203	coadd cutouts	313314315316318
4.200 4.201 4.202 4.203 4.204	coadd cutouts	 313 314 315 316 318 319
4.200 4.201 4.202 4.203 4.204 4.205	coadd cutouts	 313 314 315 316 318 319 320
4.200 4.201 4.202 4.203 4.204 4.205 4.206	coadd cutouts	 313 314 315 316 318 319 320 321
4.200 4.201 4.202 4.203 4.204 4.205 4.206 4.207	coadd cutouts	 313 314 315 316 318 319 320 321 322
4.200 4.201 4.202 4.203 4.204 4.205 4.206 4.207 4.208	coadd cutouts	 313 314 315 316 318 319 320 321 322 323



5

4.210	LVV-T1563 - Verify re-run on different system produces the same results	326
4.211	LVV-T1564 - Verify re-run on similar system produces the same results	327
4.212	LVV-T1745 - Verify calculation of median relative astrometric measurement er-	
	ror on 20 arcminute scales	328
4.213	LVV-T1746 - Verify calculation of fraction of relative astrometric measurement	
	error on 5 arcminute scales exceeding outlier limit	330
4.214	LVV-T1747 - Verify calculation of relative astrometric measurement error on 5	
	arcminute scales	332
4.215	LVV-T1748 - Verify calculation of median error in absolute position for RA, Dec	
	axes	334
4.216	LVV-T1749 - Verify calculation of fraction of relative astrometric measurement	
	error on 20 arcminute scales exceeding outlier limit	336
4.217	LVV-T1750 - Verify calculation of separations relative to r-band exceeding color	
	difference outlier limit	338
4.218	LVV-T1751 - Verify calculation of median relative astrometric measurement er-	
	ror on 200 arcminute scales	340
4.219	LVV-T1752 - Verify calculation of fraction of relative astrometric measurement	
	error on 200 arcminute scales exceeding outlier limit	342
4.220	LVV-T1753 - Verify calculation of RMS difference of separations relative to r-ban	d344
4.221	LVV-T1754 - Verify calculation of residual PSF ellipticity correlations for separa-	
	tions less than 5 arcmin	346
4.222	LVV-T1755 - Verify calculation of residual PSF ellipticity correlations for separa-	
	tions less than 1 arcmin	347
4.223	LVV-T1756 - Verify calculation of photometric repeatability in uzy filters	349
4.224	LVV-T1757 - Verify calculation of photometric repeatability in gri filters	351
4.225	LVV-T1758 - Verify calculation of photometric outliers in uzy bands	352
4.226	LVV-T1759 - Verify calculation of photometric outliers in gri bands	354
Reusa	able Test Cases	357
5.1	LVV-T837 - Authenticate to Notebook Aspect	357
5.2	LVV-T838 - Access an empty notebook in the Notebook Aspect	358



5.3	LVV-T849 - Authenticate to the portal aspect of the LSP	359	
5.4	LVV-T850 - Log out of the portal aspect of the LSP	359	
5.5	LVV-T860 - Initialize science pipelines	360	
5.6	LVV-T866 - Run Alert Production Payload	361	
5.7	LVV-T901 - Run MOPS payload	362	
5.8	LVV-T987 - Instantiate the Butler for reading data	363	
5.9	LVV-T1059 - Run Daily Calibration Products Update Payload	364	
5.10	LVV-T1060 - Run Periodic Calibration Products Production Payload	365	
5.11	LVV-T1064 - Run Data Release Production Payload	365	
5.12	LVV-T1207 - Execute a simple ADQL query using the TAP service in the notebook		
	aspect	366	
5.13	LVV-T1208 - Log out of the notebook aspect of the LSP	367	
5.14	LVV-T1744 - Run validate_drp on precursor data	368	
Deprecated Test Cases			

A Traceability

6



LSST Data Management Acceptance Test Specification

Test Spec for LSST Data Management

1 Introduction

This document is intended to specify the acceptance test procedures for the LSST Data Management System. It is a work in progress; the current version provides Test Cases covering $\sim 35\%$ of the requirements. It does not yet provide full Test Plans for comprehensive testing nor identify the fraction of each requirement covered by the existing Test Cases.

This document will be updated as work continues on completing Test Cases, Test Plans, and requirements coverage.

1.1 Objectives

This document describes the test cases required to validate the Data Management System requirements described in the LSST DM Subsystem Requirements document LSE-61. It identifies test cases and procedures for the tests as well as the pass/fail criteria for each test.

A full description of the LSST Data Management System is provided in the Data Management System Design document, LDM-148 with the science requirements detailed in the LSST Science Requirements Document LPM-17.

1.2 Scope

This document provides the acceptance test plan for the whole Data Management System (DMS), as described by the Data Management System Requirements in LSE-61.



1.3 Applicable Documents

- LPM-17 LSST Science Requirements Document
- LDM-148 LSST Data Management System Design
- LDM-294 LSST DM Organization & Management
- LDM-503 LSST DM Test Plan
- LSE-61 LSST DM Subsystem Requirements
- LSE-163 LSST Data Products Definition Document
- LDM-151 LSST DM Science Pipelines Design
- LSE-180 Level 2 Photometric Calibration for the LSST Survey
- LSE-30 LSST Observatory System Specifications

1.4 References

- [1] **[LSE-30]**, Claver, C.F., The LSST Systems Engineering Integrated Project Team, 2018, *Observatory System Specifications (OSS)*, LSE-30, URL https://ls.st/LSE-30
- [2] **[LSE-61]**, Dubois-Felsmann, G., Jenness, T., 2018, *LSST Data Management Subsystem Re-quirements*, LSE-61, URL https://ls.st/LSE-61
- [3] **[LDM-554]**, Dubois-Felsmann, G., Ciardi, D., Mueller, F., Economou, F., 2018, *Science Plat-form Requirements*, LDM-554, URL https://ls.st/LDM-554
- [4] [LPM-17], Ivezić, Ž., The LSST Science Collaboration, 2018, LSST Science Requirements Document, LPM-17, URL https://ls.st/LPM-17
- [5] **[LSE-131]**, Jacoby, S., Emmons, B., Selvy, B., 2017, *Interface between Data Management and Education and Public Outreach*, LSE-131, URL https://ls.st/LSE-131
- [6] **[LSE-180]**, Jones, L., 2013, *Level 2 Photometric Calibration for the LSST Survey*, LSE-180, URL https://ls.st/LSE-180
- [7] **[LSE-163]**, Jurić, M., et al., 2017, *LSST Data Products Definition Document*, LSE-163, URL https://ls.st/LSE-163
- [8] [LDM-142], Kantor, J., 2017, Network Sizing Model, LDM-142, URL https://ls.st/LDM-142



- [10] [LDM-294], O'Mullane, W., Swinbank, J., Jurić, M., DMLT, 2018, Data Management Organization and Management, LDM-294, URL https://ls.st/LDM-294
- [11] [LDM-503], O'Mullane, W., Swinbank, J., Jurić, M., Economou, F., 2018, Data Management Test Plan, LDM-503, URL https://ls.st/LDM-503
- [12] [LDM-151], Swinbank, J.D., et al., 2017, Data Management Science Pipelines Design, LDM-151, URL https://ls.st/LDM-151

1.5 Acronyms

Acronym	Description			
AP	Alerts Production			
С	Specific programming language (also called ANSI-C)			
CPP	C++ Programming language			
DAC	Data Access Center			
DB	DataBase			
DBB	Data BackBone			
DM	Data Management			
DMCCB	DM Change Control Board			
DMS	Data Management Sub-system			
DR	Data Release			
DRP	Data Release Production			
EFD	Engineering Facilities Database			
IT	Integration Test			
IVOA	International Virtual-Observatory Alliance			
К	Kelvin; SI unit of temperature			
LAN	Local Area Network			
LDM	LSST Data Management (handle for controlled documents)			
LPM	LSST Project Management (Document Handle)			
LSE	LSST Systems Engineering (Document Handle)			
LSP	LSST Science Platform			
LSST	Large Synoptic Survey Telescope			

Latest Revision 2020-02-17



М	Mega; SI units prefix for 1E6			
MOPS	Moving Object Pipeline System			
OCS	Observatory Control System			
PDAC	Prototype Data Access Center			
S	Strip (CCD chip along-scan coordinate identifier in focal plane)			
SODA	SCOS ORATOS Distributed Access			
SQL	Structured Query Language			
STS	System Test Specification			
W	Watt; SI unit of power			
р	pico; SI units prefix for 1E-12			

Test Spec for LSST Data Management

2 Approach

This document describes the acceptance tests for the integrated Data Management System, with a focus on whether the data products and functionality provided satisfy the requirements described in LSE-61.

The requirements from LSE-61 are extracted into the Jira "LSST Verification and Validation" Project, managed through the Jira Test Management Plugin system. Each LSE-61 requirement leads to a "LSST Verification and Validation" (LVV) Element. Each LVV Element comprises one or more more Test Cases. Each Test Case describes a Test Script to be executed, the coverage, pre-conditions, configuration, test results, and other details as specified by LDM-503. Test Scripts may have common set up and analysis steps. The Jira system allows for these steps to be shared by other Test Scripts. This improves clarity and consistency across all Test Cases.

In this document, each Test Case is listed here with the LVV Element it tests, a summary of the Test Items exercised by the Test Case, and the detailed steps to be executed by the Test Case. Shared steps between Test Scripts have been explicitly written out to appear fully in each Test Case.

2.1 Features to be tested

All top-level requirements for the LSST Data Management System described in LSE-61 are to be tested, including



- Data Products
- Alert, Calibration and Data Release Production
- LSST science pipeline software and middleware
- LSST facilities including the data archive, base, summit, and the communications between them to accept science and engineering data

2.2 Features not to be tested

This document does not describe facilities for periodically generating or collecting key performance metrics (KPMs), except insofar as those KPMs are incidentally measured as part of executing the documented test cases.

2.3 Pass/fail criteria

The results of all tests will be assessed using the criteria described in LDM-503 §4.

Note that when executing pipelines, tasks, or individual algorithms, any unexplained or unexpected errors or warnings appearing in the associated log or on screen output must be described in the documentation for the system under test. Any warning or error for which this is not the case must be filed as a software problem report and filed with the DMCCB.

2.4 Suspension criteria and resumption requirements

Refer to individual test cases where applicable.

2.5 Naming convention

LVV : Is the label for the "LSST Verification and Validation" project in Jira.

- **LVV-XXX** : Are Verification Elements, where XXX is the Verification Element identifier. Each Verification Element has at least one Test Case.
- **LVV-TYYY** : Are Test Cases. Each Test Case is associated with a Verification Element, where YYY is the Test Case identifier.



LDM-639

Latest Revision 2020-02-17

The Verification Elements are drawn from LSE-61 requirements which have names of the form DMS-REQ-ZZZZ.



Latest Revision 2020-02-17



3 Test Cases Summary

Test Id	Test Name			
LVV-T23	Verify implementation of Storing Approximations of Per-pixel Metadata			
LVV-T24	Verify implementation of Computing Derived Quantities			
LVV-T25	Verify implementation of Denormalizing Database Tables			
LVV-T26	Verify implementation of Maximum Likelihood Values and Covariances			
LVV-T27	Verify implementation of Data Availability			
LVV-T28	Verify implementation of Measurements in catalogs			
LVV-T29	Verify implementation of Raw Science Image Data Acquisition			
LVV-T30	Verify implementation of Wavefront Sensor Data Acquisition			
LVV-T31	Verify implementation of Crosstalk Corrected Science Image Data Acqui-			
	sition			
LVV-T32	Verify implementation of Raw Image Assembly			
LVV-T33	Verify implementation of Raw Science Image Metadata			
LVV-T34	Verify implementation of Guider Calibration Data Acquisition			
LVV-T35	Verify implementation of Nightly Data Accessible Within 24 hrs			
LVV-T36	Verify implementation of Difference Exposures			
LVV-T37	Verify implementation of Difference Exposure Attributes			
LVV-T38	Verify implementation of Processed Visit Images			
LVV-T39	Verify implementation of Generate Photometric Zeropoint for Visit Image			
LVV-T40	Verify implementation of Generate WCS for Visit Images			
LVV-T41	Verify implementation of Generate PSF for Visit Images			
LVV-T42	Verify implementation of Processed Visit Image Content			
LVV-T43	Verify implementation of Background Model Calculation			
LVV-T44	Verify implementation of Documenting Image Characterization			
LVV-T45	-T45 Verify implementation of Prompt Processing Data Quality Report Def			
	tion			
LVV-T46	Verify implementation of Prompt Processing Performance Report Defini-			
	tion			
LVV-T47	Verify implementation of Prompt Processing Calibration Report Definition			
LVV-T48	Verify implementation of Exposure Catalog			
LVV-T49	Verify implementation of DIASource Catalog			
LVV-T50	Verify implementation of Faint DIASource Measurements			
LVV-T51	Verify implementation of DIAObject Catalog			
LVV-T52	Verify implementation of DIAObject Attributes			



LDM-639

Latest Revision 2020-02-17

Test ld	Test Name			
LVV-T53	Verify implementation of SSObject Catalog			
LVV-T54	Verify implementation of Alert Content			
LVV-T55	Verify implementation of DIAForcedSource Catalog			
LVV-T56	Verify implementation of Characterizing Variability			
LVV-T57	Verify implementation of Calculating SSObject Parameters			
LVV-T58	Verify implementation of Matching DIASources to Objects			
LVV-T59	Verify implementation of Regenerating L1 Data Products During Data Re-			
	lease Processing			
LVV-T60	Verify implementation of Publishing predicted visit schedule			
LVV-T61	Verify implementation of Associate Sources to Objects			
LVV-T62	Verify implementation of Provide PSF for Coadded Images			
LVV-T63	Verify implementation of Produce Images for EPO			
LVV-T64	Verify implementation of Coadded Image Provenance			
LVV-T65	Verify implementation of Source Catalog			
LVV-T66	Verify implementation of Forced-Source Catalog			
LVV-T67	Verify implementation of Object Catalog			
LVV-T68	Verify implementation of Provide Photometric Redshifts of Galaxies			
LVV-T69	Verify implementation of Object Characterization			
LVV-T71	Verify implementation of Detecting extended low surface brightness ob-			
	jects			
LVV-T72	Verify implementation of Coadd Image Method Constraints			
LVV-T73	Verify implementation of Deep Detection Coadds			
LVV-T74	Verify implementation of Template Coadds			
LVV-T75	Verify implementation of Multi-band Coadds			
LVV-T76	Verify implementation of All-Sky Visualization of Data Releases			
LVV-T77	Verify implementation of Best Seeing Coadds			
LVV-T78	Verify implementation of Persisting Data Products			
LVV-T79	Verify implementation of PSF-Matched Coadds			
LVV-T80	Verify implementation of Detecting faint variable objects			
LVV-T81	Verify implementation of Targeted Coadds			
LVV-T82	Verify implementation of Tracking Characterization Changes Between			
	Data Releases			
LVV-T83	Verify implementation of Bad Pixel Map			
LVV-T84	Verify implementation of Bias Residual Image			



Test ld	Test Name			
LVV-T85	Verify implementation of Crosstalk Correction Matrix			
LVV-T86	Verify implementation of Illumination Correction Frame			
LVV-T87	Verify implementation of Monochromatic Flatfield Data Cube			
LVV-T88	Verify implementation of Calibration Data Products			
LVV-T89	Verify implementation of Calibration Image Provenance			
LVV-T90	Verify implementation of Dark Current Correction Frame			
LVV-T91	Verify implementation of Fringe Correction Frame			
LVV-T92	Verify implementation of Processing of Data From Special Programs			
LVV-T93	Verify implementation of Level 1 Processing of Special Programs Data			
LVV-T94	Verify implementation of Special Programs Database			
LVV-T95	Verify implementation of Constraints on Level 1 Special Program Products Generation			
LVV-T96	Verify implementation of Query Repeatability			
LVV-T97	Verify implementation of Uniqueness of IDs Across Data Releases			
LVV-T98	Verify implementation of Selection of Datasets			
LVV-T99	Verify implementation of Processing of Datasets			
LVV-T100	Verify implementation of Transparent Data Access			
LVV-T101	Verify implementation of Transient Alert Distribution			
LVV-T102	Verify implementation of Solar System Objects Available Within Specified			
	Time			
LVV-T103	Verify implementation of Generate Data Quality Report Within Specified Time			
LVV-T104	Verify implementation of Generate DMS Performance Report Within Spec- ified Time			
LVV-T105	Verify implementation of Generate Calibration Report Within Specified Time			
LVV-T106	Verify implementation of Calibration Images Available Within Specified Time			
LVV-T107	Verify implementation of Level-1 Production Completeness			
LVV-T108	Verify implementation of Level 1 Source Association			
LVV-T109	Verify implementation of SSObject Precovery			
LVV-T110	Verify implementation of DIASource Precovery			
LVV-T111	Verify implementation of Use of External Orbit Catalogs			
LVV-T112	Verify implementation of Alert Filtering Service			



Test ld	Test Name			
LVV-T113	Verify implementation of Performance Requirements for LSST Alert Filter- ing Service			
LVV-T114	Verify implementation of Pre-defined alert filters			
LVV-T115	Verify implementation of Calibration Production Processing			
LVV-T116	Verify implementation of Associating Objects across data releases			
LVV-T117	Verify implementation of DAC resource allocation for Level 3 processing			
LVV-T118	Verify implementation of Level 3 Data Product Self Consistency			
LVV-T119	Verify implementation of Provenance for Level 3 processing at DACs			
LVV-T120	Verify implementation of Software framework for Level 3 catalog process- ing			
LVV-T121	Verify implementation of Software framework for Level 3 image process- ing			
LVV-T122	Verify implementation of Level 3 Data Import			
LVV-T123	Verify implementation of Access Controls of Level 3 Data Products			
LVV-T124	Verify implementation of Software Architecture to Enable Community Re- Use			
LVV-T125	Verify implementation of Simulated Data			
LVV-T126	Verify implementation Image Differencing			
LVV-T127	Verify implementation of Provide Source Detection Software			
LVV-T128	Verify implementation Provide Astrometric Model			
LVV-T129	Verify implementation of Provide Calibrated Photometry			
LVV-T130	Verify implementation of Enable a Range of Shape Measurement Approaches			
LVV-T131	Verify implementation of Provide User Interface Services			
LVV-T132	Verify implementation of Pre-cursor and Real Data			
LVV-T133	Verify implementation of Provide Beam Projector Coordinate Calculation Software			
LVV-T134	Verify implementation of Provide Image Access Services			
LVV-T136	Verify implementation of Data Product and Raw Data Access			
LVV-T137	Verify implementation of Data Product Ingest			
LVV-T138	Verify implementation of Bulk Download Service			
LVV-T140	Verify implementation of Production Orchestration			
LVV-T141	Verify implementation of Production Monitoring			
LVV-T142	Verify implementation of Production Fault Tolerance			



Test ld	Test Name				
LVV-T144	Verify implementation of Task Specification				
LVV-T145	Verify implementation of Task Configuration				
LVV-T146	Verify implementation of DMS Initialization Component				
LVV-T147	Verify implementation of Control of Level-1 Production				
LVV-T148	Verify implementation of Unique Processing Coverage				
LVV-T149	Verify implementation of Catalog Queries				
LVV-T150	Verify implementation of Maintain Archive Publicly Accessible				
LVV-T151	Verify Implementation of Catalog Export Formats From the Notebook Aspect				
LVV-T152	Verify implementation of Keep Historical Alert Archive				
LVV-T153	Verify implementation of Provide Engineering and Facility Database Archive				
LVV-T154	Verify implementation of Raw Data Archiving Reliability				
LVV-T155	Verify implementation of Un-Archived Data Product Cache				
LVV-T156	Verify implementation of Regenerate Un-archived Data Products				
LVV-T157	Verify implementation Level 1 Data Product Access				
LVV-T158	Verify implementation Level 1 and 2 Catalog Access				
LVV-T159	Verify implementation of Regenerating Data Products from Previous Data				
	Releases				
	Verify implementation of Providing a Precovery Service				
	Verify implementation of Logging of catalog queries				
LVV-1162	Verify Implementation of Access to Previous Data Releases				
LVV-1163	Verify Implementation of Data Access Services				
LVV-1164	Verify implementation of Operations Subsets				
LVV-1165	Verify implementation of Subsets Support				
	Verify Implementation of Access Services Performance				
LVV-1167	Verify Capability to serve older Data Releases at Full Performance				
LVV-1168	Model				
LVV-T169	Verify implementation of Older Release Behavior				
LVV-T170	Verify implementation of Query Availability				
LVV-T171	Verify implementation of Pipeline Availability				
LVV-T172	Verify implementation of Optimization of Cost, Reliability and Availability				
LVV-T173	Verify implementation of Pipeline Throughput				



Test ld	Test Name			
LVV-T174	Verify implementation of Re-processing Capacity			
LVV-T175	Verify implementation of Temporary Storage for Communications Links			
LVV-T176	Verify implementation of Infrastructure Sizing for "catching up"			
LVV-T177	Verify implementation of Incorporate Fault-Tolerance			
LVV-T178	Verify implementation of Incorporate Autonomics			
LVV-T179	Verify implementation of Compute Platform Heterogeneity			
LVV-T180	Verify implementation of Data Management Unscheduled Downtime			
LVV-T182	Verify implementation of Prefer Computing and Storage Down			
LVV-T183	Verify implementation of DMS Communication with OCS			
LVV-T185	Verify implementation of Summit to Base Network Availability			
LVV-T186	Verify implementation of Summit to Base Network Reliability			
LVV-T187	Verify implementation of Summit to Base Network Secondary Link			
LVV-T188	Verify implementation of Summit to Base Network Ownership and Oper-			
	ation			
LVV-T189	Verify implementation of Base Facility Infrastructure			
LVV-T190	Verify implementation of Base Facility Co-Location with Existing Facility			
LVV-T191	Verify implementation of Commissioning Cluster			
LVV-T192	Verify implementation of Base Wireless LAN (WiFi)			
LVV-T193	Verify implementation of Base to Archive Network			
LVV-T194	Verify implementation of Base to Archive Network Availability			
LVV-T195	Verify implementation of Base to Archive Network Reliability			
LVV-T196	Verify implementation of Base to Archive Network Secondary Link			
LVV-T197	Verify implementation of Archive Center			
LVV-T198	Verify implementation of Archive Center Disaster Recovery			
LVV-T199	Verify implementation of Archive Center Co-Location with Existing Facility			
LVV-T200	Verify implementation of Archive to Data Access Center Network			
LVV-T201	Verify implementation of Archive to Data Access Center Network Availabil			
	ity			
LVV-T202	Verify implementation of Archive to Data Access Center Network Reliabil-			
	ity			
LVV-T203	Verify implementation of Archive to Data Access Center Network Sec-			
	ondary Link			
LVV-T204	Verify implementation of Access to catalogs for external Level 3 process-			
	ing			



-

Test Id	Test Name			
LVV-T205	Verify implementation of Access to input catalogs for DAC-based Level 3			
	processing			
LVV-T206	Verify implementation of Federation with external catalogs			
LVV-T207	Verify implementation of Access to images for external Level 3 processing			
LVV-T208	Verify implementation of Access to input images for DAC-based Level 3 processing			
LVV-T209	Verify implementation of Data Access Centers			
LVV-T210	Verify implementation of Data Access Center Simultaneous Connections			
LVV-T211	Verify implementation of Data Access Center Geographical Distribution			
LVV-T212	Verify implementation of No Limit on Data Access Centers			
LVV-T376	Verify the Calculation of Ellipticity Residuals and Correlations			
LVV-T377	Verify Calculation of Photometric Performance Metrics			
LVV-T378	Verify Calculation of Astrometric Performance Metrics			
LVV-T385	Verify implementation of minimum number of simultaneous retrievals of			
	CCD-sized coadd cutouts			
LVV-T1097	Verify Summit to Base Network Implementation			
LVV-T1168	Verify Summit - Base Network Integration			
LVV-T1232	Verify Implementation of Catalog Export Formats From the Portal Aspect			
LVV-T1240	Verify implementation of minimum astrometric standards per CCD			
LVV-T1250	Verify implementation of minimum number of simultaneous DM EFD			
	query users			
LVV-T1251	Verify implementation of maximum time to retrieve DM EFD query results			
LVV-T1252	Verify number of simultaneous alert filter users			
LVV-T1264	Verify implementation of archiving camera test data			
LVV-T1276	Verify implementation of latency of reporting optical transients			
LVV-T1277	Verify processing of maximum number of calibration exposures			
LVV-T1332	Verify implementation of maximum time for retrieval of CCD-sized coadd cutouts			
LVV-T1524	Verify Implementation of Exporting MOCs as FITS			
LVV-T1525	Verify Implementation of Linkage Between HiPS Maps and Coadded Im-			
	ages			
LVV-T1526	Verify Availability of Secure and Authenticated HiPS Service			
LVV-T1527	Verify Support for HiPS Visualization			
LVV-T1528	Verify Visualization of MOCs via Science Platform			



Test ld	Test Name		
LVV-T1529	Verify Production of All-Sky HiPS Map		
LVV-T1530	Verify Production of Multi-Order Coverage Maps for Survey Data		
LVV-T1560	Verify archiving of processing provenance		
LVV-T1561	Verify provenance availability to science users		
LVV-T1562	Verify availability of re-run tools		
LVV-T1563	Verify re-run on different system produces the same results		
LVV-T1564	Verify re-run on similar system produces the same results		
LVV-T1745	Verify calculation of median relative astrometric measurement error on		
	20 arcminute scales		
LVV-T1746	Verify calculation of fraction of relative astrometric measurement error		
	on 5 arcminute scales exceeding outlier limit		
LVV-T1747 Verify calculation of relative astrometric measurement error on 5			
	cminute scales		
LVV-T1748	Verify calculation of median error in absolute position for RA, Dec axes		
LVV-T1749	Verify calculation of fraction of relative astrometric measurement error		
	on 20 arcminute scales exceeding outlier limit		
LVV-T1750	Verify calculation of separations relative to r-band exceeding color differ-		
	ence outlier limit		
LVV-T1751	Verify calculation of median relative astrometric measurement error on		
	200 arcminute scales		
LVV-T1752	Verify calculation of fraction of relative astrometric measurement error		
	on 200 arcminute scales exceeding outlier limit		
LVV-T1753	Verify calculation of RMS difference of separations relative to r-band		
LVV-T1754	/V-T1754 Verify calculation of residual PSF ellipticity correlations for separation		
	less than 5 arcmin		
LVV-T1755	Verify calculation of residual PSF ellipticity correlations for separations		
	less than 1 arcmin		
LVV-T1756	Verify calculation of photometric repeatability in uzy filters		
LVV-T1757	Verify calculation of photometric repeatability in gri filters		
LVV-T1758	Verify calculation of photometric outliers in uzy bands		
LVV-T1759	Verify calculation of photometric outliers in gri bands		



LDM-639

4 Active Test Cases

This section documents all active test cases that have a status in the Jira/ATM system of Draft, Defined or Approved.

4.1 LVV-T23 - Verify implementation of Storing Approximations of Per-pixel Metadata

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Simon Krughoff
Open LVV-T23 in Jira				

4.1.1 Verification Elements

• LVV-157 - DMS-REQ-0326-V-01: Storing Approximations of Per-pixel Metadata

4.1.2 Test Items

Test Items

Show that the compressed form depth and mask maps adequately represents the exact version of the same information.

4.1.3 Predecessors

- 4.1.4 Environment Needs
- 4.1.4.1 Software

4.1.4.2 Hardware



4.1.5 Input Specification

Test data: A data repository containing a full DRP data reduction of the HSC PDR dataset.

4.1.6 Output Specification

4.1.7 Test Procedure

Step	Description, l	nput Data and Expected Result
1-1 from LVV-T860	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:
		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash
		From the command line, execute the commands below in the example code:
	Test Data	
	Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.
		To check versions in use, type: _eups list -s
2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.
3	Description	For each of the expected data products types (listed in Test Items section 004.3.2) and each of the expected units (PVIs, coadds, etc), retrieve the data product from the Butler and verify that it is non-empty.
	Test Data	No data.



Step

4

5

9

Description, Input Data and Expected Result					
Expected					
Result					
Description	Create the coadd pixel level depth map for the HSC PDR dataset.				
Test Data	No data.				
Expected					
Result					
Description	Generate compressed representation of the pixel level depth map.				
Test Data	No data.				
Expected					
Result					

Test Spec for LSST Data Management

LDM-639

Latest Revision 2020-02-17

	Description	Create the coadd pixel level mask map for the HSC PDR dataset.
6	Test Data	No data.
	Expected	
	Result	
	Description	Generate compressed representation of the mask map.
7	Test Data	No data.
	Expected	
	Result	
	Description	Sample randomly from both the pixel level and compressed depth maps. Compare the
8		distribution of depths sampled from the pixel level depth map to that sampled from the
		compressed representation.
	Test Data	No data.
	Expected	
	Result	
	Description	Divide the mask planes into two groups: INFO and BAD. BAD flags are any that would

cause a particular pixel to be excluded from processing: e.g. EDGE, SAT, BAD. Sample masks from both the pixel level mask map and the compressed mask map.

For each sample, compute sum(mask_pixel xor mask_compressed). Produce the distribution of the number of bits that differ between the samples.

Repeat for both the INFO flags and the BAD flags.

Test Data No data.



Step Description, Input Data and Expected Result Expected

Result

4.2 LVV-T24 - Verify implementation of Computing Derived Quantities

Version	Status	Priority	Verification Type	Owner			
1	Draft	Normal	Test	Melissa Graham			
Open I VV-T24 in lira							

4.2.1 Verification Elements

• LVV-162 - DMS-REQ-0331-V-01: Computing Derived Quantities

4.2.2 Test Items

To confirm that common derived quantities (apparent magnitude, FWHM in arcsec, ellipticity) are available to an end-user by, e.g., ensuring a color-color diagram is easy to construction, fitting functions to derived data, or generating other common scientific derivatives.

4.2.3 Predecessors

4.2.4 Environment Needs

4.2.4.1 Software

4.2.4.2 Hardware



LDM-639

4.2.5 Input Specification

Example data set (e.g., non-LSST or LSST commissioning) loaded into the Science Platform in a format consistent with the DPDD.

4.2.6 Output Specification

4.2.7 Test Procedure

Step	Description, I	nput Data and Expected Result
1-1 from LVV-T860	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:
		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash
		From the command line, execute the commands below in the example code:
	Test Data Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.
		To check versions in use, type: _eups list -s
2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- _lowing:
LVV-T987	Expected Result	Butler repo available for reading.
3	Description	For each of the expected data product types (listed in Test Items section 004.3.2) and each of the expected units (PVIs, coadds, etc), retrieve the data product from the Butler and verify it to be non-empty.

DRAFT NOT YET APPROVED – The contents of this document are subject to configuration control by the LSST DM Change Control Board. – DRAFT NOT YET APPROVED



Test	Spec	for	LSST	Data	Management
	opee			Duru	in an agoin one

Step	Description, Input Data and Expected Result			
	Expected Result			
	Description	Load into DPDD+Science Platform		
4	Test Data	No data.		
	Expected			
	Result			
	Description	Constructing color-color diagram and fitting stellar locus in Science Platform.		
5	Test Data	No data.		
	Expected			
	Result			
6	Description	Invite three members of commissioning team to create color-color diagram from coadd catalogs based on merged coadd reference catalog.		
	Test Data	No data.		
	Expected			
	Result			

4.3 LVV-T25 - Verify implementation of Denormalizing Database Tables

Version	Status	Priority	Verification Type	Owner		
1	Draft	Normal	Test	Colin Slater		
Open LVV-T25 in lira						

4.3.1 Verification Elements

• LVV-163 - DMS-REQ-0332-V-01: Denormalizing Database Tables

4.3.2 Test Items

Verify that commonly useful views of data are easy to obtain through the Science Platform.



4.3.3 Predecessors

4.3.4 Environment Needs

4.3.4.1 Software

4.3.4.2 Hardware

4.3.5 Input Specification

4.3.6 Output Specification

4.3.7 Test Procedure

Step	Description, Input Data and Expected Result				
	Description	Connect to the Science Platform's portal query interface.			
1	Test Data	No data.			
	Expected				
	Result				
	Description	List the available views in the database.			
2	Test Data	No data.			
	Expected				
	Result				
3	Description	Take 20 sampled queries and determine which are easily done on views and which require complicated joins. Discuss the complicated ones and determine if any could be simplified by adding additional views.			
	Test Data	No data.			
	Expected				
	Result				

4.4 LVV-T26 - Verify implementation of Maximum Likelihood Values and Covariances



Version	Status	Priority	Verification Type	Owner		
1	Draft	Normal	Test	Jim Bosch		
Open LVV-T26 in Jira						

4.4.1 Verification Elements

• LVV-164 - DMS-REQ-0333-V-01: Maximum Likelihood Values and Covariances

4.4.2 Test Items

- Check that all measurements in source and object schemas include columns containing uncertainties, including covariances between jointly-measured quantities.
- Check that all model-fit measurements in source and object schemas include columns that report goodness-of-fit.
- Check that most sources and objects with successful measurements report finite uncertainty values for those measurements.
- Check that most sources and objects with successful model-fit measurements report finite goodness-of-fit values.

4.4.3 Predecessors

4.4.4 Environment Needs

- 4.4.4.1 Software
- 4.4.4.2 Hardware

4.4.5 Input Specification

4.4.6 Output Specification


4.4.7 Test Procedure

Step	Description, Input Data and Expected Result			
1-1 from LVV-T860	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:		
		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash 		
		From the command line, execute the commands below in the example code:		
	Test Data	Science nineline software is available for use. If additional nackages are needed (for example 'obs'		
	Result	packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.		
		To check versions in use, type: _eups list -s		
2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol-		
LVV-T987	Test Data			
	Expected	Butler repo available for reading.		
	Result			
3	Description	For each of the expected data product types (listed in Test Items section 004.3.2) and each of the expected units (PVIs, coadds, etc), retrieve the data product from the Butler and verify it to be non-empty.		
	Test Data	No data.		
	Expected			
	Result			
4	Description	Verify that maximum likelihood and covariant quantities are provided. Test and manually inspect that they are reasonable (finite, appropriately normed).		
	Test Data	No data.		
	Expected			
	Result			
	Result			



4.5 LVV-T27 - Verify implementation of Data Availability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Gregory Dubois-Felsmann
Open LVV-T27 in Jira				

4.5.1 Verification Elements

• LVV-177 - DMS-REQ-0346-V-01: Data Availability

4.5.2 Test Items

Determine if all required categories of raw data (specifically enumerated: raw exposures, calibration frames, telemetry, configuration metadata) can be located through the Science Platform and are available for download. Verify through (1) administrative review; (2) checking with precursor data; (3) checking on early data feeds from the Summit such as from AuxTel and ComCam.

4.5.3 Predecessors

4.5.4 Environment Needs

4.5.4.1 Software

4.5.4.2 Hardware

- 4.5.5 Input Specification
- 4.5.6 Output Specification

4.5.7 Test Procedure



Step	Description, Input Data and Expected Result		
1	Description	Invite two reviewers to review that plan that seems reasonable to expect the archiving and provision of raw data	
	Test Data	No data.	
	Expected		
	Result		
2	Description	Pass a set of HSC data through (equal in size to the first public data release) the data backbone through ingest and provide interface	
-	Test Data	No data.	
	Expected		
	Result		
2	Description	Track the ingestion of AuxTel data during one month in 2018-2019 and verify delivery and test download.	
5	Test Data	No data.	
	Expected		
	Result		

4.6 LVV-T28 - Verify implementation of Measurements in catalogs

Version	Status	Priority	Verification Type	Owner	
1	Approved	Normal	Test	Colin Slater	
Open LVV-T28 in Jira					

4.6.1 Verification Elements

• LVV-178 - DMS-REQ-0347-V-01: Measurements in catalogs

4.6.2 Test Items

Verify that source measurements in catalogs are in flux units.

4.6.3 Predecessors



4.6.4 Environment Needs

- 4.6.4.1 Software
- 4.6.4.2 Hardware

4.6.5 Input Specification

4.6.6 Output Specification

4.6.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.
	Result	

2	Description	Identify and read appropriate processed precursor datasets with the Butler, including one containing single-visit images, one with coadds, and one with difference imaging.
-	Test Data	No data.
	Expected	
	Result	
3	Description	Verify that each of the single-visit, coadd, and difference image catalogs provide measure- ments in flux units.
	Test Data	No data.
	Expected	Confirmation of measurements in catalogs encoded in flux units.
	Result	

4.7 LVV-T29 - Verify implementation of Raw Science Image Data Acquisition

Version Status Priority Verification Type Owner



1 Defined Normal Test Kian-Tat Lim

Open LVV-T29 in Jira

4.7.1 Verification Elements

• LVV-8 - DMS-REQ-0018-V-01: Raw Science Image Data Acquisition

4.7.2 Test Items

Verify acquisition of raw data from L1 Test Stand DAQ while simulating all modes

4.7.3 Predecessors

- 4.7.4 Environment Needs
- 4.7.4.1 Software
- 4.7.4.2 Hardware

4.7.5 Input Specification

4.7.6 Output Specification

4.7.7 Test Procedure

Step Description, Input Data and Expected Result 1 Description Ingest raw data from L1 Test Stand DAQ, simulating each observing mode 1 Test Data No data. Expected Result 2 Description



Test Spec for LSST D	ata Management	LDM-639

Latest Revision 2020-02-17

Step	Description, Input Data and Expected Result				
	Test Data	Test Data No data.			
Expected Well-formed image dat		Well-formed image data with appropriate associated metadata.			
	Result				

4.8 LVV-T30 - Verify implementation of Wavefront Sensor Data Acquisition

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Kian-Tat Lim
		Open LV	/V-T30 in Jira	

4.8.1 Verification Elements

• LVV-9 - DMS-REQ-0020-V-01: Wavefront Sensor Data Acquisition

4.8.2 Test Items

Verify successful ingestion of wavefront sensor data from L1 Test Stand DAQ while simulating all modes.

4.8.3 Predecessors

4.8.4 Environment Needs

4.8.4.1 Software

4.8.4.2 Hardware

4.8.5 Input Specification



4.8.6 Output Specification

4.8.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Ingest wavefront sensor data from L1 Test Stand DAQ while simulating all modes	
1	Test Data	No data.	
	Expected		
	Result		
	Description	Observe wavefront sensor data and metadata archived in the Data Backbone.	
2	Test Data	No data.	
	Expected	Well-formed wavefront sensor image data with appropriate associated metadata.	
	Result		

4.9 LVV-T31 - Verify implementation of Crosstalk Corrected Science Image Data Acquisition

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim
Open LVV-T31 in Jira				

4.9.1 Verification Elements

• LVV-10 - DMS-REQ-0022-V-01: Crosstalk Corrected Science Image Data Acquisition

4.9.2 Test Items

Verify successful ingestion of crosstalk corrected data from L1 Test Stand DAQ while simulating all modes.

4.9.3 Predecessors



4.9.4 Environment Needs

- 4.9.4.1 Software
- 4.9.4.2 Hardware
- 4.9.5 Input Specification

4.9.6 Output Specification

4.9.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Inject signals of different relative strength	
1	Test Data	No data.	
	Expected		
	Result		
	Description	Apply Camera cross-talk correction	
2	Test Data	No data.	
	Expected		
	Result		
	Description	Verify that DMS sytem can import the cross-talk corrected images	
3	Test Data	No data.	
	Expected		
	Result		
	Description	Verify that images are corrected for crosstalk	
4	Test Data	No data.	
	Expected		
	Result		

4.10 LVV-T32 - Verify implementation of Raw Image Assembly



Version	Status	Priority	Verification Type	Owner	
1	Defined	Normal	Test	Kian-Tat Lim	
Open LVV-T32 in lira					

4.10.1 Verification Elements

• LVV-11 - DMS-REQ-0024-V-01: Raw Image Assembly

4.10.2 Test Items

Verify that the raw exposure data from all readout channels in a sensor can be assembled into a single image, and that all required/relevant metadata are associated with the image data.

4.10.3 Predecessors

4.10.4 Environment Needs

- 4.10.4.1 Software
- 4.10.4.2 Hardware
- 4.10.5 Input Specification
- 4.10.6 Output Specification
- 4.10.7 Test Procedure

|--|

Description Ingest data from the L1 Camera Test Stand DAQ.

1 Test Data No data.



T	C	c	LCCT	Data	N.4
lest	Spec	TOR	L33 I	Data	ivianagement

Latest Revision 2020-02-17

Step	Description, Input Data and Expected Result		
	Expected		
	Result		
	Description	Simulate all different modes of data gathering.	
2	Test Data	No data.	
	Expected		
	Result		
	Description	Verify that a raw image is constructed in correct format.	
3	Test Data	No data.	
	Expected	A single raw image combining data from all readout channels for a given sensor.	
	Result		
	Description	Verify that a raw image is constructed with correct metadata.	
4	Test Data	No data.	
	Expected	Image header or ancillary table contains the required metadata about the observing con-	
	Result	text in which data were gathered.	

4.11 LVV-T33 - Verify implementation of Raw Science Image Metadata

Version	Status	Priority	Verification Type	Owner		
1	Defined	Normal	Test	Kian-Tat Lim		
Open LVV-T33 in Jira						

4.11.1 Verification Elements

- LVV-28 DMS-REQ-0068-V-01: Raw Science Image Metadata
- LVV-1234 OSS-REQ-0122-V-01: Provenance

4.11.2 Test Items

Verify successful ingestion of raw data from L1 Test Stand DAQ and that image metadata is present and queryable.



LDM-639

4.11.3 Predecessors

LVV-T29, LVV-T32

4.11.4 Environment Needs

- 4.11.4.1 Software
- 4.11.4.2 Hardware
- 4.11.5 Input Specification

4.11.6 Output Specification

4.11.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Identify (or gather) a dataset of raw science images.		
1	Test Data	No data.		
	Expected			
	Result			
	Description	Verify that time of exposure start/end, site metadata, telescope metadata, and camera		
2		metadata are stored in DMS system.		

Test Data	No data.
Expected	Raw image data contain the required metadata.
Result	

4.12 LVV-T34 - Verify implementation of Guider Calibration Data Acquisition

Version Status Priority Verification Type Owner



1 Defined Normal Test Kian-Tat Lim

Open LVV-T34 in Jira

4.12.1 Verification Elements

• LVV-96 - DMS-REQ-0265-V-01: Guider Calibration Data Acquisition

4.12.2 Test Items

Verify successful

- 1. Ingestion of calibration frames from L1 Test Stand DAQ
- 2. Execution of CPP payloads
- 3. Availability of observed guider calibration products

4.12.3 Predecessors

4.12.4 Environment Needs

4.12.4.1 Software

4.12.4.2 Hardware

4.12.5 Input Specification

4.12.6 Output Specification

4.12.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Ingest calibration frames for the guider sensors from L1 Test Stand DAQ
1	Test Data	No data.



Step Description, Input Data and Expected Result

	Expected Result	
2-1 from LVV-	Description	Execute the Calibration Products Production payload. The payload uses raw calibration images and information from the Transformed EFD to generate a subset of Master Calibration Images and Cali
T1060	Test Data	
	Expected	
	Result	
2-2 from LVV- T1060	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present and well-formed.
	Test Data	
	Expected	
	Result	

	Description	Observe that guider calibration products have been produced.
3	Test Data	No data.
	Expected	Well-formed calibration frames for the guider sensors.
	Result	

4.13 LVV-T35 - Verify implementation of Nightly Data Accessible Within 24 hrs

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm
		Open LV	V-T35 in lira	

4.13.1 Verification Elements

• LVV-175 - DMS-REQ-0004-V-01: Time to L1 public release

4.13.2 Test Items

Test Items



Verify that

- 1. Alerts are available within OTT1
- 2. Level 1 Data Products are available within L1PublicT

3. Solar System Object orbits are available within L1PublicT of the updated calculations completion on the following night.

4.13.3 Predecessors

- 4.13.4 Environment Needs
- 4.13.4.1 Software
- 4.13.4.2 Hardware
- 4.13.5 Input Specification
- 4.13.6 Output Specification

4.13.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from Description The 'path' that you will use depends on where you are running the science pipelines. Options: LVV-T860

local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash

- development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash
- LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash

From the command line, execute the commands below in the example code:

Test Data



		Test Spec for LSST Data Management LDM-639 Latest Revision 2020-02-17
Step	Description, li	nput Data and Expected Result
	Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.
		To check versions in use, type: _eups list -s
2-1 from LVV-T866	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is presumed that these are automated for a given dataset.
	Expected Result	An output dataset including difference images and DIASource and DIAObject measurements.
2-2 from LVV-T866	Description Test Data Expected Result	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
3	Description	Time processing of data starting from (pre-ingested) raw files until an alert is available for distribution; verify that this time is less than OTT1.
0	Test Data	No data.
	Expected	
	Result	
4	Description	Time processing of data starting from (pre-ingested) raw files until the required data prod- ucts are available in the Science Platform. Verify that this time is less than L1PublicT.
•	Test Data	No data.
	Expected	
	Result	
5	Description	Run MOPS on 1 night equivalent of LSST observing worth of precursor data and verify that Solar System Object orbits can be updated within 24 hours.
	Test Data	No data.
	Expected	
	Result	
6	Description	Record time between completion of MOPS processing and availability of the updated SSObject catalogue through the Science Platform; verify this time is less than L1PublicT.



Test Spec for LSS	Data Management	LDM-639

Latest Revision 2020-02-17

Step	Description, Input Data and Expected Result				
	Test Data	No data.			
	Expected				
	Result				

4.14 LVV-T36 - Verify implementation of Difference Exposures

Version	Status	Priority	Verification 1	Гуре	Owner
1	Draft	Normal	Test		Eric Bellm
Open LVV-T36 in Jira					

4.14.1 Verification Elements

• LVV-7 - DMS-REQ-0010-V-01: Difference Exposures

4.14.2 Test Items

Verify successful creation of a

- 1. PSF-matched template image for a given Processed Visit Image
- 2. Difference Exposure from each Processed Visit Image

4.14.3 Predecessors

- 4.14.4 Environment Needs
- 4.14.4.1 Software

4.14.4.2 Hardware

4.14.5 Input Specification



LDM-639

4.14.6 Output Specification

4.14.7 Test Procedure

Step	Description, I	nput Data and Expected Result
1-1 from LVV-T860	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:
		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash
		From the command line, execute the commands below in the example code:
	Test Data	
	Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.
		To check versions in use, type: _eups list -s
2-1 from LVV-T866	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is presumed that these are automated for a given dataset.
	Test Data	
	Expected Result	An output dataset including difference images and DIASource and DIAObject measurements.
2-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
LVV-T866	Test Data	
	Expected	



Step	Description, Input Data and Expected Result							
3	Description	Demonstrate successful creation of a template image from HSC PDF and DECAM HiTS data. Demonstrate successful creation of a Difference Exposure for at least 10 other images from survey, ideally at a range of arimass. In particular, HiTS has 2013A u-band data. While the Blanco 4-m does have an ADC, there are still some chromatic effects and we should demonstrate that we can successfully produce Difference Exposures and templates for diferent airmass bins.						
	Test Data	No data.						
	Expected							
	Result							

Latest Revision 2020-02-17

4.15 LVV-T37 - Verify implementation of Difference Exposure Attributes

Test Spec for LSST Data Management

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Eric Bellm	
Open LVV-T37 in Jira					

4.15.1 Verification Elements

- LVV-32 DMS-REQ-0074-V-01: Difference Exposure Attributes
- LVV-1234 OSS-REQ-0122-V-01: Provenance

4.15.2 Test Items

Verify that for each Difference Exposure the DMS stores

- 1. The identify of the input exposures and related provenance information
- 2. Metadata attributes of the subtraction, including the PSF-matching kernel used.

4.15.3 Predecessors

4.15.4 Environment Needs

4.15.4.1 Software



LDM-639

4.15.4.2 Hardware

4.15.5 Input Specification

4.15.6 Output Specification

4.15.7 Test Procedure

Description, Input Data and Expected Result Step

Description The 'path' that you will use depends on where you are running the science pipelines. Options: 1-1 from

LVV-T860

- -

- -

•	local (newinstall.sh - b	based install):[path	_to_	_installation]/loa	adLSST.bash
---	--------------------------	----------------------	------	--------------------	-------------

- development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash
- LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash

From the command line, execute the commands below in the example code:

	Test Data	
	Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.
		To check versions in use, type: _eups list -s
2-1 from LVV-T866	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is presumed that these are automated for a given dataset.
	Test Data	
	Expected Result	An output dataset including difference images and DIASource and DIAObject measurements.
2-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
LVV-T866	Test Data	
	Expected	
	Result	

DRAFT NOT YET APPROVED - The contents of this document are subject to configuration control by the LSST DM Change Control Board. - DRAFT NOT YET APPROVED



_ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _

Test	Snec	for	ISST	Data	Management
	opee			Duru	management

LDM-639

Latest Revision 2020-02-17

Step	Description,	Input Data and	Expected Result

3	Description	For each of HSC PDR and DECAM HiTS data: set up three different templates and run subtractions on 10 different images from at least two different filters. Verify that we can recover the provenance information about which template was used for each subtraction, which input images were used for that template, and that we can successfull extract the PSF matching kernel.
	Test Data	No data.
	Expected	
	Result	

4.16 LVV-T38 - Verify implementation of Processed Visit Images

Version	Status	Priority	Verification Type	Owner	
1	Defined	Normal	Test	Eric Bellm	
Onen I VV-T38 in lira					

4.16.1 Verification Elements

• LVV-29 - DMS-REQ-0069-V-01: Processed Visit Images

4.16.2 Test Items

Verify that the DMS

1. Successfully produces Processed Visit Images, where the instrument signature has been removed.

2. Successfully combines images obtained during a standard visit.

4.16.3 Predecessors

4.16.4 Environment Needs

4.16.4.1 Software



LDM-639

4.16.4.2 Hardware

4.16.5 Input Specification

4.16.6 Output Specification

4.16.7 Test Procedure

Step	Description, Input Data and Expected Result				
	Description	Identify suitable precursor datasets containing unprocessed raw images.			
1	Test Data	No data.			
	Expected				
	Result				
2	Description	Run the Prompt Processing payload on these data. Verify that Processed Visit Images are generated at correct size and with significant instrumental artifacts removed.			
-	Test Data	No data.			
	Expected	Raw precursor dataset images have been processed into Processed Visit Images, with			
	Result	instrumental artifacts corrected.			
	Description	Run camera test stand data through full acquisition+backbone+ISR.			
3	Test Data	No data.			
	Expected				
	Result				
4	Description	Run simulated LSST data with calibrations through prompt processing system and inspect Processed Visit images to verify that they have been cleaned of significant artifacts and are of the correct, shape, and described orientation.			
	Test Data	No data.			
	Expected	Raw images have been processed into Processed Visit Images, with instrumental artifacts			
	Result	corrected.			

4.17 LVV-T39 - Verify implementation of Generate Photometric Zeropoint for Visit Image

Version Status Priority Verification Type Owner



Test	Spec	for	LSST	Data	Management
------	------	-----	------	------	------------

1 Draft Normal Test Jim Bosch

Open LVV-T39 in Jira

4.17.1 Verification Elements

• LVV-12 - DMS-REQ-0029-V-01: Generate Photometric Zeropoint for Visit Image

4.17.2 Test Items

Verify that Processed Visit Image data products produced by the DRP and AP pipelines include the parameters of a model that relates the observed flux on the image to physical flux units.

4.17.3 Predecessors

- 4.17.4 Environment Needs
- 4.17.4.1 Software

4.17.4.2 Hardware

- 4.17.5 Input Specification
- 4.17.6 Output Specification

4.17.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Delegate to Alert Production
1	Test Data	No data.
	Expected	
	Result	



4.18 LVV-T40 - Verify implementation of Generate WCS for Visit Images

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jim Bosch
Open LVV-T40 in Jira				

4.18.1 Verification Elements

• LVV-13 - DMS-REQ-0030-V-01: Absolute accuracy of WCS

4.18.2 Test Items

Verify that Processed Visit Images produced by the AP and DRP pipelines include FITS WCS accurate to specified **astrometricAccuracy** over the bounds of the image.

4.18.3 Predecessors

4.18.4 Environment Needs

4.18.4.1 Software

4.18.4.2 Hardware

4.18.5 Input Specification

4.18.6 Output Specification

4.18.7 Test Procedure

Step Description, Input Data and Expected Result

Description Identify an appropriate processed dataset for this test.

1 Test Data No data.



Step Description, Input Data and Expected Result

	Expected Result	A dataset with Processed Visit Images available.
2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.
	Result	
	Description	Select a single visit from the dataset, and extract its WCS object and the source list.
3	Test Data	No data.
	Expected	A table containing detected sources, and a WCS object associated with that catalog.
	Result	
Λ	Description	Confirm that each CCD within the visit image contains at least astrometricMinStan- dards astrometric standards that were used in deriving the astrometric solution.
•	Test Data	No data.
	Expected	At least astrometricMinStandards from each CCD were used in determining the WCS
	Result	solution.
5	Description	Starting from the XY pixel coordinates of the sources, apply the WCS to obtain RA, Dec coordinates.

	Test Data	No data.
	Expected	A list of RA, Dec coordinates for all sources in the catalog.
	Result	
6	Description	We will assume that Gaia provides a source of "truth." Match the source list to Gaia DR2, and calculate the positional offset between the test data and the Gaia catalog.
	Test Data	No data.
	Expected	A matched catalog of sources in common between the test source list and Gaia DR2.
	Result	
	Description	Apply appropriate cuts to extract the optimal dataset for comparison, then calculate statis-
7		tics (median, 1-sigma range, etc.; also plot a histogram) of the offsets in milliarcseconds.
		Confirm that the offset is less than astrometricAccuracy .
	Test Data	No data.



Latest Revision 2020-02-17

Step	Description, Input Data and Expected Result		
	Expected Result	Histogram and relevant statistics needed to confirm that the WCS transformation is accurate.	
8	Description	Repeat Step 5, but for subregions of the image, to confirm that the accuracy criterion is met at all positions.	
	Test Data	No data.	
	Expected	astrometricAccuracy requirement is met over the entire image.	
	Result		

4.19 LVV-T41 - Verify implementation of Generate PSF for Visit Images

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jim Bosch
Open LVV-T41 in Jira				

4.19.1 Verification Elements

• LVV-30 - DMS-REQ-0070-V-01: Generate PSF for Visit Images

4.19.2 Test Items

Verify that Processed Visit Images produced by the DRP and AP pipelines are associated with a model from which one can obtain an image of the PSF given a point on the image.

4.19.3 Predecessors

- 4.19.4 Environment Needs
- 4.19.4.1 Software

4.19.4.2 Hardware



4.19.5 Input Specification

4.19.6 Output Specification

4.19.7 Test Procedure

Step	Description, Input Data and Expected Result					
	Description	Identify a dataset with processed visit images in multiple filters.				
1	Test Data	No data.				
	Expected					
	Result					
2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- _lowing:				
LVV-T987	Test Data					
	Expected	Butler repo available for reading.				
	Result					
3	Description	Select Objects classified as point sources on at least 10 different processed visit images (including all bands). Evaluate the PSF model at the positions of these Objects, and verify that subtracting a scaled version of the PSF model from the processed visit image yields residuals consistent with pure noise.				
	Test Data	No data.				
	Expected	Images with the PSF model subtracted, leaving only residuals that are consistent with				
	Result	being noise.				

4.20 LVV-T42 - Verify implementation of Processed Visit Image Content

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Jim Bosch
Open LVV-T42 in Jira				

4.20.1 Verification Elements

• LVV-31 - DMS-REQ-0072-V-01: Processed Visit Image Content



4.20.2 Test Items

Verify that Processed Visit Images produced by the DRP and AP pipelines include the observed data, a mask array, a variance array, a PSF model, and a WCS model.

4.20.3 Predecessors

- 4.20.4 Environment Needs
- 4.20.4.1 Software
- 4.20.4.2 Hardware
- 4.20.5 Input Specification

4.20.6 Output Specification

4.20.7 Test Procedure

Step Description, Input Data and Expected Result

-

	Description	Ingest the data from an appropriate processed dataset.
2	Test Data	No data.
	Expected	
	Result	
3	Description	Select a single visit from the dataset, and extract its WCS object, calexp image, psf model, and source list.
5	Test Data	No data.



Result

Step Description, Input Data and Expected Result Expected Result **Description** Inspect the calexp image to ensure that 4 1. A well-formed image is present, 2. The variance plane is present and well-behaved, 3. Mask planes are present and contain information about defects. Test Data No data. Expected An astronomical image with mask and variance planes. This can be readily visualized using Firefly, which displays mask planes by default. Result Description Plot images of the PSF model at various points, and verify that the PSF differs with position. 5 Test Data No data. Expected A "star-like" image of the PSF evaluated at various positions. The PSF should vary slightly with position (this could be readily visualized by taking a difference of PSFs at two posi-Result tions). Description Starting from the XY pixel coordinates of the sources, apply the WCS to obtain RA, Dec coordinates. Plot these positions and confirm that they match the expected values from 6 the WCS object. Test Data No data. Expected RA, Dec coordinates that are returned should be near the central position of the visit coordinate as given in either the calexp metadata or the WCS. Result Description Repeat steps 2-6, but now with difference images created by the Alert Production pipeline (for example, in the 'ap_verify' test data processing). 7 Test Data No data. Expected

4.21 LVV-T43 - Verify implementation of Background Model Calculation

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jim Bosch
	(Open LVV-	T43 in Jira	



4.21.1 Verification Elements

• LVV-158 - DMS-REQ-0327-V-01: Background Model Calculation

4.21.2 Test Items

Verify that Processed Visit Images produced by the DRP and AP pipelines have had a model of the background subtracted, and that this model is persisted in a way that permits the background subtracted from any CCD to be retrieved along with the image for that CCD.

4.21.3 Predecessors

LVV-T15 LVV-T19

4.21.4 Environment Needs

4.21.4.1 Software

4.21.4.2 Hardware

4.21.5 Input Specification

4.21.6 Output Specification

4.21.7 Test Procedure

Step	Description, l	nput Data and Expected Result
	Description	Identify a dataset with processed visit images in multiple filters.
1	Test Data	No data.
	Expected	
	Result	
2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	AFT NOT VET APPR	OVED - The contents of this document are subject to configuration control by the



Step	Description, l	nput Data and Expected Result
	Test Data	
	Expected	Butler repo available for reading.
	Result	
3	Description	Display an image of the background model for a full CCD. Repeat this for all available filters, and confirm that the background is smoothly varying and defined over the full
	Test Data	No data.
	Expected	Well-formed background covering the entire CCD for all CCDs in all filters.
	Result	

LDM-639

Latest Revision 2020-02-17

4.22 LVV-T44 - Verify implementation of Documenting Image Characterization

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch
		Onen I V	V-T44 in lira	

4.22.1 Verification Elements

• LVV-159 - DMS-REQ-0328-V-01: Documenting Image Characterization

4.22.2 Test Items

Verify that the persisted format for Processed Visit Images and associated instrument-signatureremoval data products is documented.

4.22.3 Predecessors

4.22.4 Environment Needs

4.22.4.1 Software



LDM-639

4.22.4.2 Hardware

4.22.5 Input Specification

4.22.6 Output Specification

4.22.7 Test Procedure

Step	Description, li	nput Data and Expected Result	
	Description	Delegate to Alert Production	
1	Test Data	No data.	
	Expected		
	Result		

4.23 LVV-T45 - Verify implementation of Prompt Processing Data Quality Report Definition

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Eric Bellm
		Open LVV	/-T45 in Jira	

4.23.1 Verification Elements

• LVV-39 - DMS-REQ-0097-V-01: Level 1 Data Quality Report Definition

4.23.2 Test Items

Verify that the DMS produces a Prompt Processing Data Quality Report. Specifically check absolute value and temporal variation of

- 1. Photometric zeropoint
- 2. Sky brightness
- 3. Seeing



LDM-639

- 4. PSF
- 5. Detection efficiency

4.23.3 Predecessors

- 4.23.4 Environment Needs
- 4.23.4.1 Software
- 4.23.4.2 Hardware
- 4.23.5 Input Specification

4.23.6 Output Specification

4.23.7 Test Procedure

Step	Description, I	nput Data and Expected Result
	Description	Ingest raw data from L1 Test Stand DAQ.
1	Test Data	No data.
	Expected	
	Result	
2-1 from LVV-T866	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is presumed that these are automated for a given dataset.
	Test Data	
	Expected Result	An output dataset including difference images and DIASource and DIAObject measurements.
2-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
LVV-T866	Test Data	
	Expected	
	Result	

DRAFT NOT YET APPROVED – The contents of this document are subject to configuration control by the LSST DM Change Control Board. – DRAFT NOT YET APPROVED



Step	Description, l	nput Data and Expected Result
3	Description	Load the Prompt Processing QC reports, and observe that a dynamically updated Data Quality Report has become available at the relevant UI.
5	Test Data	No data.
	Expected	A Prompt Processing QC report is available via a UI, and contains information about the
	Result	photometric zeropoint, sky brightness, seeing, PSF, and detection efficiency, and possibly other relevant quantities.
	Description	Check that a static report is created and archived in a readily-accessible location.
4	Test Data	No data.
	Expected	Persistence of a static QC report in an accessible location, containing the same information
	Result	as in the report from Step 3.

4.24 LVV-T46 - Verify implementation of Prompt Processing Performance Report Definition

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm
		Open LV	V-T46 in Jira	

4.24.1 Verification Elements

• LVV-41 - DMS-REQ-0099-V-01: Level 1 Performance Report Definition

4.24.2 Test Items

Verify that the DMS produces a Prompt Processing Performance Report. Specifically check that the number of observations that describe each of the following:

- 1. Successfully processed, recoverable failures, unrecoverable failures.
- 2. Archived
- 3. Result in science.

This is testing more the processing rather than the observatory system.



- 4.24.3 Predecessors
- 4.24.4 Environment Needs
- 4.24.4.1 Software
- 4.24.4.2 Hardware
- 4.24.5 Input Specification
- 4.24.6 Output Specification

4.24.7 Test Procedure

Step	Description, Ir	nput Data and Expected Result
	Description	Execute single-day operations rehearsal, observe report
1	Test Data	No data.
	Expected	
	Result	

4.25 LVV-T47 - Verify implementation of Prompt Processing Calibration Report Definition

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Eric Bellm
		Open LVV	/-T47 in lira	

4.25.1 Verification Elements

• LVV-43 - DMS-REQ-0101-V-01: Level 1 Calibration Report Definition



4.25.2 Test Items

Verify that the DMS produces a Prompt Processing Calibration Report. Specifically check that this report is capable of identifying when aspects of the telescope or camera are changing with time.

4.25.3 Predecessors

- 4.25.4 Environment Needs
- 4.25.4.1 Software
- 4.25.4.2 Hardware
- 4.25.5 Input Specification
- 4.25.6 Output Specification

4.25.7 Test Procedure

|--|

1	Description	Identify precursor and simulated calibration datasets on which to run the L1 calibration pipeline.			
•	Test Data	No data.			
	Expected				
	Result				
2-1 from LVV-	Description	Execute the Daily Calibration Products Update payload. The payload uses raw calibration images and information from the Transformed EFD to generate a subset of Master Calibration Images andCalibration Database entries in the Data Backbone.			
T1059	Test Data				
	Expected				
	Result				
2-2 from	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present			
LVV- T1059	Test Data				

DRAFT NOT YET APPROVED – The contents of this document are subject to configuration control by the LSST DM Change Control Board. – DRAFT NOT YET APPROVED



Step	Description, Input Data and Expected Result				
	Expected				
	Result				
	Description	Check that a dynamic report is created that triggers alerts if calibrations go out of range.			
3	Test Data	No data.			
	Expected	A dynamic report is available via UI to users, and if any out-of-spec changes have occurred,			
	Result	alerts have been issued.			
	Description	Check that a static report is created and archived in a readily-accessible location.			
4	Test Data	No data.			
	Expected	An archived version of the calibration report is available and will be retained in a static file			
	Result	format.			

4.26 LVV-T48 - Verify implementation of Exposure Catalog

Version	Status	Priority	Verification Type	Owner			
1	Defined	Normal	Test	Jim Bosch			
Open LVV-T48 in Jira							

4.26.1 Verification Elements

• LVV-97 - DMS-REQ-0266-V-01: Exposure Catalog

4.26.2 Test Items

Verify that the DMS creates an Exposure Catalog that includes

- 1. Observation datetime, exposure time
- 2. Filter
- 3. Dome, telescope orientation and status
- 4. Calibration status
- 5. Airmass and zenith
- 6. Environmental information


7. Per-sensor information

4.26.3 Predecessors

- 4.26.4 Environment Needs
- 4.26.4.1 Software
- 4.26.4.2 Hardware
- 4.26.5 Input Specification
- 4.26.6 Output Specification

4.26.7 Test Procedure

Step Description, Input Data and Expected Result

1	Description	Verify that Exposure Catalogs contain the required elements. At present, the form of the exposure catalog is not defined. This information can be found for a given Butler repo from the metadata, but will ultimately be aggregated into a database/table summarizing available exposures.
_	Test Data	No data.
-	Expected Result	A list of the required metadata for a set of exposures is returned and both human- and machine-readable.

4.27 LVV-T49 - Verify implementation of DIASource Catalog

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm
		0.000		

Open LVV-T49 in Jira



LDM-639

4.27.1 Verification Elements

• LVV-100 - DMS-REQ-0269-V-01: DIASource Catalog

4.27.2 Test Items

Verify that the DMS produces a Source catalog from Difference Exposures with the required attributes.

4.27.3 Predecessors

- 4.27.4 Environment Needs
- 4.27.4.1 Software
- 4.27.4.2 Hardware
- 4.27.5 Input Specification
- 4.27.6 Output Specification

4.27.7 Test Procedure

Step Description, Input Data and Expected Result

Description The 'path' that you will use depends on where you are running the science pipelines. Options: 1-1 from

LVV-T860

- local (newinstall.sh based install):[path_to_installation]/loadLSST.bash
- development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash
- LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash

From the command line, execute the commands below in the example code:



Jiep		
	Test Data	
	Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.
		To check versions in use, type: _eups list -s
2-1 from LVV-T866	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is _presumed that these are automated for a given dataset.
	Test Data	
	Expected	An output dataset including difference images and DIASource and DIAObject measurements.
	Result	
2-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
LVV-T866	Test Data	
	Expected	
	Result	
3-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.
	Result	
	<u> </u>	
	Description	Verify that products are produced for DIASource catalog
4	Test Data	No data.
	Expected	
	Result	

LDM-639

Latest Revision 2020-02-17

4.28 LVV-T50 - Verify implementation of Faint DIASource Measurements

Version Status Priority Verification Type Owner



Eric Bellm 1 Draft Normal Test

Open LVV-T50 in Jira

4.28.1 Verification Elements

• LVV-101 - DMS-REQ-0270-V-01: Faint DIASource Measurements

4.28.2 Test Items

Verify that the DMS can produces DIASources measurements for sources below the nominal S/N cutoff that satisfy additional criteria.

4.28.3 Predecessors

- 4.28.4 Environment Needs
- 4.28.4.1 Software

4.28.4.2 Hardware

4.28.5 Input Specification

Input Data DECam HiTS data.

4.28.6 Output Specification

4.28.7 Test Procedure



Step Description, Input Data and Expected Result

1-1 from LVV-T860	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:
		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash
		From the command line, execute the commands below in the example code:
	Test Data	
	Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.
		To check versions in use, type: _eups list -s
2-1 from LVV-T866	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is presumed that these are automated for a given dataset.
	lest Data	
	Expected	An output dataset including difference images and DIASource and DIAObject measurements.
	Result	
2-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
LVV-T866	Test Data	
	Expected	
	Result	
3	Description	As an example of selecting with constrains, Re-run source detection as an afterburner to select isolated sources (defined as more than 2 arcseconds away from any other objects in the single-image-depth catalog) that are fainter than the fiducial transSNR cut.
	Test Data	No data.
	Expected	
	Result	



TELESCOPE

Test Spec for LSST Data Management

LDM-639

4.29 LVV-T51 - Verify implementation of DIAObject Catalog

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm
		Open LV	V-T51 in Jira	

4.29.1 Verification Elements

• LVV-102 - DMS-REQ-0271-V-01: Max nearby galaxies associated with DIASource

4.29.2 Test Items

Verify that the DIAObject includes a unique ID, identifiers for nearest stars and nearest galaxies, and probability of matching to static Object.

4.29.3 Predecessors

4.29.4 Environment Needs

- 4.29.4.1 Software
- 4.29.4.2 Hardware
- 4.29.5 Input Specification
- 4.29.6 Output Specification
- 4.29.7 Test Procedure



Latest Revision 2020-02-17

Step Description, Input Data and Expected Result

1-1 from LVV-T866	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is _presumed that these are automated for a given dataset.
	Test Data	
	Expected	An output dataset including difference images and DIASource and DIAObject measurements.
	Result	
1-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable _values for measured quantities of interest.
LVV-T866	Test Data	
	Expected	
	Result	
2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.
	Result	
3	Description	Verify that DIAObjects have diaNearbyObjMaxStar and diaNearbyObjMaxGalaxies that point to the Object catalog and are within dianNearbyObjRadius; the probability of association; and the required DIAObject properties.
	Test Data	No data.
	Expected	

4.30 LVV-T52 - Verify implementation of DIAObject Attributes

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm
		Open LV	V-T52 in Jira	



4.30.1 Verification Elements

• LVV-103 - DMS-REQ-0272-V-01: DIAObject Attributes

4.30.2 Test Items

Verify that the DMS provides summary attributes for each DIAObject, including periodicity measures.

4.30.3 Predecessors

- 4.30.4 Environment Needs
- 4.30.4.1 Software
- 4.30.4.2 Hardware
- 4.30.5 Input Specification

4.30.6 Output Specification

4.30.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration,
LVV-T866		difference imaging, DIASource detection/measurement, source association). During Operations, it is _presumed that these are automated for a given dataset.
	Test Data	
	Expected	An output dataset including difference images and DIASource and DIAObject measurements.
	Result	
1-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
LVV-T866	Test Data	



Step	Description, Input Data and Expected Result		
	Expected		
	Result		
2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:	
LVV-T987	Test Data		
	Expected	Butler repo available for reading.	
	Result		
	Description	Confirm that the DIAObjects include summary attributes as specified.	
3	Test Data	No data.	
	Expected		
	Result		

Latest Revision 2020-02-17

Test Spec for LSST Data Management

4.31 LVV-T53 - Verify implementation of SSObject Catalog

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm
		Open LV	V-T53 in Jira	

4.31.1 Verification Elements

• LVV-104 - DMS-REQ-0273-V-01: SSObject Catalog

4.31.2 Test Items

Verify that the DMS produces a catalog of Solar System Objects identify from Moving Object Processing.

Verify that the SSObject catalog includes orbital elements and additional related quanitites.

4.31.3 Predecessors



4.31.4 Environment Needs

- 4.31.4.1 Software
- 4.31.4.2 Hardware

4.31.5 Input Specification

4.31.6 Output Specification

4.31.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from LVV-T866	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is presumed that these are automated for a given dataset.
	Expected	An output dataset including difference images and DIASource and DIAObject measurements.
	Result	
1-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
LVV-T866	Test Data	
	Expected	
	Result	

2-1 from LVV-T901	Description	Perform the steps of Moving Object Pipeline (MOPS) processing on newly detected DIASources, and generate Solar System data products including Solar System objects with associated Keplerian orbits, errors, and detected DIASources. This includes running processes to link DIASource detections within a night (called tracklets), to link these tracklets across multiple nights (into tracks), to fit the tracks with an orbital model to identify those tracks that are consistent with an asteroid orbit, to match these new orbits with existing SSObjects, and to update the SSObject table.
	Test Data	
	Expected	An output dataset consisting of an updated SSObject database with SSObjects both added and
	Result	pruned as the orbital fits have been refined, and an updated DIASource database with DIASources assigned and unassigned to SSObjects.
2-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
LVV-T901	Test Data	



Step	Description, l	nput Data and Expected Result
	Expected	
	Result	
3-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.
	Result	
	Description	Inspect SSObject catalog and verify the presence of the required elements (LVV-104).
4	Test Data	No data.
	Expected	
	Result	

Latest Revision 2020-02-17

Test Spec for LSST Data Management

4.32 LVV-T54 - Verify implementation of Alert Content

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm
		Open LV	V-T54 in Jira	

4.32.1 Verification Elements

• LVV-105 - DMS-REQ-0274-V-01: Alert Content

4.32.2 Test Items

Verify that the DMS creates an Alert for each detected DIASource Verify that this Alert is broadcasted using community protocols Verify that the context of the Alert packet match requirements.

4.32.3 Predecessors



4.32.4 Environment Needs

- 4.32.4.1 Software
- 4.32.4.2 Hardware
- 4.32.5 Input Specification

4.32.6 Output Specification

4.32.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from LVV-T866	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is presumed that these are automated for a given dataset.
	Test Data	
	Expected	An output dataset including difference images and DIASource and DIAObject measurements.
	Result	
1-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
LVV-T866	Test Data	
	Expected	
	Result	

C	Description	Examine the serialized alert packets to confirm the presence of the required elements (LVV-105).
Z	Test Data	No data.
	Expected	
	Result	

4.33 LVV-T55 - Verify implementation of DIAForcedSource Catalog

Version Status Priority Verification Type Owner



1 Draft Normal Test Eric Bellm

Open LVV-T55 in Jira

4.33.1 Verification Elements

• LVV-148 - DMS-REQ-0317-V-01: DIAForcedSource Catalog

4.33.2 Test Items

Verify that the DMS produces a DIAForcedSource Catalog and that the catalog contains measured fluxes for DIAObjects.

4.33.3 Predecessors

- 4.33.4 Environment Needs
- 4.33.4.1 Software

4.33.4.2 Hardware

4.33.5 Input Specification

4.33.6 Output Specification

4.33.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from LVV-T866	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is _presumed that these are automated for a given dataset.
	Test Data	
	Expected Result	An output dataset including difference images and DIASource and DIAObject measurements.



Step	Description, li	nput Data and Expected Result
1-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
LVV-T866	Test Data	
	Expected	
	Result	
2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.
	Result	
	Description	Confirm that the DIAForcedSource catalog contains measurements for each source.
3	Test Data	No data.
	Expected	
	Result	

Latest Revision 2020-02-17

4.34 LVV-T56 - Verify implementation of Characterizing Variability

Test Spec for LSST Data Management

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm
		Open LV	V-T56 in Jira	

4.34.1 Verification Elements

• LVV-150 - DMS-REQ-0319-V-01: Characterizing Variability

4.34.2 Test Items

Verify that the variability characterization in the DIAObject catalog includes data collected within previous "diaCharacterizationCutoff" period of time.



4.34.3 Predecessors

4.34.4 Environment Needs

- 4.34.4.1 Software
- 4.34.4.2 Hardware
- 4.34.5 Input Specification

4.34.6 Output Specification

4.34.7 Test Procedure

Result

Step Description, Input Data and Expected Result

1-1 from LVV-T866	Description Test Data Expected Result	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is presumed that these are automated for a given dataset. An output dataset including difference images and DIASource and DIAObject measurements.
1-2 from LVV-T866	Description Test Data Expected Result	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
2	Description Test Data Expected	Verify that the issued alerts contain measurements during the diaCharacterizationCutoff. No data.

4.35 LVV-T57 - Verify implementation of Calculating SSObject Parameters



Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm
		Open LV	V-T57 in Jira	

4.35.1 Verification Elements

• LVV-154 - DMS-REQ-0323-V-01: Calculating SSObject Parameters

4.35.2 Test Items

Verify that the DMS database provides functions to compute phase angles and magnitudes in LSST bands for every SSObject.

4.35.3 Predecessors

4.35.4 Environment Needs

4.35.4.1 Software

4.35.4.2 Hardware

4.35.5 Input Specification

4.35.6 Output Specification

4.35.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process-
		ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging. DIASource detection/measurement, source association). During Operations, it is
LVV-1800		presumed that these are automated for a given dataset.



LDM-639

Latest Revision 2020-02-17

Step Description, Input Data and Expected Result

	Test Data	
	Expected	An output dataset including difference images and DIASource and DIAObject measurements.
	Result	
1-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
LVV-T866	Test Data	
	Expected	
	Result	
2-1 from	Description	Perform the steps of Moving Object Pipeline (MOPS) processing on newly detected DIASources, and generate Solar System data products including Solar System objects with associated Keplerian orbits,
LVV-T901		errors, and detected DIASources. This includes running processes to link DIASource detections within a night (called tracklets), to link these tracklets across multiple nights (into tracks), to fit the tracks with an orbital model to identify those tracks that are consistent with an asteroid orbit, to match these
	Test Data	
	Expected	An output dataset consisting of an updated SSObject database with SSObjects both added and
	Result	pruned as the orbital fits have been refined, and an updated DIASource database with DIASources assigned and unassigned to SSObjects.
2-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
LVV-T901	Test Data	
	Expected	
	Result	
	Description	Computer the phase angle, reduced and absolute asteroid magnitudes for objects iden-

	Description	computer the phase diffic, reduced and absolute asteroid magnitudes for objects iden
3		tified in SSObject Catalog
	Test Data	No data.
	Expected	
	Result	

4.36 LVV-T58 - Verify implementation of Matching DIASources to Objects

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm
		Open LV	V-T58 in Jira	



4.36.1 Verification Elements

• LVV-155 - DMS-REQ-0324-V-01: Matching DIASources to Objects

4.36.2 Test Items

Verify that a cross-match table is available between DIASources and Objects.

- 4.36.3 Predecessors
- 4.36.4 Environment Needs
- 4.36.4.1 Software
- 4.36.4.2 Hardware
- 4.36.5 Input Specification
- 4.36.6 Output Specification

4.36.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from LVV-T866	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is presumed that these are automated for a given dataset.
	Expected	An output dataset including difference images and DIASource and DIAObject measurements.
	Result	
1-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
LVV-T866	Test Data	
	Expected	
	Result	



LDM-639

Latest Revision 2020-02-17

Step Description, Input Data and Expected Result

2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- _lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.
	Result	
З	Description	Verify that a cross-match table between the Prompt DIASources and DRP Objects is avail- able.
5	Test Data	No data.
	Expected	
	Result	

4.37 LVV-T59 - Verify implementation of Regenerating L1 Data Products During Data Release Processing

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim
Open LVV-T59 in Jira				

4.37.1 Verification Elements

 LVV-156 - DMS-REQ-0325-V-01: Regenerating L1 Data Products During Data Release Processing

4.37.2 Test Items

Verify that the Prompt Processing data products are regenerated during DRP.

4.37.3 Predecessors



4.37.4 Environment Needs

- 4.37.4.1 Software
- 4.37.4.2 Hardware
- 4.37.5 Input Specification
- 4.37.6 Output Specification

4.37.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Execute DRP
1	Test Data	No data.
	Expected	
	Result	
	Description	Observe production of difference image data products
2	Description Test Data	Observe production of difference image data products No data.
2	Description Test Data Expected	Observe production of difference image data products No data.

4.38 LVV-T60 - Verify implementation of Publishing predicted visit schedule

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm
		Open LV	V-T60 in lira	

4.38.1 Verification Elements

• LVV-184 - DMS-REQ-0353-V-01: Publishing predicted visit schedule



4.38.2 Test Items

Verify that a predict-visit schedule can be published by the OCS.

4.38.3 Predecessors

- 4.38.4 Environment Needs
- 4.38.4.1 Software
- 4.38.4.2 Hardware
- 4.38.5 Input Specification

4.38.6 Output Specification

4.38.7 Test Procedure

Step	Description,	Input Data	and E	хре	ected Result
	Description				
1	Test Data	No data.			
	Expected				
	Result				

4.39 LVV-T61 - Verify implementation of Associate Sources to Objects

Version	Status	Priority	Verification Type	Owner	
1	Defined	Normal	Test	Jim Bosch	
Open LVV-T61 in Jira					



4.39.1 Verification Elements

• LVV-16 - DMS-REQ-0034-V-01: Associate Sources to Objects

4.39.2 Test Items

Verify that each Source record contains an ID that associates it with a best guess at the Object it corresponds to.

4.39.3 Predecessors

- 4.39.4 Environment Needs
- 4.39.4.1 Software
- 4.39.4.2 Hardware
- 4.39.5 Input Specification

4.39.6 Output Specification

4.39.7 Test Procedure

Step	Description, I	escription, Input Data and Expected Result					
1-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- _lowing:					
LVV-T987	Test Data						
	Expected	Butler repo available for reading.					
	Result						
	Description	Read a dataset via the Butler and extract its source and object catalogs.					
2	Test Data	No data.					
	Expected						
	Result						



LDM-639

Step	Description, Input Data and Expected Result					
	Description	Verify that sources have objects				
3	Test Data	No data.				
	Expected					
	Result					
	Description	Verify that objects list sources that seem reasonably near them.				
4	Test Data	No data.				
	Expected					
	Result					

4.40 LVV-T62 - Verify implementation of Provide PSF for Coadded Images

Version	Status	Priority	Verification Type	Owner	
2	Approved	Normal	Test	Jim Bosch	
Open LVV-T62 in lira					

4.40.1 Verification Elements

• LVV-20 - DMS-REQ-0047-V-01: Provide PSF for Coadded Images

4.40.2 Test Items

Verify that all coadd images produced by the DRP pipelines include a model from which an image of the PSF at any point on the coadd can be obtained.

4.40.3 Predecessors

- 4.40.4 Environment Needs
- 4.40.4.1 Software



LDM-639

4.40.4.2 Hardware

4.40.5 Input Specification

Fully covered by preconditions for LVV-T16.

4.40.6 Output Specification

4.40.7 Test Procedure

Step	Description, Input Data and Expected Result				
	Description	Identify a dataset with coadded images in multiple filters.			
1	Test Data	No data.			
	Expected	Multi-band data that has been processed through the coaddition stage.			
	Result				
2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:			
LVV-T987	Test Data				
	Expected	Butler repo available for reading.			
	Result				
3	Description	Load the exposures, then select Objects classified as point sources on at least 10 differ- ent coadd images (including all bands). Evaluate the PSF model at the positions of these Objects, and verify that subtracting a scaled version of the PSF model from the processed visit image yields residuals consistent with pure noise.			
	Test Data	No data.			
	Expected	Images with the PSF model subtracted, leaving only residuals that are consistent with			
	Result	being noise.			

4.41 LVV-T63 - Verify implementation of Produce Images for EPO

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Gregory Dubois-Felsmann
Open LVV-T63 in Jira				



4.41.1 Verification Elements

• LVV-45 - DMS-REQ-0103-V-01: Produce Images for EPO

4.41.2 Test Items

This test will verify that the DRP pipelines produce the image data products called out in LSE-131. Currently this is limited to a color all-sky HiPS map. This will be verified (1) by inspection of pipeline configurations and (2) in operations rehearsals on precursor data. The production of a usable HiPS map will be verified by browsing it with community tools.

4.41.3 Predecessors

- 4.41.4 Environment Needs
- 4.41.4.1 Software

4.41.4.2 Hardware

4.41.5 Input Specification

In order for an operational test to be successful, as a precondition the inputs to that production must exist. For the only currently mandated image data production in LSE-131, a color all-sky HiPS map down to 1 arcsecond resolution, the prerequisite inputs to that are the single-filter coadds in the bands required by the yet-to-be-specified color prescription.

4.41.6 Output Specification

4.41.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	Test Data	



		Test Spec for LSST Data Management	LDM-639	Latest Revision 2020-02-17
Step	Description, l	nput Data and Expected Result		
	Expected	Butler repo available for reading.		
	Result			
2	Description	For each of the expected data produce the data product from the Butler and	ct types needed for cr l verify it to be non-er	reation of HiPS images, retrieve
2	Test Data	No data.	<u> </u>	
	Expected			
	Result			
3	Description	Verify that a HiPS image map coverin 1 arcsecond resolution, has been p by EPO (in updates to LSE-131 whic available").	g the LSST survey are roduced matching th h are expected to be	a, with a limiting depth yielding e color prescriptions provided e made "once ComCam data is
	Test Data	No data.		
	Expected			
	Result			
4	Description	Place the image map in a location ac with the client running in the EPO da	cessible to a Firefly a ta systems environme	nd an Aladin Lite client, ideally ent.
	Test Data	No data.		
	Expected			
	Result			
5	Description	Use Firefly to manually explore the in the entire sky. Sample in various loc Confirm using Aladin Lite that the for community tool.	mage map at the larg ations to confirm the mat of the image ma	est scales to verify coverage of 1 arcsecond maximum depth. p is supported by this common
	Test Data	No data.		
	Expected			
	Result			
6	Description	Verify programmatically, perhaps bot the tiles created at the 1-arcsecond-re its specifications.	h by sampling a varie esolution depth, that t	ty of locations, and by counting the map is complete and meets
	Test Data	No data.		
	Expected			
	Result			
	Description	Apply an IVOA-community HiPS servi	ce validation tool, if av	vailable, to the service location.
7	Test Data	No data.		



Step	Description, Input Data and Expected Result		
	Expected		
	Result		
	Description	Verify that the HiPS map created is in a location accessible to the EPO data systems.	
8	Test Data	No data.	
	Expected		
	Result		

Latest Revision 2020-02-17

4.42 LVV-T64 - Verify implementation of Coadded Image Provenance

Test Spec for LSST Data Management

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch
		Open LV	V-T64 in lira	

4.42.1 Verification Elements

- LVV-46 DMS-REQ-0106-V-01: Coadded Image Provenance
- LVV-1234 OSS-REQ-0122-V-01: Provenance

4.42.2 Test Items

Verify that all coadd data products produced by the DRP pipelines are associated with provenance information that includes the set of input epochs contributing to that coadd as well as any additional information needed to exactly produce that coadd.

4.42.3 Predecessors

4.42.4 Environment Needs

4.42.4.1 Software



LDM-639

4.42.4.2 Hardware

4.42.5 Input Specification

4.42.6 Output Specification

4.42.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from Description The 'path' that you will use depends on where you are running the science pipelines. Options:

LVV-T860

		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash
	Test Data	
	Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.
		To check versions in use, type: _eups list -s
2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- _lowing:
	Expected Result	Butler repo available for reading.
3	Description	For each of the expected data product types and each of the expected units (PVIs, coadds, etc), retrieve the data product from the Butler and verify it to be non-empty.
5	Test Data	No data.
	Expected	
	Result	



LDM-639

Latest Revision 2020-02-17

Step Description, Input Data and Expected Result

4	Description	Query and verify provenance of input images, and software versions that went into pro- ducing stack.
·	Test Data	No data.
	Expected	
	Result	
5	Description	Test re-generating 10 different coadds tract+patches based on the provenance image given
5	Description Test Data	Test re-generating 10 different coadds tract+patches based on the provenance image given No data.
5	Description Test Data Expected	Test re-generating 10 different coadds tract+patches based on the provenance image given No data.

4.43 LVV-T65 - Verify implementation of Source Catalog

Version	Status	Priority	Verification Type	Owner	
1	Defined	Normal	Test	Jim Bosch	
Open I VV-T65 in lira					

4.43.1 Verification Elements

• LVV-98 - DMS-REQ-0267-V-01: Source Catalog

4.43.2 Test Items

Verify that all Sources produced by the DRP pipelines contain the entries listed in DMS-REQ-0267.

4.43.3 Predecessors

4.43.4 Environment Needs

4.43.4.1 Software



LDM-639

4.43.4.2 Hardware

4.43.5 Input Specification

4.43.6 Output Specification

4.43.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Identify a suitable small dataset to process through the DRP.
1	Test Data	No data.
	Expected	
	Result	
2-1 from LVV- T1064	Description Test Data Expected Result	Process data with the Data Release Production payload, starting from raw science images and gen- erating science data products, placing them in the Data Backbone.

	Description	Confirm that source catalogs have been produced for single visits and coadds, and that it
3		contains the required measurements.
-	Test Data	No data.
	Expected	A source catalog containing the measured attributes (and associated errors), including
	Result	location on the focal plane; a static point-source model fit to world coordinates and flux;
		a centroid and adaptive moments; and surface brightnesses through elliptical multiple
		apertures that are concentric, PSF-homogenized, and logarithmically spaced in intensity.

4.44 LVV-T66 - Verify implementation of Forced-Source Catalog

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch

Open LVV-T66 in Jira



4.44.1 Verification Elements

• LVV-99 - DMS-REQ-0268-V-01: Forced-Source Catalog

4.44.2 Test Items

Verify that all ForcedSources produced by the DRP pipelines contain fluxes measured on difference and direct single-epoch images, associated uncertainties, an Object ID, and a Visit ID.

4.44.3 Predecessors

- 4.44.4 Environment Needs
- 4.44.4.1 Software
- 4.44.4.2 Hardware
- 4.44.5 Input Specification

4.44.6 Output Specification

4.44.7 Test Procedure

Step	Description, I	Description, input Data and Expected Result		
1-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- _lowing:		
LVV-T987	Test Data			
	Expected	Butler repo available for reading.		
	Result			
	Description	Retrieve the forced-source catalog from the Butler and verify it to be non-empty.		
2	Test Data	No data.		



Step Description, Input Data and Expected Result Expected Result Description Verify that there exist entries in the forced-photometry table for all coadd objects for the PVIs on which the object should appear. 3 Test Data No data. Expected Result Description Verify that there exist entries in a forced-photometry table for each image for all DIAObjects. 4 Test Data No data. Expected Result

4.45 LVV-T67 - Verify implementation of Object Catalog

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Jim Bosch	
Open LVV-T67 in Jira					

4.45.1 Verification Elements

• LVV-106 - DMS-REQ-0275-V-01: Object Catalog

4.45.2 Test Items

Verify that the DRP pipelines produce an Object catalog derived from detections made on both coadded images and difference images and measurements performed on coadds and possibly overlapping single-epoch images.



LDM-639

4.45.3 Predecessors

4.45.4 Environment Needs

4.45.4.1 Software

4.45.4.2 Hardware

4.45.5 Input Specification

Input Data

DECam HiTS data (raw science images and master calibrations) HSC "RC2" data (raw science images and master calibrations)

4.45.6 Output Specification

4.45.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	load LSST DM Stack		
1	Test Data	No data.		
	Expected			
	Result			
	Description	Run the single-frame processing and self-calibration steps of the DRP pipeline.		
2	Test Data	No data.		
	Expected			
	Result			



Step Description, Input Data and Expected Result

	Description	Insert simulated sources into all single-frame images, including:
3		 static objects (e.g. galaxies), including some too faint to be detectable in single-epoch images; objects with static positions that are sufficiently bright and variable that they should be detectable in single-epoch difference images; transient objects that appear in only a few epochs; stars with significant proper motions and parallaxes, some below the single-epoch detection limit simulated solar system objects with orbits that can be constrained from just the epochs in the test dataset
	Test Data	No data.
	Expected	
	Result	
	Description	Run all remaining DRP pipeline steps.
4	Test Data	No data.
	Expected	
	Result	
	Description	Load data into DRP database
5	Description Test Data	Load data into DRP database No data.
5	Description Test Data Expected	Load data into DRP database No data.
5	Description Test Data Expected Result	Load data into DRP database No data.
5	Description Test Data Expected Result Description	Load data into DRP database No data. Verify that the injected simulated objects are recovered at a rate consistent with their S/N <i>when not blended with each other or real objects</i> , and that flags indicating how each Object was detected are consistent with their properties:
5	Description Test Data Expected Result Description	Load data into DRP database No data. Verify that the injected simulated objects are recovered at a rate consistent with their S/N <i>when not blended with each other or real objects</i> , and that flags indicating how each Object was detected are consistent with their properties: • static objects should be detected in coadds only (not difference images) • static-position/variable-flux objects should be detected in coadds and possibly dif- ference images
5	Description Test Data Expected Result Description	Load data into DRP database No data. Verify that the injected simulated objects are recovered at a rate consistent with their S/N <i>when not blended with each other or real objects</i> , and that flags indicating how each Object was detected are consistent with their properties: • static objects should be detected in coadds only (not difference images) • static-position/variable-flux objects should be detected in coadds and possibly dif- ference images • transient objects should be detected in difference images only • stars with significant proper motions may be detected in either coadds or differ-
5	Description Test Data Expected Result Description	Load data into DRP database No data. Verify that the injected simulated objects are recovered at a rate consistent with their S/N when not blended with each other or real objects, and that flags indicating how each Object was detected are consistent with their properties: • static objects should be detected in coadds only (not difference images) • static-position/variable-flux objects should be detected in coadds and possibly difference images • transient objects should be detected in difference images only • stars with significant proper motions may be detected in either coadds or difference images
5	Description Test Data Expected Result Description	Load data into DRP database No data. Verify that the injected simulated objects are recovered at a rate consistent with their S/N when not blended with each other or real objects, and that flags indicating how each Object was detected are consistent with their properties: • static objects should be detected in coadds only (not difference images) • static-position/variable-flux objects should be detected in coadds and possibly difference images • transient objects should be detected in difference images only • stars with significant proper motions may be detected in either coadds or difference images • solar system objects should be detected in difference images only.
5	Description Test Data Expected Result Description	Load data into DRP database No data. Verify that the injected simulated objects are recovered at a rate consistent with their S/N when not blended with each other or real objects, and that flags indicating how each Object was detected are consistent with their properties: • static objects should be detected in coadds only (not difference images) • static-position/variable-flux objects should be detected in coadds and possibly difference images • transient objects should be detected in difference images only • stars with significant proper motions may be detected in either coadds or difference images • solar system objects should be detected in difference images only.
5	Description Test Data Expected Result Description Test Data Expected	Load data into DRP database No data. Verify that the injected simulated objects are recovered at a rate consistent with their S/N when not blended with each other or real objects, and that flags indicating how each Object was detected are consistent with their properties: • static objects should be detected in coadds only (not difference images) • static-position/variable-flux objects should be detected in coadds and possibly difference images • transient objects should be detected in difference images only • stars with significant proper motions may be detected in either coadds or difference images • solar system objects should be detected in difference images only. No data.



LDM-639

4.46 LVV-T68 - Verify implementation of Provide Photometric Redshifts of Galaxies

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Jim Bosch	
Open LVV-T68 in Jira					

4.46.1 Verification Elements

• LVV-19 - DMS-REQ-0046-V-01: Provide Photometric Redshifts of Galaxies

4.46.2 Test Items

Verify that Object catalogs produced by the DRP Pipeline include photometric redshift information.

4.46.3 Predecessors

- 4.46.4 Environment Needs
- 4.46.4.1 Software

4.46.4.2 Hardware

4.46.5 Input Specification

Input Data

HSC Public Data Release (raw science images, master calibrations) Assorted public spectroscopic catalogs and high-accuracy photometric redshift catalogs in the HSC PDR footprint.

4.46.6 Output Specification



4.46.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Run DRP processing steps through (at least) final galaxy photometry measurements.		
1	Test Data	No data.		
	Expected			
	Result			
2	Description	Train photometric redshift algorithm(s) on spectroscopic and high-accuracy photometric redshift catalogs.		
	Test Data	No data.		
	Expected			
	Result			
	Description	Estimate photometric redshifts for all Objects generated by DRP processing.		
3	Test Data	No data.		
	Expected			
	Result			
	Description	Load into DRP Database		
4	Test Data	No data.		
	Expected			
	Result			
	Description	Inspect database to verify that photometric redshifts are present for all objects		
5	Test Data	No data.		
	Expected			
	Result			

4.47 LVV-T69 - Verify implementation of Object Characterization

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Jim Bosch	
Open LVV-T69 in Jira					


4.47.1 Verification Elements

• LVV-107 - DMS-REQ-0276-V-01: Object Characterization

4.47.2 Test Items

Verify that Object catalogs produced by the DRP pipeline include all measurements listed in DMS-REQ-0276: a point-source model fit, a bulge-disk model fit, standard colors, a centroid, adap- tive moments, Petrosian and Kron fluxes, surface brightness at multiple apertures, proper motion and parallax, and a variability characterization.

4.47.3 Predecessors

- 4.47.4 Environment Needs
- 4.47.4.1 Software
- 4.47.4.2 Hardware

4.47.5 Input Specification

4.47.6 Output Specification

4.47.7 Test Procedure

Step	Description, Input Data and Expected Result						
	Description	Precursor data, execute DRP, load results, observe catalog contents					
1	Test Data No data.						
	Expected	Expected					
	Result	Result					



LDM-639

4.48 LVV-T71 - Verify implementation of Detecting extended low surface brightness objects

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch
Open LVV-T71 in Jira				

4.48.1 Verification Elements

• LVV-180 - DMS-REQ-0349-V-01: Detecting extended low surface brightness objects

4.48.2 Test Items

Verify that low-surface brightness objects (including those whose PSF S/N is lower than the detection threshold) are detected in coadds.

4.48.3 Predecessors

4.48.4 Environment Needs

4.48.4.1 Software

4.48.4.2 Hardware

4.48.5 Input Specification

Input Data HSC "RC2" data (raw science images and master calibrations)

4.48.6 Output Specification

4.48.7 Test Procedure



LDM-639

Step	Description, Input Data and Expected Result		
	Description	load LSST DM Stack	
1	Test Data	No data.	
	Expected		
	Result		
	Description	Run the single-frame processing and self-calibration steps of the DRP pipeline.	
2	Test Data	No data.	
	Expected		
	Result		
	Description	Insert simulated low-surface-brightness galaxies (with exponential profiles) consistently	
3		into all calibrated single-epoch images.	
	Test Data	No data.	
	Expected		
	Result		
	Description	Run all remaining DRP pipeline steps.	
4	Test Data	No data.	
	Expected		
	Result		
	Description	Load data into DRP database	
5	Test Data	No data.	
	Expected		
	Result		
	Description	Verify that the injected simulated objects are recovered at a rate consistent with their S/N	
6		and true profile when not blended with each other or real objects.	
	Test Data	No data.	
	Expected		
	Result		

4.49 LVV-T72 - Verify implementation of Coadd Image Method Constraints

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch
Open LVV-T72 in Jira				



4.49.1 Verification Elements

• LVV-109 - DMS-REQ-0278-V-01: Coadd Image Method Constraints

4.49.2 Test Items

Verify the implementation of how Coadd images are created.

4.49.3 Predecessors

- 4.49.4 Environment Needs
- 4.49.4.1 Software
- 4.49.4.2 Hardware
- 4.49.5 Input Specification

4.49.6 Output Specification

4.49.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Identify a dataset that has been processed to create coadd images.
1	Test Data	No data.
	Expected	
	Result	
2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.
	Result	



LDM-639

Step Description, Input Data and Expected Result 3 Description Retrieve the coadds in the dataset and verify that they are non-empty. 3 Test Data No data. Expected No data.

	Result	
	Description	Verify that coadds were created following specification
4	Test Data	No data.
	Expected	
	Result	

4.50 LVV-T73 - Verify implementation of Deep Detection Coadds

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Jim Bosch	
	Open LVV-T73 in lira				

4.50.1 Verification Elements

• LVV-110 - DMS-REQ-0279-V-01: Deep Detection Coadds

4.50.2 Test Items

Verify that the DRP pipelines produce a suite of per-band coadded images that are optimized for depth.

4.50.3 Predecessors

4.50.4 Environment Needs

4.50.4.1 Software



LDM-639

4.50.4.2 Hardware

4.50.5 Input Specification

4.50.6 Output Specification

4.50.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.
	Result	

	Description	Verify through inspection that per-filter coadds exist for each tract+patch possible
2	Test Data	No data.
	Expected	
	Result	
2	Description	Verify through inspection that the images used to generate those coadds met specified conditions
5	Test Data	No data.
	Expected	
	Result	
4	Description	Visually inspect a subset of the coadds to verify that they visually appear reasonable and to be from good quality data.
	Test Data	No data.
	Expected	
	Result	

4.51 LVV-T74 - Verify implementation of Template Coadds

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm





LDM-639

Latest Revision 2020-02-17

Open LVV-T74 in Jira

4.51.1 Verification Elements

• LVV-111 - DMS-REQ-0280-V-01: Template Coadds

4.51.2 Test Items

Verify that the DMS can produce Template Coadds for DIA processing.

4.51.3 Predecessors

- 4.51.4 Environment Needs
- 4.51.4.1 Software
- 4.51.4.2 Hardware

4.51.5 Input Specification

4.51.6 Output Specification

4.51.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration,
LVV-T866		difference imaging, DIASource detection/measurement, source association). During Operations, it is presumed that these are automated for a given dataset
	Test Data	
	Expected	An output dataset including difference images and DIASource and DIAObject measurements.
	Result	
1-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
LVV-T866		



Step	Description, Input Data and Expected Result
	Test Data
	Expected
	Result
	Description Confirm that the template coadds have been created and are well-formed.
2	Test Data No data.
	Expected

LDM-639

Latest Revision 2020-02-17

4.52 LVV-T75 - Verify implementation of Multi-band Coadds

Test Spec for LSST Data Management

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Jim Bosch	
Open LVV-T75 in lira					

4.52.1 Verification Elements

Result

• LVV-112 - DMS-REQ-0281-V-01: Multi-band Coadds

4.52.2 Test Items

Verify that the DRP pipelines produce multi-band coadds for detection purposes.

4.52.3 Predecessors

- 4.52.4 Environment Needs
- 4.52.4.1 Software

4.52.4.2 Hardware



LDM-639

4.52.5 Input Specification

4.52.6 Output Specification

4.52.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol-	
LVV-T987	Test Data		
	Expected	Butler repo available for reading.	
	Result		

Description Verify that deep detection coadds exist based on all filters.

2

Test Data	No data.		
Expected			
Result			

4.53 LVV-T76 - Verify implementation of All-Sky Visualization of Data Releases

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Simon Krughoff	
Open LVV-T76 in lira					

4.53.1 Verification Elements

• LVV-160 - DMS-REQ-0329-V-01: All-Sky Visualization of Data Releases

4.53.2 Test Items

Show that it's possible to produce large area visualizations from Data Release data products.



LDM-639

4.53.3 Predecessors

4.53.4 Environment Needs

4.53.4.1 Software

4.53.4.2 Hardware

4.53.5 Input Specification

Input Data

Dataset of perhaps ~100 square degrees. The first HSC Public Data Release will be used for this test. Larger (in sky area) datasets should be identified for further testing.

4.53.6 Output Specification

4.53.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.
	Result	

	Description	Run all sky tile generation task to produce the data products necessary for serving the all
2		sky visualization.
	Test Data	No data.
	Expected	
	Result	



Step	Description, li	nput Data and Expected Result		
3	Description	Manually perform, and log (including timing where applicable), the following steps against that all sky visualization application. At all steps take special care to note any missing or un-rendered image tiles:		
		 Navigate to the all sky viewer and log the URL, browser and version. Zoom to native pixel display (1 image pixel per display pixel) Zoom to fit the full PDR footprint Zoom to 1/4x native resolution Pan to eastern edge of the footprint. Pan to western edge of the footprint. Navigate to the middle of the footprint. Zoom to max magnification 		
	Test Data No data.			
	Expected			
	Result			

4.54 LVV-T77 - Verify implementation of Best Seeing Coadds

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch
		Open LV	V-T77 in Jira	

4.54.1 Verification Elements

• LVV-161 - DMS-REQ-0330-V-01: Best Seeing Coadds

4.54.2 Test Items

Verify that the DRP pipelines produce a suite of per-band coadds with input images filtered to optimize the size of the effective PSF on the coadd.

4.54.3 Predecessors



LDM-639

4.54.4 Environment Needs

- 4.54.4.1 Software
- 4.54.4.2 Hardware
- 4.54.5 Input Specification
- 4.54.6 Output Specification

4.54.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from LVV-T860

local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash

development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash

LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash

From the command line, execute the commands below in the example code:

Test Data	
Expected	Science pipeline software is available for use. If additional packages are needed (for example, 'obs'
Result	packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.

To check versions in use, type: eups list -s

2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- _lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.
	Result	



LDM-639

Step Description, Input Data and Expected Result

	Description	Explicitly create a coadd for a specified seeing range in each filter.
3	Test Data	No data.
	Expected	
	Result	
	Description	Verify that these coadds exist.
4	Description Test Data	Verify that these coadds exist. No data.
4	Description Test Data Expected	Verify that these coadds exist. No data.

4.55 LVV-T78 - Verify implementation of Persisting Data Products

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Kian-Tat Lim	
Open LVV-T78 in lira					

4.55.1 Verification Elements

• LVV-165 - DMS-REQ-0334-V-01: Persisting Data Products

4.55.2 Test Items

Verify that per-band deep coadds and best-seeing coadds are present, kept, and available.

4.55.3 Predecessors

- 4.55.4 Environment Needs
- 4.55.4.1 Software



LDM-639

4.55.4.2 Hardware

4.55.5 Input Specification

Precursor data from HSC PDR.

4.55.6 Output Specification

4.55.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Produce some relevant coadds and store them in the Archive		
1	Test Data	No data.		
	Expected			
	Result			
	Description	Examine the data retention policies for those products		
2	Test Data	No data.		
	Expected			
	Result			

4.56 LVV-T79 - Verify implementation of PSF-Matched Coadds

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jim Bosch
Open LVV-T79 in Jira				

4.56.1 Verification Elements

• LVV-166 - DMS-REQ-0335-V-01: PSF-Matched Coadds



4.56.2 Test Items

Verify that the DRP pipelines produce PSF matched coadds.

4.56.3 Predecessors

- 4.56.4 Environment Needs
- 4.56.4.1 Software
- 4.56.4.2 Hardware
- 4.56.5 Input Specification

4.56.6 Output Specification

4.56.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.
	Result	

	Description	Verify that PSF-matched coadds were created.
2	Test Data	No data.
	Expected	
	Result	

4.57 LVV-T80 - Verify implementation of Detecting faint variable objects

Version Status Priority Verification Type Owner



1 Draft Normal Test Melissa Graham

Open LVV-T80 in Jira

4.57.1 Verification Elements

• LVV-168 - DMS-REQ-0337-V-01: Detecting faint variable objects

4.57.2 Test Items

To verify that the Data Release Production pipeline will be able to detect faint sources with long-term variability (e.g., quasars, proper motion stars) via, e.g., shorter timescale coadds (month to a few months).

4.57.3 Predecessors

- 4.57.4 Environment Needs
- 4.57.4.1 Software

4.57.4.2 Hardware

4.57.5 Input Specification

Input Data such as: DECam HiTS data. Gaia catalog of faint moving objects. Catalog of spectroscopically confirmed quasars. (Alternative: input data injected with faint variable sources).

4.57.6 Output Specification

4.57.7 Test Procedure



LDM-639

Latest Revision 2020-02-17

Step Description, Input Data and Expected Result

1-1 from LVV-T866	Description Test Data Expected Result	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is presumed that these are automated for a given dataset. An output dataset including difference images and DIASource and DIAObject measurements.
1-2 from		verify that the expected data products have been produced, and that catalogs contain reasonable _values for measured quantities of interest.
LVV-T866	Test Data	
	Expected	
2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- _lowing:
	Expected Result	Butler repo available for reading.
3	Description	Identify 100 objects from Gaia with proper motions high enough to have detectably moved during HSC observations.
-	Test Data	No data.
	Expected	
	Result	
4	Description	Measure reported proper motion of these objects in DM Stack processing. Verify that it is consistent with Gaia objects.
	Test Data	No data.
	Expected	
	Result	
-	Description	Identify 100 quasars from color-space or existing extragalactic spectroscopic catalog.
5	Test Data	No data.
	Result	
6	Description	Measure lightcurves of these quasars. Determine if structure function is reasonable (may require at least a year to determine if the structure function of 100 quasars is "reason-able").



Step	Description, Input Data and Expected Result		
	Test Data	No data.	
	Expected		
	Result		
7	Description	(Alternative: if faint variable source can be injected into the input data, test to see if they are recovered).	
	Test Data	No data.	
	Expected	(This Alternative would enable us not only to tell if faint variable objects are detected, but	
	Result	exactly which kinds, how faint, and with what efficiency.)	

4.58 LVV-T81 - Verify implementation of Targeted Coadds

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Jim Bosch	
Open LVV-T81 in Jira					

4.58.1 Verification Elements

• LVV-169 - DMS-REQ-0338-V-01: Targeted Coadds

4.58.2 Test Items

Verify that small sections of any coadd produced by the DRP pipelines can be retained, even if the full coadd is not.

4.58.3 Predecessors

4.58.4 Environment Needs

4.58.4.1 Software



LDM-639

4.58.4.2 Hardware

4.58.5 Input Specification

4.58.6 Output Specification

4.58.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Remove DR from disk		
1	Test Data	No data.		
	Expected			
	Result			
	Description	Observe retention of designated coadd sections		
2	Test Data	No data.		
	Expected			
	Result			
	Description	Observe accessibility of designated coadd sections via simulated DAC LSP instance		
3	Test Data	No data.		
	Expected			
	Result			

4.59 LVV-T82 - Verify implementation of Tracking Characterization Changes Between Data Releases

Version	Status	Priority	Verification Type	Owner	
1	Defined	Normal	Test	Jim Bosch	
Open LVV-T82 in lira					



4.59.1 Verification Elements

• LVV-170 - DMS-REQ-0339-V-01: Tracking Characterization Changes Between Data Releases

4.59.2 Test Items

Verify that small-area subsets of a DR can be retained when most of that DR is retired, for comparison with future DRs.

4.59.3 Predecessors

- 4.59.4 Environment Needs
- 4.59.4.1 Software
- 4.59.4.2 Hardware
- 4.59.5 Input Specification

4.59.6 Output Specification

4.59.7 Test Procedure

Step	Description, Input Data and Expected Result			
1	Description	Prepare a second DRP run -> DPDD with different configuration parameters for this sec- ond test Data Release.		
I	Test Data	No data.		
	Expected			
	Result			
2-1 from	Description	Process data with the Data Release Production payload, starting from raw science images and gen- erating science data products, placing them in the Data Backbone.		
LVV- T1064	Test Data			



Step	Description, Input Data and Expected Result			
	Expected			
	Result			
	Description	Stage subset of products from first test Data Release to separate storage.		
3	Test Data	No data.		
	Expected			
	Result			
	Description	Scientifically compare the results of the subset of that region of sky to those in the second		
4		test Data Release comparing the results of the DRP Scientific Verification tests.		
	Test Data	No data.		
	Expected	Diagnostic plots quantifying the differences between scientific outputs between the first		
	Result	and second test datasets.		

4.60 LVV-T83 - Verify implementation of Bad Pixel Map

Version	Status	Priority	Verification Type	Owner	
1	Defined	Normal	Test	Robert Lupton	
Open LVV-T83 in Jira					

4.60.1 Verification Elements

• LVV-22 - DMS-REQ-0059-V-01: Bad Pixel Map

4.60.2 Test Items

Verify that the DMS can produce a map of detector pixels that suffer from pathologies, and that these pathologies are encoded in at least 32-bit values.

4.60.3 Predecessors



LDM-639

4.60.4 Environment Needs

- 4.60.4.1 Software
- 4.60.4.2 Hardware
- 4.60.5 Input Specification
- 4.60.6 Output Specification

4.60.7 Test Procedure

Step Description, Input Data and Expected Result

1	Description	Interrogate the calibRegistry for the metadata associated with a bad pixel map, where the validity range contains the date of interest.
·	Test Data	No data.
	Expected	A bad pixel map for the requested date has been returned.
	Result	
2	Description	Check that the bad pixel pathologies are encoded as at least 32-bit values, and that the various pathologies are represented by different encoding.
2	Description Test Data	Check that the bad pixel pathologies are encoded as at least 32-bit values, and that the various pathologies are represented by different encoding. No data.
2	Description Test Data Expected	Check that the bad pixel pathologies are encoded as at least 32-bit values, and that the various pathologies are represented by different encoding. No data. Bad pixel values can be decoded to determine their pathologies using their 32-bit values.

4.61 LVV-T84 - Verify implementation of Bias Residual Image

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton
		Opon	VAL TRA in lina	

Open LVV-T84 in Jira



4.61.1 Verification Elements

• LVV-23 - DMS-REQ-0060-V-01: Bias Residual Image

4.61.2 Test Items

Verify that DMS can construct a bias residual image that corrects for temporally-stable bias structures.

Verify that DMS can do this on demand.

4.61.3 Predecessors

- 4.61.4 Environment Needs
- 4.61.4.1 Software
- 4.61.4.2 Hardware
- 4.61.5 Input Specification

4.61.6 Output Specification

4.61.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Identify the location of an appropriate precursor dataset.		
1	Test Data	No data.		
	Expected			
	Result			
2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:		
LVV-T987	Test Data			
	Expected	Butler repo available for reading.		
	Result			

DRAFT NOT YET APPROVED – The contents of this document are subject to configuration control by the LSST DM Change Control Board. – DRAFT NOT YET APPROVED



Latest Revision 2020-02-17

Step Description, Input Data and Expected Result

	Description	Import the standard libraries required for the rest of this test:
3	Test Data	No data.
	Example	import osimport lsst.afw.display as afwDisplay
	Code	from lsst.daf.persistence import Butler
		from lsst.ip.isr import IsrTask
		from firefly_client import FireflyClient
		from IPython.display import IFrame
	Expected	
	Result	
	Description	Ingest the dataset from step 1 using the Butler (e.g., following example code below).
4	Test Data	No data.
	Example	butler = Butler(\$REPOSITORY_PATH)
	Code	raw = butler.get("raw", visit=\$VISIT_ID, detector=2)
		bias = butler.get("bias", visit=\$VISIT_ID, detector=2)
	Expected	
	Result	
	Description	Display the bias image and inspect that its pixels contain unique values.
5	Test Data	No data.
	Expected	A relatively flat image showing the bias level with roughly Poisson noise.
	Result	
	Description	Configure and run an Instrument Signature Removal (ISR) task on the raw data. Most
6		corrections are disabled for simplicity, but the bias frame is applied.

Test Data	No data.
Example	isr_config = lsrTask.ConfigClass()
Code	isr_config.doDark=False
	isr_config.doFlat=False
	isr_config.doFringe=False
	isr_config.doDefect=False
	isr_config.doAddDistortionModel=False
	isr_config.doLinearize=False
	isr = IsrTask(config=isr_config)
	result = isr.run(raw, bias=bias)



LDM-639

Step	Description, Input Data and Expected Result			
	Expected Result	A trimmed, bias-corrected image in 'result'.		
	Description	Display the 'result' image and confirm that the bias correction has been performed.		
7	Test Data	No data.		
	Expected	A displayed image with bias removed (i.e., typical background counts reduced relative to		
	Result	the raw frame).		

4.62 LVV-T85 - Verify implementation of Crosstalk Correction Matrix

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton
		Open L	.VV-T85 in lira	

4.62.1 Verification Elements

• LVV-24 - DMS-REQ-0061-V-01: Crosstalk Correction Matrix

4.62.2 Test Items

Verify that the DMS can generate a cross-talk correction matrix from appropriate calibration data.

Verify that the DMS can measure the effectiveness of the cross-talk correction matrix.

4.62.3 Predecessors

- 4.62.4 Environment Needs
- 4.62.4.1 Software

4.62.4.2 Hardware



LDM-639

4.62.5 Input Specification

4.62.6 Output Specification

4.62.7 Test Procedure

Step Description, Input Data and Expected Result

1	Description	Identify an appropriate calibration dataset that can be used to derive the crosstalk cor- rection matrix.
1	Test Data	No data.
	Expected	
	Result	
2-1 from	Description	Execute the Calibration Products Production payload. The payload uses raw calibration images and
LVV-		information from the Transformed EFD to generate a subset of Master Calibration Images and Cali- bration Database entries in the Data Backbone
T1060	Test Data	
	Expected	
	Result	
2-2 from	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present
LVV-	Test Data	
T1060	Expected	
	Result	
	Description	Confirm that the crosstalk correction matrix is produced and persisted.
3	Test Data	No data.
	Expected	A correction matrix quantifying what fraction of the signal detected in any given amplifier
	Result	on each sensor in the focal plane appears in any other amplifier.
4	Description	Apply the crosstalk correction to simulated images, and confirm that the correction is performing as expected.
·	Test Data	No data.
	Expected	A noticeable difference between images before and after applying the correction.
	Result	

4.63 LVV-T86 - Verify implementation of Illumination Correction Frame



Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Lupton
Open LVV-T86 in Jira				

4.63.1 Verification Elements

• LVV-25 - DMS-REQ-0062-V-01: Illumination Correction Frame

4.63.2 Test Items

Verify that the DMS can produce an illumination correction frame calibration product. Verify that the DMS can determine the effectiveness of an illumination correction and determine how often it should be updated.

4.63.3 Predecessors

4.63.4 Environment Needs

- 4.63.4.1 Software
- 4.63.4.2 Hardware
- 4.63.5 Input Specification
- 4.63.6 Output Specification

4.63.7 Test Procedure

Step Description, Input Data and Expected Result

Description Delegate to CPP

1 Test Data No data.



Step	Description, Input Data and Expected Result		
	Expected		
	Result		

4.64 LVV-T87 - Verify implementation of Monochromatic Flatfield Data Cube

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Lupton
Open LVV-T87 in Jira				

4.64.1 Verification Elements

• LVV-26 - DMS-REQ-0063-V-01: Monochromatic Flatfield Data Cube

4.64.2 Test Items

Verify that the DMS can generate a calibration image/cube that corrects for pixel-to-pixel wavelength-dependent detector response.

Verify that the DMS can measure the effectiveness of this monochromatic flatfield data cube.

4.64.3 Predecessors

4.64.4 Environment Needs

4.64.4.1 Software

4.64.4.2 Hardware

4.64.5 Input Specification



4.64.6 Output Specification

4.64.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Delegate to CPP	
1	Test Data	No data.	
	Expected		
	Result		

4.65 LVV-T88 - Verify implementation of Calibration Data Products

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton
Onen I W-T88 in lira				

4.65.1 Verification Elements

• LVV-57 - DMS-REQ-0130-V-01: Calibration Data Products

4.65.2 Test Items

Verify that the DMS can produce and archive the required Calibration Data Products: cross talk correction, bias, dark, monochromatic dome flats, broad-band flats, fringe correction, and illumination corrections.

4.65.3 Predecessors

4.65.4 Environment Needs

4.65.4.1 Software



LDM-639

4.65.4.2 Hardware

4.65.5 Input Specification

4.65.6 Output Specification

4.65.7 Test Procedure

Step Description, Input Data and Expected Result

1	Description	Identify a suitable set of calibration frames, including biases, dark frames, and flat-field frames.
	Test Data	No data.
	Expected	
	Result	
2-1 from	Description	Execute the Calibration Products Production payload. The payload uses raw calibration images and
LVV-		information from the Transformed EFD to generate a subset of Master Calibration Images and Cali- bration Database entries in the Data Backbone.
T1060	Test Data	
-	Expected	
	Result	
2-2 from	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present
LVV-	Test Data	
T1060	Expected	
	Result	

	Description	Confirm that the expected data products are created, and that they have the expected
3		properties.
-	Test Data	No data.
	Expected	A full set of calibration data products has been created, and they are well-formed.
	Result	
	Description	Test that the calibration products are archived, and can readily be applied to science data
4		to produce the desired corrections.
•	Test Data	No data.
	Expected	Confirmation that application of the calibration products to processed data has the de-
	Result	sired effects.



4.66 LVV-T89 - Verify implementation of Calibration Image Provenance

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton

Open LVV-T89 in Jira

4.66.1 Verification Elements

- LVV-59 DMS-REQ-0132-V-01: Calibration Image Provenance
- LVV-1234 OSS-REQ-0122-V-01: Provenance

4.66.2 Test Items

Verify that the DMS records the required provenance information for the Calibration Data Products.

4.66.3 Predecessors

- 4.66.4 Environment Needs
- 4.66.4.1 Software

4.66.4.2 Hardware

- 4.66.5 Input Specification
- 4.66.6 Output Specification

4.66.7 Test Procedure



Step Description, Input Data and Expected Result Description Ingest an appropriate precursor calibration dataset into a Butler repo. Test Data 1 No data. Expected Result 2-1 from Description Execute the Calibration Products Production payload. The payload uses raw calibration images and information from the Transformed EFD to generate a subset of Master Calibration Images and Cali-LVVbration Database entries in the Data Backbone. T1060 Test Data Expected Result 2-2 from Description Confirm that the expected Master Calibration images and Calibration Database entries are present _ _ _ _and_well-formed. _ _ _ _ _ _ _ _ _ LVV-Test Data T1060 Expected Result Description Load the relevant database/Butler data product, and observe that all provenance information has been retained. 3 Test Data No data.

Expected	A dataset consisting of calibration images, with provenance information recorded and
Result	properly associated with the calibration images.

4.67 LVV-T90 - Verify implementation of Dark Current Correction Frame

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton
Open LVV-T90 in Jira				

4.67.1 Verification Elements

• LVV-113 - DMS-REQ-0282-V-01: Dark Current Correction Frame



4.67.2 Test Items

Verify that the DMS can produce a dark correction frame calibration product. Verify that the DMS can determine the effectiveness of a dark correction and determine how often it should be updated.

4.67.3 Predecessors

- 4.67.4 Environment Needs
- 4.67.4.1 Software
- 4.67.4.2 Hardware
- 4.67.5 Input Specification
- 4.67.6 Output Specification

4.67.7 Test Procedure

Step Description, Input Data and Expected Result

4	Description	Identify the path to a dataset containing dark frames (i.e., exposures taken with the shut-
1		ter closed).
	Test Data	No data.
	Expected	
	Result	
	Description	Execute the relevant steps from 'cp_pipe' (the calibration pipeline) to produce dark cor-
2		rection frames.
2	Test Data	No data.
	Expected	
	Result	
	Description	Inspect the resulting dark correction frame to confirm that it appears as expected.
3	Test Data	No data.



LDM-639

Step	Description, Input Data and Expected Result		
	Expected Result	A well-formed dark correction frame is present and accessible via the Data Butler.	
4	Description	Determining whether the dark correction is being done properly will require on-sky sci- ence data. The dark correction can be applied to these frames and the results inspected to ensure that the correction was correctly measured and applied.	
	Test Data	No data.	
	Expected	Applying the dark correction to a dataset produces noticeable differences between the	
	Result	original frame(s) and the corrected outputs.	

4.68 LVV-T91 - Verify implementation of Fringe Correction Frame

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Lupton
Open LVV/ T01 in line				

Open LVV-T91 in Jira

4.68.1 Verification Elements

• LVV-114 - DMS-REQ-0283-V-01: Fringe Correction Frame

4.68.2 Test Items

Verify that the DMS can produce an fringe-correction frame calibration product. Verify that the DMS can determine the effectiveness of the fringe-correction frame and determine how often it should be updated.

4.68.3 Predecessors

4.68.4 Environment Needs

4.68.4.1 Software



LDM-639

4.68.4.2 Hardware

4.68.5 Input Specification

4.68.6 Output Specification

4.68.7 Test Procedure

Step	Description, li	nput Data and Expected Result	
	Description	Delegate to CPP	
1	Test Data	No data.	
	Expected		
	Result		

4.69 LVV-T92 - Verify implementation of Processing of Data From Special Programs

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Melissa Graham
Open LVV-T92 in Jira				

4.69.1 Verification Elements

• LVV-151 - DMS-REQ-0320-V-01: Processing of Data From Special Programs

4.69.2 Test Items

For a simulated night of observing that includes some special program observations, show that the SP observations are reduced using their designated reconfigured pipelines (i.e., that the image metadata is sufficient to trigger the processing and include all other relevant images in the processing).



LDM-639

4.69.3 Predecessors

4.69.4 Environment Needs

4.69.4.1 Software

4.69.4.2 Hardware

4.69.5 Input Specification

A variety of imaging data from Special Programs, including these scenarios:

(1) Special Programs data that can be processed by the Prompt pipeline (i.e., standard visits)
(2) Special Programs data that requires 'real-time' (~24) processing with a reconfigured pipeline (e.g., DDF imaging sequence)

(3) Special Programs data that can (should) be processed by the Data Release pipeline (e.g., North Ecliptic Spur standard visits)

4.69.6 Output Specification

4.69.7 Test Procedure

Step	Description, Input Data and Expected Result			
1	Description	 (1) Special Programs data that can be processed by the Prompt pipeline (i.e., standard visits). Check that all images with the header keyword for SP were processed by the Prompt pipeline. Check that the Prompt pipeline's data products – DIASource, DIAObject catalogs and the Alerts – contain items flagged with their origin as that SP. 		
	Test Data	No data.		
	Expected			
	Result			
2	Description	(2) Special Programs data that requires 'real-time' (~24) processing with a reconfigured pipeline (e.g., DDF imaging sequence)		
		reconfigured pipeline. Check that the pipeline's data products have been updated, and passed their QA.		
	Test Data	No data.		


Step Description, Input Data and Expected Result

	Expected	
	Result	
3	Description	(3) Special Programs data that can (should) be processed by the Data Release pipeline (e.g., North Ecliptic Spur standard visits).
5		SP data would be added manually to the DRP processing. Check that the DRP's data prod- ucts – Source, Object, CoAdds – contain items flagged as originating in that SP.
	Test Data	No data.
	Expected	
	Result	

4.70 LVV-T93 - Verify implementation of Level 1 Processing of Special Programs Data

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Melissa Graham
Open I VV-T93 in lira				

4.70.1 Verification Elements

• LVV-152 - DMS-REQ-0321-V-01: Level 1 Processing of Special Programs Data

4.70.2 Test Items

Execute multi-day operations rehearsal. Observe whether Prompt Processing data products generated in time and confirm whether processing has completed before the start of the next simulated night.

4.70.3 Predecessors



LDM-639

4.70.4 Environment Needs

4.70.4.1 Software

4.70.4.2 Hardware

4.70.5 Input Specification

Imaging data obtained under a Special Program: for example, a sequence of consecutive images of a deep drilling field.

4.70.6 Output Specification

4.70.7 Test Procedure

Step	Description, l	Description, Input Data and Expected Result		
1	Description	escription If imaging data for a Special Program that requires processing with the Prompt pipeline was obtained the previous night, check that there exist DIASources/Objects/Alerts with flags that they originated from the Special Program.		
	Test Data	No data.		
	Expected			
	Result			
2	Description	If imaging data for a Special Program that requires prompt processing with a reconfigured pipeline was obtained the previous night, check that the relevant data products have been updated.		
	Test Data	No data.		
	Expected			
	Result			

4.71 LVV-T94 - Verify implementation of Special Programs Database

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Melissa Graham





LDM-639

Open LVV-T94 in Jira

4.71.1 Verification Elements

• LVV-153 - DMS-REQ-0322-V-01: Special Programs Database

4.71.2 Test Items

To confirm that data products from Special Programs are based solely on images obtained as part of SP via, e.g., metadata queries. To confirm that the SP data products can be joined to Prompt and DRP products by attempting to do so via, e.g., coordinate table joins, and attempting to e.g., find the faint counterparts in a Deep Drilling stack to variables with no Object detections in the DRP coadds.

4.71.3 Predecessors

- 4.71.4 Environment Needs
- 4.71.4.1 Software

4.71.4.2 Hardware

4.71.5 Input Specification

Databases created by reconfigured pipelines for processing Special Programs data (e.g., DIAObject/DIASource catalogs for a Deep Drilling Field).

4.71.6 Output Specification

4.71.7 Test Procedure



Step	Description, Input Data and Expected Result		
1	Description	SP data product: DDF DIAObjects catalog Non-SP data product: WFD DIAObjects catalog Test: join the two catalogs by coordinate (e.g., to get a longer time baseline for variable stars in the DDF)	
	Test Data	No data.	
	Expected		
	Result		
2	Description	SP data product: DDF Objects catalog Non-SP data product: WFD DIAObjects catalog Test: join the two catalogs by coordinate to identify faint host galaxies of transients found in WFD	
	Test Data	No data.	
	Expected		
	Result		

4.72 LVV-T95 - Verify implementation of Constraints on Level 1 Special Program Products Generation

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Melissa Graham
Open LVV-T95 in Jira				

4.72.1 Verification Elements

- LVV-175 DMS-REQ-0004-V-01: Time to L1 public release
- LVV-1276 OSS-REQ-0127-V-01: Level 1 Data Product Availability

4.72.2 Test Items

Execute single-day operations rehearsal. Observe Prompt Processing data products generated in time. Confirm that data from Special Programs is processed with the same latency as required for main survey data: release of public data within L1publicT and Alerts within OTT1.



LDM-639

4.72.3 Predecessors

4.72.4 Environment Needs

4.72.4.1 Software

4.72.4.2 Hardware

4.72.5 Input Specification

Data from a Special Program that is appropriate for the Prompt pipeline (i.e., a Deep Drilling type series of standard visits from a non-crowded field).

4.72.6 Output Specification

4.72.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from LVV-T866	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is _presumed that these are automated for a given dataset.
	Test Data	
	Expected	An output dataset including difference images and DIASource and DIAObject measurements.
	Result	
1-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
LVV-T866	Test Data	
	Expected	
	Result	

	Description	Confirm that Special Program prompt data products have been generated within 24
2		hours.
	Test Data	No data.
	Expected	
	Result	

DRAFT NOT YET APPROVED – The contents of this document are subject to configuration control by the LSST DM Change Control Board. – DRAFT NOT YET APPROVED



Step Description, Input Data and Expected Result

4.73 LVV-T96 - Verify implementation of Query Repeatability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater
Open LVV-T96 in Jira				

4.73.1 Verification Elements

• LVV-122 - DMS-REQ-0291-V-01: Query Repeatability

4.73.2 Test Items

Verify that prior queries can be rerun with identical results, or with new additional data for live (Alert Production) databases.

4.73.3 Predecessors

- 4.73.4 Environment Needs
- 4.73.4.1 Software
- 4.73.4.2 Hardware
- 4.73.5 Input Specification
- 4.73.6 Output Specification

4.73.7 Test Procedure



Step	Description, Input Data and Expected Result		
1	Description	Select and download (deterministic) random subsample of records from Data Release Object and Source tables.	
·	Test Data	No data.	
	Expected		
	Result		
	Description	Select and download random subsample of PPDB DIAObject and DIASource tables.	
2	Test Data	No data.	
	Expected		
	Result		
2	Description	As appropriate, wait for some amount of non-trivial database usage to occur, such as Prompt Processing ingestion or ingestion of other DRP database tables.	
5	Test Data	No data.	
	Expected		
	Result		
	Description	Re-run the queries in steps 1 and 2 and verify that the resulting data are identical.	
4	Test Data	No data.	
	Expected		
	Result		

4.74 LVV-T97 - Verify implementation of Uniqueness of IDs Across Data Releases

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Kian-Tat Lim
Open LVV-T97 in Jira				

4.74.1 Verification Elements

• LVV-123 - DMS-REQ-0292-V-01: Uniqueness of IDs Across Data Releases



LDM-639

4.74.2 Test Items

Verify that the IDs of Objects, Sources, DIAObjects, and DIASources from different Data Releases are unique.

4.74.3 Predecessors

- 4.74.4 Environment Needs
- 4.74.4.1 Software
- 4.74.4.2 Hardware
- 4.74.5 Input Specification

4.74.6 Output Specification

4.74.7 Test Procedure

Step Description, Input Data and Expected Result

1	Description	Identify an appropriate precursor dataset to be processed through Data Release Produc- tion.
	Test Data	No data.
	Expected	
	Result	
2-1 from	Description	Process data with the Data Release Production payload, starting from raw science images and gen
T1064	Test Data	
11004	Expected	
	Result	
3-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	Test Data	



Step	Description, Input Data and Expected Result					
	Expected Butler repo available for reading.					
	Result					
1	Description	After running the DRP payload multiple times, load the resulting data products (both data release and prompt products) using the Butler.				
	Test Data	No data.				
	Expected	Multiple datasets resulting from processing of the same input data.				
	Result					
	Description	Inspect the IDs in the multiple data products and confirm that all IDs are unique.				
5	Test Data	No data.				
	Expected	No IDs are repeated between multiple processings of the identical input dataset.				
	Result					

Latest Revision 2020-02-17

4.75 LVV-T98 - Verify implementation of Selection of Datasets

Test Spec for LSST Data Management

Version	Status	Priority	Verification Type	Owner	
1	Defined	Normal	Test	Kian-Tat Lim	
Open LVV-T98 in lira					

4.75.1 Verification Elements

• LVV-124 - DMS-REQ-0293-V-01: Selection of Datasets

4.75.2 Test Items

Verify that the DMS can identify and retrieve datasets consisting of logical groupings of Exposures, metadata, provenance, etc., or other groupings that are processed or produced as a logical unit.

4.75.3 Predecessors



4.75.4 Environment Needs

- 4.75.4.1 Software
- 4.75.4.2 Hardware
- 4.75.5 Input Specification

4.75.6 Output Specification

4.75.7 Test Procedure

Step Description, Input Data and Expected Result

Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
Test Data	
Expected	Butler repo available for reading.
Result	
	Description Test Data Expected Result

	Description	Ingest data from an appropriate processed dataset.
2	Test Data	No data.
	Expected	
	Result	
	Description	Observe retrieval of single Processed Visit Image (PVI) with metadata.
3	Test Data	No data.
	Expected	A PVI and its associated metadata.
	Result	
	Description	Observe retrieval of multiple PVIs with metadata.
_		
4	Test Data	No data.
4	Test Data Expected	No data. A set of PVIs and their associated metadata.
4	Test Data Expected Result	No data. A set of PVIs and their associated metadata.
4	Test Data Expected Result Description	No data. A set of PVIs and their associated metadata. Observe retrieval of coadd patch with metadata and provenance information.
4 5	Test Data Expected Result Description Test Data	No data. A set of PVIs and their associated metadata. Observe retrieval of coadd patch with metadata and provenance information. No data.



Fest	Snec	for	ISST	Data	Management
	opee				in an agoin on a

Latest Revision 2020-02-17

Step	Description, Input Data and Expected Result				
	Expected Result	An image of coadded data in a patch, along with its metadata and information describing the provenance of the patch constituents.			
	Description	Observe retrieval of subset of rows in each of the above catalogs.			
6	Test Data	No data.			
	Expected				
	Result				

4.76 LVV-T99 - Verify implementation of Processing of Datasets

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Kian-Tat Lim	
Onen I VV-T99 in lira					

4.76.1 Verification Elements

• LVV-125 - DMS-REQ-0294-V-01: Processing of Datasets

4.76.2 Test Items

Execute AP and DRP, simulate failures, observe correct processing

4.76.3 Predecessors

- 4.76.4 Environment Needs
- 4.76.4.1 Software

4.76.4.2 Hardware



4.76.5 Input Specification

4.76.6 Output Specification

4.76.7 Test Procedure

Step	Description, li	nput Data and Expected Result
	Description	Execute AP and DRP
1	Test Data	No data.
	Expected	
	Result	
	Description	Simulate failures
2	Test Data	No data.
	Expected	
	Result	
	Description	Observe correct processing
3	Test Data	No data.
	Expected	
	Result	

4.77 LVV-T100 - Verify implementation of Transparent Data Access

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Kian-Tat Lim	
Open LVV-T100 in Jira					

4.77.1 Verification Elements

• LVV-126 - DMS-REQ-0295-V-01: Transparent Data Access



LDM-639

4.77.2 Test Items

Test Items

Observe dataset retrieval from multiple LSP instances

4.77.3 Predecessors

- 4.77.4 Environment Needs
- 4.77.4.1 Software
- 4.77.4.2 Hardware
- 4.77.5 Input Specification
- 4.77.6 Output Specification

4.77.7 Test Procedure

Step	Description, Input Data	and Expected Result

	Description	Observe dataset retrieval from multiple LSP instances
1	Test Data	No data.
	Expected	
	Result	

4.78 LVV-T101 - Verify implementation of Transient Alert Distribution

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Kian-Tat Lim	
Open LVV-T101 in Jira					

DRAFT NOT YET APPROVED – The contents of this document are subject to configuration control by the LSST DM Change Control Board. – DRAFT NOT YET APPROVED



4.78.1 Verification Elements

• LVV-3 - DMS-REQ-0002-V-01: Transient Alert Distribution

4.78.2 Test Items

Precursor or simulated data, execute AP, observe distribution to simulated clients using standard protocols

4.78.3 Predecessors

- 4.78.4 Environment Needs
- 4.78.4.1 Software
- 4.78.4.2 Hardware

4.78.5 Input Specification

Obtain precursor or simulated data; duplicated by LVV-T217 – delete?

4.78.6 Output Specification

4.78.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Execute AP	
1	Test Data	No data.	
	Expected		
	Result		
	Description	Observe distribution to simulated clients using standard protocols	
2	Test Data	No data.	



Step Description, Input Data and Expected Result Expected Result

4.79 LVV-T102 - Verify implementation of Solar System Objects Available Within Specified Time

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim
		Open L\	/V-T102 in lira	

4.79.1 Verification Elements

- LVV-36 DMS-REQ-0089-V-01: Solar System Objects Available Within Specified Time
- LVV-1276 OSS-REQ-0127-V-01: Level 1 Data Product Availability
- LVV-9803 DMS-REQ-0004-V-03: Time to availability of Solar System Object orbits

4.79.2 Test Items

Execute single-day operations rehearsal, observe data products generated in time

4.79.3 Predecessors

4.79.4 Environment Needs

4.79.4.1 Software

4.79.4.2 Hardware



4.79.5 Input Specification

4.79.6 Output Specification

4.79.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Execute single-day operations rehearsal		
1	Test Data	No data.		
	Expected			
	Result			
	Description	Observe data products generated in time		
2	Test Data	No data.		
	Expected			
	Result			

4.80 LVV-T103 - Verify implementation of Generate Data Quality Report Within Specified Time

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Kian-Tat Lim
		Open LV	V-T103 in Jira	

4.80.1 Verification Elements

• LVV-38 - DMS-REQ-0096-V-01: Generate Data Quality Report Within Specified Time

4.80.2 Test Items

Verify that the DMS can generate a nightly L1 Data Quality Report within **dqReportCom-plTime = 4[hour]**, in both human- and machine-readable formats.



4.80.3	Predecessors
--------	--------------

4.80.4 Environment Needs

- 4.80.4.1 Software
- 4.80.4.2 Hardware
- 4.80.5 Input Specification
- 4.80.6 Output Specification

4.80.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Execute single-day operations rehearsal	
1	Test Data	No data.	
	Expected		
	Result		
2	Description	After dqReportComplTime = 4[hour] has passed, confirm (via timestamps) that the data quality report has been generated within dqReportComplTime = 4[hour] , and that it contains the correct contents.	
2	Description Test Data	After dqReportComplTime = 4[hour] has passed, confirm (via timestamps) that the data quality report has been generated within dqReportComplTime = 4[hour] , and that it con- tains the correct contents. No data.	

4.81 LVV-T104 - Verify implementation of Generate DMS Performance Report Within Specified Time

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim
Open LVV-T104 in Jira				



4.81.1 Verification Elements

• LVV-40 - DMS-REQ-0098-V-01: Generate DMS Performance Report Within Specified Time

4.81.2 Test Items

Verify that the DMS can generate a nightly Perfomance Report within perfReportComplTime

- 4.81.3 Predecessors
- 4.81.4 Environment Needs
- 4.81.4.1 Software
- 4.81.4.2 Hardware
- 4.81.5 Input Specification
- 4.81.6 Output Specification

4.81.7 Test Procedure

Description, Input Data and Expected Result			
Description	Execute single-day operations rehearsal		
Test Data	No data.		
Expected			
Result			
Description	Observe performance report is generated on time and with correct contents		
Test Data	No data.		
Expected			
Result			
	Description, In Description Test Data Expected Result Description Test Data Expected Result		





LDM-639

4.82 LVV-T105 - Verify implementation of Generate Calibration Report Within **Specified Time**

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim
Open LVV-T105 in Jira				

4.82.1 Verification Elements

• LVV-42 - DMS-REQ-0100-V-01: Generate Calibration Report Within Specified Time

4.82.2 Test Items

Verify that the DMS can generate a night Calibration Report in both human-readable and machine-parseable forms.

4.82.3 Predecessors

4.82.4 Environment Needs

4.82.4.1 Software

4.82.4.2 Hardware

- 4.82.5 Input Specification
- 4.82.6 Output Specification
- 4.82.7 Test Procedure



Step	Description, Input Data and Expected Result				
	Description	Execute single-day operations rehearsal			
1	Test Data	No data.			
	Expected				
	Result				
	Description	Observe calibration report is generated on time and with correct contents			
2	Test Data	No data.			
	Expected				
	Result				

4.83 LVV-T106 - Verify implementation of Calibration Images Available Within Specified Time

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Kian-Tat Lim
		Open L\	/V-T106 in Jira	

4.83.1 Verification Elements

• LVV-58 - DMS-REQ-0131-V-01: Time allowed to process calibs

4.83.2 Test Items

Execute single-day operations rehearsal, observe data products generated

4.83.3 Predecessors

4.83.4 Environment Needs

4.83.4.1 Software



LDM-639

4.83.4.2 Hardware

4.83.5 Input Specification

4.83.6 Output Specification

4.83.7 Test Procedure

Step	Description, I	nput Data and Expected Result
1	Description	Identify a dataset of raw calibration exposures containing at least nCalExpProc = 25 exposures. (If it contains more than 25 exposures, use only 25 for the test.)
•	Test Data	No data.
	Expected	
	Result	
2-1 from LVV-	Description	Execute the Daily Calibration Products Update payload. The payload uses raw calibration images and information from the Transformed EFD to generate a subset of Master Calibration Images and Calibration Database entries in the Data Backbone.
T1059	Test Data	
	Expected	
	Result	
2-2 from	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present and well-formed.
LVV-	Test Data	
T1059	Expected	
	Result	
	Description	Confirm that the processing completed successfully within calProcTime = 1200 seconds .
3	Test Data	No data.
	Expected	Calibration products resulting from processed raw calibration exposures are present
	Result	within calProcTime, and are well-formed images.

4.84 LVV-T107 - Verify implementation of Level-1 Production Completeness

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm

DRAFT NOT YET APPROVED – The contents of this document are subject to configuration control by the LSST DM Change Control Board. – DRAFT NOT YET APPROVED





Latest Revision 2020-02-17

Open LVV-T107 in Jira

4.84.1 Verification Elements

• LVV-115 - DMS-REQ-0284-V-01: Level-1 Production Completeness

4.84.2 Test Items

Verify that the DMS successfully processes all images of sufficiently quality for processing are eventually processed even after connectivity failures.

4.84.3 Predecessors

LVV-T284

- 4.84.4 Environment Needs
- 4.84.4.1 Software
- 4.84.4.2 Hardware
- 4.84.5 Input Specification
- 4.84.6 Output Specification

4.84.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Ingest raw data while simulating failures and outages, observe eventual recovery		
1	Test Data	No data.		
	Expected			
	Result			



4.85 LVV-T108 - Verify implementation of Level 1 Source Association

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm
Open LVV-T108 in Jira				

4.85.1 Verification Elements

• LVV-116 - DMS-REQ-0285-V-01: Level 1 Source Association

4.85.2 Test Items

Verify that the DMS associates DIASources into a DIAObject or SSObject.

- 4.85.3 Predecessors
- 4.85.4 Environment Needs
- 4.85.4.1 Software
- 4.85.4.2 Hardware
- 4.85.5 Input Specification
- 4.85.6 Output Specification
- 4.85.7 Test Procedure
- Step Description, Input Data and Expected Result

Description Delegate to AP

1 Test Data No data.



Step Description, Input Data and Expected Result Expected Result

4.86 LVV-T109 - Verify implementation of SSObject Precovery

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm
Open LVV-T109 in Jira				

4.86.1 Verification Elements

• LVV-117 - DMS-REQ-0286-V-01: SSObject Precovery

4.86.2 Test Items

Verify that the DMS associates additional DIAObjects (both forward and back in time) with objects classified as SSObjects.

4.86.3 Predecessors

- 4.86.4 Environment Needs
- 4.86.4.1 Software
- 4.86.4.2 Hardware
- 4.86.5 Input Specification

4.86.6 Output Specification



LDM-639

4.86.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Delegate to AP		
1	Test Data	No data.		
	Expected			
	Result			

4.87 LVV-T110 - Verify implementation of DIASource Precovery

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm
Open LVV-T110 in Jira				

4.87.1 Verification Elements

• LVV-118 - DMS-REQ-0287-V-01: Max look-back time for precovery

4.87.2 Test Items

Verify that DMS performs forced photometry for new DIAObjects at all available images within the precoveryWindow.

4.87.3 Predecessors

- 4.87.4 Environment Needs
- 4.87.4.1 Software

4.87.4.2 Hardware



4.87.5 Input Specification

4.87.6 Output Specification

4.87.7 Test Procedure

Step	Description, Input Data and Expected Result				
	Description	Execute single-day operations rehearsal, observe data products generated in time			
1	Test Data	No data.			
	Expected				
	Result				

4.88 LVV-T111 - Verify implementation of Use of External Orbit Catalogs

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm
Open LVV-T111 in lira				

4.88.1 Verification Elements

• LVV-119 - DMS-REQ-0288-V-01: Use of External Orbit Catalogs

4.88.2 Test Items

Verify that the DMS can make use of external catalogs to improve identification of SSObjects.

- 4.88.3 Predecessors
- 4.88.4 Environment Needs
- 4.88.4.1 Software



LDM-639

4.88.4.2 Hardware

- 4.88.5 Input Specification
- 4.88.6 Output Specification

4.88.7 Test Procedure

Step	Description, li	nput Data and Expected Result	
	Description	Delegate to AP	
1	Test Data	No data.	
	Expected		
	Result		

4.89 LVV-T112 - Verify implementation of Alert Filtering Service

Version	Status	Priority	Verification Type	Owner	
1	Defined	Normal	Test	Eric Bellm	
Open LVV-T112 in lira					

4.89.1 Verification Elements

• LVV-173 - DMS-REQ-0342-V-01: Alert Filtering Service

4.89.2 Test Items

Verify that user-defined filters can be used to generate a basic alert filtering service.

4.89.3 Predecessors



4.89.4 Environment Needs

- 4.89.4.1 Software
- 4.89.4.2 Hardware
- 4.89.5 Input Specification

4.89.6 Output Specification

4.89.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Identify a suitable precursor dataset for processing through the Alert Production pipeline.
1	Test Data	No data.
	Expected	
	Result	
2-1 from LVV-T866	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is _presumed that these are automated for a given dataset.
	Test Data	
	Expected	An output dataset including difference images and DIASource and DIAObject measurements.
	Result	
2-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable
LVV-T866	Test Data	
	Expected	
	Result	

2	Description	Confirm that alerts are generated, and that an Alert Distribution service is making them available via a stream.
2	Test Data	No data.
	Expected	Via either a UI or API, confirmation that a stream of alerts are available.
	Result	



Step	Description, I	Description, Input Data and Expected Result		
4	Description	Confirm that a UI (or API) exists that allows users to define simple filters. Define a fil- ter, and observe both the full and the filtered alert streams to confirm that the filter has reduced the volume of alerts.		
	Test Data	No data.		
	Expected	The user-defined filter has reduced the number of alerts being received relative to the full		
	Result	stream.		

4.90 LVV-T113 - Verify implementation of Performance Requirements for LSST Alert Filtering Service

Version	Status	Priority	Verification Type	Owner		
1	Defined	Normal	Test	Eric Bellm		
Open LVV-T113 in lira						

4.90.1 Verification Elements

• LVV-174 - DMS-REQ-0343-V-01: Number of full-size alerts

4.90.2 Test Items

Verify that the DMS alert filter service provides sufficient bandwidth for **numBrokerUsers = 100** simultaneously-operating brokers to receive up to **numBrokerAlerts = 20** alerts per visit.

4.90.3 Predecessors

- 4.90.4 Environment Needs
- 4.90.4.1 Software

4.90.4.2 Hardware



4.90.5 Input Specification

4.90.6 Output Specification

4.90.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Create a simulated alert stream.	
1	Test Data	No data.	
	Expected		
	Result		
2	Description	Simultaneously execute user-defined alert filters for at least numBrokerUsers = 100 users, and confirm that the system successfully filters the stream as requested. Confirm that the bandwidth requirement of numBrokerAlerts = 20 per user was met.	
	Test Data	No data.	
	Expected	All of the (simulated) users successfully receive their requested filtered alerts, with num -	
	Result	BrokerAlerts = 20 per user.	

4.91 LVV-T114 - Verify implementation of Pre-defined alert filters

Version	Status	Priority	Verification Type	Owner		
1	Defined	Normal	Test	Eric Bellm		
Open LVA/ T114 in live						

Open LVV-T114 in Jira

4.91.1 Verification Elements

• LVV-179 - DMS-REQ-0348-V-01: Pre-defined alert filters

4.91.2 Test Items

Verify that users of the Alert Filtering service can use a predefined set of filters.

4.91.3 Predecessors



4.91.4 Environment Needs

- 4.91.4.1 Software
- 4.91.4.2 Hardware
- 4.91.5 Input Specification
- 4.91.6 Output Specification

4.91.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Create a simulated alert stream. Confirm that alerts are generated, and that an Alert
1		Distribution service is making them available.
	Test Data	No data.
	Expected	A stream of alerts that is confirmed to be generated and distributed.
	Result	
	Description	Confirm that a UI (or API) exists that presents users some pre-defined filters.
2	Test Data	No data.
	Expected	The UI (or API) for accessing alert streams has some pre-defined filters available for users.
	Result	
3	Description	Select one of the pre-defined filters, and confirm that the results have been properly fil- tered.
5	Test Data	No data.
	Expected	After applying the pre-defined filter, the number of alerts has decreased relative to the
	Result	raw stream.

4.92 LVV-T115 - Verify implementation of Calibration Production Processing

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Kian-Tat Lim

Open LVV-T115 in Jira



4.92.1 Verification Elements

• LVV-120 - DMS-REQ-0289-V-01: Calibration Production Processing

4.92.2 Test Items

Execute CPP on a variety of representative cadences, and verify that the calibration pipeline correctly produces necessary calibration products.

4.92.3 Predecessors

4.92.4 Environment Needs

- 4.92.4.1 Software
- 4.92.4.2 Hardware
- 4.92.5 Input Specification

4.92.6 Output Specification

4.92.7 Test Procedure

Step	Description, li	Description, Input Data and Expected Result		
1	Description	Identify a suitable set of calibration frames, including biases, dark frames, and flat-field frames.		
	Test Data	No data.		
	Expected			
	Result			
2-1 from LVV-	Description	Execute the Calibration Products Production payload. The payload uses raw calibration images and information from the Transformed EFD to generate a subset of Master Calibration Images and Calibration Database entries in the Data Backbone.		
2-1 from LVV- T1060	Description	Execute the Calibration Products Production payload. The payload uses raw calibration images and information from the Transformed EFD to generate a subset of Master Calibration Images and Calibration_Database_entries_in_the_Data_Backbone.		
2-1 from LVV- T1060	Description Test Data Expected	Execute the Calibration Products Production payload. The payload uses raw calibration images and information from the Transformed EFD to generate a subset of Master Calibration Images and Cali		

DRAFT NOT YET APPROVED – The contents of this document are subject to configuration control by the LSST DM Change Control Board. – DRAFT NOT YET APPROVED



LDM-639

Latest Revision 2020-02-17

Step	Description, l	nput Data and Expected Result
2-2 from	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present and well-formed.
LVV- T1060	Test Data	
	Expected	
	Result	

	Description	Confirm that the expected data products are created, and that they have the expected
3		properties.
0	Test Data	No data.
	Expected	Repos containing valid calibration products that are well-formed and ready to be applied
	Result	to processed datasets.

4.93 LVV-T116 - Verify implementation of Associating Objects across data releases

Versior	n Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Kian-Tat Lim	
Open LVV-T116 in lira					

4.93.1 Verification Elements

• LVV-181 - DMS-REQ-0350-V-01: Associating Objects across data releases

4.93.2 Test Items

Load DR, observe queryable association

4.93.3 Predecessors

4.93.4 Environment Needs

4.93.4.1 Software



LDM-639

4.93.4.2 Hardware

4.93.5 Input Specification

4.93.6 Output Specification

4.93.7 Test Procedure

Step	Description, In	put Data and Expected Result
	Description	Load DR
1	Test Data	No data.
	Expected	
	Result	
	Description	Observe queryable association
2	Test Data	No data.
	Expected	
	Result	

4.94 LVV-T117 - Verify implementation of DAC resource allocation for Level 3 processing

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Colin Slater	
Open LVV-T117 in Jira					

4.94.1 Verification Elements

• LVV-47 - DMS-REQ-0119-V-01: DAC resource allocation for Level 3 processing

4.94.2 Test Items

Verify that compute time and storage space allocations can be granted to science users.



- 4.94.3 Predecessors
- 4.94.4 Environment Needs
- 4.94.4.1 Software
- 4.94.4.2 Hardware
- 4.94.5 Input Specification
- 4.94.6 Output Specification

4

4.94.7	Test Procedur	e					
Step	Description, Input Data and Expected Result						
	Description	Create a test user account for the Science Platform.					
1	Test Data	No data.					
	Expected						
	Result						
	Description	Set the LSP resource allocations for the test user to very low values.					
2	Test Data	No data.					
	Expected						
	Result						
3	Description	Initiate example batch jobs and notebook sessions that will exceed the specified resource limits.					
	Test Data	No data.					
	Expected	Quota error.					
	Result						
4	Description	Transfer sufficient data volumes into the user workspace and MyDB tables that would exceed the resource quotas.					
	Test Data	No data.					
	Expected	Quota error.					
	Result						
	Description	Reset the user resource quotas to normal values.					



Step	Description, Input Data and Expected Result				
	Test Data	No data.			
	Expected				
	Result				
6	Description	Initiate the same example batch jobs and notebook sessions that previously caused an error.			
0	Test Data	No data.			
	Expected	Successful notebook and batch job execution.			
	Result				
7	Description	Transfer the same data volumes into the user workspace and MyDB tables that previously caused an error.			
/	Test Data	No data.			
	Expected	Successful data transfer.			
	Result				

4.95 LVV-T118 - Verify implementation of Level 3 Data Product Self Consistency

Version	Status	Priority	Verification Type	Owner				
1	Draft	Normal	Test	Colin Slater				
Open LVV-T118 in Jira								

4.95.1 Verification Elements

• LVV-48 - DMS-REQ-0120-V-01: Level 3 Data Product Self Consistency

4.95.2 Test Items

Verify that user-driven Level 3 processing is conducted on consistent sets of input data.

4.95.3 Predecessors


4.95.4 Environment Needs

- 4.95.4.1 Software
- 4.95.4.2 Hardware
- 4.95.5 Input Specification
- 4.95.6 Output Specification

4.95.7 Test Procedure

Step	Description, Input Data and Expected Result					
	Description	Execute representative processing on DR in PDAC, observe consistency				
1	Test Data	No data.				
	Expected					
	Result					

4.96 LVV-T119 - Verify implementation of Provenance for Level 3 processing at DACs

Version	Status	Priority	Verification Type	Owner		
1	Draft	Normal	Test	Colin Slater		
Open LVV-T119 in Jira						

4.96.1 Verification Elements

- LVV-49 DMS-REQ-0121-V-01: Provenance for Level 3 processing at DACs
- LVV-1234 OSS-REQ-0122-V-01: Provenance



4.96.2 Test Items

Verify that provenance information is recorded and accessible for user-generated Level 3 products.

- 4.96.3 Predecessors
- 4.96.4 Environment Needs
- 4.96.4.1 Software
- 4.96.4.2 Hardware
- 4.96.5 Input Specification
- 4.96.6 Output Specification

4.96.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Execute representative processing on DR in PDAC, observe provenance recording
1	Test Data	No data.
	Expected	
	Result	

4.97 LVV-T120 - Verify implementation of Software framework for Level 3 catalog processing

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater

Open LVV-T120 in Jira



4.97.1 Verification Elements

• LVV-53 - DMS-REQ-0125-V-01: Software framework for Level 3 catalog processing

4.97.2 Test Items

Verify that user-driven Level 3 processing can be consistently applied to all records in a catalog.

- 4.97.3 Predecessors
- 4.97.4 Environment Needs
- 4.97.4.1 Software
- 4.97.4.2 Hardware
- 4.97.5 Input Specification
- 4.97.6 Output Specification
- 4.97.7 Test Procedure

Step	Description, Input Data and Expected Result						
	Description	Execute representative processing on DR in PDAC, observe recognition of and recovery					
1		from failures					
	Test Data	No data.					
	Expected						
	Result						

4.98 LVV-T121 - Verify implementation of Software framework for Level 3 image processing



Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater
		Open LV	V-T121 in lira	

4.98.1 Verification Elements

• LVV-56 - DMS-REQ-0128-V-01: Software framework for Level 3 image processing

4.98.2 Test Items

Verify that user-specified Level 3 processing can be applied to the desired set of images.

- 4.98.3 Predecessors
- 4.98.4 Environment Needs
- 4.98.4.1 Software
- 4.98.4.2 Hardware
- 4.98.5 Input Specification
- 4.98.6 Output Specification
- 4.98.7 Test Procedure
- Step Description, Input Data and Expected Result

 Description
 Execute representative processing on DR in PDAC, observe recognition of and recovery from failures

 Test Data
 No data.

 Expected
 Result



4.99 LVV-T122 - Verify implementation of Level 3 Data Import

Version	Status	Priority	Verification Type	Owner		
1	Draft	Normal	Test	Colin Slater		
Open LVV-T122 in Jira						

4.99.1 Verification Elements

LVV-121 - DMS-REQ-0290-V-01: Level 3 Data Import

4.99.2 Test Items

Verify that the Science Platform can ingest data from community-standard file formats.

- 4.99.3 Predecessors
- 4.99.4 Environment Needs
- 4.99.4.1 Software
- 4.99.4.2 Hardware
- 4.99.5 Input Specification
- 4.99.6 Output Specification
- 4.99.7 Test Procedure

Step	Step Description, Input Data and Expected Result					
	Description	Use the Science Platform catalog upload tool to ingest a small example FITS table.				

			0 1	0	
1	Test Data	No data.			



Test	Spec	for	LSST	Data	Management
	opee			Duru	in an agoin one

Step	Description, Input Data and Expected Result					
	Expected					
	Result					
	Description	Use the Science Platform catalog upload tool to ingest a small example CSV table.				
2	Test Data	No data.				
	Expected					
	Result					
2	Description	Use the Science Platform catalog upload tool to ingest a large FITS table that needs to be spatially-sharded in the database.				
0	Test Data	No data.				
	Expected					
	Result					
	Description	Perform example queries on each of the three tables to verify that all data is present.				
4	Test Data	No data.				
	Expected	Data returned in the queries is identical to the data uploaded.				
	Result					

4.100 LVV-T123 - Verify implementation of Access Controls of Level 3 Data Products

Version	Status	Priority	Verification Type	Owner		
1	Draft	Normal	Test	Robert Gruendl		
Open LVV-T123 in Jira						

4.100.1 Verification Elements

• LVV-171 - DMS-REQ-0340-V-01: Access Controls of Level 3 Data Products

4.100.2 Test Items

This test touches upon the interface between the following areas: IT Security, Identity Management, LSP Portal, and Parallel Distributed Database. The purpose is to show that access



LDM-639

Latest Revision 2020-02-17

to user generated data products (previously Level 3) can have a variety of access restrictions varying from single-user, a list, a named group, or open access.

4.100.3 Predecessors

- 4.100.4 Environment Needs
- 4.100.4.1 Software
- 4.100.4.2 Hardware
- 4.100.5 Input Specification
- 4.100.6 Output Specification

4.100.7 Test Procedure

Description, Input Data and Expected Result		
Description	Configure representative access controls in PDAC, observe proper restrictions	
Test Data	No data.	
Expected		
Result		
	Description, li Description Test Data Expected Result	

4.101 LVV-T124 - Verify implementation of Software Architecture to Enable Community Re-Use

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Simon Krughoff
Open LVV-T124 in lira				



4.101.1 Verification Elements

• LVV-139 - DMS-REQ-0308-V-01: Software Architecture to Enable Community Re-Use

4.101.2 Test Items

Show that the LSST software is capable of being executed in multiple contexts: single user instance, batch processing, continuous integration.

Also show that the algorithms can be reconfigured and, if desired, completely replaced at run time.

4.101.3 Predecessors

- 4.101.4 Environment Needs
- 4.101.4.1 Software
- 4.101.4.2 Hardware
- 4.101.5 Input Specification
- 4.101.6 Output Specification

4.101.7 Test Procedure



Step	Description.	Input Data and	Expected Result
ocep	Description	inpac baca and	

1-1 from LVV-T860	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:
		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash
		From the command line, execute the commands below in the example code:
	Test Data	
	Expected	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.
		To check versions in use, type: _eups list -s
2	Description	Using curated test datasets for multiple precursor instruments, verify and log that the prototype DRP pipelines execute successfully in three contexts: 1. The CI system 2. On a single user system: laptop, desktop, or notebook running in the Notebook aspect of the LSP. 3. Project workflow system
	Test Data	No data.
	Expected Result	
3	Description	 Using a template testing notebook in the Notebook aspect of the LSP, verify and log the following: 1. Individual pipeline steps (tasks) are importable and executable on their own. this is not comprehensive, but demonstrative. 2. Individual pipeline steps may be overridden by configuration. 3. Users can implement a custom pipeline step and insert i into the processing flow via configuration.
	Test Data	No data.
	Expected Result	
4-1 from LVV-T987	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- _lowing:



		Test Spec for LSST Data Management	LDM-639	Latest Revision 2020-02-17
Stop	Description I	anut Data and Exported Posult		
Step		iput Data and Expected Result		
	Test Data			
	Expected	Butler repo available for reading.		
	Result			
5	Description	Read the resulting dataset using the products.	Bulter, and confirm th	at it produced the desired data
•	Test Data	No data.		
	Expected			
	Result			
6	Description	Run subset of full DRP from previous easy? Did the performance scale ap	step on an individual r propriately?	node. Was this organizationally
0	Test Data	No data.		
	Expected			
	Result			
	Description	Re-run aperture correction on subse	t. Verify that same re	esults as DRP run are achieved.
7	Test Data	No data.		
	Expected			
	Result			
8	Description	Re-run photometric redshift estimat same results are achieved as from fu	ion algorithm on subs	set coadd catalogs. Verify that
0	Test Data	No data.		
	Expected			
	Result			

4.102 LVV-T125 - Verify implementation of Simulated Data

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Lupton
Open LVV-T125 in Jira				



LDM-639

4.102.1 Verification Elements

• LVV-6 - DMS-REQ-0009-V-01: Simulated Data

4.102.2 Test Items

Verify that the DMS can inject simulated data into data products for testing.

4.102.3	Predecessors
4.102.4	Environment Needs
4.102.4.1	Software
4.102.4.2	2 Hardware
4.102.5	Input Specification
4.102.6	Output Specification
4.102.7	Test Procedure
Step	Description, Input Data and Expected Result
	Description Delegate to AP and DRP
1	Test Data No data.
	Expected
	Result

4.103 LVV-T126 - Verify implementation Image Differencing

Version Status Priority Verification Type Owner



Latest Revision 2020-02-17

1 Draft Normal Test Eric Bellm

Open LVV-T126 in Jira

4.103.1 Verification Elements

• LVV-14 - DMS-REQ-0032-V-01: Image Differencing

4.103.2 Test Items

Verify that the DMS can performance image differencing from single exposures and coadds.

4.103.3 Predecessors

- 4.103.4 Environment Needs
- 4.103.4.1 Software
- 4.103.4.2 Hardware
- 4.103.5 Input Specification
- 4.103.6 Output Specification

4.103.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Delegate to AP and DRP
1	Test Data	No data.
-	Expected	
	Result	



4.104 LVV-T127 - Verify implementation of Provide Source Detection Software

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton
Open LVV-T127 in Jira				

4.104.1 Verification Elements

• LVV-15 - DMS-REQ-0033-V-01: Provide Source Detection Software

4.104.2 Test Items

Verify that the DMS provides source detection software that can be applied to calibrated images, including both difference images and coadds. This will be verified using simulated data, but could also be done by inserting artificial sources into existing datasets.

4.104.3 Predecessors

4.104.4 Environment Needs

4.104.4.1 Software

4.104.4.2 Hardware

- 4.104.5 Input Specification
- 4.104.6 Output Specification

4.104.7 Test Procedure



Step	Description, l	nput Data and Expected Result
1	Description	Run DRP and AP processing, including source detection and measurement algorithms, on a small portion of the data from a simulated dataset.
·	Test Data	No data.
	Expected	Source catalogs containing measurements of all sources detected in the input images.
	Result	
2	Description	Confirm that the output repos contain catalogs of source detections. Compare these out- put catalogs to the original simulated source catalogs, and confirm that a large fraction of the sources within a reasonable signal-to-noise range were recovered.
	Test Data	No data.
	Expected	Most sources above a reasonable S/N threshold were detected, and their measured fluxes
	Result	are reasonably close to the simulated inputs.

4.105 LVV-T128 - Verify implementation Provide Astrometric Model

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater
		Open LV	V-T128 in lira	

4.105.1 Verification Elements

• LVV-17 - DMS-REQ-0042-V-01: Provide Astrometric Model

4.105.2 Test Items

Verify that an astrometric model is available for Objects and DIAObjects.

4.105.3 Predecessors

4.105.4 Environment Needs

4.105.4.1 Software



LDM-639

- 4.105.4.2 Hardware
- 4.105.5 Input Specification
- 4.105.6 Output Specification

4.105.7 Test Procedure

Step	Description, li	nput Data and Expected Result	
	Description	Delegate to AP and DRP	
1	Test Data	No data.	
	Expected		
	Result		

4.106 LVV-T129 - Verify implementation of Provide Calibrated Photometry

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton
		Open L	VV-T129 in lira	

4.106.1 Verification Elements

• LVV-18 - DMS-REQ-0043-V-01: Provide Calibrated Photometry

4.106.2 Test Items

Verify that the DMS provides photometry calibrated in AB mags and fluxes (in nJy) for all measured objects and sources. Must be tested for both DRP and AP products.

4.106.3 Predecessors



4.106.4 Environment Needs

- 4.106.4.1 Software
- 4.106.4.2 Hardware
- 4.106.5 Input Specification

4.106.6 Output Specification

4.106.7 Test Procedure

Step Description, Input Data and Expected Result

Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
Test Data	
Expected	Butler repo available for reading.
Result	
	Description Test Data Expected Result

	Description	Ingest the data products from an appropriate DRP-processed dataset.
2	Test Data	No data.
	Expected	
	Result	~
3	Description	Confirm that AB-calibrated magnitudes and fluxes are available for all measured Sources and Objects. [An enhanced verification could include matching the sources to an external source catalog and comparing the magnitudes to show that they are well-calibrated.]
	Test Data	No data.
	Expected	Calibrated fluxes and magnitudes are available for all sources, as well as tools to convert
	Result	measured fluxes to magnitudes (and vice-versa).
	Description	Ingest the data products from an appropriate AP processing dataset.
4	Test Data	No data.
	Expected	
	Result	



. _

LDM-639

Step	Description, Input Data and Expected Result		
5	Description	Confirm that AB-calibrated magnitudes and fluxes are available for all measured Sources, DIASources, and Objects. [An enhanced verification could include matching the sources to an external source catalog and comparing the magnitudes to show that they are well- calibrated.]	
	Test Data	No data.	
	Expected	Calibrated fluxes and magnitudes are available for all Sources, DIASources, and Objects,	
	Result	as well as tools to convert measured fluxes to magnitudes (and vice-versa).	

. .

4.107 LVV-T130 - Verify implementation of Enable a Range of Shape Measurement Approaches

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater
		OpenIV	V T120 in lira	

Open LVV-T130 in Jira

4.107.1 Verification Elements

• LVV-21 - DMS-REQ-0052-V-01: Enable a Range of Shape Measurement Approaches

4.107.2 Test Items

Verify that multiple shape measurement algorithms can be used.

4.107.3 Predecessors

- 4.107.4 Environment Needs
- 4.107.4.1 Software

4.107.4.2 Hardware



4.107.5 Input Specification

4.107.6 Output Specification

4.107.7 Test Procedure

Step	Description, Input Data and Expected Result	
		-

	Description	Delegate to AP and DRP
1	Test Data	No data.
	Expected	
	Result	

4.108 LVV-T131 - Verify implementation of Provide User Interface Services

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Gregory Dubois-Felsmann
		0	pen LVV-T131 in Jira	3

4.108.1 Verification Elements

• LVV-63 - DMS-REQ-0160-V-01: Provide User Interface Services

4.108.2 Test Items

Verify the availability and functionality of the broad range of user interface services called for in the requirement, as applied to both Nightly and DRP data. This will primarily be done by verifications performed at the LSST Science Platform level, based on the requirements in LDM-554; however, a high-level set of tests corresponding to the DMS-REQ-0160 requirement are defined below.

4.108.3 Predecessors





4.108.4 Environment Needs

4.108.4.1 Software

4.108.4.2 Hardware As noted in Verification Configuration, the systems required to carry out the tests include both an "inside" test execution platform - the ability to execute test notebooks within the Science Platform Notebook Aspect - and an "outside" test execution platform with connectivity to the Science Platform instance under test that is comparable to that available to offsite science users.

Test Spec for LSST Data Management

4.108.5 Input Specification

- 1. Testing this requirement relies on a set of data products meeting the data model implied by the DPDD existing in a deployment of the Science Platform and its underlying database and file services.
 - (a) In particular, both image and catalog data products are required.
 - (b) From the specific language of the underlying requirement, it appears clear that coadded data products are required, but in practice single-epoch data products should be included in the test as well.
- 2. Depending on when this requirement is tested, the tests may involve either or both of precursor data and LSST commissioning data. The use of the latter is ultimately essential to ensure that the tests are performed with as LSST-like a dataset as possible.

4.108.6 Output Specification

4.108.7 Test Procedure



Step Description, Input Data and Expected Result

	Description	Establishment of test coordinates:
1		Establish sky positions and surrounding regions (e.g., cones or polygons), field sizes, filter bands, and temporal epochs for the tests that are consistent with the known content of the test dataset, whether precursor or LSST commissioning data. Establishing sky positions should include pre-determining the corresponding LSST "tract and patch" identifiers. If the plan to not keep all calibrated single-epoch images on disk is still in place at the time of the test, identify for use in the test both images that are, and are not, on disk. Establish target image boundaries, projections, and pixel scales to be used for resampling tests. Ensure that at least some of these test conditions include coadded image bound- aries that cross tract and patch boundaries, and single-epoch image boundaries that cross
	Test Data	No data.
	Expected	
	Result	
	Description	Butler image access:
	-	
2		From within the Notebook Aspect, verify that coadded images for the identified regions of sky and filter bands are accessible via the Butler. Verify that the same images are available whether obtained by direct reference to the previous established tract/patch identifiers or by the use of LSST stack code for retrieving images based on sky coordinates. From within the Notebook Aspect, verify that single-epoch raw images for the selected locations and times are available. Verify that calibrated images (PVIs) for the selected locations and times are available; depending on the details of the test dataset, verify that PVIs still on disk can be retrieved immediately. Verify that lists or tables of image metadata, not just individual images, can be retrieved. E.g., a list of all the single-epoch images covering a selected sky location.
2	Test Data	From within the Notebook Aspect, verify that coadded images for the identified regions of sky and filter bands are accessible via the Butler. Verify that the same images are available whether obtained by direct reference to the previous established tract/patch identifiers or by the use of LSST stack code for retrieving images based on sky coordinates. From within the Notebook Aspect, verify that single-epoch raw images for the selected locations and times are available. Verify that calibrated images (PVIs) for the selected locations and times are available; depending on the details of the test dataset, verify that PVIs still on disk can be retrieved immediately. Verify that lists or tables of image metadata, not just individual images, can be retrieved. E.g., a list of all the single-epoch images covering a selected sky location. No data.
2	Test Data Expected	From within the Notebook Aspect, verify that coadded images for the identified regions of sky and filter bands are accessible via the Butler. Verify that the same images are available whether obtained by direct reference to the previous established tract/patch identifiers or by the use of LSST stack code for retrieving images based on sky coordinates. From within the Notebook Aspect, verify that single-epoch raw images for the selected locations and times are available. Verify that calibrated images (PVIs) for the selected locations and times are available; depending on the details of the test dataset, verify that PVIs still on disk can be retrieved immediately. Verify that lists or tables of image metadata, not just individual images, can be retrieved. E.g., a list of all the single-epoch images covering a selected sky location. No data.



Step Description, Input Data and Expected Result

Description Programmatic PVI re-creation:

3

From within the Notebook Aspect, verify that the recreation on demand of a PVI can be performed. Ideally, this should be done as follows:

- Verify that recreation of a PVI that is still available works and that it reproduces the original PVI exactly (except for provenance metadata that must be different) or within the reasonable ability of processing systems to do so (e.g., taking into account that the original calibration and the recreation may have run on different CPU architectures).
- The test conditions should ensure the verification that a recreation was actually performed, i.e., that the still-available PVI was not returned instead.
- Note that it does not appear to be a requirement that at Butler level recreation on demand of PVIs is a completely transparent process. If this is decided to be a requirement, the test must also verify that it has been satisfied. If it is not a requirement, verify that adequate documentation on the PVI-recreation process (e.g., the SuperTasks and configuration to be used) is available.

	Test Data	No data.
	Expected	
	Result	
	Description	Butler catalog access:
4		From within the Notebook Aspect, verify that all the catalog data products described in
		the DPDD can be retrieved for the coordinates selected above via the Butler. (This test
		should include access to SSObject data, but the details of how such a test would depend
	Test Data	On the coordinate selections require additional thought.)
	Exported	
	Expected	
	Result	
	Description	LSST-stack-based resampling/reprojection:
5		Verify the availability of software in the LSST stack, and associated documentation, that
		permits the resampling of LSST images to different pixel grids and projections.
		Exercise this capability for the test conditions selected in Step 1 above.
		Perform photometric and astrometric tests on the resulting resampled images to provide
		evidence that the transformations performed were correct to the accuracy supported by
	Test Data	the data.
	Test Data	No data.
	F ()	
	Expected	



Step Description, Input Data and Expected Result

6	Description Test Data Expected Result	Comment: The following API Aspect test steps should be carried out on the required "offsite-like" test platform, to ensure that their success does not reflect any privileged access given to processes inside the Data Access Center or other Science Platform instance. However, at least a small sampling of them should <i>also</i> be carried out <i>within</i> the Science Platform environment, i.e., in the Notebook Aspect, and the results compared. No data.
7	Description	API Aspect image access: Using IVOA services such as the Registry and ObsTAP, from the "offsite-like" test platform, verify that the existence of the classes of image data products foreseen in the DPDD can be determined. Verify that ObsTAP and/or SIAv2 can be used to find the same images and lists of images for the established test coordinates that were retrieved via the Butler in Step 2 above. Verify that the selected images are retrievable from the Web services. Verify that the retrieved images are identical in their pixel content and metadata. The tests must include both coadded and single-epoch images.
	Test Data Expected Result	No data.
8	Description Test Data Expected Result	API Aspect image transformations: Verify that image cutouts and resamplings can be performed via the IVOA SODA service, and that the results are identical to those obtained for the same parameters from the LSST-stack-based tests in Step 5. (The requirements for supported reprojections, if any, in the SODA service have not been established at the time of writing.) No data.
9	Description Test Data	API Aspect catalog data access: Verify that the IVOA Registry, RegTAP, TAP_SCHEMA, and other relevant mechanisms can be used to discover the existence of all the catalog data products foreseen in the DPDD. Using the IVOA TAP service, verify that all the catalog data products foreseen in the DPDD can be retrieved for the coordinates determined in Step 1. Verify that their scientific content is the same as when they are retrieved via the Butler. No data.



Step	Description, li	nput Data and Expected Result
	Expected	
	Result	
	Description	Comment:
10		The Portal Aspect tests below should be carried out from a web browser on an "offsite- like" test platform, to ensure that no privileged access provided to intra-data-center clients is relied upon.
	Test Data	No data.
	Expected	
	Result	
	Description	Portal Aspect data browsing:
11		Verify that the Portal Aspect can be used to discover the existence of all the data products foreseen in the DPDD. Verify that the UI permits locating the data for the coordinates selected in Step 1 by visual means, e.g., by zooming and panning in from an all-sky view. Verify that the UI permits locating the data by typing in coordinates as well.
	Test Data	No data.
	Expected	
	Result	
12	Description	Portal Aspect image access: Verify that the Portal Aspect allows both the retrieval of "original" image data, i.e., in its native LSST pixel projection and with full metadata, as well as retrieval of on-demand UI cutouts of coadded image data for selected locations.
	Test Data	No data.
	Expected	
	Result	
	Description	Portal Aspect catalog query and visualization:
13		verify that the Portal Aspect allows graphical querying of DPDD catalog data, both coad- ded and single-epoch, for selected regions of sky and/or with selected properties, and supports the visualization of the results (including histogramming, scatterplots, time se- ries, table manipulations, and overplotting on image data). (Note that the Science Platform requirements, LDM-554, lay out a detailed set of require- ments on the selection and visualization of catalog data.)
	Test Data	No data.
	Expected	
	Result	



LDM-639

Step	Description, Input Data and Expected Result		
14	Description	Portal Aspect data download: Verify that data identified and/or visualized in the Portal Aspect can be downloaded to the remote system running the web browser in which the Portal is displayed, as well as to the User Workspace.	
	Test Data	No data.	
	Expected		
	Result		

4.109 LVV-T132 - Verify implementation of Pre-cursor and Real Data

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Robert Gruendl
		Open LV	V-T132 in lira	

4.109.1 Verification Elements

• LVV-127 - DMS-REQ-0296-V-01: Pre-cursor, and Real Data

4.109.2 Test Items

Demonstrate that pixel-oriented data from astronomical imaging cameras (precursor or otherwise) can be processed using LSST Science Algorithms and organized for access through the Data Butler Access Client.

4.109.3 Predecessors

- 4.109.4 Environment Needs
- 4.109.4.1 Software

4.109.4.2 Hardware



4.109.5 Input Specification

4.109.6 Output Specification

4.109.7 Test Procedure

Step Description, Input Data and Expected Result

1	Description	Confirm that the Cl jobs used to test DRP processing successfully run. These jobs use precursor datasets from cameras other than LSST.
·	Test Data	No data.
	Expected	
	Result	
2	Description	For the precursor dataset, instantiate the Butler, load the data products, and confirm that they exist as expected.
2	Description Test Data	For the precursor dataset, instantiate the Butler, load the data products, and confirm that they exist as expected. No data.
2	Description Test Data Expected	For the precursor dataset, instantiate the Butler, load the data products, and confirm that they exist as expected. No data. Processed images, catalogs, calibration information, and other related data products are

4.110 LVV-T133 - Verify implementation of Provide Beam Projector Coordinate Calculation Software

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Lupton
		Open L\	/V-T133 in Jira	

4.110.1 Verification Elements

• LVV-182 - DMS-REQ-0351-V-01: Provide Beam Projector Coordinate Calculation Software

4.110.2 Test Items

Verify that the DMS provides software to calculate coordinates relating the collimated beam projector position and telescope pupil position to the illumination position on the telescope



optical elements and focal plane.

4.110.3 Predecessors

- 4.110.4 Environment Needs
- 4.110.4.1 Software
- 4.110.4.2 Hardware
- 4.110.5 Input Specification

4.110.6 Output Specification

4.110.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	On the LSST development cluster or notebook aspect, git clone the repo containing the	
1		CBP package: https://github.com/lsst/cbp	
	Test Data	No data.	
	Expected		
	Result		
	Description	Follow the steps in the package README to install the package.	
2	Test Data	No data.	
	Expected		
	Result		
3	Description	Confirm that the package can be loaded in python, and that some of the tests in the 'tests/' folder will execute.	
	Test Data	No data.	
	Expected	Successful execution of test scripts, which demonstrate the calculation of beam projector	
	Result	coordinates.	

4.111 LVV-T134 - Verify implementation of Provide Image Access Services



Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Inspection	Gregory Dubois-Felsmann
Open LVV-T134 in Jira				

4.111.1 Verification Elements

• LVV-27 - DMS-REQ-0065-V-01: Provide Image Access Services

4.111.2 Test Items

Verify that images can be identified and that images and image cut-outs can be retrieved using the network interfaces - primarily IVOA standards-based - and Python APIs provided for image access by science users.

4.111.3 Predecessors

4.111.4 Environment Needs

4.111.4.1 Software

4.111.4.2 Hardware

4.111.5 Input Specification

Testing requires the establishment of running services such as SIAv2 and SODA to which the tests can be applied.

4.111.6 Output Specification

4.111.7 Test Procedure



Step	Description, Input Data and Expected Result			
1	Description Inspect that the following test cases have been executed and passed: LVV-T803, LVV-T810 LVV-T811, LVV-T812.			
	The requirement is fully satisfied by lower-level LSP test cases.			
	Test Data No data.			
	Expected Test cases LVV-T803, LVV-T810, LVV-T811, LVV-T812 passed without blocking issues.			
	Result			

4.112 LVV-T136 - Verify implementation of Data Product and Raw Data Access

Version	Status	Priority	Verification Type	Owner	
1	Defined	Normal	Test	Colin Slater	
Open LVV-T136 in Jira					

4.112.1 Verification Elements

• LVV-129 - DMS-REQ-0298-V-01: Data Product and Raw Data Access

4.112.2 Test Items

Verify that available image, file, and catalog data products, and their metadata and provenance information, can be listed and retrieved.

4.112.3 Predecessors

- 4.112.4 Environment Needs
- 4.112.4.1 Software

4.112.4.2 Hardware



4.112.5 Input Specification

4.112.6 Output Specification

4.112.7 Test Procedure

Step	Description, Input Data and Expected Result		
1	Description	Details of the Gen3 Butler and ObsTAP tables are still being worked out. The gener overview of this test will be to use some combination of the Gen3 Butler and TAP acce to the ObsTAP tables to test that the required access is provided.	
	Test Data	No data.	
	Expected Result	ted Verification that the relevant data products and their related tables, metadata, and protect nance information are available and readily accessible.	

4.113 LVV-T137 - Verify implementation of Data Product Ingest

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Colin Slater
		Open LVV	/-T137 in lira	

4.113.1 Verification Elements

• LVV-130 - DMS-REQ-0299-V-01: Data Product Ingest

4.113.2 Test Items

Verify that data products can be ingested.

4.113.3 Predecessors

4.113.4 Environment Needs

4.113.4.1 Software



LDM-639

4.113.4.2 Hardware

4.113.5 Input Specification

4.113.6 Output Specification

4.113.7 Test Procedure

Result

Step Description, Input Data and Expected Result Description Identify a suitable set of raw data to be run through "mini-DRP" processing.

1	Test Data	No data.
	Expected	
	Result	
2-1 from LVV- T1064	Description Test Data Expected Result	Process data with the Data Release Production payload, starting from raw science images and gen- erating science data products, placing them in the Data Backbone.
3-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.

	Description	Confirm that the data products from the DRP processing have been ingested into the Data
1		Backbone.
-	Test Data	No data.
	Expected	Processed images, catalogs, calibration information, and other related data products are
	Result	present and accessible via the Butler.

4.114 LVV-T138 - Verify implementation of Bulk Download Service

Version Status Priority Verification Type Owner



LDM-639

Latest Revision 2020-02-17

1 Draft Normal Test Robert Gruendl

Open LVV-T138 in Jira

4.114.1 Verification Elements

• LVV-131 - DMS-REQ-0300-V-01: Bulk Download Service

4.114.2 Test Items

Bulk Download

- 4.114.3 Predecessors
- 4.114.4 Environment Needs
- 4.114.4.1 Software
- 4.114.4.2 Hardware

4.114.5 Input Specification

A large dataset (at least a few TB) must be available.

Requires identity management to confirm bulk download use.

While this can be tested and shown to work using LSST DAC, Chilean DAC, and IN2P3 endpoints, this should also be tested to demonstrate expected throughput for outside users (e.g. FNAL, NERSC sites could be tested).

4.114.6 Output Specification

4.114.7 Test Procedure



Step	Description, Input Data and Expected Result			
	Description	Setup large transfer request and examine the data transfer rates achieved.		
1	Test Data	No data.		
	Expected			
	Result			
2	Description	Test should be repeated while observing in firehose mode (with LSSTCam) during science verification to ensure that bulk transfer does not compromise normal nightly operations.		
-	Test Data	No data.		
	Expected			
	Result			

4.115 LVV-T140 - Verify implementation of Production Orchestration

Version	Status	Priority	Verification Type	Owner		
1	Defined	Normal	Test	Robert Gruendl		
Open LVV-T140 in Jira						

4.115.1 Verification Elements

• LVV-133 - DMS-REQ-0302-V-01: Production Orchestration

4.115.2 Test Items

Demonstrate use to orchestration software to perform real-time and batch production on LSST compute platform(s).

- 4.115.3 Predecessors
- 4.115.4 Environment Needs

4.115.4.1 Software



LDM-639

4.115.4.2 Hardware

4.115.5 Input Specification

4.115.6 Output Specification

4.115.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Identify an appropriate precursor dataset.		
1	Test Data	No data.		
	Expected			
	Result			
2	Description	Execute a batch processing job using the orchestration system, and confirm (manually and/or via QA tools typically used for HSC reprocessing) that the pipeline executed and produced all expected products (or error logs in cases of failure).		
	Test Data	No data.		
	Expected	Calexp single-visit and coadd images, and associated catalogs, are present in a Butler		
	Result	repository. Logs of the processing are available to be inspected for identification of prob- lems in the processing.		

4.116 LVV-T141 - Verify implementation of Production Monitoring

Version	Status	Priority	Verification Type	Owner	
1	Defined	Normal	Test	Robert Gruendl	
Open LVV-T141 in Jira					

4.116.1 Verification Elements

• LVV-134 - DMS-REQ-0303-V-01: Production Monitoring



LDM-639

4.116.2 Test Items

Demonstrate monitoring capabilities that give real-time view of pipeline execution and production systems usage/load.

4.116.3 Predecessors

LVV-T140

4.116.4 Environment Needs

4.116.4.1 Software

4.116.4.2 Hardware

4.116.5 Input Specification

Data set and mechanism for Production Orchestration as outlined in LVV-T140.

4.116.6 Output Specification

4.116.7 Test Procedure

Step	Description, l	nput Data and Expected Result
1-1 from LVV- T1064	Description Test Data Expected	Process data with the Data Release Production payload, starting from raw science images and gen- erating science data products, placing them in the Data Backbone.
	Result 	
2	Description	While DRP processing is executing, monitor the progress and resource usage of process- ing.
	Test Data	No data.



LDM-639

Step	Description, Input Data and Expected Result		
	Expected Result	Ability to monitor in real-time the orchestrated production processing, including resource usage.	

4.117 LVV-T142 - Verify implementation of Production Fault Tolerance

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Robert Gruendl	
Open LVV-T142 in Jira					

4.117.1 Verification Elements

• LVV-135 - DMS-REQ-0304-V-01: Production Fault Tolerance

4.117.2 Test Items

Demonstrate production systems report faults in pipeline executions and that system is able to recover. Where recovery can mean the ability to provide production artifacts for examination, return production elements ready for subsequent use, and/or reset and repeat production attempts.

4.117.3 Predecessors

4.117.4 Environment Needs

4.117.4.1 Software

4.117.4.2 Hardware

4.117.5 Input Specification



LDM-639

4.117.6 Output Specification

4.117.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Execute AP and DRP, simulate failures, observe correct processing		
1	Test Data	No data.		
	Expected			
	Result			

4.118 LVV-T144 - Verify implementation of Task Specification

Version	Status	Priority	Verification Type	Owner		
1	Defined	Normal	Test	Kian-Tat Lim		
Open I W-T144 in lira						

4.118.1 Verification Elements

• LVV-136 - DMS-REQ-0305-V-01: Task Specification

4.118.2 Test Items

Verify that the DMS provides the ability to define a new or modified pipeline task without recompilation.

4.118.3 Predecessors

4.118.4 Environment Needs

4.118.4.1 Software


LDM-639

4.118.4.2 Hardware

4.118.5 Input Specification

4.118.6 Output Specification

4.118.7 Test Procedure

Step	Description, Input Data and Expected Result			
1	Description	Inspect software architecture. Verify that there exist Tasks that can be run and configured without re-compilation.		
	Test Data	No data.		
	Expected	Confirmation that the software architecture has allowed for reconfiguring and running		
	Result	Tasks without recompilation.		
2	Description	Verify that an example science algorithm can be run through one of these Tasks. Three ex- amples from different areas: source measurement, image subtraction, and photometric- redshift estimation.		
	Test Data	No data.		
	Expected	Successful Task execution with different configurations, including confirmation that the		
	Result	outputs are different from tasks with altered configurations.		

4.119 LVV-T145 - Verify implementation of Task Configuration

Version	Status	Priority	Verification Type	Owner	
1	Defined	Normal	Test	Robert Lupton	
Open LVV-T145 in Jira					

4.119.1 Verification Elements

• LVV-137 - DMS-REQ-0306-V-01: Task Configuration



4.119.2 Test Items

Verify that the DMS software provides configuration control to define, override, and verify the configuration for a DMS Task.

- 4.119.3 Predecessors
- 4.119.4 Environment Needs
- 4.119.4.1 Software
- 4.119.4.2 Hardware
- 4.119.5 Input Specification
- 4.119.6 Output Specification

4.119.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Inspect software design to verify that one can define the configuration for a Task.
1	Test Data	No data.
	Expected	
	Result	
2	Description	Run a Task with a known invalid configuration. Verify that the error is caught before the science algorithm executes.
-	Test Data	No data.
	Expected	
	Result	
3	Description	Run a simple task with two different configurations that make a material difference for a Task. E.g., specify a different source detection threshold. Verify that the configuration is different between the two runs through difference in recorded provenance and in results.
	Test Data	No data.



Step	Description, Input Data and Expected Result
	Expected
	Result

4.120 LVV-T146 - Verify implementation of DMS Initialization Component

Version	Status	Priority	Verification Type	Owner	
1	Defined	Normal	Test	Robert Gruendl	
Open LVV-T146 in Jira					

4.120.1 Verification Elements

• LVV-128 - DMS-REQ-0297-V-01: DMS Initialization Component

4.120.2 Test Items

Demonstrate that the DMS can be initialized in a safe state that will not allow data corruption/loss.

- 4.120.3 Predecessors
- 4.120.4 Environment Needs
- 4.120.4.1 Software
- 4.120.4.2 Hardware
- 4.120.5 Input Specification
- 4.120.6 Output Specification



4.120.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Power-cycle all of the DM systems at each Facility.		
1	Test Data	No data.		
	Expected	Restart of all DM systems.		
	Result			
	Description	Observe each system and ensure that it has recovered in a properly initialized state.		
2	Test Data	No data.		
	Expected	Systems are all active and initialized for their designated purpose.		
	Result			

4.121 LVV-T147 - Verify implementation of Control of Level-1 Production

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Robert Gruendl	
Open I W-T147 in lira					

4.121.1 Verification Elements

• LVV-132 - DMS-REQ-0301-V-01: Control of Level-1 Production

4.121.2 Test Items

Demonstrate that the DMS can control all Prompt Processing across DMS facilities.

- 4.121.3 Predecessors
- 4.121.4 Environment Needs
- 4.121.4.1 Software



LDM-639

- 4.121.4.2 Hardware
- 4.121.5 Input Specification
- 4.121.6 Output Specification

4.121.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Observe existence and capability of Prompt DMCS	
1	Test Data	No data.	
	Expected		
	Result		

4.122 LVV-T148 - Verify implementation of Unique Processing Coverage

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Colin Slater	
Open LVV-T148 in lira					

4.122.1 Verification Elements

• LVV-138 - DMS-REQ-0307-V-01: Unique Processing Coverage

4.122.2 Test Items

Verify that a user-specified criterion can be used to process each record in a table exactly once.

4.122.3 Predecessors



4.122.4 Environment Needs

- 4.122.4.1 Software
- 4.122.4.2 Hardware
- 4.122.5 Input Specification
- 4.122.6 Output Specification

4.122.7 Test Procedure

 Step
 Description, Input Data and Expected Result

 1
 Description
 Execute representative processing, observe lack of duplicates or missing rows even in the presence of failures

 1
 Test Data
 No data.

 Expected
 Result

4.123 LVV-T149 - Verify implementation of Catalog Queries

Version	Status	Priority	Verification Type	Owner	
1	Defined	Normal	Test	Colin Slater	
Open LVV-T149 in Jira					

4.123.1 Verification Elements

• LVV-33 - DMS-REQ-0075-V-01: Catalog Queries

4.123.2 Test Items

Verify that SQL, or a similar structured language, can be used to query catalogs.



LDM-639

4.123.3 Predecessors

4.123.4 Environment Needs

4.123.4.1 Software

4.123.4.2 Hardware

4.123.5 Input Specification

An operational QSERV database that has been verified via LVV-T1085 and LVV-T1086.

4.123.6 Output Specification

4.123.7 Test Procedure

Step	Description, li	nput Data and Expected Result
1	Description	Execute a simple query (for example, the one below) and confirm that it returns the expected result.
	Test Data	No data.
	Example	SELECT * FROM Object WHERE qserv_areaspec_box(316.582327, -6.839078, 316.653938,
	Code	-6.781822)
	Expected	A catalog of objects satisfying the specified constraints.
	Result	
2	Description	Repeat the query from all available access routes (e.g., an external VO client, internal DM tools on the development cluster, the Science Platform query tool, and from within the Notebook Aspect), confirming in each case that the results are as expected.
	Test Data	No data.
	Expected	
	Result	

4.124 LVV-T150 - Verify implementation of Maintain Archive Publicly Accessible



Version	Status	Priority	Verification Type	Owner	
1	Defined	Normal	Test	Colin Slater	
Open LVV-T150 in Jira					

4.124.1 Verification Elements

• LVV-34 - DMS-REQ-0077-V-01: Maintain Archive Publicly Accessible

4.124.2 Test Items

Verify that prior data releases remain accessible.

- 4.124.3 Predecessors
- 4.124.4 Environment Needs
- 4.124.4.1 Software

4.124.4.2 Hardware

4.124.5 Input Specification

Availability of at least three (3) data releases, of which at least one of them must be archived outside the QSERV database. These can be precursor datasets, if needed.

4.124.6 Output Specification

4.124.7 Test Procedure



Step	Description, Input Data and Expected Result			
1	Description	Confirm that at least two data releases (the most recent, and one previous) are accessible to users (and can be queried) from the standard channels.		
·	Test Data	No data.		
	Expected	Simple queries return catalog data from the data releases that are available in QSERV.		
	Result			
2	Description	Confirm that previous data releases are accessible for bulk download (perhaps with sig- nificant latency) from tape or other bulk store, and that the downloaded tables contain the expected data products.		
	Test Data	No data.		
	Expected	A download of an entire previous data release from its bulk store.		
	Result			

4.125 LVV-T151 - Verify Implementation of Catalog Export Formats From the Notebook Aspect

Version	Status	Priority	Verification Type	Owner		
1	Defined	Normal	Test	Colin Slater		
Open LVV-T151 in Jira						

4.125.1 Verification Elements

• LVV-35 - DMS-REQ-0078-V-01: Catalog Export Formats

4.125.2 Test Items

Verify that catalog data is exportable from the notebook aspect in a variety of communitystandard formats.

4.125.3 Predecessors



4.125.4 Environment Needs

- 4.125.4.1 Software
- 4.125.4.2 Hardware
- 4.125.5 Input Specification

4.125.6 Output Specification

4.125.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from LVV-T837	Description Test Data	Authenticate to the notebook aspect of the LSST Science Platform (NB-LSP). This is currently at https://lsst-lsp-stable.ncsa.illinois.edu/nb.
	Expected	Redirection to the spawner page of the NB-LSP allowing selection of the containerized stack version
	Result	and machine flavor.
1-2 from LVV-T837	Description	 Spawn a container by: 1) choosing an appropriate stack version: e.g. the latest weekly. 2) choosing an appropriate machine flavor: e.g. medium 3) click "Spawn"
	Test Data	
	Expected	Redirection to the JupyterLab environment served from the chosen container containing the correct
	Result	stack version.

7 1 from	Description	Open a new launcher by navigating in the top menu bar "File" -> "New Launcher"				
LVV-T838	Test Data					
	Expected	A launcher window with several sections, potentially with several kernel versions for each.				
	Result					
	Description	Select the option under "Notebook" labeled "LSST" by clicking on the icon.				
	Test Data					
LVV-1838	Expected	An empty notebook with a single empty cell. The kernel show up as "LSST" in the top right of the				
	Result	notebook.				



Latest Revision 2020-02-17

Step Description, Input Data and Expected Result

3-1 from	Description	Execute a query in a notebook to select a small number of stars. In the example code below, we				
LVV-		query the WISE catalog, then extract the results to an Astropy table.				
T1207	Test Data					
	Expected					
	Result					

4 Using the example code below, save the files to your storage space on the LSP Notebook Aspect.

	Confirm that non-empty output files appear on disk.			
Test Data	No data.			
Example	tab.write('test.csv', format='ascii.csv')			
Code	tab.write('test.vot', format='votable')			
	tab.write('test.fits', format='fits')			
Expected	For the example given here, there should be the following files with the file size as listed:			
Result	 test.csv 5.7M test.vot 16M test.fits 4.5M 			

	Description	Check that these files contain the same number of rows:			
5	Test Data	No data.			
	Example	from astropy.table import Table			
	Code	dat_csv = Table.read('test.csv', format='ascii.csv')			
		dat_vot = Table.read('test.vot', format='votable')			
		dat_fits = Table.read('test.fits', format='fits')			
		import numpy as np			
		print(pp cizo(dat ccv), pp cizo(dat vot), pp cizo(dat fitc))			

		phint(hp.size(dat_csv), hp.size(dat_vot), hp.size(dat_nts))	
	Expected Print statement produces output "97058 97058 97058".		
	Result		
6-1 from LVV- T1208	Description	Under the 'File' menu at the top of your Jupyter notebook session, select one of the following:	
		 Save All, Exit, and Log Out Exit and Log Out Without Saving 	

DRAFT NOT YET APPROVED – The contents of this document are subject to configuration control by the LSST DM Change Control Board. – DRAFT NOT YET APPROVED



Step	Description,	Input Data and Expected Result
	Test Data	
	Expected	You will be returned to the LSP landing page: https://lsst-lsp-stable.ncsa.illinois.edu/ It is now
	Result	safe to close the browser window.

Latest Revision 2020-02-17

4.126 LVV-T152 - Verify implementation of Keep Historical Alert Archive

Test Spec for LSST Data Management

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Eric Bellm	
Open LVV-T152 in Jira					

4.126.1 Verification Elements

• LVV-37 - DMS-REQ-0094-V-01: Keep Historical Alert Archive

4.126.2 Test Items

Verify that the DMS preserves and makes accessible an Alert Archive for reference and for false alert analyses

4.126.3 Predecessors

4.126.4 Environment Needs

4.126.4.1 Software

4.126.4.2 Hardware

4.126.5 Input Specification



LDM-639

4.126.6 Output Specification

4.126.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Simulated alert stream, load Alert DB, observe access to Alert DB		
1	No data.			
	Expected			
	Result			

4.127 LVV-T153 - Verify implementation of Provide Engineering and Facility Database Archive

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Gruendl
		Open L	VV-T153 in lira	

4.127.1 Verification Elements

• LVV-44 - DMS-REQ-0102-V-01: Provide Engineering & Facility Database Archive

4.127.2 Test Items

Demonstrate Engineering and Facilities Data (images, associated metadata, and observatory environment and control data) are archived and available for public access within **L1PublicT** (24 hours).

4.127.3 Predecessors

4.127.4 Environment Needs

4.127.4.1 Software



LDM-639

4.127.4.2 Hardware

4.127.5 Input Specification

4.127.6 Output Specification

4.127.7 Test Procedure

Step	Description, Input Data and Expected Result			
1	Description	Execute a single-day operations rehearsal, ingesting (simulated) OCS commands into the EFD.		
I	Test Data	No data.		
	Expected			
	Result			
2	Description	Wait at least L1PublicT=24 hours, then access the archived EFD. Confirm that the data products are present in the archived EFD after L1PublicT=24 hours have elapsed.		
-	Test Data	No data.		
	Expected	The EFD contains the simulated OCS commands, and they were ingested		
	Result	within L1PublicT=24 hours of the operations rehearsal.		
2	Description	From the public access portal to the EFD, execute a query and demonstrate that the data are publicly available.		
0	Test Data	No data.		
	Expected	A query at the public interface to the EFD successfully executes and returns EFD data.		
	Result			

4.128 LVV-T154 - Verify implementation of Raw Data Archiving Reliability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater
Open LVV-T154 in Jira				



LDM-639

4.128.1 Verification Elements

• LVV-140 - DMS-REQ-0309-V-01: Raw Data Archiving Reliability

4.128.2 Test Items

Verify that raw images are reliably archived.

- 4.128.3 Predecessors
- 4.128.4 Environment Needs
- 4.128.4.1 Software
- 4.128.4.2 Hardware
- 4.128.5 Input Specification
- 4.128.6 Output Specification

4.128.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Analyze sources of loss or corruption after mitigation to compute estimated reliability		
1	Test Data	No data.		
	Expected			
	Result			

4.129 LVV-T155 - Verify implementation of Un-Archived Data Product Cache

Version Status Priority Verification Type Owner



1 Draft Normal Test Robert Gruendl

Open LVV-T155 in Jira

4.129.1 Verification Elements

• LVV-141 - DMS-REQ-0310-V-01: Un-Archived Data Product Cache

4.129.2 Test Items

Demonstrate that the DMS provides low-latency storage for at least I1CacheLifetime (30 days) to keep prompt processing pre-covery images on hand.

4.129.3 Predecessors

- 4.129.4 Environment Needs
- 4.129.4.1 Software
- 4.129.4.2 Hardware
- 4.129.5 Input Specification
- 4.129.6 Output Specification

4.129.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Delegate to DBB
1	Test Data	No data.
	Expected	
	Result	



LDM-639

4.130 LVV-T156 - Verify implementation of Regenerate Un-archived Data Products

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Simon Krughoff
Open LVV-T156 in Jira				

4.130.1 Verification Elements

• LVV-142 - DMS-REQ-0311-V-01: Regenerate Un-archived Data Products

4.130.2 Test Items

Not all of the ancillary data products produced by a data release will be archived permanently. These ancillary products have been promised as accessible to the community. Show that these products can be produced from an archived data release after the fact.

4.130.3 Predecessors

- 4.130.4 Environment Needs
- 4.130.4.1 Software

4.130.4.2 Hardware

- 4.130.5 Input Specification
- 4.130.6 Output Specification

4.130.7 Test Procedure



Step	Description, Input Data and Expected Result			
	Description	Run a small DRP processing job and download unarchived data products.		
1	Test Data	No data.		
	Expected			
	Result			
2	Description	Wait for (or force) a processing stack change so that the subsequent re-processing will be forced to use an older software build.		
۷	Test Data	No data.		
	Expected			
	Result			
3	Description	Using provenance information from the products in Step 1, request a re-processing and compare results with previously unarchived products.		
5	Test Data	No data.		
	Expected			
	Result			

4.131 LVV-T157 - Verify implementation Level 1 Data Product Access

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Colin Slater	
Open LVV-T157 in Jira					

4.131.1 Verification Elements

• LVV-143 - DMS-REQ-0312-V-01: Level 1 Data Product Access

4.131.2 Test Items

Verify that Level 1 Data Products are accessible by science users.

4.131.3 Predecessors



4.131.4 Environment Needs

- 4.131.4.1 Software
- 4.131.4.2 Hardware
- 4.131.5 Input Specification
- 4.131.6 Output Specification

4.131.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Delegate to LSP	
1	Test Data	No data.	
	Expected		
	Result		

4.132 LVV-T158 - Verify implementation Level 1 and 2 Catalog Access

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater
Open LVV-T158 in Jira				

4.132.1 Verification Elements

• LVV-144 - DMS-REQ-0313-V-01: Level 1 & 2 Catalog Access

4.132.2 Test Items

Verify that Data Release Products are accessible by science users.



ANGE STRUFTIC S		Test Spec for LSST Data Management	LDM-639	Latest Revision 2020-02-17
4.132.3	Predecessors			
4.132.4	Environment	Needs		
4.132.4.1	Software			
4.132.4.2	Hardware			
4.132.5	Input Specifie	cation		
4.132.6	Output Speci	fication		
4.132.7	Test Procedu	re		
Step	Description. Ir	nput Data and Expected Resul	t	
	Description			
1	Tost Data	No data		
I	Exported			
	Expected			
	Nesult			

4.133 LVV-T159 - Verify implementation of Regenerating Data Products from Previous Data Releases

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Simon Krughoff	
Open LVV-T159 in Jira					

4.133.1 Verification Elements

• LVV-167 - DMS-REQ-0336-V-01: Regenerating Data Products from Previous Data Releases



4.133.2 Test Items

Show that un-archived data products from previous data releases can be generated using through the LSST Science Platform.

- 4.133.3 Predecessors
- 4.133.4 Environment Needs
- 4.133.4.1 Software
- 4.133.4.2 Hardware
- 4.133.5 Input Specification
- 4.133.6 Output Specification

4.133.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Delegate to LSP
1	Test Data	No data.
-	Expected	
	Result	

4.134 LVV-T160 - Verify implementation of Providing a Precovery Service

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Gregory Dubois-Felsmann

Open LVV-T160 in Jira



4.134.1 Verification Elements

• LVV-172 - DMS-REQ-0341-V-01: Max elapsed time for precovery results

4.134.2 Test Items

Verify that a technical capability to perform user-directed precovery analyses on difference images exists and that it is exposed through the LSST Science Platform. Verified by testing against precursor datasets.

(Involves: LSP Portal, MOPS and Forced Photometry)

4.134.3 Predecessors

- 4.134.4 Environment Needs
- 4.134.4.1 Software

4.134.4.2 Hardware

4.134.5 Input Specification

- 1. DECam HiTS data could be an appropriate set for this activity.
- 2. Precovery pipelines for follow-on to alert processing must exist and be made available as a containerized version within the Science Platform.
- 3. Determine limitations over which general precovery is supported. I would suggest that precovery services be limited to current (or last two) DRP campaigns with the possible addition of including non-DRP products to encompass observations over the preceding year (does this then require means to re-generate PVIs from Alert Production in addition to DRP?)
- 4. Could re-use elements of LVV-T80 where quasars are used to test faint object detection.

4.134.6 Output Specification



4.134.7 Test Procedure

Step	Description, Input Data and Expected Result			
1	Description	Run Precovery within follow-on Alert Production (i.e. daily post-processing on 30 day store).		
·	Test Data	No data.		
	Expected			
	Result			
2	Description	Within Science Platform, initiate request to perform precovery for a list of sources over same period (and longer). Include among the sources for precovery quasars from LVV-T80.		
	Test Data	No data.		
	Expected			
	Result			
3	Description	Examine the results. Compare the results for the period where there is overlap with precovery run and quasar photometry with those from LVV-T80 to verify user service performs as production services.		
	Test Data	No data.		
	Expected			
	Result			

4.135 LVV-T161 - Verify implementation of Logging of catalog queries

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl
		Open	LVV-T161 in Jira	

4.135.1 Verification Elements

• LVV-176 - DMS-REQ-0345-V-01: Logging of catalog queries



4.135.2 Test Items

Demonstrate logging of queries of LSST databases. Logged queries are globally available to DB administrators but otherwise private excepting the user that made the query.

4.135.3 Predecessors

- 4.135.4 Environment Needs
- 4.135.4.1 Software
- 4.135.4.2 Hardware
- 4.135.5 Input Specification
- 4.135.6 Output Specification

4.135.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Delegate to LSP
1	Test Data	No data.
-	Expected	
	Result	

4.136 LVV-T162 - Verify implementation of Access to Previous Data Releases

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Gregory Dubois-Felsmann

Open LVV-T162 in Jira



4.136.1 Verification Elements

• LVV-189 - DMS-REQ-0363-V-01: Access to Previous Data Releases

4.136.2 Test Items

Verify this high-level requirement, which states that the other data access requirements, for images and catalogs, all must be satisfied for multiple data releases. Verified by inspection, i.e., by determining that the data access system components, from middleware through APIs to user interfaces, are designed to support data from multiple releases, as well as by direct testing using a synthetic test environment containing multiple releases.

(Involves: Data Backbone, Managed Database, LSP Portal, LSP JupyterLab, LSP Web APIs, Parallel Distributed Database)

4.136.3 Predecessors

- 4.136.4 Environment Needs
- 4.136.4.1 Software

4.136.4.2 Hardware

4.136.5 Input Specification

Requires two or more (fake) releases within DAC (or PDAC) with common area/observations (preferably with some differing results but could use metadata identifying provenance).

4.136.6 Output Specification

4.136.7 Test Procedure



Step	Description, Input Data and Expected Result			
1	Description	From Science Platform initiate request for image and catalog products from one of the two release sets.		
I	Test Data	No data.		
	Expected			
	Result			
	Description	From Science Platform re-issue the same request but specifying the alternate/earlier re-		
2		lease set.		
-	Test Data	No data.		
	Expected			
	Result			
3	Description	Compare results and identify differences that are germaine to the relevant Data Release Sets are found.		
J	Test Data	No data.		
	Expected			
	Result			

4.137 LVV-T163 - Verify implementation of Data Access Services

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl
		Open	LVV-T163 in Jira	

4.137.1 Verification Elements

• LVV-190 - DMS-REQ-0364-V-01: Total number of data releases

4.137.2 Test Items

Demonstrate that Data Access Services are capable of scaling to serve data from nDRTot (11) data releases over a surveyYears (10) year survey.

4.137.3 Predecessors



4.137.4 Environment Needs

- 4.137.4.1 Software
- 4.137.4.2 Hardware
- 4.137.5 Input Specification
- 4.137.6 Output Specification

4.137.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Delegate to LSP
1	Test Data	No data.
	Expected	
	Result	

4.138 LVV-T164 - Verify implementation of Operations Subsets

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl
		Open	LVV-T164 in Jira	

4.138.1 Verification Elements

• LVV-191 - DMS-REQ-0365-V-01: Operations Subsets



LDM-639

4.138.2 Test Items

Demonstrate that Data Access Services are designed such that subsets of a Data Release may be retained and served (made available) after a Data Release has been superseded. (Data Backbone, Managed Database, LSP Portal, LSP JupyterLab, LSP Web APIs, Parallel Distributed Database)

- 4.138.3 Predecessors
- 4.138.4 Environment Needs
- 4.138.4.1 Software
- 4.138.4.2 Hardware
- 4.138.5 Input Specification
- 4.138.6 Output Specification
- 4.138.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Delegate to LSP		
1	Test Data	No data.		
	Expected			
	Result			

4.139 LVV-T165 - Verify implementation of Subsets Support

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Lupton
		Open L	.VV-T165 in Jira	



4.139.1 Verification Elements

• LVV-192 - DMS-REQ-0366-V-01: Subsets Support

4.139.2 Test Items

Verify that the DMS can provide designated subsets of previous Data Releases.

 4.139.3
 Predecessors

 4.139.4
 Environment Needs

 4.139.4.1
 Software

 4.139.4.1
 Software

 4.139.4.2
 Hardware

 4.139.5
 Input Specification

 4.139.6
 Output Specification

 4.139.7
 Test Procedure

 Step
 Description, Input Data and Expected Result

 1
 Test Data
 No data.

 Expected
 Result

4.140 LVV-T166 - Verify implementation of Access Services Performance

Version Status Priority Verification Type Owner



LDM-639

Latest Revision 2020-02-17

1 Draft Normal Test Robert Gruendl

Open LVV-T166 in Jira

4.140.1 Verification Elements

• LVV-193 - DMS-REQ-0367-V-01: Access Services Performance

4.140.2 Test Items

Demonstrate monitoring of Data Access Services that give real and long-time views of system performance and usage.

4.140.3 Predecessors

- 4.140.4 Environment Needs
- 4.140.4.1 Software

4.140.4.2 Hardware

- 4.140.5 Input Specification
- 4.140.6 Output Specification

4.140.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Delegate to LSP
1	Test Data	No data.
	Expected	
	Result	



LDM-639

4.141 LVV-T167 - Verify Capability to serve older Data Releases at Full Performance

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl
Open LVV-T167 in Jira				

4.141.1 Verification Elements

• LVV-194 - DMS-REQ-0368-V-01: Implementation Provisions

4.141.2 Test Items

Verify that implementation of the data access services do not preclude serving all older Data Releases with the same performance requirements as current Data Releases. Note that it is an operational consideration whether sufficient compute and storage resources would actually be provisioned to meet those requirements.

4.141.3 Predecessors

- 4.141.4 Environment Needs
- 4.141.4.1 Software
- 4.141.4.2 Hardware
- 4.141.5 Input Specification
- 4.141.6 Output Specification

4.141.7 Test Procedure



Latest Revision 2020-02-17

Step	Description, Input Data and Expected Result		
	Description	Delegate to LSP	
1	Test Data	No data.	
	Expected		
	Result		

4.142 LVV-T168 - Verify design of Data Access Services allows Evolution of the LSST Data Model

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl
Open LVV-T168 in Jira				

4.142.1 Verification Elements

• LVV-195 - DMS-REQ-0369-V-01: Evolution

4.142.2 Test Items

Verify that the design of the Data Access Services are able to accommodate changes/evolution of the LSST data model from one release to another.

4.142.3 Predecessors

4.142.4 Environment Needs

4.142.4.1 Software

4.142.4.2 Hardware

4.142.5 Input Specification



4.142.6 Output Specification

4.142.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Delegate to LSP	
1	Test Data	No data.	
	Expected		
	Result		

4.143 LVV-T169 - Verify implementation of Older Release Behavior

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Gregory Dubois-Felsmann
Open I W-T169 in Jira				

4.143.1 Verification Elements

• LVV-196 - DMS-REQ-0370-V-01: Older Release Behavior

4.143.2 Test Items

Verify that the components of the data access system are technically capable of handling data releases beyond the two for which full services are required. DMS-REQ-0364 requires that up to 11 be supported. Verified by inspection, i.e., by determination that the system design and implementation contain the necessary features to support this number of releases, and by direct test in a synthetic test environment with multiple releases.

(Involves: Data Backbone, Managed Database, LSP Portal, LSP JupyterLab, LSP Web APIs, Parallel Distributed Database)

4.143.3 Predecessors



4.143.4 Environment Needs

- 4.143.4.1 Software
- 4.143.4.2 Hardware
- 4.143.5 Input Specification
- 4.143.6 Output Specification

4.143.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Delegate to LSP
1	Test Data	No data.
	Expected	
	Result	

. . .

4.144 LVV-T170 - Verify implementation of Query Availability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Colin Slater
		Open LV	V-T170 in Jira	

4.144.1 Verification Elements

• LVV-197 - DMS-REQ-0371-V-01: Query Availability

4.144.2 Test Items

Verify that queries continue to be successfully executable over time.



		Test Spec for LSST Data Management	LDM-639	Latest Revision 2020-02-17
4.144.3	Predecessors			
4.144.4	Environment	Needs		
4.144.4.1	Software			
4.144.4.2	2 Hardware			
4.144.5	Input Specifi	cation		
4.144.6	Output Speci	fication		
4.144.7	Test Procedu	re		
Step	Description, Ir	nput Data and Expected Res	sult	
	Description	Delegate to LSP		
1	Test Data	No data.		
	Expected			
	Result			

4.145 LVV-T171 - Verify implementation of Pipeline Availability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl
Open LVV-T171 in Jira				

4.145.1 Verification Elements

• LVV-5 - DMS-REQ-0008-V-01: Pipeline Availability



4.145.2 Test Items

Demonstrate that Data Management System pipelines are available for use without disruptions of greater than productionMaxDowntime (24 hours). This requires a regimented change control process and testing infrastructure for all pipelines and their underlying software services, and regimented management and monitoring of compute and networking resources. The list of services covered by this test include: Image and EFD Archiving, Prompt Processing, OCS Driven Batch, Telemetry Gateway, Alert Distribution, Alert Filtering, Batch Production, Data Backbone, Compute/Storage/LAN, Inter-Site Networks, and Service Management and Monitoring.

4.145.3 Predecessors

- 4.145.4 Environment Needs
- 4.145.4.1 Software
- 4.145.4.2 Hardware
- 4.145.5 Input Specification
- 4.145.6 Output Specification

4.145.7 Test Procedure

Step	Description, Input Data and Expected Result		
1	Description	Analyze sources of downtime after mitigation to compute estimated reliability; observe unscheduled downtime of developer, integration, and pre-production systems	
·	Test Data	No data.	
	Expected		
	Result		




LDM-639

4.146 LVV-T172 - Verify implementation of Optimization of Cost, Reliability and **Availability**

Version	Status	Priority	Verification Type	Owner		
1	Draft	Normal	Test	Robert Gruendl		
Open LVV-T172 in Jira						

4.146.1 Verification Elements

• LVV-64 - DMS-REQ-0161-V-01: Optimization of Cost, Reliability and Availability in Order

4.146.2 Test Items

In matters of cost, system reliability (functioning properly at a given time) has precedence over system availability (ability to use the system at a given time). The optimization may be outside the realm of direct testing as it is more of a system provisioning guideline but on its face it demands that the Data Management System include failure reporting, regimented change control, acceptance testing, maintenance and monitoring.

4.146.3 Predecessors

- 4.146.4 Environment Needs
- 4.146.4.1 Software
- 4.146.4.2 Hardware
- 4.146.5 Input Specification
- 4.146.6 Output Specification

4.146.7 Test Procedure



Step	Description, Input Data and Expected Result					
	Description	Analyze resource management policy				
1	Test Data	No data.				
	Expected					
	Result					

4.147 LVV-T173 - Verify implementation of Pipeline Throughput

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Robert Gruendl	
Open LVV-T173 in Jira					

4.147.1 Verification Elements

• LVV-65 - DMS-REQ-0162-V-01: Pipeline Throughput

4.147.2 Test Items

Demonstrate that the Alert Production Pipeline is capable of processing nRawExpNightMax (2800) science exposures within a (24-nightDurationMax) 12 hour period and issue alerts in offline batch mode.

4.147.3 Predecessors

4.147.4 Environment Needs

4.147.4.1 Software

4.147.4.2 Hardware

4.147.5 Input Specification



4.147.6 Output Specification

4.147.7 Test Procedure

Step	Description, Input Data and Expected Result					
	Description	Execute single-day operations rehearsal, observe data products generated in time				
1	Test Data	No data.				
	Expected					
	Result					

4.148 LVV-T174 - Verify implementation of Re-processing Capacity

Version	Status	Priority	Verification Type	Owner		
1	Draft	Normal	Test	Robert Gruendl		
Open LWLT174 in lira						

4.148.1 Verification Elements

• LVV-66 - DMS-REQ-0163-V-01: Re-processing Capacity

4.148.2 Test Items

Verify that the DMS has sufficient processing, storage, and network to reprocess all data within "drProcessingPeriod" (1 year) while maintaining full Prompt Processing capability.

4.148.3 Predecessors

- 4.148.4 Environment Needs
- 4.148.4.1 Software



LDM-639

- 4.148.4.2 Hardware
- 4.148.5 Input Specification
- 4.148.6 Output Specification

4.148.7 Test Procedure

Step	Description, Input Data and Expected Result						
	Description	Analyze sizing model; execute DRP, observe scaling					
1	Test Data	No data.					
	Expected						
	Result						

4.149 LVV-T175 - Verify implementation of Temporary Storage for Communications Links

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl
		Open	LVV-T175 in Jira	

4.149.1 Verification Elements

• LVV-67 - DMS-REQ-0164-V-01: Temporary Storage for Communications Links

4.149.2 Test Items

Demonstrate that storage capacity is present and usable to prevent data loss if networking is interrupted between summit and base, base and archive, or archive and DAC. The requirement is to have storage necessary to hold tempStorageReIMTTR (200%) of the expected raw data that would arrive during the Mean Time to Repair (summToBaseNetMTTR = 24 hours, baseToArchNetMTTR = 48 hours, archToDacNetMTTR = 48 hours). This scale is further set by nCalibExpDay + nRawExpNightMax = 450 + 2800 = 3250 exposures/day.



Test	Spec	for	LSST	Data	Management
------	------	-----	------	------	------------

4.149.3	Predecessors
4.149.4	Environment Needs
4.149.4. 1	l Software
4.149.4.2	2 Hardware
4.149.5	Input Specification
4.149.6	Output Specification
4.149.7	Test Procedure
Step	Description, Input Data and Expected Result
	Description Analyze sizing model and network/storage design
1	Test Data No data.
	Expected
	Result

4.150 LVV-T176 - Verify implementation of Infrastructure Sizing for "catching up"

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Robert Gruendl	
Open LVV-T176 in lira					

4.150.1 Verification Elements

- LVV-68 DMS-REQ-0165-V-01: Infrastructure Sizing for "catching up"
- LVV-994 OSS-REQ-0051-V-01: Summit-Base Connectivity Loss



LDM-639

4.150.2 Test Items

Demonstrate Data Management System has sufficient excess capacity (compute infrastructure) to process one night's data (2800 exposures) within 24 hours while also maintaining nightly Alert Production (note this is very similar to LVV-T173).

4.150.3 Predecessors

- 4.150.4 Environment Needs
- 4.150.4.1 Software
- 4.150.4.2 Hardware
- 4.150.5 Input Specification
- 4.150.6 Output Specification

4.150.7 Test Procedure

Step Description, Input Data and Expected Result

1	Description	Execute single-day operations rehearsal including catch-up after failure, observe data products generated in time
•	Test Data	No data.
	Expected	
	Result	

4.151 LVV-T177 - Verify implementation of Incorporate Fault-Tolerance

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl

Open LVV-T177 in Jira



4.151.1 Verification Elements

• LVV-69 - DMS-REQ-0166-V-01: Incorporate Fault-Tolerance

4.151.2 Test Items

Demonstrate that Data Management Systems have features that prevent data loss. Includes: MD5SUM/checksum verification for data transfer; RAID to eliminate single-point disk failures; multi-site and tape for disaster recovery of raw data; multiple site (and tape?) for backup/recovery of Data Release products; DB transaction logging and backup to maintain DB integrity. (Note: storage to prevent loss in case of networking failures is covered in LVV-T175).

4.151.3 Predecessors

- 4.151.4 Environment Needs
- 4.151.4.1 Software
- 4.151.4.2 Hardware
- 4.151.5 Input Specification
- 4.151.6 Output Specification

4.151.7 Test Procedure

Step	Description, Input Data and Expected Result				
1	Description	Analyze design; execute single-day operations rehearsal including failures, observe recov- ery without loss of data			
·	Test Data	No data.			
	Expected				
	Result				



4.152 LVV-T178 - Verify implementation of Incorporate Autonomics

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl
		•		

Open LVV-T178 in Jira

4.152.1 Verification Elements

• LVV-70 - DMS-REQ-0167-V-01: Incorporate Autonomics

4.152.2 Test Items

Demonstrate that production systems monitor and report faults. Where possible fault mitigation can include re-start, re-submission, or return of partial products for triage.

4.152.3 Predecessors

4.152.4 Environment Needs

- 4.152.4.1 Software
- 4.152.4.2 Hardware
- 4.152.5 Input Specification
- 4.152.6 Output Specification
- 4.152.7 Test Procedure

Step	Description,	Input Data and	Expected Result

	Description	Analyze design; execute single-day operations rehearsal including failures, observe auto-
1		mated recovery and continuation of processing



Step	Description, Input Data and Expected Result				
	Test Data	No data.			
	Expected				
	Result				

4.153 LVV-T179 - Verify implementation of Compute Platform Heterogeneity

Version	ersion Status Priority		Verification Ty	pe Owner	
1	Draft Normal		Test	Robert Gruendl	
Open LVV-T179 in Jira					

4.153.1 Verification Elements

• LVV-145 - DMS-REQ-0314-V-01: Compute Platform Heterogeneity

4.153.2 Test Items

Demonstrate that production results are the same (within machine accuracy) when production occurs on different platforms (OS, kernel, hardware provisioning).

4.153.3 Predecessors

4.153.4 Environment Needs

4.153.4.1 Software

4.153.4.2 Hardware

4.153.5 Input Specification



4.153.6 Output Specification

4.153.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Configure heterogeneous cluster, execute AP+DRP+LSP, observe correct functioning		
1	Test Data	No data.		
	Expected			
	Result			

4.154 LVV-T180 - Verify implementation of Data Management Unscheduled Downtime

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Robert Gruendl	
Open I W-T180 in lira					

4.154.1 Verification Elements

• LVV-149 - DMS-REQ-0318-V-01: Data Management Unscheduled Downtime

4.154.2 Test Items

This applies only to downtime that would prevent the collection of survey data. Verification means that analysis has occurred to identify likely hardware failures that would prevent survey operations and that mitigations that minimize the downtime to less than DMDowntime (1 day/year) are in place. Known systems that fall in this category include: Image and EFD Archiving, Observatory Operations Data, Telemetry Gateway, Data Backbone, Managed Database, Inter-Site Networks, and Service Management and Monitoring.

4.154.3 Predecessors



4.154.4 Environment Needs

- 4.154.4.1 Software
- 4.154.4.2 Hardware
- 4.154.5 Input Specification
- 4.154.6 Output Specification

4.154.7 Test Procedure

Step	Description, Input Data and Expected Result			
1	Description	Analyze likely hardware failures with mitigations to compute estimated unplanned down- time		
I	Test Data	No data.		
	Expected			
	Result			

4.155 LVV-T182 - Verify implementation of Prefer Computing and Storage Down

Version	Status	Priority	Verification Type	Owner	
1 Draft		Normal	Test	Robert Gruendl	
Open LVV-T182 in Jira					

4.155.1 Verification Elements

• LVV-72 - DMS-REQ-0170-V-01: Prefer Computing and Storage Down



4.155.2 Test Items

Only build compute or storage facilities at the summit that are justified by operational need or to prevent loss of data during networking downtimes.

- 4.155.3 Predecessors
- 4.155.4 Environment Needs
- 4.155.4.1 Software
- 4.155.4.2 Hardware
- 4.155.5 Input Specification
- 4.155.6 Output Specification

4.155.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Analyze design	
1	Test Data	No data.	
-	Expected		
	Result		

4.156 LVV-T183 - Verify implementation of DMS Communication with OCS

Version	Status	Priority	Verification Type	Owner	
1	Defined	Normal	Test	Gregory Dubois-Felsmann	
Open LVV/ T182 in line					

Open LVV-T183 in Jira



4.156.1 Verification Elements

• LVV-146 - DMS-REQ-0315-V-01: DMS Communication with OCS

4.156.2 Test Items

Verify that the DMS at the Base Facility can receive commands from the OCS and send command responses, events, and telemetry back. Verified by Early Integration activities and during AuxTel commissioning.

4.156.3 Predecessors

- 4.156.4 Environment Needs
- 4.156.4.1 Software
- 4.156.4.2 Hardware
- 4.156.5 Input Specification

4.156.6 Output Specification

4.156.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	From the Base Site, connect to the (simulated) OCS telemetry stream.	
1	Test Data	No data.	
	Expected		
	Result		
	Description	Send a command to the OCS, and observe that the command has been executed.	
2	Test Data	No data.	
	Expected	Confirmation that the OCS command successfully executed.	
	Result		



LDM-639

Latest Revision 2020-02-17

Step	Description, Input Data and Expected Result			
2	Description	Extract information from the telemetry being broadcast by the OCS, and ensure that these data are readable.		
5	Test Data	No data.		
	Expected	A readable extract from the OCS telemetry stream.		
	Result			

4.157 LVV-T185 - Verify implementation of Summit to Base Network Availability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Inspection	Robert Gruendl
Open LVV-T185 in Jira				

4.157.1 Verification Elements

• LVV-74 - DMS-REQ-0172-V-01: Summit to Base Network Availability

4.157.2 Test Items

Monitor summit to base networking for at least 1 week, model annual availability, and verify that the mean time between failures is less than summToBaseNetMTBF (90 days) over 1 year.

4.157.3 Predecessors

See pre-conditions.

4.157.4 Environment Needs

4.157.4.1 Software See pre-conditions.



4.157.4.2 Hardware See pre-conditions.

4.157.5 Input Specification

PMCS DMTC-7400-2400 Complete.

perSonar installed in Summit and publishing statistics to MadDash.

4.157.6 Output Specification

4.157.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Delegate to Networks	
1	Test Data	No data.	
	Expected		
	Result		

4.158 LVV-T186 - Verify implementation of Summit to Base Network Reliability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Demonstration	Robert Gruendl
Open LVV-T186 in Jira				

4.158.1 Verification Elements

• LVV-75 - DMS-REQ-0173-V-01: Summit to Base Network Reliability

4.158.2 Test Items

This approach is necessitated by not wanting to actually cut the fiber just for test purposes:

• Pick a point on the network (Time Domain graph) and simulate a fault (e.g. disconnect



LDM-639

a cable).

- Detect there a fault.
- Diagnose that it is a break.
- Measure the cable with the OTDR to locate the distance from the end point.
- Elapse time to simulate the following:
 - Go to the most inaccessible place which would mean carrying all the tools/splicer/generator/tent equipment some metres.
 - Erect a tent to make the splice
 - Start the generator
 - Do a splice on some random piece of cable
 - At an end point measure the cable again to ensure it is break free.
 - Take down and reinstall an isolate pole (not in the actual fiber path)
 - Put the cable on the pole.
- Restore connection (e.g. reconnect cable)
- Measure with OTDR to ensure back to normal state.

4.158.3 Predecessors

See pre-conditions.

4.158.4 Environment Needs

4.158.4.1 Software See pre-conditions.

4.158.4.2 Hardware See pre-conditions.

4.158.5 Input Specification

PMCS DMTC-7400-2400 Complete



4.158.6 Output Specification

4.158.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Delegate to Networks	
1	Test Data	No data.	
	Expected		
	Result		

4.159 LVV-T187 - Verify implementation of Summit to Base Network Secondary Link

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl
Open I W-T187 in lira				

4.159.1 Verification Elements

• LVV-76 - DMS-REQ-0174-V-01: Summit to Base Network Secondary Link

4.159.2 Test Items

Transfer data between summit and base on primary equipment (LSST Summit - Base) over uninterrupted 1 day period. Simulate outage by disconnecting fiber from equipment on primary and verify that network fails over to secondary equipment. Demonstrate transfer of data at or exceeding rates specified in LDM-142 between summit and base over secondary equipment uninterrupted 1 day period (except for <=60s to fail-over to secondary and recover to primary connection execution). Verify that link is capable of transferring 1 night of raw data (nCalibExpDay + nRawExpNightMax = 450 + 2800 = 3250 exposures) within summ-ToBaseNet2TransMax (72 hours). Restore connection between fiber and primary equipment (i.e. reconnect primary), verify that network recovers to primary.



LDM-639

4.159.3 Predecessors

See pre-conditions.

4.159.4 Environment Needs

- 4.159.4.1 Software See pre-conditions.
- 4.159.4.2 Hardware See pre-conditions.

4.159.5 Input Specification

PMCS DMTC-7400-2400 complete.

4.159.6 Output Specification

4.159.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Delegate to Networks	
1	Test Data	No data.	
	Expected		
	Result		

4.160 LVV-T188 - Verify implementation of Summit to Base Network Ownership and Operation

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Inspection	Robert Gruendl
Open LVV-T188 in Jira				



4.160.1 Verification Elements

• LVV-77 - DMS-REQ-0175-V-01: Summit to Base Network Ownership and Operation

4.160.2 Test Items

Inspect construction and operations contracts and Indefeasible Rights to Use (IRUs).

4.160.3 Predecessors

- PMCS DMTC-7400-2140, -2240, -2330 Complete
- 4.160.4 Environment Needs
- 4.160.4.1 Software None
- 4.160.4.2 Hardware None
- 4.160.5 Input Specification
- 4.160.6 Output Specification

4.160.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Delegate to Networks	
1	Test Data	No data.	
	Expected		
	Result		

4.161 LVV-T189 - Verify implementation of Base Facility Infrastructure



Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl
Open LVV-T189 in Jira				

4.161.1 Verification Elements

• LVV-78 - DMS-REQ-0176-V-01: Base Facility Infrastructure

4.161.2 Test Items

Verify that the (a) planned infrastructure and (b) as-built infrastructure for the Base Facility satisfies the needs for data transfer and buffering, a copy of the Archive Facility, and support for Commissioning.

- 4.161.3 Predecessors
- 4.161.4 Environment Needs
- 4.161.4.1 Software
- 4.161.4.2 Hardware
- 4.161.5 Input Specification
- 4.161.6 Output Specification
- 4.161.7 Test Procedure

Step	Description,	Input Data and	Expected Result
	1 1		

Description Analyze design and sizing model

1 Test Data No data.



Step Description, Input Data and Expected Result Expected Result

4.162 LVV-T190 - Verify implementation of Base Facility Co-Location with Existing Facility

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Robert Gruendl	
Open LVV-T190 in Jira					

4.162.1 Verification Elements

• LVV-80 - DMS-REQ-0178-V-01: Base Facility Co-Location with Existing Facility

4.162.2 Test Items

Verify that the Base Facility is located at an existing known supported facility.

- 4.162.3 Predecessors
- 4.162.4 Environment Needs
- 4.162.4.1 Software
- 4.162.4.2 Hardware
- 4.162.5 Input Specification
- 4.162.6 Output Specification



LDM-639

4.162.7 Test Procedure

Step	Description, Input Data and Expected Result				
	Description	Analyze design			
1	Test Data	No data.			
	Expected				
	Result				

4.163 LVV-T191 - Verify implementation of Commissioning Cluster

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Robert Gruendl	
Open LVV-T191 in Jira					

4.163.1 Verification Elements

• LVV-147 - DMS-REQ-0316-V-01: Commissioning Cluster

4.163.2 Test Items

Verify that the Commissioning Cluster has sufficient Compute/Storage/LAN at the Base Facility to support Commissioning.

4.163.3 Predecessors

- 4.163.4 Environment Needs
- 4.163.4.1 Software

4.163.4.2 Hardware



4.163.5 Input Specification

4.163.6 Output Specification

4.163.7 Test Procedure

Step	Description,	Input Data and	d Expected Result
------	--------------	----------------	-------------------

	Description	Analyze design and budget
1	Test Data	No data.
	Expected	
	Result	

4.164 LVV-T192 - Verify implementation of Base Wireless LAN (WiFi)

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Robert Gruendl	
Open I VV-T192 in lira					

4.164.1 Verification Elements

• LVV-183 - DMS-REQ-0352-V-01: Base Wireless LAN (WiFi)

4.164.2 Test Items

Verify (a) plannned and (b) as-built wireless network at the Base Facility supports minBaseWiFi bandwidth (1000 Mbs). Test internet web browsing and file download, email at summit and base over wireless. Verify wireless signal strength meets or exceeds typical, and average and peak bandwidths meet or exceed minBaseWiFl bandwidth.

4.164.3 Predecessors

PMCS DLP-465 Complete.



LDM-639

4.164.4 Environment Needs

4.164.4.1 Software See pre-conditions.

4.164.4.2 Hardware Desktop with WiFi NIC, email reader, internet browser.

4.164.5 Input Specification

Base Wireless LAN is installed/configured and Test Personnel have accounts for email, internet access.

4.164.6 Output Specification

4.164.7 Test Procedure

Step	Description, Input Data and Expected Result				
	Description	Delegate to Networks			
1	Test Data	No data.			
	Expected				
	Result				

4.165 LVV-T193 - Verify implementation of Base to Archive Network

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Robert Gruendl	
Open LVV-T193 in Jira					

4.165.1 Verification Elements

• LVV-81 - DMS-REQ-0180-V-01: Base to Archive Network



4.165.2 Test Items

Transfer data between base and archive over uninterrupted 1 day period (with repeated transfers on normal observing cadence). Analyze the network and show that data acquired by a DAQ can be transferred within the required time, i.e. verify that link is capable of transferring image for prompt processing in oArchiveMaxTransferTime = 5[second]. Verify transfer of data at or exceeding rates specified in LDM-142.

4.165.3 Predecessors

PMCS DM-Net-5 Complete

4.165.4 Environment Needs

- 4.165.4.1 Software See pre-conditions.
- 4.165.4.2 Hardware See pre-conditions.

4.165.5 Input Specification

Archiver/Forwarders are configured at Base, connected to REUNA DWDM, loaded with simulated or pre-cursor data.

Archiver/Forwarder receivers or other capability is on configured at LDF, connected to Base -Archive Network.

4.165.6 Output Specification

4.165.7 Test Procedure

Step	Description, Input Data and Expected Result				
	Description Delegate to Networks				
1	Test Data	No data.			



Step Description, Input Data and Expected Result Expected Result

4.166 LVV-T194 - Verify implementation of Base to Archive Network Availability

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Robert Gruendl	
Open LVV-T194 in Jira					

4.166.1 Verification Elements

• LVV-82 - DMS-REQ-0181-V-01: Base to Archive Network Availability

4.166.2 Test Items

Transfer data between base and archive over uninterrupted 1 week period. Extrapolate to a full year to estimate if expect to meet baseToArchNetMTBF = 180[day]. Note that this is for complete loss of transfer service (all paths), not a single path failure with successful fail-over. Demonstrate transfer of data at or exceeding rates specified in LDM-142, verify achieved average and peak throughput and latency.

4.166.3 Predecessors

PMCS DMTC-7400-2130 Complete

4.166.4 Environment Needs

4.166.4.1 Software



LDM-639

4.166.4.2 Hardware

4.166.5 Input Specification

Archiver/Forwarders are configured at Base, connected to REUNA DWDM, loaded with simulated or pre-cursor data.

Archiver/Forwarder receivers or other capability is on configured at LDF, connected to Base -Archive Network.

4.166.6 Output Specification

4.166.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Delegate to Networks
1	Test Data	No data.
	Expected	
	Result	

. ..

4.167 LVV-T195 - Verify implementation of Base to Archive Network Reliability

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Robert Gruendl	
Open LVV-T195 in Jira					

4.167.1 Verification Elements

• LVV-83 - DMS-REQ-0182-V-01: Base to Archive Network Reliability



LDM-639

4.167.2 Test Items

Disconnect, reconnect and recover transfer of data between base and archive, after disconnecting fiber at an intermediate location between base and archive. Verify recovery can occur within baseToArchNetMTTR = 48[hour]. Demonstrate reconnection and recovery to transfer of data at or exceeding rates specified in LDM-142.

4.167.3 Predecessors

PMCS DM-NET-5 Complete

4.167.4 Environment Needs

- 4.167.4.1 Software See pre-conditions.
- 4.167.4.2 Hardware See pre-conditions.

4.167.5 Input Specification

Archiver/Forwarders are configured at Base, connected to REUNA DWDM, loaded with simulated or pre-cursor data.

Archiver/Forwarder receivers or other capability is on configured at LDF, connected to Base -Archive Network.

4.167.6 Output Specification

4.167.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Delegate to Networks	
1	Test Data	No data.	
	Expected		
	Result		



LDM-639

4.168 LVV-T196 - Verify implementation of Base to Archive Network Secondary Link

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl
Open LVV-T196 in Jira				

4.168.1 Verification Elements

LVV-84 - DMS-REQ-0183-V-01: Base to Archive Network Secondary Link

4.168.2 Test Items

FOR EACH SEGMENT (LS - SCL, SCL - FL, FL - CHI, CHI - CHMPGN): Transfer data between base and archive on primary links over uninterrupted 1 day period. Simulate outage by disconnecting fiber on primary and verify that network fails over to secondary links. Transfer data between base and archive over secondary equipment uninterrupted 1 day period. Restore connection on primary link verify that network recovers to primary. Transfer data between base and archive on primary links over uninterrupted 1 day period. Demonstrate transfer of data at or exceeding rates specified in LDM-142 throughout fail-over period except for <=60s fail-over fail-over to secondary and recover to primary connection execution.

4.168.3 Predecessors

PMCS DM-NET-5 Complete PMCS DMTC-8000-0990 Complete PMCS DMTC-8100-2130 Complete PMCS DMTC-8100-2530 Complete PMCS DMTC-8200-0600 Complete

4.168.4 Environment Needs

4.168.4.1 Software See pre-conditions.



LDM-639

4.168.4.2 Hardware See pre-conditions.

4.168.5 Input Specification

Archiver/Forwarders are configured at Base, connected to REUNA DWDM, loaded with simulated or pre-cursor data.

Archiver/Forwarder receivers or other capability is on configured at LDF, connected to Base -Archive Network.

4.168.6 Output Specification

4.168.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Delegate to Networks
1	Test Data	No data.
	Expected	
	Result	

. ..

4.169 LVV-T197 - Verify implementation of Archive Center

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl
		Open	LVV-T197 in Jira	

4.169.1 Verification Elements

• LVV-85 - DMS-REQ-0185-V-01: Archive Center



LDM-639

4.169.2 Test Items

Verify that the Archive Center is sufficiently provisioned to support prompt processing, DRP, and data access needs.

- 4.169.3 Predecessors
- 4.169.4 Environment Needs
- 4.169.4.1 Software
- 4.169.4.2 Hardware
- 4.169.5 Input Specification
- 4.169.6 Output Specification

4.169.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Analyze design and sizing model
1	Test Data	No data.
-	Expected	
	Result	

4.170 LVV-T198 - Verify implementation of Archive Center Disaster Recovery

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl
Open LVV-T198 in Jira				



LDM-639

4.170.1 Verification Elements

• LVV-86 - DMS-REQ-0186-V-01: Archive Center Disaster Recovery

4.170.2 Test Items

Verify disaster recovery plan for Archive Center.

- 4.170.3 Predecessors
- 4.170.4 Environment Needs
- 4.170.4.1 Software
- 4.170.4.2 Hardware
- 4.170.5 Input Specification
- 4.170.6 Output Specification

4.170.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Analyze design; simulate storage failure, observe restore from disaster recovery	
1	Test Data	No data.	
	Expected		
	Result		

4.171 LVV-T199 - Verify implementation of Archive Center Co-Location with Existing Facility

Version Status Priority Verification Type Owner



1 Draft Normal Test Robert Gruendl

Open LVV-T199 in Jira

4.171.1 Verification Elements

• LVV-87 - DMS-REQ-0187-V-01: Archive Center Co-Location with Existing Facility

4.171.2 **Test Items**

Verify the Archive Center is located at an existing supported facility.

4.171.3 Predecessors

- 4.171.4 Environment Needs
- 4.171.4.1 Software
- 4.171.4.2 Hardware
- 4.171.5 Input Specification
- 4.171.6 Output Specification

4.171.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Analyze design
1	Test Data	No data.
	Expected	
	Result	



LDM-639

4.172 LVV-T200 - Verify implementation of Archive to Data Access Center Network

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl
Open LVV-T200 in Jira				

4.172.1 Verification Elements

· LVV-88 - DMS-REQ-0188-V-01: Archive to Data Access Center Network

4.172.2 Test Items

Transfer data between archive and both DACs over uninterrupted 1 day period (data can be simulated, i.e. files of similar size and quantity to real data). Verify can meet archTo-DacBandwidth = 10000[megabit per second]. Analyze the network and show that data can be transferred within the required time. Demonstrate transfer of data at or exceeding rates specified in LDM-142.

4.172.3 Predecessors

PMCS DMTC-8100-2550 Complete

4.172.4 Environment Needs

- **4.172.4.1 Software** See pre-conditions.
- **4.172.4.2 Hardware** See pre-conditions.

4.172.5 Input Specification

Data is staged in LDF and data transfer capabilities to US DAC and Chilean DAC are in place.



4.172.6 Output Specification

4.172.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Delegate to Networks	
1	Test Data	No data.	
	Expected		
	Result		

4.173 LVV-T201 - Verify implementation of Archive to Data Access Center Network Availability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl
Open LVV-T201 in Jira				

4.173.1 Verification Elements

• LVV-89 - DMS-REQ-0189-V-01: Archive to Data Access Center Network Availability

4.173.2 Test Items

Transfer data between archive and DACs over uninterrupted 1 week period. Extrapolate to 1 year to estimate can meet archToDacNetMTBF = 180[day]. Demonstrate transfer of data at or exceeding rates specified in LDM-142, verify achieved average and peak throughput and latency.

4.173.3 Predecessors

PMCS DMTC-8100-2550 Complete



LDM-639

4.173.4 Environment Needs

- 4.173.4.1 Software See pre-conditions.
- **4.173.4.2 Hardware** See pre-conditions.

4.173.5 Input Specification

Data is staged in LDF and data transfer capabilities to US DAC and Chilean DAC are in place.

4.173.6 Output Specification

4.173.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Delegate to Networks	
1	Test Data	No data.	
	Expected		
	Result		

4.174 LVV-T202 - Verify implementation of Archive to Data Access Center Network Reliability

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Robert Gruendl
Open LVV-T202 in Jira				

4.174.1 Verification Elements

• LVV-90 - DMS-REQ-0190-V-01: Archive to Data Access Center Network Reliability


LDM-639

4.174.2 Test Items

Reconnect and recover transfer of data between archive and DACs, after disconnecting fiber at an intermediate location between archive and DACs. Verify can meet chToDacNetMTTR = 48[hour]. Demonstrate reconnection and recovery to transfer of data at or exceeding rates specified in LDM-142.

4.174.3 Predecessors

PMCS DMTC-8100-2550 Complete

- 4.174.4 Environment Needs
- **4.174.4.1 Software** See pre-conditions.
- 4.174.4.2 Hardware See pre-conditions.

4.174.5 Input Specification

Data is staged in LDF and data transfer capabilities to US DAC and Chilean DAC are in place.

4.174.6 Output Specification

4.174.7 Test Procedure

Step	Description, Input Data and Expected Result				
	Description	Delegate to Networks			
1	Test Data	No data.			
	Expected				
	Result				

4.175 LVV-T203 - Verify implementation of Archive to Data Access Center Network Secondary Link

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Kian-Tat Lim	
Open LVV-T203 in Jira					

4.175.1 Verification Elements

• LVV-91 - DMS-REQ-0191-V-01: Archive to Data Access Center Network Secondary Link

4.175.2 Test Items

FOR EACH SEGMENT (LS - SCL, SCL - FL, FL - CHI, CHI - CHMPGN): Transfer data between base and archive on primary links over uninterrupted 1 day period. Simulate outage by disconnecting fiber on primary and verify that network fails over to secondary links. Transfer data between base and archive over secondary equipment uninterrupted 1 day period. Restore connection on primary link verify that network recovers to primary. Transfer data between base and archive on primary links over uninterrupted 1 day period. Demonstrate transfer of data at or exceeding rates specified in LDM-142 throughout fail-over period except for <=60s fail-over fail-over to secondary and recover to primary connection execution.

4.175.3 Predecessors

PMCS DMTC-8100-2550 Complete

4.175.4 Environment Needs

4.175.4.1 Software See pre-conditions.

4.175.4.2 Hardware See pre-conditions.





4.175.5 Input Specification

Data is staged in LDF and data transfer capabilities to US DAC and Chilean DAC are in place.

4.175.6 Output Specification

4.175.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Take primary network link down		
1	Test Data	No data.		
	Expected			
	Result			
	Description	Observe operations support over secondary link		
2	Test Data	No data.		
	Expected			
	Result			
	Description	Bring primary network link back up		
3	Test Data	No data.		
	Expected			
	Result			
	Description	Observe catch-up capability over secondary link		
4	Test Data	No data.		
	Expected			
	Result			

4.176 LVV-T204 - Verify implementation of Access to catalogs for external Level 3 processing

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Kian-Tat Lim	

Open LVV-T204 in Jira



4.176.1 Verification Elements

• LVV-50 - DMS-REQ-0122-V-01: Access to catalogs for external Level 3 processing

4.176.2 Test Items

Verify that catalog export, and maintenance/validation tools for Level 3 products to outside of the Data Access Centers.

4.176.3 Predecessors

- 4.176.4 Environment Needs
- 4.176.4.1 Software
- 4.176.4.2 Hardware
- 4.176.5 Input Specification

4.176.6 Output Specification

4.176.7 Test Procedure

Step	Description, Input Data and Expected Result				
	Description	Execute bulk distribution of DRP catalogs			
1	Test Data	No data.			
	Expected				
	Result				
	Description	Observe correct transfer and use of maintenance/validation tools			
2	Test Data	No data.			
	Expected				
	Result				



4.177 LVV-T205 - Verify implementation of Access to input catalogs for DACbased Level 3 processing

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Robert Gruendl	
Open LVV-T205 in Jira					

4.177.1 Verification Elements

• LVV-51 - DMS-REQ-0123-V-01: Access to input catalogs for DAC-based Level 3 processing

4.177.2 Test Items

Verify that data products are available at the Data Access Centers for use in Level 3 processing.

- 4.177.3 Predecessors
- 4.177.4 Environment Needs
- 4.177.4.1 Software
- 4.177.4.2 Hardware
- 4.177.5 Input Specification
- 4.177.6 Output Specification
- 4.177.7 Test Procedure

Step	Description,	Input Data ar	nd Expected Result
	· · · ·		

Description Load Prompt and DR catalogs into PDAC, observe access via LSP

1 Test Data No data.



Step Description, Input Data and Expected Result Expected Result

4.178 LVV-T206 - Verify implementation of Federation with external catalogs

Version	Status	Priority	Verification Type	Owner		
1	Draft	Normal	Test	Colin Slater		
Open LVV-T206 in Jira						

4.178.1 Verification Elements

• LVV-52 - DMS-REQ-0124-V-01: Federation with external catalogs

4.178.2 Test Items

Verify that LSST-produced data can be combined with external datasets.

4.178.3 Predecessors

- 4.178.4 Environment Needs
- 4.178.4.1 Software
- 4.178.4.2 Hardware
- 4.178.5 Input Specification
- 4.178.6 Output Specification
- 4.178.7 Test Procedure



LDM-639

Latest Revision 2020-02-17

Step	Description, Input Data and Expected Result					
1	Description	Load external catalog into PDAC (using VO if possible), observe federation with other cat- alogs via LSP				
·	Test Data	No data.				
	Expected					
	Result					

4.179 LVV-T207 - Verify implementation of Access to images for external Level 3 processing

Version	Status	Priority	Verification Type	Owner		
1	Draft	Normal	Test	Kian-Tat Lim		
Open LVV-T207 in Jira						

4.179.1 Verification Elements

• LVV-54 - DMS-REQ-0126-V-01: Access to images for external Level 3 processing

4.179.2 Test Items

Verify that bulk distribution of images, and accompanying maintenance/validation tools for Level 3 image products to outside of the Data Access Centers.

4.179.3 Predecessors

- 4.179.4 Environment Needs
- 4.179.4.1 Software

4.179.4.2 Hardware



4.179.5 Input Specification

4.179.6 Output Specification

4.179.7 Test Procedure

Step	Description, Input Data and Expected Result				
	Description	Execute bulk distribution of DRP images			
1	Test Data	No data.			
	Expected				
	Result				
	Description	Observe correct transfer and use of maintenance/validation tools			
2	Test Data	No data.			
	Expected				
	Result				

4.180 LVV-T208 - Verify implementation of Access to input images for DAC-based Level 3 processing

Version	Status	Priority	Verification Type	Owner		
1	Draft	Normal	Test	Kian-Tat Lim		
Open LVV-T208 in Jira						

4.180.1 Verification Elements

• LVV-55 - DMS-REQ-0127-V-01: Access to input images for DAC-based Level 3 processing

4.180.2 Test Items

Verify that prompt processing and DRP products are available at the DACs for Level 3 processing at the DACs.



ARGE SYNOPTIC :	SURVEY TELESCOPE	Test Spec for LSST Data Management	LDM-639	Latest Revision 2020-02-17
4.180.3	Predecessors	5		
4.180.4	Environment	Needs		
4.180.4.1	l Software			
4.180.4.2	2 Hardware			
4.180.5	Input Specifi	cation		
4.180.6	Output Speci	ification		
4.180.7	Test Procedu	ire		
Step	Description, l	nput Data and Expected Result		
	Description	Load Prompt and DR images into PDA	AC	
1	Test Data	No data.		
	Expected Result			
	Description	Observe access via LSP		
2	Test Data	No data.		
	Expected			
	Result			

4.181 LVV-T209 - Verify implementation of Data Access Centers

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Analysis	Kian-Tat Lim	
Open LVV-T209 in Jira					



4.181.1 Verification Elements

• LVV-92 - DMS-REQ-0193-V-01: Data Access Centers

4.181.2 Test Items

Verify that the Data Access Centers are provisioned with computing resources necessary to support end-user access to LSST Data Products.

4.181.3	Predecessors	
4.181.4	Environment	Needs
4.181.4.1	l Software	
4.181.4.2	2 Hardware	
4.181.5	Input Specifi	cation
4.181.6	Output Speci	fication
4.181.7	Test Procedu	re
Step	Description, Ir	nput Data and Expected Result
	Description	Analyze design
1	Test Data	No data.
	Expected	
	Result	

4.182 LVV-T210 - Verify implementation of Data Access Center Simultaneous **Connections**



Version	Status	Priority	Verification Type	Owner		
1	Draft	Normal	Test	Kian-Tat Lim		
Open LVV-T210 in lira						

4.182.1 Verification Elements

• LVV-93 - DMS-REQ-0194-V-01: Data Access Center Simultaneous Connections

4.182.2 Test Items

Verify that the each DAC can support at least dacMinConnections simultaneously

- 4.182.3 Predecessors
- 4.182.4 Environment Needs
- 4.182.4.1 Software
- 4.182.4.2 Hardware
- 4.182.5 Input Specification
- 4.182.6 Output Specification

4.182.7 Test Procedure

1

Step Description, Input Data and Expected Result

	Description	Simulate data access to PDAC
-	Test Data	No data.
-	Expected	
	Result	



Latest Revision 2020-02-17

Step	Description, Input Data and Expected Result		
	Description	Observe scaling	
2	Test Data	No data.	
	Expected		
	Result		

4.183 LVV-T211 - Verify implementation of Data Access Center Geographical Distribution

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Analysis	Kian-Tat Lim	
Open LVV-T211 in Jira					

4.183.1 Verification Elements

• LVV-94 - DMS-REQ-0196-V-01: Data Access Center Geographical Distribution

4.183.2 Test Items

Verify that the DACs are geographically distributed to provide low-latency access to data-rights community.

4.183.3 Predecessors

- 4.183.4 Environment Needs
- 4.183.4.1 Software

4.183.4.2 Hardware



4.183.5 Input Specification

4.183.6 Output Specification

4.183.7 Test Procedure

Step Description, Input Data and Expected Resu
--

	Description	Analyze design
1	Test Data	No data.
	Expected	
	Result	

4.184 LVV-T212 - Verify implementation of No Limit on Data Access Centers

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Test	Colin Slater	
Open LVV-T212 in lira					

4.184.1 Verification Elements

• LVV-95 - DMS-REQ-0197-V-01: No Limit on Data Access Centers

4.184.2 Test Items

Verify that additional Data Access Centers can be set up.

- 4.184.3 Predecessors
- 4.184.4 Environment Needs
- 4.184.4.1 Software



LDM-639

- 4.184.4.2 Hardware
- 4.184.5 Input Specification
- 4.184.6 Output Specification

4.184.7 Test Procedure

Step	Description, Input Data and Expected Result				
	Description	Analyze design; instantiate and load simulated DAC, observe correct functioning			
1	Test Data	No data.			
	Expected				
	Result				

4.185 LVV-T376 - Verify the Calculation of Ellipticity Residuals and Correlations

Version	Status	Priority	Verification Type	Owner		
1	Approved	Normal	Test	Leanne Guy		
Open LVV-T376 in lira						

4.185.1 Verification Elements

- LVV-3404 DMS-REQ-0362-V-01: Median residual PSF ellipticity correlations on 5 arcmin scales
- LVV-9780 DMS-REQ-0362-V-02: Max fraction of excess ellipticity residuals on 1 and 5 arcmin scales

4.185.2 Test Items

Verify that the DMS includes software to enable the calculation of the ellipticity residuals and correlation metrics defined in the OSS.



4.185.3 Predecessors

4.185.4 Environment Needs

4.185.4.1 Software

4.185.4.2 Hardware

4.185.5 Input Specification

4.185.6 Output Specification

4.185.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.
	Result	

	Description	Point the butler to an appropriate (precursor or simulated) dataset containing data in all
2		filters, that is sufficient for the purposes of measuring astrometric performance metrics.
	Test Data	No data.
	Expected	
	Result	
	Description	
3		this dataset to perform the measurements of the metrics.
-	Test Data	No data.
	Expected	Measurements of validation metrics and the presence of QA plots resulting from the val-
	Result	idation pipeline.
	Description	Compare measured ellipticity correlations to known (for simulated data) or measured (if
4		using precursor data) values from input (precursor or simulated) data, and confirm that
		the output values for all of the ellipticity performance metrics are as expected.
	Test Data	No data.



LDM-639

Step	Description, Input Data and Expected Result		
	Expected Result	Measured ellipticity metrics that are within reasonable values given the (known) input dataset.	

4.186 LVV-T377 - Verify Calculation of Photometric Performance Metrics

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Leanne Guy
		Open LVV-	-T377 in Jira	

4.186.1 Verification Elements

- LVV-3401 DMS-REQ-0359-V-01: RMS photometric repeatability in uzy
- LVV-9751 DMS-REQ-0359-V-02: Max fraction of sensors with excess unusable pixels
- LVV-9757 DMS-REQ-0359-V-08: Max cross-talk imperfections
- LVV-9755 DMS-REQ-0359-V-06: Accuracy of photometric transformation
- LVV-9754 DMS-REQ-0359-V-05: Repeatability outlier limit in gri
- LVV-9752 DMS-REQ-0359-V-03: Max fraction of outliers among non-saturated sources
- LVV-9756 DMS-REQ-0359-V-07: RMS width of zero point in u-band
- LVV-9753 DMS-REQ-0359-V-04: Accuracy of zero point for colors with u-band
- LVV-9762 DMS-REQ-0359-V-13: Max sky brightness error
- LVV-9760 DMS-REQ-0359-V-11: Fraction of zero point outliers
- LVV-9759 DMS-REQ-0359-V-10: RMS photometric repeatability in gri
- LVV-9758 DMS-REQ-0359-V-09: Repeatability outlier limit in uzy
- LVV-9761 DMS-REQ-0359-V-12: Max fraction of unusable pixels per sensor
- LVV-9764 DMS-REQ-0359-V-15: Percentage of image area with ghosts



- LVV-9766 DMS-REQ-0359-V-17: Max RMS of resolved/unresolved flux ratio
- LVV-9763 DMS-REQ-0359-V-14: RMS width of zero point in all bands except u
- LVV-9765 DMS-REQ-0359-V-16: Accuracy of zero point for colors without u-band

4.186.2 Test Items

Verify that the DMS system provides software to calculate photometric performance metrics, and that the algorithms are properly calculating the desired quantities. Note that because the DMS requirement is that the software shall be provided (and not on the actual measured values of the metrics), we verify all of the requirements via a single test case.

4.186.3 Predecessors

- 4.186.4 Environment Needs
- 4.186.4.1 Software
- 4.186.4.2 Hardware
- 4.186.5 Input Specification
- 4.186.6 Output Specification

4.186.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- _lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.
	Result	



Step Description, Input Data and Expected Result Description Point the butler to a simulated dataset containing data in all filters, that is sufficient for the purposes of measuring photometric performance metrics. 2 Test Data No data. Expected Result Description Execute the LSST Stack package 'validate_drp' (or an alternate package that is relevant) on this dataset to perform the measurements of the metrics. 3 Test Data No data. Expected Measurements of validation metrics and the presence of QA plots resulting from the validation pipeline. Result Description Compare measured photometry to known values from input simulated data, and confirm that the output values for all of the photometric performance metrics are as expected. 4 Test Data No data. Expected Measured astrometry metrics that are within reasonable values given the (known) input dataset. Result

4.187 LVV-T378 - Verify Calculation of Astrometric Performance Metrics

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Leanne Guy
Open LVV-T378 in Jira				

4.187.1 Verification Elements

- LVV-9778 DMS-REQ-0360-V-12: RMS difference between r-band and other filter separation
- LVV-9777 DMS-REQ-0360-V-11: Max fraction of r-band color difference outliers
- LVV-9779 DMS-REQ-0360-V-13: Max fraction exceeding limit on 200 arcmin scales
- LVV-9773 DMS-REQ-0360-V-07: Outlier limit on 5 arcmin scales
- LVV-9770 DMS-REQ-0360-V-05: Outlier limit on 20 arcmin scales



- LVV-9775 DMS-REQ-0360-V-09: Outlier limit on 200 arcmin scales
- LVV-9769 DMS-REQ-0360-V-04: Median absolute error in RA, Dec
- LVV-9774 DMS-REQ-0360-V-08: Median astrometric error on 200 arcmin scales
- LVV-9768 DMS-REQ-0360-V-03: Median astrometric error on 5 arcmin scales
- LVV-9771 DMS-REQ-0360-V-06: Color difference outlier limit relative to r-band
- LVV-9776 DMS-REQ-0360-V-10: Max fraction exceeding limit on 20 arcmin scales
- LVV-9767 DMS-REQ-0360-V-02: Max fraction exceeding limit on 5 arcmin scales

4.187.2 Test Items

Verify that the DMS system provides software to calculate astrometric performance metrics, and that the algorithms are properly calculating the desired quantities. Note that because the DMS requirement is that the software shall be provided (and not on the actual measured values of the metrics), we verify all of the requirements via a single test case.

4.187.3 Predecessors

- 4.187.4 Environment Needs
- 4.187.4.1 Software

4.187.4.2 Hardware

- 4.187.5 Input Specification
- 4.187.6 Output Specification

4.187.7 Test Procedure



Latest Revision 2020-02-17

Step	Description, li	Description, Input Data and Expected Result		
1-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:		
LVV-T987	Test Data			
	Expected	Butler repo available for reading.		
	Result			
2	Description	Point the butler to an appropriate (precursor or simulated) dataset containing data in all filters, that is sufficient for the purposes of measuring astrometric performance metrics.		
	Test Data	No data.		
	Expected			
	Result			
	Description	Execute the LSST Stack package 'validate_drp' (or an alternate package that is relevant) on		
3		this dataset to perform the measurements of the metrics.		
	Test Data	No data.		
	Expected	Measurements of validation metrics and the presence of QA plots resulting from the val-		
	Result	idation pipeline.		
	Description	Compare measured astrometry to known (for simulated data) or measured (if using pre-		
4		cursor data) values from input (precursor or simulated) data, and confirm that the output		
	Toct Data	values for all of the astrometric performance metrics are as expected.		
	Expected	Measured astrometry metrics that are within reasonable values given the (known) input		
	Result	dataset.		

4.188 LVV-T385 - Verify implementation of minimum number of simultaneous retrievals of CCD-sized coadd cutouts

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Leanne Guy
		Open LV	/-T385 in Jira	



4.188.1 Verification Elements

• LVV-3394 - DMS-REQ-0377-V-01: Min number of simultaneous single-CCD coadd cutout image users

4.188.2 Test Items

Verify that at least **ccdRetrievalUsers = 20** users can simultaneously retrieve a single CCDsized coadd cutout using the IVOA SODA protocol.

4.188.3 Predecessors

- 4.188.4 Environment Needs
- 4.188.4.1 Software
- 4.188.4.2 Hardware
- 4.188.5 Input Specification

4.188.6 Output Specification

4.188.7 Test Procedure

Step	Description, Ir	Description, Input Data and Expected Result		
1	Description	Confirm that CCD-sized cutouts from coadds, also containing mask and variance planes, are available on the SODA server. If none are available, copy an image (or some images) to the server.		
	Test Data	No data.		
	Expected	At least one CCD-sized coadd cutout is available, and is a well-formed image.		
	Result			
	Description	Simulate SODA queries by at least ccdRetrievalUsers = 20 users at the same time.		
2	Test Data	No data.		



Step	Description, Input Data and Expected Result	
	Expected Result	
	Description	Confirm that all simulated users retrieved the desired image(s) and that the returned
3	Description	images are well-formed, with (at least) image, mask, and variance planes.
-	Test Data	No data.
	Expected	All of the simulated ccdRetrievalUsers = 20 users retrieved images within the specified
	Result	time (see related Verification Element and Test Case).

4.189 LVV-T1097 - Verify Summit to Base Network Implementation

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeff Kantor
		Open LVV	/-T1097 in Jira	

4.189.1 Verification Elements

• LVV-71 - DMS-REQ-0168-V-01: Summit Facility Data Communications

4.189.2 Test Items

Control the AuxTel through a night of Observing, read out data and transfer data to LSST Summit DWDM. Verify that data acquired by a AuxTel DAQ can be transferred to LSST Summit DWDM and loaded in EFD without problems.

4.189.3 Predecessors

PMCS DMTC-7400-2400 Complete PMCS T&SC-2600-1545 Complete



LDM-639

4.189.4 Environment Needs

- **4.189.4.1 Software** See pre-conditions
- 4.189.4.2 Hardware See pre-conditions.

4.189.5 Input Specification

- 1. Summit Control Network and Camera Data Backbone installed and operating properly.
- 2. Summit Base Network installed and operating properly.
- 3. AuxTel hardware and control systems are functional with LATISS. AuxTel TCS, AuxTel EFD, AuxTel CCS, AuxTel DAQ are connected via LSST Control Network on Summit to LSST DWDM (with at least 2 x 10 Gbps ethernet port client cards).
- 4. AuxTel Archiver/forwarders installed in Summit and operating properly.

4.189.6 Output Specification

4.189.7 Test Procedure

Step	Description, Input Data and Expected Result		
1	Description	Verify the available documentation in order to ensure that the Summit to Base Network has been set-up and is working.	
I	Test Data	No data.	
	Expected	List of documents that demonstrate the network implementation	
	Result		

4.190 LVV-T1168 - Verify Summit - Base Network Integration

Version Status Priority Verification Type Owner



LDM-639

Latest Revision 2020-02-17

1 Approved Normal Inspection Jeff Kantor

Open LVV-T1168 in Jira

4.190.1 Verification Elements

• LVV-73 - DMS-REQ-0171-V-01: Summit to Base Network

4.190.2 Test Items

3 phases done (in collaboration with equipment/installation vendors):

- 1. Installation of fiber optic cables and Optical Time Domain Reflector (OTDR) fiber testing (completed 20170602 REUNA deliverable RD10)
- Installation of AURA DWDM and Data Transfer Node (DTN) (completed 20171218 DMTR-82)
- 3. Installation of LSST DWDM and Bit Error Rate Tester (BERT) data (completed 20190505 collection-7743, 20191108 DAQ DWDM Connection Tests)

4.190.3 Predecessors

See pre-conditions by phase above.

4.190.4 Environment Needs

- **4.190.4.1 Software** perfsonar on DTN.
- 4.190.4.2 Hardware OTDR, DTN.

4.190.5 Input Specification

PMCS DMTC-7400-2330 COMPLETE By phase:





- 1. Posts from Cerro Pachon to AURA Gatehouse repaired/improved. Fiber installed on posts from Cerro Pachon to AURA Gatehouse. Fiber installed from AURA Gatehouse to AURA compound in La Serena. OTDR purchased.
- 2. AURA DWDM installed in caseta on Cerro Pachon and in existing computer room in La Serena. DTN installed in La Serena. DTN loaded with software and test data staged.
- 3. Base Data Center (BDC) ready for installation of LSST DWDM. Fiber connecting existing computer room to BDC. LSST DWDM equipment installed in Summit Computer Room and BDC.

4.190.6 Output Specification

Fiber tested to within acceptable Db. Bandwidth, latency within specifications.

4.190.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Test optical fiber with OTDR	
1	Test Data	OTDR generated optical data	
	Expected	Fiber tested to within acceptable Db.	
	Result		
	Description	Test AURA DWDM	
2	Test Data	DTN perfSonar generated data	
	Expected	Summit - Base bandwidth and latency within specifications	
	Result		
	Description	Test LSST DWDM	
3	Test Data	BERT generated data	
	Expected	Summit - Base bandwidth, latency, bit error rate within specifications	
	Result		

LVV-T1232 - Verify Implementation of Catalog Export Formats From the 4.191 **Portal Aspect**

Status Verification Type Version Priority Owner



LDM-639

Latest Revision 2020-02-17

1 Defined Normal Test Colin Slater

Open LVV-T1232 in Jira

4.191.1 Verification Elements

• LVV-35 - DMS-REQ-0078-V-01: Catalog Export Formats

4.191.2 Test Items

Verify that catalog data is exportable from the portal aspect in a variety of community-standard formats.

4.191.3 Predecessors

- 4.191.4 Environment Needs
- 4.191.4.1 Software

4.191.4.2 Hardware

4.191.5 Input Specification

4.191.6 Output Specification

4.191.7 Test Procedure

Step Description, Input Data and Expected Result

1-1 from	Description	Navigate to the Portal Aspect endpoint. The stable version should be used for this test and is cur- _rently_located_at: https://lsst-lsp-stable.ncsa.illinois.edu/portal/app/
LVV-T849	Test Data	
	Expected	A credential-entry screen should be displayed.
	Result	



Latest Revision 2020-02-17

Step	Description, i	
1-2 from	Description Test Data	Enter a valid set of credentials for an LSST user with LSP access on the instance under test.
LVV-1849	Expected Result	The Portal Aspect UI should be displayed following authentication.
	Description	Select query type "ADQL".
2	Test Data	No data.
	Expected	
	Result	
3	Description	Execute the example query given in the example code below by entering the text in the ADQL Query box, then clicking "Search" at the lower left corner of the page.
0	Test Data	No data.
	Example Code	SELECT cntr, ra, decl, w1mpro_ep, w2mpro_ep, w3mpro_ep FROM wise_00.allwise_p3as_mep WHERE CONTAINS(POINT('ICRS', ra, decl), CIRCLE('ICRS', 192.85, 27, 13, .2)) = 1
	Expected	A new page will load with the search results as a table, with some plots as well.
	Result	
4	Description	Click the icon that looks like a floppy disk (it says "Save the content as an IPAC, CSV, or TSV table" when you mouse over it).
	Test Data	No data.
	Expected	
	Result	
5	Description	 Select "CSV", then specify a destination to save the file on your local computer. Select "VOTable", then specify a destination to save the file on your local computer. Select "FITS", then specify a destination to save the file on your local computer.
	Test Data	No data.
	Expected	
	Result	
6	Description	Open each of the files (either in TOPCAT, or using Astropy io tools). Confirm that the data tables are well-formed, and that each table contains the same columns and the same number of rows.
	Test Data	No data.
	Expected	
	Result	

Step Description, Input Data and Expected Result



Step	Description,	Input Data and Expected Result				
7-1 from LVV-T850	Description	Description Currently, there is no logout mechanism on the portal. This should be updated as the system matures.				
	Test Data	Simply close the browser window.				
	Expected Result	Closed browser window. When navigating to the portal endpoint, expect to execute the steps in LVV-T849.				

Latest Revision 2020-02-17

Test Spec for LSST Data Management

4.192 LVV-T1240 - Verify implementation of minimum astrometric standards per CCD

Version	Status	Priority	Verification Type	Owner	
1	Approved	Normal	Test	Jim Bosch	
Open LVV-T1240 in Jira					

4.192.1 Verification Elements

• LVV-9741 - DMS-REQ-0030-V-02: Minimum astrometric standards per CCD

4.192.2 Test Items

Verify that each CCD in a processed dataset had its astrometric solution determined by at least **astrometricMinStandards = 5** astrometric standards.

- 4.192.3 Predecessors
- 4.192.4 Environment Needs
- 4.192.4.1 Software



LDM-639

4.192.4.2 Hardware

4.192.5 Input Specification

4.192.6 Output Specification

4.192.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Identify an appropriate processed dataset for this test.
1	Test Data	No data.
	Expected	A dataset with Processed Visit Images.
	Result	
2-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:
LVV-T987	Test Data	
	Expected	Butler repo available for reading.
	Result	
	Description	Select a single visit from the dataset, and extract its calibration data. For a subset of
3		CCDs, check how many astrometric standards contributed to the solution. Confirm that
		this number is at least astrometricMinStandards = 5.

Test Data	No data.
Expected	At least astrometricMinStandards from each CCD were used in determining the WCS
Result	solution.

4.193 LVV-T1250 - Verify implementation of minimum number of simultaneous DM EFD query users

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin
Open LVV-T1250 in lira				



4.193.1 Verification Elements

• LVV-3400 - DMS-REQ-0358-V-01: Min number of simultaneous DM EFD query users

4.193.2 Test Items

Verify that the DM EFD can support **dmEfdQueryUsers = 5** simultaneous queries. The additional requirement that each query must last no more than **dmEfdQueryTime = 10 seconds** will be verified separately in LVV-T1251, but these must be satisfied together.

4.193.3 Predecessors

- 4.193.4 Environment Needs
- 4.193.4.1 Software
- 4.193.4.2 Hardware
- 4.193.5 Input Specification

4.193.6 Output Specification

4.193.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Send multiple (at least 5) simultaneous queries to the DM EFD.	
1	Test Data	No data.	
	Expected		
	Result		
2	Description	Confirm that (a) the queries executed successfully, and that (b) they return reasonable results.	
	Test Data	No data.	
	Expected		
	Result		

DRAFT NOT YET APPROVED – The contents of this document are subject to configuration control by the LSST DM Change Control Board. – DRAFT NOT YET APPROVED



LDM-639

Latest Revision 2020-02-17

Step	Description, l	Description, Input Data and Expected Result			
3	Description	Repeat the above steps for different queries, and different numbers of simultaneous queries, to confirm that the expected performance is met regardless of the query being executed.			
	Test Data	No data.			
	Expected				
	Result				

4.194 LVV-T1251 - Verify implementation of maximum time to retrieve DM EFD query results

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin
Open LVV-T1251 in Jira				

4.194.1 Verification Elements

• LVV-9788 - DMS-REQ-0358-V-02: Max time to retrieve DM EFD query results

4.194.2 Test Items

Verify that the DM EFD can support **dmEfdQueryUsers = 5** simultaneous queries, with each query must executing in no more than **dmEfdQueryTime = 10 seconds.** The requirement on at least 5 simultaneous queries will be verified separately in LVV-T1250, but these must be satisfied together.

4.194.3 Predecessors

4.194.4 Environment Needs

4.194.4.1 Software



LDM-639

4.194.4.2 Hardware

4.194.5 Input Specification

4.194.6 Output Specification

4.194.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Send multiple (at least 5) simultaneous queries to the DM EFD.		
1	Test Data	No data.		
	Expected			
	Result			
2	Description	Confirm that (a) the queries executed successfully, and that (b) they return reasonable results. Check that the time of execution for all queries was less than 10 seconds.		
2	Test Data	No data.		
	Expected			
	Result			
3	Description	Repeat the above steps for different queries, and different numbers of simultaneous queries, to confirm that the expected performance is met regardless of the query being executed.		
	Test Data	No data.		
	Expected			
	Result			

4.195 LVV-T1252 - Verify number of simultaneous alert filter users

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Eric Bellm
Open LVV-T1252 in Jira				



4.195.1 Verification Elements

• LVV-9748 - DMS-REQ-0343-V-02: Number of simultaneous users

4.195.2 Test Items

Verify that the DMS alert filter service supports **numBrokerUsers = 100** simultaneous brokers.

4.195.3 Predecessors

- 4.195.4 Environment Needs
- 4.195.4.1 Software
- 4.195.4.2 Hardware
- 4.195.5 Input Specification

4.195.6 Output Specification

4.195.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Create a simulated alert stream.	
1	Test Data	No data.	
	Expected		
	Result		
2	Description	Simultaneously execute user-defined alert filters for at least numBrokerUsers = 100 users, and confirm that the system successfully filters the stream as requested. Confirm that the bandwidth requirement of numBrokerAlerts = 20 per user was	
		met.Simultaneously execute user-defined alert filters for at least 100 users, and confirm that the system successfully filters the stream as requested.	
	Test Data	No data.	



LDM-639

Step	Description, Input Data and Expected Result		
	Expected Result	All of the (simulated) numBrokerUsers = 100 users successfully receive their requested filtered alerts.	

4.196 LVV-T1264 - Verify implementation of archiving camera test data

Version	Status	Priority	Verification Type	Owner
1	Defined	Normal	Test	Robert Gruendl
Open LVV-T1264 in Jira				

4.196.1 Verification Elements

• LVV-9637 - DMS-REQ-0372-V-01: Archiving Camera Test Data

4.196.2 Test Items

Verify that a subset of camera test data has been ingested into Butler repos and is available through standard data access tools.

- 4.196.3 Predecessors
- 4.196.4 Environment Needs
- 4.196.4.1 Software
- 4.196.4.2 Hardware
- 4.196.5 Input Specification
- 4.196.6 Output Specification



4.196.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Obtain some data on a camera test stand.	
1	Test Data	No data.	
	Expected		
	Result		
2	Description	Wait a sufficient amount of time, then confirm that automatic transfer/ingest of the data has occurred, and a repo is available at NCSA.	
-	Test Data	No data.	
	Expected	The data is present at NCSA in non-empty repos.	
	Result		
	Description	Identify the relevant Butler repo of ingested camera test stand data.	
3	Test Data	No data.	
	Expected		
	Result		
4-1 from	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the fol- lowing:	
LVV-T987	Test Data		
	Expected	Butler repo available for reading.	
	Result		
5	Description	Read various repo data products with the Butler, and confirm that they contain the expected data.	
5	Test Data	No data.	
	Expected	Camera test stand data that is well-formed.	

Result

4.197 LVV-T1276 - Verify implementation of latency of reporting optical transients

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Eric Bellm
Open LVV-T1276 in Jira				

DRAFT NOT YET APPROVED – The contents of this document are subject to configuration control by the LSST DM Change Control Board. – DRAFT NOT YET APPROVED



LDM-639

4.197.1 Verification Elements

• LVV-9740 - DMS-REQ-0004-V-02: Latency of reporting optical transients

4.197.2 Test Items

Verify that alerts are generated for optical transients within **OTT1 = 1 minute** of the completion of the readout of the last image.

4.197.3 Predecessors

- 4.197.4 Environment Needs
- 4.197.4.1 Software
- 4.197.4.2 Hardware
- 4.197.5 Input Specification

4.197.6 Output Specification

4.197.7 Test Procedure

Step	Description, Input Data and Expected Result		
1	Description	Identify a precursor dataset containing raw images (and templates), that is suitable for testing the Alert Production.	
·	Test Data	No data.	
	Expected		
	Result		
2-1 from	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame process- ing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration,	
LVV-T866		difference imaging, DIASource detection/measurement, source association). During Operations, it is presumed that these are automated for a given dataset.	
	Test Data		

DRAFT NOT YET APPROVED – The contents of this document are subject to configuration control by the LSST DM Change Control Board. – DRAFT NOT YET APPROVED


_	-	-		_	
Fest	Spec	for	LSST	Data	Management

Latest Revision 2020-02-17

Step Description, Input Data and Expected Result

	Expected	An output dataset including difference images and DIASource and DIAObject measurements.
	Result	
2-2 from	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
LVV-T866	Test Data	
	Expected	
	Result	
	D	

	Description	Time processing of data starting from (pre-ingested) raw files until an alert is available for
3		distribution; verify that this time is less than OTT1.
C	Test Data	No data.
-	Expected	Alerts are received via the alert stream within OTT1=1 minute from the time the Alert
	Result	Production payload was executed.

4.198 LVV-T1277 - Verify processing of maximum number of calibration exposures

Version	Status	Priority	Verification Type	Owner		
1	Draft	Normal	Test	Kian-Tat Lim		
Open LVV-T1277 in Jira						

4.198.1 Verification Elements

• LVV-9745 - DMS-REQ-0131-V-02: Max number of calibs to be processed

4.198.2 Test Items

Verify that as many as **nCalExpProc = 25** calibration exposures can be processed together within time calProcTime.

4.198.3 Predecessors



4.198.4 Environment Needs

- 4.198.4.1 Software
- 4.198.4.2 Hardware
- 4.198.5 Input Specification

4.198.6 Output Specification

4.198.7 Test Procedure

Step Description, Input Data and Expected Result

1	Description Test Data	Identify a dataset of raw calibration exposures containing at least nCalExpProc = 25 exposures. (If it contains more than 25 exposures, use only 25 for the test.) No data.
	Expected	
	Result	
2-1 from	Description	Execute the Daily Calibration Products Update payload. The payload uses raw calibration images
LVV-		and information from the Transformed EFD to generate a subset of Master Calibration Images and Calibration Database entries in the Data Backbone.
T1059	Test Data	
	Expected	
	Result	
2-2 from	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present
LVV-	Test Data	
T1059	Expected	
	Result	

	Description	Confirm that the processing completed successfully within calProcTime = 1200 seconds.
3	Test Data	No data.
	Expected	Calibration products resulting from processed raw calibration exposures are present
	Result	within calProcTime, and are well-formed images.
	Description	Perform the test again with <i>more than</i> nCalExpProc = 25 images, and confirm that the
4		processing completes within calProcTime = 1200 seconds.



Test	C	£	ICCT	Data	Managaman
rest	Spec	IOL	L331	Data	wanagemen

Latest Revision 2020-02-17

Step	Description,	Description, Input Data and Expected Result			
	Test Data	No data.			
	Expected Result	Calibration products resulting from processed raw calibration exposures are present within calProcTime, and are well-formed images. (To verify that the test with 25 images was not at the limits of what the software can handle – should be able to exceed that bare minimum.)			

4.199 LVV-T1332 - Verify implementation of maximum time for retrieval of CCDsized coadd cutouts

Version	Status	Priority	Verification Type	Owner		
1	Defined	Normal	Test	Leanne Guy		
Open LVV-T1332 in lira						

4.199.1 Verification Elements

• LVV-9797 - DMS-REQ-0377-V-02: Max time to retrieve single-CCD coadd cutout image

4.199.2 Test Items

Verify that at least **ccdRetrievalUsers = 20** users can retrieve CCD-sized coadd cutouts using the IVOA SODA protocol within a maximum retrieval time of **ccdRetrievalTime = 15 seconds**.

4.199.3 Predecessors

- 4.199.4 Environment Needs
- 4.199.4.1 Software

4.199.4.2 Hardware



4.199.5 Input Specification

4.199.6 Output Specification

4.199.7 Test Procedure

|--|

1	Description Test Data	Confirm that CCD-sized cutouts from coadds, also containing mask and variance planes, are available on the SODA server. If none are available, copy an image (or some images) to the server. No data.
	Expected	At least one CCD-sized coadd cutout is available, and is a well-formed image.
	Result	
	Description	Simulate SODA queries by at least ccdRetrievalUsers = 20 users at the same time.
2	Test Data	No data.
	Expected	
	Result	
3	Description	Monitor the time that each query takes to complete, and confirm that all simulated users retrieved the desired image(s) within ccdRetrievalTime = 15 seconds.
-	Test Data	No data.
	Expected	All of the simulated ccdRetrievalUsers = 20 users retrieved images within ccdRetrieval -
	Result	Time = 15 seconds.

4.200 LVV-T1524 - Verify Implementation of Exporting MOCs as FITS

Version	Status	Priority	Verification Type	Owner		
1	Draft	Normal	Demonstration	Jeffrey Carlin		
Open LVV-T1524 in Jira						

4.200.1 Verification Elements

• LVV-18222 - DMS-REQ-0384-V-01: Export MOCs As FITS_1



LDM-639

4.200.2 Test Items

Verify that the Data Management system provides a means for exporting the LSST-generated MOCs in the FITS serialization form defined in the IVOA MOC Recommendation.

- 4.200.3 Predecessors
- 4.200.4 Environment Needs
- 4.200.4.1 Software
- 4.200.4.2 Hardware
- 4.200.5 Input Specification
- 4.200.6 Output Specification

4.200.7 Test Procedure

Step Description, Input Data and Expected Result

	Description		
1	Test Data	No data.	
	Expected		
	Result		

4.201 LVV-T1525 - Verify Implementation of Linkage Between HiPS Maps and Coadded Images

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Demonstration	Jeffrey Carlin	
Open LVV-T1525 in Jira					



4.201.1 Verification Elements

• LVV-18223 - DMS-REQ-0381-V-01: HiPS Linkage to Coadds_1

4.201.2 Test Items

Verify that the HiPS maps produced by the Data Management system provide for straightforward linkage from the HiPS data to the underlying LSST coadded images, and that this has been implemented using a mechanism supported by both the LSST Science Platform and by community tools.

4.201.3 Predecessors

- 4.201.4 Environment Needs
- 4.201.4.1 Software
- 4.201.4.2 Hardware
- 4.201.5 Input Specification
- 4.201.6 Output Specification

4.201.7 Test Procedure

Step	Description, Input Data and Expected Result					
	Description					
1	Test Data	No data.				
	Expected					
	Result					

4.202 LVV-T1526 - Verify Availability of Secure and Authenticated HiPS Service



LDM-639

Latest Revision 2020-02-17

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Demonstration	Jeffrey Carlin	
Open LVV-T1526 in Jira					

4.202.1 Verification Elements

• LVV-18224 - DMS-REQ-0380-V-01: HiPS Service_1

4.202.2 Test Items

Verify that the Data Management system includes a secure and authenticated Internet endpoint for an IVOA-compliant HiPS service. Confirm that this service is advertised via Registry as well as in the HiPS community mechanism operated by CDS, or whatever equivalent mechanism may exist in the LSST operations era.

4.202.3 Predecessors

4.202.4 Environment Needs

4.202.4.1 Software

4.202.4.2 Hardware

4.202.5 Input Specification

4.202.6 Output Specification

4.202.7 Test Procedure

Step Description, Input Data and Expected Result

Description

1



Step	Description, Input Data and Expected Result					
	Test Data	No data.				
	Expected					
	Result					

4.203 LVV-T1527 - Verify Support for HiPS Visualization

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Demonstration	Jeffrey Carlin	
Open LVV-T1527 in Jira					

4.203.1 Verification Elements

• LVV-18225 - DMS-REQ-0382-V-01: HiPS Visualization_1

4.203.2 Test Items

Verify that the LSST Science Platform supports the visualization of LSST-generated HiPS image maps as well as other HiPS maps which satisfy the IVOA HiPS Recommendation. Also verify that integrated behavior is available, such as the overplotting of catalog entries, comparable to that provided for individual source images (e.g., PVIs and coadd tiles).

4.203.3 Predecessors

- 4.203.4 Environment Needs
- 4.203.4.1 Software

4.203.4.2 Hardware

4.203.5 Input Specification



4.203.6 Output Specification

4.203.7 Test Procedure

Step	Description, Input Data and Expected Result					
	Description					
1	Test Data	No data.				
	Expected					
	Result					

4.204 LVV-T1528 - Verify Visualization of MOCs via Science Platform

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Demonstration	Jeffrey Carlin	
Open LVV-T1528 in Jira					

4.204.1 Verification Elements

• LVV-18226 - DMS-REQ-0385-V-01: MOC Visualization_1

4.204.2 Test Items

Verify that the LSST Science Platform supports the visualization of the LSST-generated MOCs as well as other MOCs which satisfy the IVOA MOC Recommendation.

4.204.3 Predecessors

4.204.4 Environment Needs

4.204.4.1 Software



LDM-639

- 4.204.4.2 Hardware
- 4.204.5 Input Specification
- 4.204.6 Output Specification

4.204.7 Test Procedure

Step	Description, l	nput Data and Expected Result	
	Description		
1	Test Data	No data.	
	Expected		
	Result		

4.205 LVV-T1529 - Verify Production of All-Sky HiPS Map

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Demonstration	Jeffrey Carlin	
Open LVV-T1529 in Jira					

4.205.1 Verification Elements

• LVV-18227 - DMS-REQ-0379-V-01: Produce All-Sky HiPS Map_1

4.205.2 Test Items

Verify that Data Release Production includes the production of an all-sky image map for the existing coadded image area in each filter band, and at least one pre-defined all-sky color image map, following the IVOA HiPS Recommendation.

4.205.3 Predecessors



ARGE STINOPTIC 3	SURVET TELESCOPE	Test Spec for LSST Data Management	LDM-639	Latest Revision 2020-02-17
4.205.4	Environment	Needs		
4.205.4. 1	l Software			
4.205.4.2	2 Hardware			
4.205.5	Input Specific	cation		
4.205.6	Output Speci	fication		
4.205.7	Test Procedu	re		
Step	Description, Ir	nput Data and Expected Result		
	Description			
1	Test Data	No data.		
	Expected			
	Result			

4.206 LVV-T1530 - Verify Production of Multi-Order Coverage Maps for Survey Data

Version	Status	Priority	Verification Type	Owner	
1	Draft	Normal	Demonstration	Jeffrey Carlin	
Open LVV-T1530 in Jira					

4.206.1 Verification Elements

• LVV-18228 - DMS-REQ-0383-V-01: Produce MOC Maps_1



LDM-639

4.206.2 Test Items

Verify that Data Release Production includes the production of Multi-Order Coverage maps for the survey data, conformant with the IVOA MOC recommendation. Confirm that separate MOC are produced for each filter band for the main survey, and additional MOCs are produced to represent special-programs datasets and other collections of on-sky data.

- 4.206.3 Predecessors
- 4.206.4 Environment Needs
- 4.206.4.1 Software
- 4.206.4.2 Hardware
- 4.206.5 Input Specification
- 4.206.6 Output Specification
- 4.206.7 Test Procedure

Step	Description, Input Data and Expected Result	
	Description	
1	Test Data	No data.
	Expected	
	Result	

4.207 LVV-T1560 - Verify archiving of processing provenance

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Inspection	Jeffrey Carlin
Open LVV-T1560 in Jira				



4.207.1 Verification Elements

• LVV-18230 - DMS-REQ-0386-V-01: Archive Processing Provenance_1

4.207.2 Test Items

Verify that provenance information related to data processing, including relevant data from other subsystems, has been archived.

4.207.3	Predecessors			
4.207.4	Environment Needs			
4.207.4.1	.4.1 Software			
4.207.4.2	2 Hardware			
4.207.5	Input Specification			
4.207.6	Output Specification			
4.207.7	Test Procedure			
Step	Description, Input Data and Expected Result			
	Description			
1	Test Data No data.			
	Expected			
	Result			

4.208 LVV-T1561 - Verify provenance availability to science users

Version Status Priority Verification Type Owner



LDM-639

Latest Revision 2020-02-17

1 Draft Normal Inspection Jeffrey Carlin Open LVV-T1561 in Jira

4.208.1 Verification Elements

• LVV-18231 - DMS-REQ-0387-V-01: Serve Archived Provenance_1

4.208.2 Test Items

Verify that archived provenance data is available to science users together with the associated science data products.

- 4.208.3 Predecessors
- 4.208.4 Environment Needs
- 4.208.4.1 Software
- 4.208.4.2 Hardware
- 4.208.5 Input Specification
- 4.208.6 Output Specification
- 4.208.7 Test Procedure
- Step Description, Input Data and Expected Result

Description		
1	Test Data	No data.
	Expected	
	Result	



LDM-639

4.209 LVV-T1562 - Verify availability of re-run tools

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Demonstration	Jeffrey Carlin
		Open LV	V-T1562 in Jira	

4.209.1 Verification Elements

LVV-18232 - DMS-REQ-0388-V-01: Provide Re-Run Tools_1

4.209.2 Test Items

Verify that tools are provided to use the archived provenance data to re-run a data processing operation under the same conditions (including LSST software version, its configuration parameters, and supporting data such as calibration frames) as a previous run of that operation.

4.209.3 Predecessors

4.209.4 Environment Needs

- 4.209.4.1 Software
- 4.209.4.2 Hardware
- 4.209.5 Input Specification
- 4.209.6 Output Specification
- 4.209.7 Test Procedure



Step	Description, Input Data and Expected Result		
	Description		
1	Test Data	No data.	
	Expected		
	Result		

4.210 LVV-T1563 - Verify re-run on different system produces the same results

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Demonstration	Jeffrey Carlin
		Open LV	V-T1563 in Jira	

4.210.1 Verification Elements

• LVV-18233 - DMS-REQ-0390-V-01: Re-Runs on Other Systems_1

4.210.2 Test Items

Verify that tools are provided to use the archived provenance data to re-run a data processing operation on different systems, and that the results produced are the same to the extent computationally feasible.

4.210.3 Predecessors

4.210.4 Environment Needs

4.210.4.1 Software

4.210.4.2 Hardware

4.210.5 Input Specification



4.210.6 Output Specification

4.210.7 Test Procedure

Step	Description, Input Data and Expected Result	
	Description	
1	Test Data	No data.
	Expected	
	Result	

4.211 LVV-T1564 - Verify re-run on similar system produces the same results

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Demonstration	Jeffrey Carlin
		Open LV	V-T1564 in Jira	

4.211.1 Verification Elements

• LVV-18234 - DMS-REQ-0389-V-01: Re-Runs on Similar Systems_1

4.211.2 Test Items

Verify that a provenance-based re-run that is run on the same system, or a system with identically configured hardware and system software, produces the same results.

4.211.3 Predecessors

4.211.4 Environment Needs

4.211.4.1 Software



LDM-639

- 4.211.4.2 Hardware
- 4.211.5 Input Specification
- 4.211.6 Output Specification

4.211.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description		
1	Test Data No data.		
	Expected		
	Result		

4.212 LVV-T1745 - Verify calculation of median relative astrometric measurement error on 20 arcminute scales

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jeffrey Carlin
Open LVV-T1745 in Jira				

4.212.1 Verification Elements

• LVV-3402 - DMS-REQ-0360-V-01: Median astrometric error on 20 arcmin scales

4.212.2 Test Items

Verify that the DM system has provided the code to calculate the median relative astrometric measurement error on 20 arcminute scales and assess whether it meets the requirement that it shall be no more than AM2 = 10 milliarcseconds.

4.212.3 Predecessors



4.212.4 Environment Needs

- 4.212.4.1 Software
- 4.212.4.2 Hardware
- 4.212.5 Input Specification
- 4.212.6 Output Specification

4.212.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Identify a dataset containing at least one field with multiple overlapping visits.		
1	Test Data	No data.		
	Expected	A dataset that has been ingested into a Butler repository.		
	Result			
2-1 from LVV-T860	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:		
		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash 		
		development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash		
		LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash		
		From the command line, execute the commands below in the example code:		
	Test Data			
	Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.		
		To check versions in use, type: _eups list -s		
3-1 from LVV-	Description	Execute 'validate_drp' on a repository containing precursor data. Identify the path to the data, which we will call 'DATA/path', then execute the following (with additional flags specified as needed):		
		VED - The contents of this document are subject to configuration control by the		
DRA	DRAFT NOT TET APPROVED - The contents of this document are subject to comparation control by the			



Step	Description, Input Data and Expected Result			
	Test Data			
	Expected	JSON files (and associated figures) containing the Measurements and any associated "extras."		
	Result			
	Description	Confirm that the metric AM2 has been calculated, and that its values are reasonable.		
4	Test Data	No data.		
	Expected	A JSON file (and/or a report generated from that JSON file) demonstrating that AM2 has		
	Result	been calculated.		

LDM-639

Latest Revision 2020-02-17

4.213 LVV-T1746 - Verify calculation of fraction of relative astrometric measurement error on 5 arcminute scales exceeding outlier limit

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jeffrey Carlin
Open LVV-T1746 in Jira				

4.213.1 Verification Elements

- LVV-9767 DMS-REQ-0360-V-02: Max fraction exceeding limit on 5 arcmin scales
- LVV-9773 DMS-REQ-0360-V-07: Outlier limit on 5 arcmin scales

4.213.2 Test Items

Verify that the DM system has provided the code to calculate the maximum fraction of relative astrometric measurements on 5 arcminute scales that exceed the 5 arcminute outlier limit **AD1 = 20 milliarcseconds**, and assess whether it meets the requirement that it shall be less than **AF1 = 10 percent**.

4.213.3 Predecessors



4.213.4 Environment Needs

- 4.213.4.1 Software
- 4.213.4.2 Hardware
- 4.213.5 Input Specification
- 4.213.6 Output Specification

4.213.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Identify a dataset containing at least one field with multiple overlapping visits.
1	Test Data	No data.
	Expected	A dataset that has been ingested into a Butler repository.
	Result	
2-1 from LVV-T860	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:
		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash
		From the command line, execute the commands below in the example code:
	Test Data	
	Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.
		To check versions in use, type: _eups list -s
3-1 from LVV-	Description	Execute 'validate_drp' on a repository containing precursor data. Identify the path to the data, which we will call 'DATA/path', then execute the following (with additional flags specified as needed):
	FT NOT YET APPR	OVED – The contents of this document are subject to configuration control by the SST DM Change Control Board, – DRAFT NOT YET APPROVED



Test	Spec	for	LSST	Data	Management

Latest Revision 2020-02-17

Step	Description, Input Data and Expected Result			
	Test Data			
	Expected	JSON files (and associated figures) containing the Measurements and any associated "extras."		
	Result			
4	Description	Confirm that the metric AF1 has been calculated using the outlier limit AD1, and that its values are reasonable.		
	Test Data	No data.		
	Expected	A JSON file (and/or a report generated from that JSON file) demonstrating that AF1 has		
	Result	been calculated (and used the limit AD1).		

4.214 LVV-T1747 - Verify calculation of relative astrometric measurement error on 5 arcminute scales

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jeffrey Carlin
Open LVA/ T1747 in line				

Open LVV-T1747 in Jira

4.214.1 Verification Elements

• LVV-9768 - DMS-REQ-0360-V-03: Median astrometric error on 5 arcmin scales

4.214.2 Test Items

Verify that the DM system has provided the code to calculate the relative astrometric measurement error on 5 arcminute scales, and assess whether it meets the requirement that it shall be less than **AM1 = 10 milliarcseconds.**

4.214.3 Predecessors



4.214.4 Environment Needs

- 4.214.4.1 Software
- 4.214.4.2 Hardware
- 4.214.5 Input Specification
- 4.214.6 Output Specification

4.214.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Identify a dataset containing at least one field with multiple overlapping visits.
1	Test Data	No data.
	Expected	A dataset that has been ingested into a Butler repository.
	Result	
2-1 from LVV-T860	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:
		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash
		From the command line, execute the commands below in the example code:
	Test Data	
	Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.
		To check versions in use, type: _eups list -s
3-1 from LVV-	Description	Execute 'validate_drp' on a repository containing precursor data. Identify the path to the data, which we will call 'DATA/path', then execute the following (with additional flags specified as needed):
	FT NOT YET APPR	OVED – The contents of this document are subject to configuration control by the SST DM Change Control Board, – DRAFT NOT YET APPROVED



_	-			_	
Test	Spec	for	LSST	Data	Management

Latest Revision 2020-02-17

Step	Description, l	Description, Input Data and Expected Result		
	Test Data			
	Expected	JSON files (and associated figures) containing the Measurements and any associated "extras."		
	Result			
	Description	Confirm that the metric AM1 has been calculated, and that its values are reasonable.		
4	Test Data	No data.		
	Expected	A JSON file (and/or a report generated from that JSON file) demonstrating that AM1 has		
	Result	been calculated.		

4.215 LVV-T1748 - Verify calculation of median error in absolute position for RA, Dec axes

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jeffrey Carlin
Open I VV-T1748 in lira				

4.215.1 Verification Elements

• LVV-9769 - DMS-REQ-0360-V-04: Median absolute error in RA, Dec

4.215.2 Test Items

Verify that the DM system has provided the code to calculate the median error in absolute position for each axis, RA and DEC, and assess whether it meets the requirement that it shall be less than **AA1 = 50 milliarcseconds**.

4.215.3 Predecessors

4.215.4 Environment Needs

4.215.4.1 Software



LDM-639

4.215.4.2 Hardware

4.215.5 Input Specification

4.215.6 Output Specification

4.215.7 Test Procedure

Step	Description, Input Data and Expected Result			
	Description	Identify a dataset containing at least one field with multiple overlapping visits.		
1	Test Data	No data.		
	Expected Result	A dataset that has been ingested into a Butler repository.		
2-1 from LVV-T860	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:		
		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash 		
		development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash		
		LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash		
		From the command line, execute the commands below in the example code:		
	Test Data			
	Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.		
		To check versions in use, type: _eups list -s		
3-1 from	Description	Execute 'validate_drp' on a repository containing precursor data. Identify the path to the data, which _we will call 'DATA/path', then execute the following (with additional flags specified as needed):		
	Test Data			
11/44	Expected	JSON files (and associated figures) containing the Measurements and any associated "extras."		
	Result			
4	Description	Confirm that the metric AA1 has been calculated, and that its values are reasonable.		



Latest Revision 2020-02-17

Step	Description, Input Data and Expected Result			
	Test Data	No data.		
	Expected Result	A JSON file (and/or a report generated from that JSON file) demonstrating that AA1 has been calculated.		

4.216 LVV-T1749 - Verify calculation of fraction of relative astrometric measurement error on 20 arcminute scales exceeding outlier limit

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jeffrey Carlin
Open LW/-T1749 in lira				

4.216.1 Verification Elements

- LVV-9776 DMS-REQ-0360-V-10: Max fraction exceeding limit on 20 arcmin scales
- LVV-9770 DMS-REQ-0360-V-05: Outlier limit on 20 arcmin scales

4.216.2 Test Items

Verify that the DM system has provided the code to calculate the maximum fraction of relative astrometric measurements on 20 arcminute scales that exceed the 20 arcminute outlier limit **AD2 = 20 milliarcseconds**, and assess whether it meets the requirement that it shall be less than **AF2 = 10 percent**.

4.216.3 Predecessors

- 4.216.4 Environment Needs
- 4.216.4.1 Software

4.216.4.2 Hardware



4.216.5 Input Specification

4.216.6 Output Specification

4.216.7 Test Procedure

Step	Description, Input Data and Expected Result		
	Description	Identify a dataset containing at least one field with multiple overlapping visits.	
1	Test Data	No data.	
	Expected Result	A dataset that has been ingested into a Butler repository.	
2-1 from LVV-T860	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:	
		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash 	
		From the command line, execute the commands below in the example code:	
	Test Data		
	Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.	
		To check versions in use, type: _eups list -s	
3-1 from LVV-	Description	Execute 'validate_drp' on a repository containing precursor data. Identify the path to the data, which we will call 'DATA/path', then execute the following (with additional flags specified as needed):	
T1744 	Expected Result	JSON files (and associated figures) containing the Measurements and any associated "extras."	
4	Description	Confirm that the metric AF2 has been calculated using the outlier limit AD2, and that its values are reasonable.	
-	Test Data	No data.	

DRAFT NOT YET APPROVED – The contents of this document are subject to configuration control by the LSST DM Change Control Board. – DRAFT NOT YET APPROVED



LDM-639

Latest Revision 2020-02-17

Step	Description, Input Data and Expected Result	
	Expected Result	A JSON file (and/or a report generated from that JSON file) demonstrating that AF2 has been calculated (and used the limit AD2).

4.217 LVV-T1750 - Verify calculation of separations relative to r-band exceeding color difference outlier limit

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jeffrey Carlin
Open LVV-T1750 in lira				

4.217.1 Verification Elements

- LVV-9771 DMS-REQ-0360-V-06: Color difference outlier limit relative to r-band
- LVV-9777 DMS-REQ-0360-V-11: Max fraction of r-band color difference outliers

4.217.2 Test Items

Verify that the DM system has provided the code to calculate the separations measured relative to the r-band that exceed the color difference outlier limit **AB2 = 20 milliarcseconds**, and assess whether it meets the requirement that it shall be less than **ABF1 = 10 percent**.

4.217.3 Predecessors

- 4.217.4 Environment Needs
- 4.217.4.1 Software

4.217.4.2 Hardware



LDM-639

4.217.5 Input Specification

4.217.6 Output Specification

4.217.7 Test Procedure

Step	Description, l	nput Data and Expected Result
1	Description	Identify a dataset containing at least one field with multiple overlapping visits, and includ- ing at least one visit in r-band.
•	Test Data	No data.
	Expected	A dataset that has been ingested into a Butler repository.
	Result	
2-1 from LVV-T860	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:
		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash From the command line, execute the commands below in the example code:
	Test Data Expected	Science pipeline software is available for use. If additional packages are needed (for example, 'obs'
	Result	packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.
		To check versions in use, type: _eups list -s
3-1 from	Description	Execute 'validate_drp' on a repository containing precursor data. Identify the path to the data, which _we will call 'DATA/path', then execute the following (with additional flags specified as needed):
	Test Data	
11744	Expected	JSON files (and associated figures) containing the Measurements and any associated "extras."
	Result	
	Description	Confirm that the metric ABF1 has been calculated using the outlier limit AB2, and that its values are reasonable.
7	Test Data	No data.



LDM-639

Latest Revision 2020-02-17

Step	Description, Input Data and Expected Result		
	Expected	A JSON file (and/or a report generated from that JSON file) demonstrating that ABF1 has	
	Result	been calculated (and used the limit AB2).	

4.218 LVV-T1751 - Verify calculation of median relative astrometric measurement error on 200 arcminute scales

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jeffrey Carlin
Open LVV-T1751 in Jira				

4.218.1 Verification Elements

• LVV-9774 - DMS-REQ-0360-V-08: Median astrometric error on 200 arcmin scales

4.218.2 Test Items

Verify that the DM system has provided the code to calculate the median relative astrometric measurement error on 200 arcminute scales and assess whether it meets the requirement that it shall be no more than AM3 = 15 milliarcseconds.

4.218.3 Predecessors

- 4.218.4 Environment Needs
- 4.218.4.1 Software

4.218.4.2 Hardware

4.218.5 Input Specification



LDM-639

4.218.6 Output Specification

4.218.7 Test Procedure

Step	Description, l	nput Data and Expected Result
1	Description	Identify a dataset containing at least one field with multiple overlapping visits, and that covers an area larger than 200 arcminutes.
•	Test Data	No data.
	Expected Result	A dataset that has been ingested into a Butler repository.
2-1 from LVV-T860	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:
		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash
		From the command line, execute the commands below in the example code:
	Test Data	
	Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.
		To check versions in use, type: _eups list -s
3-1 from LVV-	Description	Execute 'validate_drp' on a repository containing precursor data. Identify the path to the data, which we will call 'DATA/path', then execute the following (with additional flags specified as needed):
T1744	Expected Result	JSON files (and associated figures) containing the Measurements and any associated "extras."
	Description	Confirm that the metric AM3 has been calculated, and that its values are reasonable.
4	Test Data	No data.
	Expected Result	A JSON file (and/or a report generated from that JSON file) demonstrating that AM3 has been calculated.



4.219 LVV-T1752 - Verify calculation of fraction of relative astrometric measurement error on 200 arcminute scales exceeding outlier limit

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jeffrey Carlin
Open LVV-T1752 in Jira				

4.219.1 Verification Elements

• LVV-9779 - DMS-REQ-0360-V-13: Max fraction exceeding limit on 200 arcmin scales

4.219.2 Test Items

Verify that the DM system has provided the code to calculate the maximum fraction of relative astrometric measurements on 200 arcminute scales that exceed the 200 arcminute outlier limit **AD3 = 30 milliarcseconds**, and assess whether it meets the requirement that it shall be less than **AF3 = 10 percent**.

4.219.3 Predecessors

- 4.219.4 Environment Needs
- 4.219.4.1 Software
- 4.219.4.2 Hardware
- 4.219.5 Input Specification
- 4.219.6 Output Specification

4.219.7 Test Procedure



Step Description, Input Data and Expected Result

1	Description	Identify a dataset containing at least one field with multiple overlapping visits, and that covers an area larger than 200 arcminutes.
,	Test Data	No data.
	Expected	A dataset that has been ingested into a Butler repository.
	Result	
2-1 from LVV-T860	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:
		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash
		From the command line, execute the commands below in the example code:
	Test Data	
	Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.
		To check versions in use, type: _eups list -s
<u> </u>	Description	
LVV-	Test Data	we will call 'DATA/path', then execute the following (with additional flags specified as needed):
T1744	Expected Result	JSON files (and associated figures) containing the Measurements and any associated "extras."
1	Description	Confirm that the metric AF3 has been calculated using the outlier limit AD3, and that its values are reasonable.
4	Test Data	No data.
	Expected Result	A JSON file (and/or a report generated from that JSON file) demonstrating that AF3 has been calculated (and used the limit AD3).





LDM-639

4.220 LVV-T1753 - Verify calculation of RMS difference of separations relative to r-band

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jeffrey Carlin
Open LVV-T1753 in Jira				

4.220.1 Verification Elements

• LVV-9778 - DMS-REQ-0360-V-12: RMS difference between r-band and other filter separation

4.220.2 Test Items

Verify that the DM system has provided the code to calculate the separations measured relative to the r-band, and assess whether it meets the requirement that it shall be less than AB1 = 10 milliarcseconds.

- 4.220.3 Predecessors
- 4.220.4 Environment Needs
- 4.220.4.1 Software
- 4.220.4.2 Hardware
- 4.220.5 Input Specification
- 4.220.6 Output Specification
- 4.220.7 Test Procedure



Step Description, Input Data and Expected Result

1	Description	Identify a dataset containing at least one field with multiple overlapping visits, and includ- ing at least one visit in r-band.
·	Test Data	No data.
	Expected	A dataset that has been ingested into a Butler repository.
	Result	
2-1 from LVV-T860	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:
		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash
		From the command line, execute the commands below in the example code:
	Test Data	
	Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.
		To check versions in use, type: _eups list -s
3-1 from LVV-	Description	Execute 'validate_drp' on a repository containing precursor data. Identify the path to the data, which _we will call 'DATA/path', then execute the following (with additional flags specified as needed):
T1744 	Expected Result	JSON files (and associated figures) containing the Measurements and any associated "extras."
	Description	Confirm that the metric AB1 has been calculated, and that its values are reasonable.
4	Test Data	No data.
	Expected Result	A JSON file (and/or a report generated from that JSON file) demonstrating that AB1 has been calculated.





Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jeffrey Carlin

Open LVV-T1754 in Jira

4.221.1 Verification Elements

• LVV-3404 - DMS-REQ-0362-V-01: Median residual PSF ellipticity correlations on 5 arcmin scales

4.221.2 Test Items

Verify that the DM system has provided the code to calculate the median residual PSF ellipticity correlations averaged over an arbitrary field of view for separations less than 5 arcmin, and assess whether it meets the requirement that it shall be no greater than TE2 = 1.0e-7[arcminuteSeparationCorrelation].

4.221.3 Predecessors

- 4.221.4 Environment Needs
- 4.221.4.1 Software
- 4.221.4.2 Hardware
- 4.221.5 Input Specification
- 4.221.6 Output Specification

4.221.7 Test Procedure


Step Description, Input Data and Expected Result Description Identify a dataset containing at least one field with multiple overlapping visits. Test Data 1 No data. Expected A dataset that has been ingested into a Butler repository. Result Description The 'path' that you will use depends on where you are running the science pipelines. Options: 2-1 from LVV-T860 • local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash • LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash From the command line, execute the commands below in the example code: Test Data Expected Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary. Result To check versions in use, type: eups list -s 3-1 from Description Execute 'validate_drp' on a repository containing precursor data. Identify the path to the data, which we will call 'DATA/path', then execute the following (with additional flags specified as needed): LVV-Test Data T1744 Expected JSON files (and associated figures) containing the Measurements and any associated "extras." Result Description Confirm that the metric TE2 has been calculated, and that its values are reasonable. 4 Test Data No data. Expected A JSON file (and/or a report generated from that JSON file) demonstrating that TE2 has been calculated. Result

4.222 LVV-T1755 - Verify calculation of residual PSF ellipticity correlations for separations less than 1 arcmin



Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jeffrey Carlin
Open LVV-T1755 in lira				

4.222.1 Verification Elements

• LVV-9782 - DMS-REQ-0362-V-04: Median residual PSF ellipticity correlations on 1 arcmin scales

4.222.2 Test Items

Verify that the DM system has provided the code to calculate the median residual PSF ellipticity correlations averaged over an arbitrary field of view for separations less than 1 arcmin, and assess whether it meets the requirement that it shall be no greater than **TE1 = 2.0e-5[arcminuteSeparationCorrelation].**

4.222.3 Predecessors

- 4.222.4 Environment Needs
- 4.222.4.1 Software
- 4.222.4.2 Hardware
- 4.222.5 Input Specification
- 4.222.6 Output Specification

4.222.7 Test Procedure



Step Description, Input Data and Expected Result Description Identify a dataset containing at least one field with multiple overlapping visits. Test Data 1 No data. Expected A dataset that has been ingested into a Butler repository. Result Description The 'path' that you will use depends on where you are running the science pipelines. Options: 2-1 from LVV-T860 • local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash • LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash From the command line, execute the commands below in the example code: Test Data Expected Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary. Result To check versions in use, type: eups list -s 3-1 from Description Execute 'validate_drp' on a repository containing precursor data. Identify the path to the data, which we will call 'DATA/path', then execute the following (with additional flags specified as needed): LVV-Test Data T1744 Expected JSON files (and associated figures) containing the Measurements and any associated "extras." Result Description Confirm that the metric TE1 has been calculated, and that its values are reasonable. 4 Test Data No data. Expected A JSON file (and/or a report generated from that JSON file) demonstrating that TE1 has been calculated. Result

4.223 LVV-T1756 - Verify calculation of photometric repeatability in uzy filters



Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jeffrey Carlin
Open LVV-T1756 in lira				

4.223.1 Verification Elements

• LVV-3401 - DMS-REQ-0359-V-01: RMS photometric repeatability in uzy

4.223.2 Test Items

Verify that the DM system has provided the code to calculate the RMS photometric repeatability of bright non-saturated unresolved point sources in the u, z, and y filters, and assess whether it meets the requirement that it shall be less than **PA1uzy = 7.5 millimagnitudes**.

- 4.223.3 Predecessors
- 4.223.4 Environment Needs
- 4.223.4.1 Software
- 4.223.4.2 Hardware
- 4.223.5 Input Specification
- 4.223.6 Output Specification
- 4.223.7 Test Procedure

Step	Description,	Input Data and	Expected Result

	Description	Identify a dataset containing at least one field in each of the u, z, and y filters with multiple
1		overlapping visits.



Step Description, Input Data and Expected Result

been calculated.

	Test Data	No data.
	Expected	A dataset that has been ingested into a Butler repository.
	Result	
2-1 from	Description	Execute 'validate_drp' on a repository containing precursor data. Identify the path to the data, which we will call 'DATA/path', then execute the following (with additional flags specified as needed):
LVV-	Test Data	
11/44	Expected	JSON files (and associated figures) containing the Measurements and any associated "extras."
	Result	
	Description	Confirm that the metric PA1uzy has been calculated, and that its values are reasonable.
3	Test Data	No data.
	Expected	A ISON file (and/or a report generated from that ISON file) demonstrating that PA1uzy has

4.224 LVV-T1757 - Verify calculation of photometric repeatability in gri filters

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jeffrey Carlin
		Open LVV-	T1757 in Jira	

4.224.1 Verification Elements

Result

• LVV-9759 - DMS-REQ-0359-V-10: RMS photometric repeatability in gri

4.224.2 Test Items

Verify that the DM system has provided the code to calculate the RMS photometric repeatability of bright non-saturated unresolved point sources in the g, r, and i filters, and assess whether it meets the requirement that it shall be less than **PA1gri = 5.0 millimagnitudes**.

4.224.3 Predecessors



4.224.4 Environment Needs

- 4.224.4.1 Software
- 4.224.4.2 Hardware
- 4.224.5 Input Specification
- 4.224.6 Output Specification

4.224.7 Test Procedure

Step Description, Input Data and Expected Result

1	Description	Identify a dataset containing at least one field in each of the g, r, and i filters with multiple overlapping visits.
·	Test Data	No data.
	Expected	A dataset that has been ingested into a Butler repository.
	Result	
2-1 from	Description	Execute 'validate_drp' on a repository containing precursor data. Identify the path to the data, which we will call 'DATA/path', then execute the following (with additional flags specified as needed):
	Test Data	
11/44	Expected	JSON files (and associated figures) containing the Measurements and any associated "extras."
	Result	

	Description	Confirm that the metric PA1gri has been calculated, and that its values are reasonable.
3	Test Data	No data.
	Expected	A JSON file (and/or a report generated from that JSON file) demonstrating that PA1gri has
	Result	been calculated.

4.225 LVV-T1758 - Verify calculation of photometric outliers in uzy bands

Version	Status	Priority	Verification Type	Owner
1	Approved	Normal	Test	Jeffrey Carlin





Open LVV-T1758 in Jira

4.225.1 Verification Elements

- LVV-9758 DMS-REQ-0359-V-09: Repeatability outlier limit in uzy
- LVV-9752 DMS-REQ-0359-V-03: Max fraction of outliers among non-saturated sources

4.225.2 Test Items

Verify that the DM system has provided the code to calculate the photometric repeatability in the u, z, and y filters, and assess whether it meets the requirement that no more than **PF1** = 10[percent] of the repeatability outliers exceed the outlier limit of PA2uzy = 22.5 millimagnitudes.

- 4.225.3 Predecessors
- 4.225.4 Environment Needs
- 4.225.4.1 Software
- 4.225.4.2 Hardware
- 4.225.5 Input Specification
- 4.225.6 Output Specification
- 4.225.7 Test Procedure

Step	Description, Input Data and Expected Result	
	Description	Identify a dataset containing at least one field in each of the u, z, and y filters with multiple
1		overlapping visits.
	Test Data	No data.



Step	Description, I	nput Data and Expected Result
	Expected Result	A dataset that has been ingested into a Butler repository.
2-1 from LVV-T860	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:
		 local (newinstall.sh - based install):[path_to_installation]/loadLSST.bash development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash
	Test Data	· · · · · · · · · · · · · · · · · · ·
	Expected Result	Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary.
		To check versions in use, type: _eups list -s
3-1 from LVV-	Description Test Data	Execute 'validate_drp' on a repository containing precursor data. Identify the path to the data, which _we will call 'DATA/path', then execute the following (with additional flags specified as needed):
	Expected Result	JSON files (and associated figures) containing the Measurements and any associated "extras."
	Description	Confirm that the metric PA2uzy has been calculated using the threshold PF1, and that its values are reasonable.
4	Test Data	No data.
	Expected Result	A JSON file (and/or a report generated from that JSON file) demonstrating that PA2uzy has been calculated (and that it used PF1).

4.226 LVV-T1759 - Verify calculation of photometric outliers in gri bands

Version Status Priority Verification Type Owner



1 Approved Normal Test Jeffrey Carlin

Open LVV-T1759 in Jira

4.226.1 Verification Elements

- LVV-9752 DMS-REQ-0359-V-03: Max fraction of outliers among non-saturated sources
- LVV-9754 DMS-REQ-0359-V-05: Repeatability outlier limit in gri

4.226.2 Test Items

Verify that the DM system has provided the code to calculate the photometric repeatability in the g, r, and i filters, and assess whether it meets the requirement that no more than **PF1 = 10[percent]** of the repeatability outliers exceed the outlier limit of **PA2gri = 15 millimagni-tudes**.

- 4.226.3 Predecessors
- 4.226.4 Environment Needs
- 4.226.4.1 Software
- 4.226.4.2 Hardware
- 4.226.5 Input Specification
- 4.226.6 Output Specification
- 4.226.7 Test Procedure

Step Description, Input Data and Expected Result

	Description	Identify a dataset containing at least one field in each of the g, r, and i filters with multiple
1		overlapping visits.



÷ .	~	c .	LCCT	D .	
lest	Spec	tor	LSS I	Data	Management

Step Description, Input Data and Expected Result Test Data No data. Expected A dataset that has been ingested into a Butler repository. Result Description The 'path' that you will use depends on where you are running the science pipelines. Options: 2-1 from LVV-T860 local (newinstall.sh - based install):[path to installation]/loadLSST.bash • development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash • LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash From the command line, execute the commands below in the example code: Test Data _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ Expected Science pipeline software is available for use. If additional packages are needed (for example, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be necessary. Result To check versions in use, type: eups list -s 3-1 from Description Execute 'validate drp' on a repository containing precursor data. Identify the path to the data, which we will call 'DATA/path', then execute the following (with additional flags specified as needed): LVV-Test Data T1744 Expected JSON files (and associated figures) containing the Measurements and any associated "extras." Result Description Confirm that the metric PA2gri has been calculated using the threshold PF1, and that its values are reasonable. 4 Toct Data No data

Test Data	NO Gata.
Expected	A JSON file (and/or a report generated from that JSON file) demonstrating that PA2gri has
Result	been calculated (and that it used PF1).



LDM-639

5 Reusable Test Cases

Test cases in this section are made up of commonly encountered steps that have been factored out into modular, reusable scripts. These test cases are meant solely for the building of actual tests used for verification, to be inserted in test scripts via the "Call to Test" functionality in Jira/ATM. They streamline the process of writing test scripts by providing pre-designed steps, while also ensuring homogeneity throughout the test suite. These reusable modules are not themselves verifying requirements. Also, these test cases shall not call other reusable test cases in their script.

5.1 LVV-T837 - Authenticate to Notebook Aspect

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin
		Open L	/V-T837 in lira	

5.1.1 Test Items

Not specifically a test – modular script to be used in multiple other Test Scripts.

aviation. Janut Data and Evenants d Daavit

5.1.2 Input Specification

Must have a user account on the LSP.

5.1.3 Test Procedure

Step	Description, input Data and Expected Result			
1	Description	Authenticate to the notebook aspect of the LSST Science Platform (NB-LSP). This is cur- rently at https://lsst-lsp-stable.ncsa.illinois.edu/nb.		
Test Data No data.		No data.		
	Expected	Redirection to the spawner page of the NB-LSP allowing selection of the containerized		
	Result	stack version and machine flavor.		



Step	Description, l	Description, Input Data and Expected Result			
2	Description	Spawn a container by: 1) choosing an appropriate stack version: e.g. the latest weekly.			
		3) click "Spawn"			
	Test Data	No data.			
	Expected	Redirection to the JupyterLab environment served from the chosen container containing			
	Result	the correct stack version.			

5.2 LVV-T838 - Access an empty notebook in the Notebook Aspect

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Simon Krughoff
		Open	LVV-T838 in Jira	

5.2.1 Test Items

The steps here cover just those necessary to gain access to an empty notebook after authentication is complete.

5.2.2 Input Specification

Authentication to the Notebook aspect.

5.2.3 Test Procedure

Step	Description, Input Data and Expected Result				
	Description	Description Open a new launcher by navigating in the top menu bar "File" -> "New Launcher"			
1	Test Data	No data.			
	Expected	A launcher window with several sections, potentially with several kernel versions for each.			
	Result				
	Description	Select the option under "Notebook" labeled "LSST" by clicking on the icon.			
2	Test Data	No data.			



LDM-639

Step Description, Input Data and Expected Result

Expected	An empty notebook with a single empty cell.	The kernel show up as "LSST" in the top right
Result	of the notebook.	

5.3 LVV-T849 - Authenticate to the portal aspect of the LSP

Version	Status	Priority	Verification Type	Owner
2	Draft	Normal	Test	Simon Krughoff
		Open	LVV-T849 in lira	

5.3.1 Test Items

Obtain an authenticated session in the portal aspect of the LSST Science Platform

5.3.2 Test Procedure

Step	Description, Input Data and Expected Result			
1	Description	Navigate to the Portal Aspect endpoint. The stable version should be used for this test and is currently located at: https://lsst-lsp-stable.ncsa.illinois.edu/portal/app/ .		
	Test Data	No data.		
	Expected	A credential-entry screen should be displayed.		
	Result			
	Description	Enter a valid set of credentials for an LSST user with LSP access on the instance under test.		
2	Test Data	No data.		
	Expected	The Portal Aspect UI should be displayed following authentication.		
	Result			

5.4 LVV-T850 - Log out of the portal aspect of the LSP

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Simon Krughoff



Open LVV-T850 in Jira

5.4.1 Test Items

Leave the portal aspect of the LSST Science Platform in a clean state

steps in LVV-T849.

5.4.2 Test Procedure

Result

Step	Description, Input Data and Expected Result		
1	Description	Currently, there is no logout mechanism on the portal. This should be updated as the system matures.	
		Simply close the browser window.	
	Test Data	No data.	
	Expected	Closed browser window. When navigating to the portal endpoint, expect to execute the	

5.5 LVV-T860 - Initialize science pipelines

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin
		Open L	/V-T860 in Jira	

5.5.1 Test Items

Initialize the science pipelines software for use.

5.5.2 Input Specification

An installed software stack, either locally, on 'lsst-dev', or through the Notebook aspect.



5.5.3 Test Procedure

Step	Description, Ir	nput Data and Expected Result
1	Description	The 'path' that you will use depends on where you are running the science pipelines. Options:

- local (newinstall.sh based install):[path_to_installation]/loadLSST.bash
- development cluster ("lsst-dev"): /software/lsstsw/stack/loadLSST.bash
- LSP Notebook aspect (from a terminal): /opt/lsst/software/stack/loadLSST.bash

From the command line, execute the commands below in the example code:

Test Data	No data.
Example Code	source 'path' setup lsst_distrib
Expected Result	Science pipeline software is available for use. If additional packages are needed (for ex- ample, 'obs' packages such as 'obs_subaru'), then additional 'setup' commands will be nec- essary. To check versions in use, type: eups list -s

5.6 LVV-T866 - Run Alert Production Payload

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin
		Open L	/V-T866 in Jira	

5.6.1 Test Items

Execute Alert Production payload on a dataset. Generate all (or a subset of) Prompt science data products including Alerts (with the exception of Solar System object orbits) and load them



LDM-639

into the Data Backbone and Prompt Products Database.

5.6.2 Test Procedure

Step	Description, li	nput Data and Expected Result
1	Description	Perform the steps of Alert Production (including, but not necessarily limited to, single frame processing, ISR, source detection/measurement, PSF estimation, photometric and astrometric calibration, difference imaging, DIASource detection/measurement, source association). During Operations, it is presumed that these are automated for a given dataset.
	Test Data	No data.
	Expected	An output dataset including difference images and DIASource and DIAObject measure-
	Result	ments.
2	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
2	Test Data	No data.
	Expected	
	Result	

5.7 LVV-T901 - Run MOPS payload

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin
		Open L\	/V-T901 in Jira	

5.7.1 Test Items

Run MOPS payload on a dataset (for example, one night's data). Generate entries in the MOPS Database and the Prompt Products Database, including Solar System Object records, measurements, and orbits. Perform precovery forced photometry of transients.

5.7.2 Predecessors

Uses results loaded into Prompt Products database and Data Backbone services in LVV-T866.



5.7.3 Test Procedure

Step	Description, I	nput Data and Expected Result
1	Description	Perform the steps of Moving Object Pipeline (MOPS) processing on newly detected DIA- Sources, and generate Solar System data products including Solar System objects with associated Keplerian orbits, errors, and detected DIASources. This includes running pro- cesses to link DIASource detections within a night (called tracklets), to link these tracklets across multiple nights (into tracks), to fit the tracks with an orbital model to identify those tracks that are consistent with an asteroid orbit, to match these new orbits with existing SSObjects, and to update the SSObject table.
	Test Data	No data.
	Expected	An output dataset consisting of an updated SSObject database with SSObjects both added
	Result	and pruned as the orbital fits have been refined, and an updated DIASource database with DIASources assigned and unassigned to SSObjects.
2	Description	Verify that the expected data products have been produced, and that catalogs contain reasonable values for measured quantities of interest.
-	Test Data	No data.
	Expected	
	Result	

5.8 LVV-T987 - Instantiate the Butler for reading data

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin
		Open L\	/V-T987 in Jira	

5.8.1 Test Items

Create a Butler client to read data from an input repository.

5.8.2 Input Specification

LVV-T860 must be executed to initialize the science pipelines.

5.8.3 Test Procedure



Step	Description, Input Data and Expected Result		
1	Description	Identify the path to the data repository, which we will refer to as 'DATA/path', then execute the following:	
·	Test Data	No data.	
	Example	import lsst.daf.persistence as dafPersist	
	Code	<pre>butler = dafPersist.Butler(inputs='DATA/path')</pre>	
	Expected	Butler repo available for reading.	
	Result		

5.9 LVV-T1059 - Run Daily Calibration Products Update Payload

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin
		Open LV	V-T1059 in Jira	

5.9.1 Test Items

Execute the Daily Calibration Products Update payload to create a subset of Master Calibration images and Calibration Database entries.

5.9.2 Test Procedure

Step	Description, Input Data and Expected Result		
1	Description	Execute the Daily Calibration Products Update payload. The payload uses raw calibra- tion images and information from the Transformed EFD to generate a subset of Master Calibration Images and Calibration Database entries in the Data Backbone.	
	Test Data	No data.	
	Expected		
	Result		
2	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present and well-formed.	
-	Test Data	No data.	



Step	Description, Input Data and Expected Result
	Expected
	Result

5.10 LVV-T1060 - Run Periodic Calibration Products Production Payload

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin
Open LVV-T1060 in Jira				

5.10.1 Test Items

Execute the Calibration Products Production payload to create a subset of Master Calibration images and Calibration Database entries.

5.10.2 Test Procedure

Step	Description, li	nput Data and Expected Result
1	Description	Execute the Calibration Products Production payload. The payload uses raw calibration images and information from the Transformed EFD to generate a subset of Master Calibration Images and Calibration Database entries in the Data Backbone.
	Test Data	No data.
	Expected	
	Result	
2	Description	Confirm that the expected Master Calibration images and Calibration Database entries are present and well-formed.
-	Test Data	No data.
	Expected	
	Result	

5.11 LVV-T1064 - Run Data Release Production Payload



Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin
Open LVV-T1064 in lira				

5.11.1 Test Items

Execute the Data Release Production payload, starting from raw images and producing science data products.

5.11.2 Test Procedure

Step	Description, l	nput Data and Expected Result
1	Description	Process data with the Data Release Production payload, starting from raw science images and generating science data products, placing them in the Data Backbone.
	Test Data	No data.
	Expected	
	Result	

5.12 LVV-T1207 - Execute a simple ADQL query using the TAP service in the notebook aspect

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Jeffrey Carlin
Open LVV-T1207 in Jira				

5.12.1 Test Items

Extract a small amount of data from a catalog via the LSST TAP service.



5.12.2 Input Specification

One must have access to the LSST Notebook Aspect, and have logged in and opened an empty notebook.

5.12.3 Test Procedure

Step	Description, li	nput Data and Expected Result			
1	Description	Execute a query in a notebook to select a small number of stars. In the example code below, we query the WISE catalog, then extract the results to an Astropy table.			
	Test Data	No data.			
	Example	import pandas			
	Code	import pyvo			
		<pre>service = pyvo.dal.TAPService('http://lsst-lsp-stable.ncsa.illinois.edu/api/tap')</pre>			
		results = service.search("SELECT ra, decl, w1mpro_ep, w2mpro_ep, w3mpro_ep FROM wise_00.allwise_p3as_mep WHERE CONTAINS(POINT('ICRS', ra, decl), CIRCLE('ICRS', 192.85, 27.13, .2)) = 1") tab = results.to_table()			
	Expected				
	Result				

5.13 LVV-T1208 - Log out of the notebook aspect of the LSP

Version	Status	Priority	Verification Type	Owner
1	Draft	Normal	Test	Simon Krughoff
Open LVV-T1208 in Jira				

5.13.1 Test Items

Leave the notebook aspect of the LSST Science Platform in a clean state

5.13.2 Test Procedure



Step Description, Input Data and Expected Result

1

Description Under the 'File' menu at the top of your Jupyter notebook session, select one of the following:

- Save All, Exit, and Log Out
- Exit and Log Out Without Saving

Test Data	No data.
Expected	You will be returned to the LSP landing page: https://lsst-lsp-stable.ncsa.illinois.
Result	edu/ It is now safe to close the browser window.

5.14 LVV-T1744 - Run validate_drp on precursor data

Version	Status	Priority	Verification Type	Owner	
1	Defined	Normal	Analysis	Jeffrey Carlin	
Open I VV-T1744 in lira					

5.14.1 Test Items

Run the validate_drp code on a precursor dataset to evaluate the metrics that have been implemented in validate_drp.

5.14.2 Test Procedure

Step	Description, l	nput Data and Expected Result
1	Description Execute 'validate_drp' on a repository containing precursor data. Identify the path to data, which we will call 'DATA/path', then execute the following (with additional flags s ified as needed):	
	Test Data No data.	
	Example validateDrp.py 'DATA/path'	
	Code	
	Expected Result	JSON files (and associated figures) containing the Measurements and any associated "ex- tras."



LDM-639

6 Deprecated Test Cases

This section includes all test cases that have been marked as deprecated. These test cases will never be executed again, but have been in the past. For this reason it is important to keep them in the baseline as a reference.

No deprecated test cases found.





LDM-639

Latest Revision 2020-02-17

A Traceability

Verification Elements	High Level Requirements	Test Cases
LVV-157 - DMS-REQ-0326-V-01: Storing Approximations of Per-pixel Metadata	OSS-REQ-0391	LVV-T23
LVV-162 - DMS-REQ-0331-V-01: Computing Derived Quantities	OSS-REQ-0391	LVV-T24
LVV-163 - DMS-REQ-0332-V-01: Denormalizing Database Tables	OSS-REQ-0133	LVV-T25
LVV-164 - DMS-REQ-0333-V-01: Maximum Likelihood Values and Covariances	OSS-REQ-0391	LVV-T26
	OSS-REQ-0004	
LVV-177 - DMS-REQ-0346-V-01: Data Availability	OSS-REQ-0167	LVV-T27
	OSS-REQ-0313	
LVV-178 - DMS-REQ-0347-V-01: Measurements in catalogs	OSS-REQ-0391	LVV-T28
LVV-8 - DMS-REQ-0018-V-01: Raw Science Image Data Acquisition	OSS-REQ-0114	LVV-T29
LVV-9 - DMS-REQ-0020-V-01: Wavefront Sensor Data Acquisition	OSS-REQ-0316	LVV-T30
	OSS-REQ-0114	
LVV-10 - DMS-REQ-0022-V-01: Crosstalk Corrected Science image Data Acqui- sition	OSS-REQ-0127	LVV-131
	OSS-REQ-0114	
LVV-11 - DMS-REQ-0024-V-01: Raw Image Assembly	OSS-REQ-0129	LVV-T32
	OSS-REQ-0122	
IVA 28 DMC DEC 0068 V 011 Daw Science Image Metadate	DMS-REQ-0320	LVV-T33
LVV-28 - DMS-REQ-0008-V-01. Raw Science image Metadata	DMS-REQ-0066	
	OSS-REQ-0171	
		LVV-T33
		LVV-T37
LVV-1234 - OSS-REQ-0122-V-01: Provenance	OSS-REQ-0123	LVV-T64
		LVV-T89
		LVV-T119
LVV-96 - DMS-REQ-0265-V-01: Guider Calibration Data Acquisition	OSS-REQ-0194	LVV-T34
VV-175 - DMS-REO-0004-V-01: Time to L1 public release	DMS-REQ-0003	LVV-T35
	OSS-REQ-0127	LVV-T95
	DMS-REQ-0011	
LVV-7 - DMS-REQ-0010-V-01: Difference Exposures	DMS-REQ-0033	LVV-T36
	OSS-REQ-0129	
LVV-32 - DMS-REQ-0074-V-01: Difference Exposure Attributes	OSS-REQ-0122	LVV-T37
	DMS-REQ-0066	
LVV-29 - DMS-REQ-0069-V-01: Processed Visit Images	OSS-REQ-0129	LVV-T38
	DMS-REQ-0090	
LVV-12 - DMS-REQ-0029-V-01: Generate Photometric Zeropoint for Visit Image	OSS-REQ-0056	LVV-139
	OSS-REQ-0152	
	DMS-REQ-0090	
LVV-13 - DMS-REQ-0030-V-01: Absolute accuracy of WCS		LVV-T40
	USS-KEQ-U149	
	055-KEQ-0162	
LVV-30 - DMS-REQ-0070-V-01: Generate PSF for Visit Images		LVV-T41
LVV-31 - DMS-REQ-0072-V-01: Processed Visit Image Content	USS-KEQ-U129	LVV-T42
LINK 159 DMC DEC 0227 V 01: Packaround Madel Calculation		
LVV-150 - DIVIS-REQ-0327-V-01: Background Model Calculation	022-KEQ-0026	LVV-143

DRAFT NOT YET APPROVED – The contents of this document are subject to configuration control by the LSST DM Change Control Board. – DRAFT NOT YET APPROVED



Verification Elements	High Level Requirements	Test Cases
LVV-159 - DMS-REQ-0328-V-01: Documenting Image Characterization	OSS-REQ-0391	LVV-T44
LVV-39 - DMS-REQ-0097-V-01: Level 1 Data Quality Report Definition	OSS-REQ-0131 DMS-REQ-0096	LVV-T45
LVV-41 - DMS-REQ-0099-V-01: Level 1 Performance Report Definition	DMS-REQ-0098 OSS-REQ-0131	LVV-T46
LVV-43 - DMS-REQ-0101-V-01: Level 1 Calibration Report Definition	OSS-REQ-0131 DMS-REQ-0100	LVV-T47
LVV-97 - DMS-REQ-0266-V-01: Exposure Catalog	OSS-REQ-0130	LVV-T48
LVV-100 - DMS-REQ-0269-V-01: DIASource Catalog	OSS-REQ-0130 DMS-REQ-0270	LVV-T49
LVV-101 - DMS-REQ-0270-V-01: Faint DIASource Measurements	OSS-REQ-0166	LVV-T50
LVV-102 - DMS-REQ-0271-V-01: Max nearby galaxies associated with DIA- Source	OSS-REQ-0130	LVV-T51
LVV-103 - DMS-REQ-0272-V-01: DIAObject Attributes	OSS-REQ-0130	LVV-T52
LVV-104 - DMS-REQ-0273-V-01: SSObject Catalog	OSS-REQ-0130	LVV-T53
LVV-105 - DMS-REQ-0274-V-01: Alert Content	OSS-REQ-0128	LVV-T54
LVV-148 - DMS-REQ-0317-V-01: DIAForcedSource Catalog	OSS-REQ-0130	LVV-T55
LVV-150 - DMS-REQ-0319-V-01: Characterizing Variability	OSS-REQ-0126	LVV-T56
LVV-154 - DMS-REQ-0323-V-01: Calculating SSObject Parameters	OSS-REQ-0126	LVV-T57
LVV-155 - DMS-REQ-0324-V-01: Matching DIASources to Objects	OSS-REQ-0126	LVV-T58
LVV-156 - DMS-REQ-0325-V-01: Regenerating L1 Data Products During Data	OSS-REQ-0135	LVV-T59
LVV-184 - DMS-REO-0353-V-01: Publishing predicted visit schedule	OSS-REO-0378	
	DMS-REQ-0081	
LVV-16 - DMS-REQ-0034-V-01: Associate Sources to Objects	OSS-REQ-0339	LVV-161
	OSS-REQ-0153	
I W-20 - DMS-REO-0047-V-01: Provide PSE for Coadded Images	DMS-REQ-0041	1\//_T62
	OSS-REQ-0136	LVV-102
	OSS-REQ-0316	
LVV-45 - DMS-REQ-0103-V-01: Produce Images for EPO	OSS-REQ-0136	LVV-T63
LVV-46 - DMS-REQ-0106-V-01: Coadded Image Provenance	OSS-REQ-0122 DMS-REQ-0104	LVV-T64
LVV-98 - DMS-REQ-0267-V-01: Source Catalog	OSS-REQ-0137	LVV-T65
LVV-99 - DMS-REQ-0268-V-01: Forced-Source Catalog	OSS-REQ-0137	LVV-T66
LVV-106 - DMS-REQ-0275-V-01: Object Catalog	OSS-REQ-0137	LVV-T67
LVV-19 - DMS-REQ-0046-V-01: Provide Photometric Redshifts of Galaxies	OSS-REQ-0133 DMS-REQ-0040	LVV-T68
LVV-107 - DMS-REQ-0276-V-01: Object Characterization	OSS-REQ-0137	LVV-T69
LVV-180 - DMS-REQ-0349-V-01: Detecting extended low surface brightness objects	OSS-REQ-0133	LVV-T71
LVV-109 - DMS-REQ-0278-V-01: Coadd Image Method Constraints	OSS-REQ-0136	LVV-T72
LVV-110 - DMS-REQ-0279-V-01: Deep Detection Coadds	OSS-REQ-0136	LVV-T73
LVV-111 - DMS-REQ-0280-V-01: Template Coadds	OSS-REQ-0136	LVV-T74
LVV-112 - DMS-REQ-0281-V-01: Multi-band Coadds	OSS-REQ-0136	LVV-T75
LVV-160 - DMS-REQ-0329-V-01: All-Sky Visualization of Data Releases	OSS-REQ-0136	LVV-T76
LVV-161 - DMS-REQ-0330-V-01: Best Seeing Coadds	OSS-REQ-0136	LVV-T77
LVV-165 - DMS-REQ-0334-V-01: Persisting Data Products	OSS-REQ-0136	LVV-T78



Verification Elements	High Level Requirements	Test Cases	
LVV-166 - DMS-REQ-0335-V-01: PSF-Matched Coadds	OSS-REQ-0133	LVV-T79	
LVV-168 - DMS-REQ-0337-V-01: Detecting faint variable objects	OSS-REQ-0136	LVV-T80	
VV-169 - DMS-REO-0338-V-01: Targeted Coadds	LSR-REQ-0040	I \/\/_T81	
	OSS-REQ-0136		
_VV-170 - DMS-REQ-0339-V-01: Tracking Characterization Changes Between	LSR-REQ-0040	LVV-T82	
	OSS-REQ-0271		
.VV-22 - DMS-REQ-0059-V-01: Bad Pixel Map	DMS-REQ-0058	LVV-T83	
	OSS-REQ-0129		
	DMS-REQ-0055		
VV-23 - DMS-REQ-0060-V-01: Bias Residual Image	OSS-REQ-0271	LVV-T84	
	OSS-REQ-0046		
VV-24 - DMS-REQ-0061-V-01: Crosstalk Correction Matrix	DMS-REQ-0056	LVV-T85	
	OSS-REQ-0349		
	OSS-REQ-0271		
VV-25 - DMS-REQ-0062-V-01: Illumination Correction Frame	OSS-REQ-0046	LVV-T86	
	DMS-REQ-0058		
	OSS-REQ-0271		
VV-26 - DMS-REQ-0063-V-01: Monochromatic Flatfield Data Cube	OSS-REQ-0046	LVV-T87	
	DIMS-REQ-0058		
	DIVIS-REQ-0076	LVV-T88	
VV-57 - DMS-REQ-0130-V-01: Calibration Data Products	OSS-REQ-0271		
	OSS REQ 0134		
VV-59 - DMS-REO-0132-V-01: Calibration Image Provenance	OSS-REQ-0122	1\//_T89	
	DMS-REQ-0130	LVV TOS	
	 OSS-REO-0271		
.VV-113 - DMS-REQ-0282-V-01: Dark Current Correction Frame	OSS-REQ-0046	LVV-T90	
	OSS-REQ-0271		
VV-114 - DMS-REQ-0283-V-01: Fringe Correction Frame	OSS-REQ-0046	LVV-T91	
	LSR-REO-0121		
VV-151 - DMS-REQ-0320-V-01: Processing of Data From Special Programs	LSR-REQ-0122	LVV-T92	
	OSS-REO-0392		
VV-153 - DMS-REQ-0322-V-01: Special Programs Database	OSS-REO-0392	LVV-T94	
	LSR-REO-0104		
	LSR-REQ-0117	LVV-T95	
VV-1276 - OSS-REQ-0127-V-01: Level 1 Data Product Availability	LSR-REQ-0118	LVV-T102	
	LSR-REQ-0126		
	OSS-REO-0181	LVV-T96	
	OSS-REO-0130		
.VV-123 - DMS-REQ-0292-V-01: Uniqueness of IDs Across Data Releases	OSS-REQ-0137	LVV-T97	
	OSS-REQ-0176		
.VV-124 - DMS-REQ-0293-V-01: Selection of Datasets	OSS-REO-0118	LVV-T98	



Verification Elements	High Level Requirements	Test Cases
	OSS-REQ-0120	
I.W.125 - DMS-REO-0294-V-01: Processing of Datasets	OSS-REQ-0119	
	OSS-REQ-0118	LVV-199
	OSS-REQ-0117	
LVV-126 - DMS-REQ-0295-V-01: Transparent Data Access	OSS-REQ-0176	LVV-T100
I.W.3 - DMS-REO-0002-V-01: Transient Alert Distribution	OSS-REQ-0184	L\A/_T101
	OSS-REQ-0127	
	DMS-REQ-0086	
LVV-36 - DMS-REQ-0089-V-01: Solar System Objects Available Within Specified	DMS-REQ-0004	LVV-T102
Time	OSS-REQ-0127	
LVV-9803 - DMS-REO-0004-V-03: Time to availability of Solar System Object	DMS-REQ-0003	I VV-T102
orbits	OSS-REQ-0127	200 002
LVV-38 - DMS-REQ-0096-V-01: Generate Data Quality Report Within Specified Time	OSS-REQ-0131	LVV-T103
LVV-40 - DMS-REQ-0098-V-01: Generate DMS Performance Report Within Specified Time	OSS-REQ-0131	LVV-T104
LVV-42 - DMS-REQ-0100-V-01: Generate Calibration Report Within Specified Time	OSS-REQ-0131	LVV-T105
	OSS-REQ-0046	
	OSS-REQ-0021	
LVV-58 - DMS-REQ-0131-V-01: Time allowed to process callos	OSS-REQ-0194	LVV-1106
	DMS-REQ-0130	
LVV-115 - DMS-REQ-0284-V-01: Level-1 Production Completeness	OSS-REQ-0052	LVV-T107
	OSS-REQ-0130	
LVV-116 - DMS-REQ-0285-V-01: Level 1 Source Association	OSS-REQ-0160	LVV-T108
	OSS-REQ-0159	
LVV-117 - DMS-REQ-0286-V-01: SSObject Precovery	OSS-REQ-0159	LVV-T109
LVV-118 - DMS-REQ-0287-V-01: Max look-back time for precovery	OSS-REQ-0130	LVV-T110
LVV-119 - DMS-REQ-0288-V-01: Use of External Orbit Catalogs	OSS-REQ-0159	LVV-T111
LVV-173 - DMS-REQ-0342-V-01: Alert Filtering Service	LSR-REQ-0025	LVV-T112
LVV 174 DMS REO 0242 V 01: Number of full size alerts	OSS-REQ-0193	
	OSS-REQ-0184	LVV-IIIS
LVV-179 - DMS-REQ-0348-V-01: Pre-defined alert filters	LSR-REQ-0026	LVV-T114
I/W-120 - DMS-PEO-0280-V-01: Calibration Production Processing	OSS-REQ-0004	
	OSS-REQ-0170	
LVV-181 - DMS-REQ-0350-V-01: Associating Objects across data releases		LVV-T116
LVV-47 - DMS-REQ-0119-V-01: DAC resource allocation for Level 3 processing	OSS-REQ-0143	LVV-T117
LVV 49 DMS DEC 0120 V 01: Lovel 2 Data Product Solf Consistency	OSS-REQ-0120	
	OSS-REQ-0118	LVV-1118
LVV-49 - DMS-REQ-0121-V-01: Provenance for Level 3 processing at DACs	OSS-REQ-0122	LVV-T119
	OSS-REQ-0122	
LVV-53 - DMS-REQ-0125-V-01: Software framework for Level 3 catalog pro-	DMS-REQ-0120	LVV-T120
cessing	OSS-REQ-0121	
	OSS-REQ-0122	
LVV-56 - DMS-REQ-0128-V-01: Software framework for Level 3 image process-	DMS-REQ-0120	LVV-T121
ing	OSS-REQ-0121	
LVV-121 - DMS-REQ-0290-V-01: Level 3 Data Import	OSS-REQ-0140	LVV-T122



Test Spec for LSST Data Management	LDM-639 Lat	test Revision 2020-02-17	
Varification Floments	High Lovel Pequirements	Tost Casos	
	OSS-REQ-0176		
LVV-171 - DMS-REQ-0340-V-01: Access Controls of Level 3 Data Products	OSS-REQ-0187	LVV-T123	
	OSS-REQ-0142		
LVV-139 - DMS-REQ-0308-V-01: Software Architecture to Enable Community Re-Use	OSS-REQ-0121	LVV-T124	
	OSS-REQ-0353		
W-6 - DMS-PEO-0000-V-01: Simulated Data	DMS-REQ-0007	1\\\/ T125	
	OSS-REQ-0351	LVV-1125	
	OSS-REQ-0354		
	OSS-REQ-0121		
	OSS-REQ-0129	LVV-1120	
	OSS-REQ-0130		
W-15 - DMS-REO-0033-V-01: Provide Source Detection Software	OSS-REQ-0137	L\\/_T127	
.vv 15 Divis reg 0055 V 01. Hovide Source Detection Software	OSS-REQ-0121		
	DMS-REQ-0080		
	OSS-REQ-0153		
VV-17 - DMS-REO-0042-V-01: Provide Astrometric Model	OSS-REQ-0149	I VV-T128	
	OSS-REQ-0160	200 1120	
	OSS-REQ-0162		
	OSS-REQ-0130		
.VV-18 - DMS-REQ-0043-V-01: Provide Calibrated Photometry	OSS-REQ-0275	LVV-T129	
	OSS-REQ-0137		
.VV-21 - DMS-REQ-0052-V-01: Enable a Range of Shape Measurement Approaches	OSS-REQ-0137	LVV-T130	
-VV-63 - DMS-REQ-0160-V-01: Provide User Interface Services	OSS-REQ-0057	LVV-T131	
VV-127 - DMS-REQ-0296-V-01: Pre-cursor, and Real Data		LVV-T132	
VV-182 - DMS-REQ-0351-V-01: Provide Beam Projector Coordinate Calcula- ion Software	OSS-REQ-0383	LVV-T133	
	OSS-REO-0180		
	OSS-REO-0176		
.VV-27 - DMS-REQ-0065-V-01: Provide Image Access Services	OSS-REQ-0181	LVV-T134	
	DMS-REQ-0066		
.VV-129 - DMS-REQ-0298-V-01: Data Product and Raw Data Access	OSS-REQ-0176		
	OSS-REQ-0141		
.vv-130 - DMS-REQ-0299-v-01: Data Product Ingest	OSS-REQ-0004	LVV-1137	
.VV-131 - DMS-REQ-0300-V-01: Bulk Download Service	OSS-REQ-0178	LVV-T138	
	OSS-REQ-0004		
VV-133 - DMS-REQ-0302-V-01: Production Orchestration	OSS-REQ-0038	LVV-T140	
	OSS-REQ-0117		
	OSS-REQ-0004		
.VV-134 - DMS-REQ-0303-V-01: Production Monitoring	OSS-REQ-0038	LVV-T141	
	OSS-REQ-0034		
-VV-135 - DMS-REQ-0304-V-01: Production Fault Tolerance	OSS-REQ-0117	LVV-T142	
	OSS-REQ-0122		

_ _ _ _ _ _ _ _ _ _

LVV-T144

LVV-T145

_ _ -

_ _ _

OSS-REQ-0121

OSS-REQ-0122

OSS-REQ-0121

LVV-136 - DMS-REQ-0305-V-01: Task Specification

LVV-137 - DMS-REQ-0306-V-01: Task Configuration



	Test	Spec	for	LSST	Data	Management	
--	------	------	-----	------	------	------------	--

Latest Revision 2020-02-17

Verification Elements	High Level Requirements	Test Cases
	OSS-REQ-0041	
IVV/128 DMS DEC 0207 V 01: DMS Initialization Component	OSS-REQ-0122	110/ 1146
	OSS-REQ-0307	LVV-1140
	OSS-REQ-0121	
LVV-132 - DMS-REQ-0301-V-01: Control of Level-1 Production	OSS-REQ-0044	LVV-T147
1/0/ 128 DMS DEC 0207 V 01: Upique Drecessing Coverage	OSS-REQ-0120	
LVV-158 - DIVIS-REQ-0507-V-01. Offique Processing Coverage	OSS-REQ-0118	LVV-1148
1/0/ 22 DMS PEO 0075 V 01: Catalog Quarias	DMS-REQ-0076	
LVV-55 - DIVIS-REQ-0075-V-01. Catalog Queries	OSS-REQ-0176	LVV-1149
IVV.24 - DMS-REQ-0077-V-01: Maintain Archive Publicly Accessible	DMS-REQ-0076	
	OSS-REQ-0186	LVV-1150
1/V/.25 - DMS-REQ.0078-V/01: Catalog Export Formats	DMS-REQ-0076	LVV-T151
EVV-55 - DIVIS-INEQ-0078-V-01. Catalog Export Formats	OSS-REQ-0176	LVV-T1232
IVV/37 - DMS-REO-0004-V-01: Keen Historical Alert Archive	DMS-REQ-0092	
	OSS-REQ-0128	LVV-1152
LVV-44 - DMS-REQ-0102-V-01: Provide Engineering & Facility Database Archive	OSS-REQ-0132	LVV-T153
LVV-140 - DMS-REQ-0309-V-01: Raw Data Archiving Reliability	OSS-REQ-0111	LVV-T154
LVV-141 - DMS-REQ-0310-V-01: Un-Archived Data Product Cache	OSS-REQ-0130	LVV-T155
LVV-142 - DMS-REQ-0311-V-01: Regenerate Un-archived Data Products	OSS-REQ-0129	LVV-T156
	OSS-REQ-0185	
LVV-143 - DMS-REQ-0312-V-01: Level 1 Data Product Access	OSS-REQ-0127	LVV-T157
LVV-144 - DMS-REO-0313-V-01: Level 1 & 2 Catalog Access	OSS-REO-0186	LVV-T158
LVV-167 - DMS-REO-0336-V-01: Regenerating Data Products from Previous	LSR-REO-0049	LVV-T159
Data Releases		
LVV-172 - DMS-REO-0341-V-01: Max elapsed time for precovery results		LVV-T160
LVV-176 - DMS-REO-0345-V-01: Logging of catalog queries	OSS-REO-0134	LVV-T161
LVV-189 - DMS-REO-0363-V-01: Access to Previous Data Releases	 OSS-RFO-0186	I VV-T162
I VV-190 - DMS-REO-0364-V-01: Total number of data releases	 OSS-REO-0396	IVV-T163
IVV-191 - DMS-REO-0365-V-01: Operations Subsets	 OSS-RFO-0398	IVV-T164
IVV-192 - DMS-REQ-0366-V-01: Subsets Support		
IVV-193 - DMS-REQ-0367-V-01: Access Services Performance		
LVV 104 DMS REQ 0307 V 01: Access Services Ferrormanice		
	OSS-REQ-0397	LVV-1169
LVV-197 - DMS-REQ-0371-V-01: Query Availability	OSS-REQ-0401	LVV-11/0
		LVV-11/1
LVV-64 - DMS-REQ-0161-V-01: Optimization of Cost, Reliability and Availability in Order		LVV-T172
	OSS-REQ-0020	
LVV-סס - טועוג-אבע-טונצ-ע-טו: Pipeline Inroughput	OSS-REQ-0127	LVV-11/3
LVV-66 - DMS-REQ-0163-V-01: Re-processing Capacity	OSS-REQ-0134	LVV-T174
LVV-67 - DMS-REQ-0164-V-01: Temporary Storage for Communications Links	DMS-REQ-0162	LVV-T175
	OSS-REQ-0052	
	OSS-REQ-0051	
LVV-68 - DMS-REQ-0165-V-01: Infrastructure Sizing for "catching up"	DMS-REO-0162	LVV-T176
	OSS-REQ-0050	
LVV-994 - OSS-REQ-0051-V-01: Summit-Base Connectivity Loss	`	LVV-T176

DRAFT NOT YET APPROVED - The contents of this document are subject to configuration control by the LSST DM Change Control Board. - DRAFT NOT YET APPROVED



Verification Elements	High Level Requirements	Test Cases
LVV-69 - DMS-REQ-0166-V-01: Incorporate Fault-Tolerance	DMS-REQ-0161	LVV-T177
LVV-70 - DMS-REQ-0167-V-01: Incorporate Autonomics	DMS-REQ-0166	LVV-T178
LVV-145 - DMS-REQ-0314-V-01: Compute Platform Heterogeneity	OSS-REQ-0177 OSS-REQ-0124	LVV-T179
LVV-149 - DMS-REQ-0318-V-01: Data Management Unscheduled Downtime	OSS-REQ-0373	LVV-T180
LVV-72 - DMS-REQ-0170-V-01: Prefer Computing and Storage Down	 DMS-REO-0161	LVV-T182
LVV-146 - DMS-REO-0315-V-01: DMS Communication with OCS	OSS-REO-0003	IVV-T183
	OSS-REO-0373	
LVV-74 - DMS-REQ-0172-V-01: Summit to Base Network Availability	DMS-REO-0161	LVV-T185
	OSS-REQ-0373	
LVV-75 - DMS-REQ-0173-V-01: Summit to Base Network Reliability	DMS-REQ-0161	LVV-T186
	DMS-REQ-0173	
LVV-76 - DMS-REQ-0174-V-01: Summit to Base Network Secondary Link	OSS-REQ-0049	LVV-T187
	DMS-REQ-0172	
	DMS-REQ-0173	
LVV-77 - DMS-REQ-0175-V-01: Summit to Base Network Ownership and Op-	OSS-REQ-0036	LVV-T188
eration	DMS-REQ-0172	
LVV-78 - DMS-REQ-0176-V-01: Base Facility Infrastructure	OSS-REQ-0003	LVV-T189
LVV 20 DMC DEC 0178 V 01: Dage English Co. Logation with Evicting English	DMS-REQ-0161	
LVV-80 - DMS-REQ-0178-V-01: Base Facility Co-Location with Existing Facility	OSS-REQ-0006	LVV-1190
LVV-147 - DMS-REQ-0316-V-01: Commissioning Cluster		LVV-T191
LVV-183 - DMS-REQ-0352-V-01: Base Wireless LAN (WiFi)	OSS-REQ-0003	LVV-T192
	OSS-REQ-0053	
LVV-81 - DMS-REQ-0180-V-01: Base to Archive Network	OSS-REQ-0055	LVV-T193
	DMS-REQ-0162	
	OSS-REQ-0053	
LVV-82 - DMS-REQ-0181-V-01: Base to Archive Network Availability	DMS-REQ-0162	LVV-T194
	DMS-REQ-0161	
LVV 82 DMS DEC 0182 V 01: Pace to Archive Network Polishility	OSS-REQ-0053	
LVV-65 - DIVIS-REQ-0162-V-01. Base to Archive Network Reliability	DMS-REQ-0161	LVV-1195
	DMS-REQ-0181	
LVV-84 - DMS-REQ-0183-V-01: Base to Archive Network Secondary Link	DMS-REQ-0182	LVV-T196
	OSS-REQ-0049	
IVV-85 - DMS-REO-0185-V-01: Archive Center	OSS-REQ-0004	I \/\/_T197
	DMS-REQ-0163	
I VV-86 - DMS-REO-0186-V-01: Archive Center Disaster Recovery	OSS-REQ-0176	\/\/_T198
	DMS-REQ-0161	
LVV-87 - DMS-REO-0187-V-01: Archive Center Co-Location with Existing Facil-	OSS-REQ-0022	I VV-T199
ity	DMS-REQ-0161	2 1155
LVV-88 - DMS-REO-0188-V-01: Archive to Data Access Center Network	OSS-REO-0004	LVV-T200
LVV-89 - DMS-REO-0189-V-01: Archive to Data Access Center Network Avail-	DMS-REO-0161	<u>LVV-T201</u>
ability	5	2 1201
LVV-90 - DMS-REQ-0190-V-01: Archive to Data Access Center Network Relia-	DMS-REQ-0161	LVV-T202
LVV-91 - DMS-REQ-0191-V-01: Archive to Data Access Center Network Secondary Link	DMS-REQ-0189 DMS-REQ-0190	LVV-T203



Test Spec for LSST Data	Management	LDM-639
	0	

Verification Elements	High Level Requirements	Test Cases
LVV-50 - DMS-REQ-0122-V-01: Access to catalogs for external Level 3 process-	OSS-REQ-0180	LVV-T204
ing	OSS-REQ-0140	
LVV-51 - DMS-REQ-0123-V-01: Access to input catalogs for DAC-based Level 3 processing	OSS-REQ-0140	LVV-T205
LVV-52 - DMS-REQ-0124-V-01: Federation with external catalogs	OSS-REQ-0140 DMS-REQ-0125	LVV-T206
LVV-54 - DMS-REQ-0126-V-01: Access to images for external Level 3 process-	OSS-REQ-0180 OSS-REQ-0140	LVV-T207
LVV-55 - DMS-REQ-0127-V-01: Access to input images for DAC-based Level 3	OSS-REQ-0140	LVV-T208
IVV-92 - DMS-REO-0193-V-01: Data Access Centers		
LW-93 - DMS-REQ-0194-V-01: Data Access Center Simultaneous Connections		LVV-T210
	DMS-REO-0193	
LVV-94 - DMS-REQ-0196-V-01: Data Access Center Geographical Distribution	OSS-REQ-0021	LVV-T211
	OSS-REQ-0022	
	DMS-REQ-0193	
LVV-95 - DMS-REQ-0197-V-01: No Limit on Data Access Centers	OSS-REQ-0021	LVV-T212
	OSS-REQ-0022	
	OSS-REQ-0403	
LVV-3404 - DMS-REQ-0362-V-01: Median residual PSF ellipticity correlations	OSS-REQ-0404	LVV-1370
on 5 arcmin scales	OSS-REQ-0405	LVV-11/54
	OSS-REQ-0403	
LVV-9780 - DMS-REQ-0362-V-02: Max fraction of excess ellipticity residuals on	OSS-REQ-0404	LVV-T376
1 and 5 arcmin scales	OSS-REQ-0405	
LVV-3401 - DMS-REQ-0359-V-01: RMS photometric repeatability in uzy	OSS-REQ-0387	LVV-T377
		LVV-11/56
pixels	OSS-REQ-0387	LVV-13//
LVV-9757 - DMS-REQ-0359-V-08: Max cross-talk imperfections	OSS-REQ-0387	LVV-T377
LVV-9755 - DMS-REQ-0359-V-06: Accuracy of photometric transformation	OSS-REQ-0387	LVV-T377
LVV-9754 - DMS-REQ-0359-V-05: Repeatability outlier limit in gri	OSS-REQ-0387	LVV-T377
IVV-9752 - DMS-REO-0359-V-03: Max fraction of outliers among non-	OSS-RFO-0387	LVV-T1758
saturated sources		LVV-T1759
LVV-9756 - DMS-REQ-0359-V-07: RMS width of zero point in u-band	OSS-REO-0387	LVV-T377
LVV-9753 - DMS-REQ-0359-V-04: Accuracy of zero point for colors with u-band	OSS-REQ-0387	LVV-T377
LVV-9762 - DMS-REQ-0359-V-13: Max sky brightness error		LVV-T377
LVV-9760 - DMS-REQ-0359-V-11: Fraction of zero point outliers	OSS-REQ-0387	LVV-T377
		LVV-T377
LVV-9759 - DMS-REQ-0359-V-10: RMS photometric repeatability in gri	USS-REQ-0387	LVV-T1757
		LVV-T377
LVV-9758 - אוט אוט אנע-אבע-טאט אנע-אינע אנע-אינע איז אין איז איז איז געראיע גערע גערע גערע גערע גערע גערע גער	USS-REQ-0387	LVV-T1758
LW-9761 - DMS-REQ-0359-V-12: Max fraction of unusable pixels per sensor	OSS-REQ-0387	LVV-T377



Fest S	pec for	LSST	Data	Management

Latest Revision 2020-02-17

Verification Elements	High Level Requirements	Test Cases
LVV-9766 - DMS-REQ-0359-V-17: Max RMS of resolved/unresolved flux ratio	OSS-REQ-0387	LVV-T377
LVV-9763 - DMS-REQ-0359-V-14: RMS width of zero point in all bands except	OSS-REQ-0387	LVV-T377
LVV-9765 - DMS-REQ-0359-V-16: Accuracy of zero point for colors without u- band	OSS-REQ-0387	LVV-T377
LVV-9778 - DMS-REQ-0360-V-12: RMS difference between r-band and other	OSS-REQ-0388	LVV-T378
filter separation		LVV-11753
LVV-9777 - DMS-REQ-0360-V-11: Max fraction of r-band color difference out-	OSS-REQ-0388	LVV-T378
liers		LVV-11/50
LVV-9779 - DMS-REQ-0360-V-13: Max fraction exceeding limit on 200 arcmin	OSS-REQ-0388	LVV-T378
scales		
LVV-9773 - DMS-REQ-0360-V-07: Outlier limit on 5 arcmin scales	OSS-REQ-0388	LVV-T378
		LVV-T378
LVV-9770 - DMS-REQ-0360-V-05: Outlier limit on 20 arcmin scales	OSS-REQ-0388	LVV-T1749
LVV-9775 - DMS-REQ-0360-V-09: Outlier limit on 200 arcmin scales	OSS-REQ-0388	LVV-T378
LVV-9769 - DMS-REQ-0360-V-04: Median absolute error in RA, Dec	OSS-REQ-0388	LVV-T378
		LVV-T1748
LVV-9774 - DMS-REQ-0360-V-08: Median astrometric error on 200 arcmin	OSS-REQ-0388	LVV-1378 LVV-T1751
scales		
LVV-9768 - DMS-REQ-0360-V-03: Median astrometric error on 5 arcmin scales	OSS-REQ-0388	LVV-1378 LVV-T1747
LVV-9771 - DMS-REQ-0360-V-06: Color difference outlier limit relative to r-	OSS-REQ-0388	LVV-T1750
band		
LVV-9776 - DMS-REQ-0360-V-10: Max fraction exceeding limit on 20 arcmin	OSS-REQ-0388	LVV-1378 LVV-T1749
scales		
LVV-9767 - DMS-REQ-0360-V-02: Max fraction exceeding limit on 5 arcmin	OSS-REQ-0388	LVV-1378 LVV-T1746
scales		
coadd cutout image users	USS-REQ-UT81	LVV-1385
LVV-71 - DMS-REQ-0168-V-01: Summit Facility Data Communications	OSS-REQ-0002	LVV-T1097
	OSS-REQ-0003	
	OSS-REQ-0127	LVV-11108
	DMS-REQ-0090	
LVV-9741 - DMS-REQ-0030-V-02: Minimum astrometric standards per CCD	DMS-REQ-0104	LVV-T1240
	OSS-REQ-0149	
LVV 2400 DMS DEC 02E8 V 01: Min number of simultaneous DM FED success	USS-KEQ-U162	
users	055-REQ-0181	LVV-11250
LVV-9788 - DMS-REQ-0358-V-02: Max time to retrieve DM EFD query results	OSS-REQ-0181	LVV-T1251
LVV-9748 - DMS-REO-0343-V-02: Number of simultaneous users	OSS-REQ-0193	LVV-T1252
	OSS-REQ-0184	
LVV-963/ - DMS-REQ-03/2-V-01: Archiving Camera Test Data		LVV-T1264
LVV-9740 - DMS-REQ-0004-V-02: Latency of reporting optical transients	OSS-REQ-0003	LVV-T1276

DRAFT NOT YET APPROVED – The contents of this document are subject to configuration control by the LSST DM Change Control Board. – DRAFT NOT YET APPROVED



Test	Spec	for	LSST	Data	Management	
------	------	-----	------	------	------------	--

Verification Elements	High Level Requirements	Test Cases
	OSS-REQ-0046	
1)4/ 074E DMS REO 0121 // 02: May pumber of calibe to be processed	OSS-REQ-0021	
LVV-9745 - DIVIS-REQ-0131-V-02. Max number of callos to be processed	OSS-REQ-0194	LVV-112//
	DMS-REQ-0130	
LVV-9797 - DMS-REQ-0377-V-02: Max time to retrieve single-CCD coadd	OSS-REQ-0181	LVV-T1332
cutout image		
LVV-18222 - DMS-REQ-0384-V-01: Export MOCs As FITS_1	OSS-REQ-0391	LVV-T1524
	OSS-REQ-0122	
LVV-18223 - DMS-REQ-0381-V-01: HIPS LINKage to Coadds_1	OSS-REQ-0061	LVV-11525
LVV-18224 - DMS-REQ-0380-V-01: HiPS Service_1	OSS-REQ-0176	LVV-T1526
LVV-18225 - DMS-REQ-0382-V-01: HiPS Visualization_1	OSS-REQ-0061	LVV-T1527
	OSS-REQ-0033	
LVV-18226 - DMS-REQ-0385-V-01: MOC Visualization_1	OSS-REQ-0061	LVV-11528
	OSS-REQ-0391	
LVV-18227 - DMS-REQ-0379-V-01: Produce All-Sky HIPS Map_1	OSS-REQ-0136	LVV-11529
	OSS-REQ-0391	
LVV-18228 - DMS-REQ-0383-V-01: Produce MOC Maps_1	OSS-REQ-0033	LVV-11530
LVV-18230 - DMS-REQ-0386-V-01: Archive Processing Provenance_1	OSS-REQ-0172	LVV-T1560
LVV-18231 - DMS-REQ-0387-V-01: Serve Archived Provenance_1	OSS-REQ-0172	LVV-T1561
	OSS-REQ-0122	
LVV-18232 - DMS-REQ-0388-V-01: Provide Re-Run Tools_1	OSS-REQ-0123	LVV-T1562
	OSS-REQ-0172	
	OSS-REQ-0122	
1)4/ 18222 DMS REO 0200 // 01: Bo Runs on Other Systems 1	OSS-REQ-0169	
	OSS-REQ-0123	LVV-11503
	OSS-REQ-0172	
	OSS-REQ-0122	
IVV/ 18224 DMS REO 0280 V/01: Bo Runs on Similar Systems 1	OSS-REQ-0169	
	OSS-REQ-0123	LVV-11504
	OSS-REQ-0172	
LVV-3402 - DMS-REQ-0360-V-01: Median astrometric error on 20 arcmin scales	OSS-REQ-0388	LVV-T1745
	OSS-REQ-0403	
LVV-9782 - DMS-REQ-0362-V-04: Median residual PSF ellipticity correlations	OSS-REQ-0404	LVV-T1755
on 1 arcmin scales	OSS-REQ-0405	